

Product Guide


GOLD LABEL™ Industrial Raw Edge V-Belts



GOLD LABEL™


Designed for **OEMs**

GOLD LABEL Raw Edge - Table of Contents



V-Belt

GOLD LABEL™




ZX-AX-BX-CX

GOLD LABEL X Classical

Raw Edge classical V-Belt.


Product description 3

Size List 4



V-Belt

GOLD LABEL™




3VX-5VX

GOLD LABEL X Narrow

Designed for more compact multiple-belt drives. Imperial design.


Product description 18

Size List 19



V-Belt

GOLD LABEL™



XPZ-XPA-XPB-XPC


GOLD LABEL X Wedge

Designed for more compact multiple-belt drives. Metric design.


Product description 25

Size List 26

GOLD LABEL X Classical - Product Description



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

V-Belt Raw Edge

Part Number Description: **AX40GL**

AX: Profile (13mm X 8mm)

40: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance.

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching


Designed for OEMs

Markets and Applications:


Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps, woods...), in particular where temperature and power capacity are critical.

Pulley standards: DIN2211-ISO4183

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX18GL	ZX	457	490	18.00	19.25	0.03	0.07
ZX19.5GL	ZX	495	528	19.50	20.75	0.03	0.08
ZX20GL	ZX	508	541	20.00	21.25	0.03	0.08
ZX20.5GL	ZX	521	554	20.50	21.75	0.03	0.08
ZX21GL	ZX	533	566	21.00	22.25	0.03	0.08
ZX21.25GL	ZX	540	573	21.25	22.50	0.03	0.09
ZX21.75GL	ZX	552	585	21.75	23.00	0.03	0.09
ZX22GL	ZX	559	592	22.00	23.25	0.04	0.09
ZX22.25GL	ZX	565	598	22.25	23.50	0.04	0.09
ZX22.5GL	ZX	572	605	22.50	23.75	0.04	0.09
ZX23GL	ZX	584	617	23.00	24.25	0.04	0.09
ZX23.5GL	ZX	597	630	23.50	24.75	0.04	0.09
ZX23.75GL	ZX	603	636	23.75	25.00	0.04	0.09
ZX24GL	ZX	610	643	24.00	25.25	0.04	0.10
ZX24.75GL	ZX	629	662	24.75	26.00	0.04	0.10
ZX25GL	ZX	635	668	25.00	26.25	0.04	0.10
ZX25.5GL	ZX	648	681	25.50	26.75	0.04	0.10
ZX25.75GL	ZX	654	687	25.75	27.00	0.04	0.10
ZX26GL	ZX	660	693	26.00	27.25	0.04	0.10
ZX26.5GL	ZX	673	706	26.50	27.75	0.04	0.11
ZX27GL	ZX	686	719	27.00	28.25	0.04	0.11
ZX27.5GL	ZX	699	732	27.50	28.75	0.04	0.11
ZX28GL	ZX	711	744	28.00	29.25	0.04	0.11
ZX28.5GL	ZX	724	757	28.50	29.75	0.05	0.11
ZX29GL	ZX	737	770	29.00	30.25	0.05	0.12
ZX29.5GL	ZX	749	782	29.50	30.75	0.05	0.12
ZX30GL	ZX	762	795	30.00	31.25	0.05	0.12
ZX30.5GL	ZX	775	808	30.50	31.75	0.05	0.12
ZX30.75GL	ZX	781	814	30.75	32.00	0.05	0.12
ZX31GL	ZX	787	820	31.00	32.25	0.05	0.12
ZX31.5GL	ZX	800	833	31.50	32.75	0.05	0.13

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX32GL	ZX	813	846	32.00	33.25	0.05	0.13
ZX32.5GL	ZX	826	859	32.50	33.75	0.05	0.13
ZX33GL	ZX	838	871	33.00	34.25	0.05	0.13
ZX33.5GL	ZX	851	884	33.50	34.75	0.05	0.13
ZX34GL	ZX	864	897	34.00	35.25	0.05	0.14
ZX34.25GL	ZX	870	903	34.25	35.50	0.05	0.14
ZX34.5GL	ZX	876	909	34.50	35.75	0.06	0.14
ZX35GL	ZX	889	922	35.00	36.25	0.06	0.14
ZX35.5GL	ZX	902	935	35.50	36.75	0.06	0.14
ZX36GL	ZX	914	947	36.00	37.25	0.06	0.14
ZX36.5GL	ZX	927	960	36.50	37.75	0.06	0.15
ZX36.75GL	ZX	933	966	36.75	38.00	0.06	0.15
ZX37GL	ZX	940	973	37.00	38.25	0.06	0.15
ZX37.5GL	ZX	953	986	37.50	38.75	0.06	0.15
ZX38GL	ZX	965	998	38.00	39.25	0.06	0.15
ZX38.25GL	ZX	972	1005	38.25	39.50	0.06	0.15
ZX38.5GL	ZX	978	1011	38.50	39.75	0.06	0.15
ZX39GL	ZX	991	1024	39.00	40.25	0.06	0.16
ZX39.5GL	ZX	1003	1036	39.50	40.75	0.06	0.16
ZX40GL	ZX	1016	1049	40.00	41.25	0.06	0.16
ZX40.5GL	ZX	1029	1062	40.50	41.75	0.06	0.16
ZX41GL	ZX	1041	1074	41.00	42.25	0.07	0.16
ZX41.5GL	ZX	1054	1087	41.50	42.75	0.07	0.17
ZX41.75GL	ZX	1060	1093	41.75	43.00	0.07	0.17
ZX42GL	ZX	1067	1100	42.00	43.25	0.07	0.17
ZX42.5GL	ZX	1080	1113	42.50	43.75	0.07	0.17
ZX43GL	ZX	1092	1125	43.00	44.25	0.07	0.17
ZX43.25GL	ZX	1099	1132	43.25	44.50	0.07	0.17
ZX44GL	ZX	1118	1151	44.00	45.25	0.07	0.18
ZX45GL	ZX	1143	1176	45.00	46.25	0.07	0.18
ZX46GL	ZX	1168	1201	46.00	47.25	0.07	0.18
ZX46.75GL	ZX	1187	1220	46.75	48.00	0.07	0.19

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX47GL	ZX	1194	1227	47.00	48.25	0.08	0.19
ZX47.5GL	ZX	1207	1240	47.50	48.75	0.08	0.19
ZX47.75GL	ZX	1213	1246	47.75	49.00	0.08	0.19
ZX48GL	ZX	1219	1252	48.00	49.25	0.08	0.19
ZX49GL	ZX	1245	1278	49.00	50.25	0.08	0.20
ZX50GL	ZX	1270	1303	50.00	51.25	0.08	0.20
ZX50.5GL	ZX	1283	1316	50.50	51.75	0.08	0.20
ZX51GL	ZX	1295	1328	51.00	52.25	0.08	0.20
ZX52GL	ZX	1321	1354	52.00	53.25	0.08	0.21
ZX53GL	ZX	1346	1379	53.00	54.25	0.08	0.21
ZX54GL	ZX	1372	1405	54.00	55.25	0.09	0.22
ZX55GL	ZX	1397	1430	55.00	56.25	0.09	0.22
ZX56GL	ZX	1422	1455	56.00	57.25	0.09	0.22
ZX57GL	ZX	1448	1481	57.00	58.25	0.09	0.23
ZX58GL	ZX	1473	1506	58.00	59.25	0.09	0.23
ZX59GL	ZX	1499	1532	59.00	60.25	0.09	0.24
ZX59.5GL	ZX	1511	1544	59.50	60.75	0.10	0.24
ZX60GL	ZX	1524	1557	60.00	61.25	0.10	0.24
ZX61GL	ZX	1549	1582	61.00	62.25	0.10	0.24
ZX62GL	ZX	1575	1608	62.00	63.25	0.10	0.25
ZX63GL	ZX	1600	1633	63.00	64.25	0.10	0.25
ZX64GL	ZX	1626	1659	64.00	65.25	0.10	0.26
ZX65GL	ZX	1651	1684	65.00	66.25	0.10	0.26
ZX66GL	ZX	1676	1709	66.00	67.25	0.11	0.26
ZX67GL	ZX	1702	1735	67.00	68.25	0.11	0.27
ZX68GL	ZX	1727	1760	68.00	69.25	0.11	0.27
ZX69GL	ZX	1753	1786	69.00	70.25	0.11	0.28
ZX70GL	ZX	1778	1811	70.00	71.25	0.11	0.28
ZX71GL	ZX	1803	1836	71.00	72.25	0.11	0.28
ZX73GL	ZX	1854	1887	73.00	74.25	0.12	0.29
ZX75GL	ZX	1905	1938	75.00	76.25	0.12	0.30

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX76GL	ZX	1930	1963	76.00	77.25	0.12	0.30
ZX78GL	ZX	1981	2014	78.00	79.25	0.12	0.31
ZX79GL	ZX	2007	2040	79.00	80.25	0.13	0.32
ZX80GL	ZX	2032	2065	80.00	81.25	0.13	0.32
ZX83GL	ZX	2108	2141	83.00	84.25	0.13	0.33
ZX85GL	ZX	2159	2192	85.00	86.25	0.14	0.34
ZX88GL	ZX	2235	2268	88.00	89.25	0.14	0.35
ZX90GL	ZX	2286	2319	90.00	91.25	0.14	0.36
ZX95GL	ZX	2413	2446	95.00	96.25	0.15	0.38
ZX98GL	ZX	2489	2522	98.00	99.25	0.16	0.39
AX18GL	AX	457	508	18.00	20.00	0.04	0.09
AX19GL	AX	483	534	19.00	21.00	0.05	0.10
AX20GL	AX	508	559	20.00	22.00	0.05	0.10
AX21GL	AX	533	584	21.00	23.00	0.05	0.10
AX22GL	AX	559	610	22.00	24.00	0.05	0.11
AX22.75GL	AX	578	629	22.75	24.75	0.05	0.11
AX23GL	AX	584	635	23.00	25.00	0.05	0.11
AX23.5GL	AX	597	648	23.50	25.50	0.06	0.12
AX24GL	AX	610	661	24.00	26.00	0.06	0.12
AX25GL	AX	635	686	25.00	27.00	0.06	0.13
AX25.5GL	AX	648	699	25.50	27.50	0.06	0.13
AX26GL	AX	660	711	26.00	28.00	0.06	0.13
AX26.5GL	AX	673	724	26.50	28.50	0.06	0.13
AX27GL	AX	686	737	27.00	29.00	0.06	0.14
AX27.5GL	AX	699	750	27.50	29.50	0.07	0.14
AX28GL	AX	711	762	28.00	30.00	0.07	0.14
AX28.5GL	AX	724	775	28.50	30.50	0.07	0.14
AX29GL	AX	737	788	29.00	31.00	0.07	0.15
AX29.5GL	AX	749	800	29.50	31.50	0.07	0.15
AX30GL	AX	762	813	30.00	32.00	0.07	0.15
AX30.5GL	AX	775	826	30.50	32.50	0.07	0.15
AX31GL	AX	787	838	31.00	33.00	0.07	0.15

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX31.5GL	AX	800	851	31.50	33.50	0.08	0.16
AX32GL	AX	813	864	32.00	34.00	0.08	0.16
AX32.5GL	AX	826	877	32.50	34.50	0.08	0.16
AX33GL	AX	838	889	33.00	35.00	0.08	0.16
AX33.5GL	AX	851	902	33.50	35.50	0.08	0.17
AX34GL	AX	864	915	34.00	36.00	0.08	0.17
AX35GL	AX	889	940	35.00	37.00	0.08	0.18
AX35.5GL	AX	902	953	35.50	37.50	0.08	0.18
AX36GL	AX	914	965	36.00	38.00	0.09	0.18
AX36.25GL	AX	921	972	36.25	38.25	0.09	0.18
AX36.5GL	AX	927	978	36.50	38.50	0.09	0.18
AX37GL	AX	940	991	37.00	39.00	0.09	0.19
AX37.5GL	AX	953	1004	37.50	39.50	0.09	0.19
AX38GL	AX	965	1016	38.00	40.00	0.09	0.19
AX38.5GL	AX	978	1029	38.50	40.50	0.09	0.19
AX39GL	AX	991	1042	39.00	41.00	0.09	0.20
AX40GL	AX	1016	1067	40.00	42.00	0.10	0.20
AX40.5GL	AX	1029	1080	40.50	42.50	0.10	0.20
AX41GL	AX	1041	1092	41.00	43.00	0.10	0.20
AX41.5GL	AX	1054	1105	41.50	43.50	0.10	0.21
AX42GL	AX	1067	1118	42.00	44.00	0.10	0.21
AX42.5GL	AX	1080	1131	42.50	44.50	0.10	0.21
AX43GL	AX	1092	1143	43.00	45.00	0.10	0.21
AX44GL	AX	1118	1169	44.00	46.00	0.11	0.22
AX45GL	AX	1143	1194	45.00	47.00	0.11	0.23
AX45.25GL	AX	1149	1200	45.25	47.25	0.11	0.23
AX45.5GL	AX	1156	1207	45.50	47.50	0.11	0.23
AX46GL	AX	1168	1219	46.00	48.00	0.11	0.23
AX46.5GL	AX	1181	1232	46.50	48.50	0.11	0.23
AX47GL	AX	1194	1245	47.00	49.00	0.11	0.24
AX48GL	AX	1219	1270	48.00	50.00	0.11	0.24
AX49GL	AX	1245	1296	49.00	51.00	0.12	0.25

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX50GL	AX	1270	1321	50.00	52.00	0.12	0.25
AX51GL	AX	1295	1346	51.00	53.00	0.12	0.25
AX52GL	AX	1321	1372	52.00	54.00	0.12	0.26
AX53GL	AX	1346	1397	53.00	55.00	0.13	0.26
AX54GL	AX	1372	1423	54.00	56.00	0.13	0.27
AX55GL	AX	1397	1448	55.00	57.00	0.13	0.28
AX56GL	AX	1422	1473	56.00	58.00	0.13	0.28
AX57GL	AX	1448	1499	57.00	59.00	0.14	0.29
AX58GL	AX	1473	1524	58.00	60.00	0.14	0.29
AX59GL	AX	1499	1550	59.00	61.00	0.14	0.30
AX60GL	AX	1524	1575	60.00	62.00	0.14	0.30
AX61GL	AX	1549	1600	61.00	63.00	0.15	0.30
AX62GL	AX	1575	1626	62.00	64.00	0.15	0.31
AX63GL	AX	1600	1651	63.00	65.00	0.15	0.31
AX63.5GL	AX	1613	1664	63.50	65.50	0.15	0.32
AX64GL	AX	1626	1677	64.00	66.00	0.15	0.32
AX65GL	AX	1651	1702	65.00	67.00	0.16	0.33
AX65.5GL	AX	1664	1715	65.50	67.50	0.16	0.33
AX66GL	AX	1676	1727	66.00	68.00	0.16	0.33
AX67GL	AX	1702	1753	67.00	69.00	0.16	0.34
AX67.5GL	AX	1715	1766	67.50	69.50	0.16	0.34
AX68GL	AX	1727	1778	68.00	70.00	0.16	0.34
AX69GL	AX	1753	1804	69.00	71.00	0.16	0.35
AX70GL	AX	1778	1829	70.00	72.00	0.17	0.35
AX71GL	AX	1803	1854	71.00	73.00	0.17	0.35
AX71.5GL	AX	1816	1867	71.50	73.50	0.17	0.36
AX72GL	AX	1829	1880	72.00	74.00	0.17	0.36
AX73GL	AX	1854	1905	73.00	75.00	0.17	0.36
AX74GL	AX	1880	1931	74.00	76.00	0.18	0.37
AX75GL	AX	1905	1956	75.00	77.00	0.18	0.38
AX75.5GL	AX	1918	1969	75.50	77.50	0.18	0.38
AX76GL	AX	1930	1981	76.00	78.00	0.18	0.38

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX77GL	AX	1956	2007	77.00	79.00	0.18	0.39
AX78GL	AX	1981	2032	78.00	80.00	0.19	0.39
AX79GL	AX	2007	2058	79.00	81.00	0.19	0.40
AX80GL	AX	2032	2083	80.00	82.00	0.19	0.40
AX81GL	AX	2057	2108	81.00	83.00	0.19	0.40
AX82GL	AX	2083	2134	82.00	84.00	0.20	0.41
AX83GL	AX	2108	2159	83.00	85.00	0.20	0.41
AX84GL	AX	2134	2185	84.00	86.00	0.20	0.42
AX85GL	AX	2159	2210	85.00	87.00	0.20	0.43
AX86GL	AX	2184	2235	86.00	88.00	0.21	0.43
AX87GL	AX	2210	2261	87.00	89.00	0.21	0.44
AX88GL	AX	2235	2286	88.00	90.00	0.21	0.44
AX89GL	AX	2261	2312	89.00	91.00	0.21	0.45
AX90GL	AX	2286	2337	90.00	92.00	0.21	0.45
AX91GL	AX	2311	2362	91.00	93.00	0.22	0.45
AX92GL	AX	2337	2388	92.00	94.00	0.22	0.46
AX93GL	AX	2362	2413	93.00	95.00	0.22	0.46
AX94GL	AX	2388	2439	94.00	96.00	0.22	0.47
AX95GL	AX	2413	2464	95.00	97.00	0.23	0.48
AX96GL	AX	2438	2489	96.00	98.00	0.23	0.48
AX97GL	AX	2464	2515	97.00	99.00	0.23	0.49
AX98GL	AX	2489	2540	98.00	100.00	0.23	0.49
AX100GL	AX	2540	2591	100.00	102.00	0.24	0.50
AX101GL	AX	2565	2616	101.00	103.00	0.24	0.50
AX102GL	AX	2591	2642	102.00	104.00	0.24	0.51
AX103GL	AX	2616	2667	103.00	105.00	0.25	0.51
AX105GL	AX	2667	2718	105.00	107.00	0.25	0.53
AX106GL	AX	2692	2743	106.00	108.00	0.25	0.53
AX107GL	AX	2718	2769	107.00	109.00	0.26	0.54
AX108GL	AX	2743	2794	108.00	110.00	0.26	0.54
AX109GL	AX	2769	2820	109.00	111.00	0.26	0.55
AX110GL	AX	2794	2845	110.00	112.00	0.26	0.55

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX112GL	AX	2845	2896	112.00	114.00	0.27	0.56
AX114GL	AX	2896	2947	114.00	116.00	0.27	0.57
AX115GL	AX	2921	2972	115.00	117.00	0.27	0.58
* AX118GL	AX	2997	3048	118.00	120.00	0.28	0.59
* AX120GL	AX	3048	3099	120.00	122.00	0.29	0.60
* AX128GL	AX	3251	3302	128.00	130.00	0.31	0.64
* AX130GL	AX	3302	3353	130.00	132.00	0.31	0.65
* AX136GL	AX	3454	3505	136.00	138.00	0.32	0.68
BX22GL	BX	559	623	22.00	24.50	0.07	0.15
BX23GL	BX	584	648	23.00	25.50	0.08	0.16
BX24GL	BX	610	674	24.00	26.50	0.08	0.17
BX25GL	BX	635	699	25.00	27.50	0.09	0.18
BX26GL	BX	660	724	26.00	28.50	0.09	0.18
BX26.5GL	BX	673	737	26.50	29.00	0.09	0.19
BX27GL	BX	686	750	27.00	29.50	0.09	0.19
BX28GL	BX	711	775	28.00	30.50	0.10	0.20
BX28.5GL	BX	724	788	28.50	31.00	0.10	0.20
BX29GL	BX	737	801	29.00	31.50	0.10	0.20
BX29.5GL	BX	749	813	29.50	32.00	0.10	0.21
BX30GL	BX	762	826	30.00	32.50	0.10	0.21
BX31GL	BX	787	851	31.00	33.50	0.11	0.22
BX31.5GL	BX	800	864	31.50	34.00	0.11	0.22
BX32GL	BX	813	877	32.00	34.50	0.11	0.22
BX32.5GL	BX	826	890	32.50	35.00	0.11	0.23
BX33GL	BX	838	902	33.00	35.50	0.11	0.23
BX33.5GL	BX	851	915	33.50	36.00	0.11	0.23
BX34GL	BX	864	928	34.00	36.50	0.12	0.24
BX34.5GL	BX	876	940	34.50	37.00	0.12	0.24
BX35GL	BX	889	953	35.00	37.50	0.12	0.25
BX35.5GL	BX	902	966	35.50	38.00	0.12	0.25
BX35.75GL	BX	908	972	35.75	38.25	0.12	0.25
BX36GL	BX	914	978	36.00	38.50	0.12	0.25

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX36.25GL	BX	921	985	36.25	38.75	0.12	0.25
BX36.5GL	BX	927	991	36.50	39.00	0.12	0.26
BX37GL	BX	940	1004	37.00	39.50	0.13	0.26
BX37.5GL	BX	953	1017	37.50	40.00	0.13	0.26
BX38GL	BX	965	1029	38.00	40.50	0.13	0.27
BX38.5GL	BX	978	1042	38.50	41.00	0.13	0.27
BX39GL	BX	991	1055	39.00	41.50	0.13	0.27
BX39.5GL	BX	1003	1067	39.50	42.00	0.13	0.28
BX40GL	BX	1016	1080	40.00	42.50	0.14	0.28
BX40.5GL	BX	1029	1093	40.50	43.00	0.14	0.28
BX41GL	BX	1041	1105	41.00	43.50	0.14	0.29
BX41.5GL	BX	1054	1118	41.50	44.00	0.14	0.29
BX42GL	BX	1067	1131	42.00	44.50	0.14	0.29
BX42.5GL	BX	1080	1144	42.50	45.00	0.14	0.30
BX43GL	BX	1092	1156	43.00	45.50	0.15	0.30
BX43.25GL	BX	1099	1163	43.25	45.75	0.15	0.30
BX44GL	BX	1118	1182	44.00	46.50	0.15	0.31
BX45GL	BX	1143	1207	45.00	47.50	0.15	0.32
BX45.5GL	BX	1156	1220	45.50	48.00	0.15	0.32
BX46GL	BX	1168	1232	46.00	48.50	0.16	0.32
BX46.5GL	BX	1181	1245	46.50	49.00	0.16	0.33
BX47GL	BX	1194	1258	47.00	49.50	0.16	0.33
BX47.5GL	BX	1207	1271	47.50	50.00	0.16	0.33
BX48GL	BX	1219	1283	48.00	50.50	0.16	0.34
BX49GL	BX	1245	1309	49.00	51.50	0.17	0.34
BX49.5GL	BX	1257	1321	49.50	52.00	0.17	0.35
BX50GL	BX	1270	1334	50.00	52.50	0.17	0.35
BX50.5GL	BX	1283	1347	50.50	53.00	0.17	0.35
BX51GL	BX	1295	1359	51.00	53.50	0.17	0.36
BX52GL	BX	1321	1385	52.00	54.50	0.18	0.36
BX52.5GL	BX	1334	1398	52.50	55.00	0.18	0.37
BX53GL	BX	1346	1410	53.00	55.50	0.18	0.37

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX53.5GL	BX	1359	1423	53.50	56.00	0.18	0.37
BX54GL	BX	1372	1436	54.00	56.50	0.18	0.38
BX55GL	BX	1397	1461	55.00	57.50	0.19	0.39
BX56GL	BX	1422	1486	56.00	58.50	0.19	0.39
BX57GL	BX	1448	1512	57.00	59.50	0.19	0.40
BX57.5GL	BX	1461	1525	57.50	60.00	0.20	0.40
BX58GL	BX	1473	1537	58.00	60.50	0.20	0.41
BX59GL	BX	1499	1563	59.00	61.50	0.20	0.41
BX60GL	BX	1524	1588	60.00	62.50	0.20	0.42
BX61GL	BX	1549	1613	61.00	63.50	0.21	0.43
BX61.5GL	BX	1562	1626	61.50	64.00	0.21	0.43
BX62GL	BX	1575	1639	62.00	64.50	0.21	0.43
BX63GL	BX	1600	1664	63.00	65.50	0.21	0.44
BX63.5GL	BX	1613	1677	63.50	66.00	0.22	0.44
BX64GL	BX	1626	1690	64.00	66.50	0.22	0.45
BX65GL	BX	1651	1715	65.00	67.50	0.22	0.46
BX66GL	BX	1676	1740	66.00	68.50	0.22	0.46
BX67GL	BX	1702	1766	67.00	69.50	0.23	0.47
BX67.5GL	BX	1715	1779	67.50	70.00	0.23	0.47
BX68GL	BX	1727	1791	68.00	70.50	0.23	0.48
BX69GL	BX	1753	1817	69.00	71.50	0.23	0.48
BX69.5GL	BX	1765	1829	69.50	72.00	0.24	0.49
BX70GL	BX	1778	1842	70.00	72.50	0.24	0.49
BX71GL	BX	1803	1867	71.00	73.50	0.24	0.50
BX72GL	BX	1829	1893	72.00	74.50	0.25	0.50
BX73GL	BX	1854	1918	73.00	75.50	0.25	0.51
BX74GL	BX	1880	1944	74.00	76.50	0.25	0.52
BX75GL	BX	1905	1969	75.00	77.50	0.26	0.53
BX76GL	BX	1930	1994	76.00	78.50	0.26	0.53
BX77GL	BX	1956	2020	77.00	79.50	0.26	0.54
BX78GL	BX	1981	2045	78.00	80.50	0.27	0.55
BX79GL	BX	2007	2071	79.00	81.50	0.27	0.55

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX80GL	BX	2032	2096	80.00	82.50	0.27	0.56
BX81GL	BX	2057	2121	81.00	83.50	0.28	0.57
BX82GL	BX	2083	2147	82.00	84.50	0.28	0.57
BX83GL	BX	2108	2172	83.00	85.50	0.28	0.58
BX83.5GL	BX	2121	2185	83.50	86.00	0.28	0.58
BX84GL	BX	2134	2198	84.00	86.50	0.29	0.59
BX85GL	BX	2159	2223	85.00	87.50	0.29	0.60
BX86GL	BX	2184	2248	86.00	88.50	0.29	0.60
BX87GL	BX	2210	2274	87.00	89.50	0.30	0.61
BX88GL	BX	2235	2299	88.00	90.50	0.30	0.62
BX89GL	BX	2261	2325	89.00	91.50	0.30	0.62
BX90GL	BX	2286	2350	90.00	92.50	0.31	0.63
BX91GL	BX	2311	2375	91.00	93.50	0.31	0.64
BX91.5GL	BX	2324	2388	91.50	94.00	0.31	0.64
BX92GL	BX	2337	2401	92.00	94.50	0.31	0.64
BX93GL	BX	2362	2426	93.00	95.50	0.32	0.65
BX94GL	BX	2388	2452	94.00	96.50	0.32	0.66
* BX95GL	BX	2413	2477	95.00	97.50	0.32	0.67
* BX96GL	BX	2438	2502	96.00	98.50	0.33	0.67
* BX97GL	BX	2464	2528	97.00	99.50	0.33	0.68
* BX98GL	BX	2489	2553	98.00	100.50	0.33	0.69
* BX99GL	BX	2515	2579	99.00	101.50	0.34	0.69
* BX100GL	BX	2540	2604	100.00	102.50	0.34	0.70
* BX101GL	BX	2565	2629	101.00	103.50	0.34	0.71
* BX102GL	BX	2591	2655	102.00	104.50	0.35	0.71
* BX102.5GL	BX	2604	2668	102.50	105.00	0.35	0.72
* BX103GL	BX	2616	2680	103.00	105.50	0.35	0.72
* BX104GL	BX	2642	2706	104.00	106.50	0.35	0.73
* BX105GL	BX	2667	2731	105.00	107.50	0.36	0.74
* BX106GL	BX	2692	2756	106.00	108.50	0.36	0.74
* BX107GL	BX	2718	2782	107.00	109.50	0.36	0.75
* BX108GL	BX	2743	2807	108.00	110.50	0.37	0.76

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
* BX108.5GL	BX	2756	2820	108.50	111.00	0.37	0.76
* BX110GL	BX	2794	2858	110.00	112.50	0.37	0.77
* BX111GL	BX	2819	2883	111.00	113.50	0.38	0.78
* BX112GL	BX	2845	2909	112.00	114.50	0.38	0.78
BX113GL	BX	2870	2934	113.00	115.50	0.38	0.79
BX114GL	BX	2896	2960	114.00	116.50	0.39	0.80
* BX115GL	BX	2921	2985	115.00	117.50	0.39	0.81
* BX116GL	BX	2946	3010	116.00	118.50	0.39	0.81
* BX118GL	BX	2997	3061	118.00	120.50	0.40	0.83
* BX119GL	BX	3023	3087	119.00	121.50	0.41	0.83
* BX120GL	BX	3048	3112	120.00	122.50	0.41	0.84
* BX123GL	BX	3124	3188	123.00	125.50	0.42	0.86
* BX124GL	BX	3150	3214	124.00	126.50	0.42	0.87
* BX126GL	BX	3200	3264	126.00	128.50	0.43	0.88
* BX128GL	BX	3251	3315	128.00	130.50	0.44	0.90
* BX130GL	BX	3302	3366	130.00	132.50	0.44	0.91
* BX132GL	BX	3353	3417	132.00	134.50	0.45	0.92
* BX136GL	BX	3454	3518	136.00	138.50	0.46	0.95
CX42GL	CX	1067	1142	42.00	45.00	0.25	0.55
CX43GL	CX	1092	1167	43.00	46.00	0.26	0.56
CX46.5GL	CX	1181	1256	46.50	49.50	0.28	0.60
CX47GL	CX	1194	1269	47.00	50.00	0.28	0.61
CX49GL	CX	1245	1320	49.00	52.00	0.29	0.64
CX50GL	CX	1270	1345	50.00	53.00	0.30	0.65
CX51GL	CX	1295	1370	51.00	54.00	0.31	0.66
CX52GL	CX	1321	1396	52.00	55.00	0.31	0.68
CX53GL	CX	1346	1421	53.00	56.00	0.32	0.69
CX54GL	CX	1372	1447	54.00	57.00	0.32	0.70
CX55GL	CX	1397	1472	55.00	58.00	0.33	0.72
CX56GL	CX	1422	1497	56.00	59.00	0.34	0.73
CX57GL	CX	1448	1523	57.00	60.00	0.34	0.74
CX58GL	CX	1473	1548	58.00	61.00	0.35	0.75

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
CX59GL	CX	1499	1574	59.00	62.00	0.35	0.77
CX60GL	CX	1524	1599	60.00	63.00	0.36	0.78
CX61GL	CX	1549	1624	61.00	64.00	0.37	0.79
CX62GL	CX	1575	1650	62.00	65.00	0.37	0.81
CX63GL	CX	1600	1675	63.00	66.00	0.38	0.82
CX64GL	CX	1626	1701	64.00	67.00	0.38	0.83
CX65GL	CX	1651	1726	65.00	68.00	0.39	0.85
CX66GL	CX	1676	1751	66.00	69.00	0.40	0.86
CX67GL	CX	1702	1777	67.00	70.00	0.40	0.87
CX68GL	CX	1727	1802	68.00	71.00	0.41	0.88
CX69GL	CX	1753	1828	69.00	72.00	0.41	0.90
CX70GL	CX	1778	1853	70.00	73.00	0.42	0.91
CX71GL	CX	1803	1878	71.00	74.00	0.43	0.92
CX72GL	CX	1829	1904	72.00	75.00	0.43	0.94
CX73GL	CX	1854	1929	73.00	76.00	0.44	0.95
CX74GL	CX	1880	1955	74.00	77.00	0.44	0.96
CX74.5GL	CX	1892	1967	74.50	77.50	0.45	0.97
CX75GL	CX	1905	1980	75.00	78.00	0.45	0.98
CX76GL	CX	1930	2005	76.00	79.00	0.46	0.99
CX76.25GL	CX	1937	2012	76.25	79.25	0.46	0.99
CX77GL	CX	1956	2031	77.00	80.00	0.46	1.00
CX78GL	CX	1981	2056	78.00	81.00	0.47	1.01
CX79GL	CX	2007	2082	79.00	82.00	0.47	1.03
CX80GL	CX	2032	2107	80.00	83.00	0.48	1.04
CX81GL	CX	2057	2132	81.00	84.00	0.49	1.05
CX82GL	CX	2083	2158	82.00	85.00	0.49	1.07
CX83GL	CX	2108	2183	83.00	86.00	0.50	1.08
CX84GL	CX	2134	2209	84.00	87.00	0.50	1.09
CX85GL	CX	2159	2234	85.00	88.00	0.51	1.11
CX86GL	CX	2184	2259	86.00	89.00	0.52	1.12
CX87GL	CX	2210	2285	87.00	90.00	0.52	1.13
CX88GL	CX	2235	2310	88.00	91.00	0.53	1.14

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
CX89GL	CX	2261	2336	89.00	92.00	0.53	1.16
CX90GL	CX	2286	2361	90.00	93.00	0.54	1.17
CX91GL	CX	2311	2386	91.00	94.00	0.55	1.18
CX92GL	CX	2337	2412	92.00	95.00	0.55	1.20
CX93GL	CX	2362	2437	93.00	96.00	0.56	1.21
CX94GL	CX	2388	2463	94.00	97.00	0.56	1.22
* CX95GL	CX	2413	2488	95.00	98.00	0.57	1.24
* CX96GL	CX	2438	2513	96.00	99.00	0.58	1.25
* CX97GL	CX	2464	2539	97.00	100.00	0.58	1.26
* CX98GL	CX	2489	2564	98.00	101.00	0.59	1.27
* CX98.5GL	CX	2502	2577	98.50	101.50	0.59	1.28
* CX99GL	CX	2515	2590	99.00	102.00	0.59	1.29
* CX100GL	CX	2540	2615	100.00	103.00	0.60	1.30
* CX101GL	CX	2565	2640	101.00	104.00	0.61	1.31
* CX102GL	CX	2591	2666	102.00	105.00	0.61	1.33
* CX103GL	CX	2616	2691	103.00	106.00	0.62	1.34
* CX104GL	CX	2642	2717	104.00	107.00	0.62	1.35
* CX105GL	CX	2667	2742	105.00	108.00	0.63	1.37
* CX107GL	CX	2718	2793	107.00	110.00	0.64	1.39
* CX108GL	CX	2743	2818	108.00	111.00	0.65	1.40
* CX109GL	CX	2769	2844	109.00	112.00	0.65	1.42
* CX110GL	CX	2794	2869	110.00	113.00	0.66	1.43
* CX111GL	CX	2819	2894	111.00	114.00	0.67	1.44
* CX112GL	CX	2845	2920	112.00	115.00	0.67	1.46
CX113GL	CX	2870	2945	113.00	116.00	0.68	1.47
CX114GL	CX	2896	2971	114.00	117.00	0.68	1.48
* CX115GL	CX	2921	2996	115.00	118.00	0.69	1.50
* CX116GL	CX	2946	3021	116.00	119.00	0.70	1.51
* CX117GL	CX	2972	3047	117.00	120.00	0.70	1.52
* CX118GL	CX	2997	3072	118.00	121.00	0.71	1.53
* CX119GL	CX	3023	3098	119.00	122.00	0.71	1.55
* CX120GL	CX	3048	3123	120.00	123.00	0.72	1.56
* CX124GL	CX	3150	3225	124.00	127.00	0.74	1.61

GOLD LABEL X Narrow - Product Description



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

V-Belt Raw Edge

Part Number Description: **3VX300GL**

3VX: Profile (9mm X 8mm)

300: Outside Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching


Designed for OEMs

Markets and Applications:

Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps...), in particular where temperature, power capacity, space and weight are critical.


Pulley Standards: ARPM/MPTA IP-22

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
3VX220GL	3VX	559	22.00	0.03	0.07
3VX230GL	3VX	584	23.00	0.03	0.07
3VX250GL	3VX	635	25.00	0.03	0.08
3VX255GL	3VX	648	25.50	0.03	0.08
3VX260GL	3VX	660	26.00	0.04	0.08
3VX265GL	3VX	673	26.50	0.04	0.08
3VX270GL	3VX	686	27.00	0.04	0.08
3VX275GL	3VX	699	27.50	0.04	0.08
3VX280GL	3VX	711	28.00	0.04	0.08
3VX290GL	3VX	737	29.00	0.04	0.09
3VX295GL	3VX	749	29.50	0.04	0.09
3VX300GL	3VX	762	30.00	0.04	0.09
3VX305GL	3VX	775	30.50	0.04	0.09
3VX310GL	3VX	787	31.00	0.04	0.09
3VX315GL	3VX	800	31.50	0.04	0.09
3VX320GL	3VX	813	32.00	0.04	0.10
3VX325GL	3VX	826	32.50	0.04	0.10
3VX330GL	3VX	838	33.00	0.05	0.10
3VX335GL	3VX	851	33.50	0.05	0.10
3VX340GL	3VX	864	34.00	0.05	0.10
3VX345GL	3VX	876	34.50	0.05	0.10
3VX350GL	3VX	889	35.00	0.05	0.11
3VX355GL	3VX	902	35.50	0.05	0.11
3VX360GL	3VX	914	36.00	0.05	0.11
3VX365GL	3VX	927	36.50	0.05	0.11
3VX370GL	3VX	940	37.00	0.05	0.11
3VX375GL	3VX	953	37.50	0.05	0.11
3VX380GL	3VX	965	38.00	0.05	0.11
3VX385GL	3VX	978	38.50	0.05	0.12
3VX390GL	3VX	991	39.00	0.05	0.12
3VX395GL	3VX	1003	39.50	0.05	0.12
3VX400GL	3VX	1016	40.00	0.05	0.12
3VX405GL	3VX	1029	40.50	0.06	0.12
3VX410GL	3VX	1041	41.00	0.06	0.12
3VX415GL	3VX	1054	41.50	0.06	0.12
3VX420GL	3VX	1067	42.00	0.06	0.13
3VX425GL	3VX	1080	42.50	0.06	0.13
3VX430GL	3VX	1092	43.00	0.06	0.13
3VX440GL	3VX	1118	44.00	0.06	0.13
3VX445GL	3VX	1130	44.50	0.06	0.13

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
3VX450GL	3VX	1143	45.00	0.06	0.14
3VX455GL	3VX	1156	45.50	0.06	0.14
3VX460GL	3VX	1168	46.00	0.06	0.14
3VX465GL	3VX	1181	46.50	0.06	0.14
3VX470GL	3VX	1194	47.00	0.06	0.14
3VX475GL	3VX	1207	47.50	0.07	0.14
3VX480GL	3VX	1219	48.00	0.07	0.14
3VX490GL	3VX	1245	49.00	0.07	0.15
3VX495GL	3VX	1257	49.50	0.07	0.15
3VX500GL	3VX	1270	50.00	0.07	0.15
3VX505GL	3VX	1283	50.50	0.07	0.15
3VX510GL	3VX	1295	51.00	0.07	0.15
3VX515GL	3VX	1308	51.50	0.07	0.15
3VX520GL	3VX	1321	52.00	0.07	0.16
3VX525GL	3VX	1334	52.50	0.07	0.16
3VX530GL	3VX	1346	53.00	0.07	0.16
3VX535GL	3VX	1359	53.50	0.07	0.16
3VX540GL	3VX	1372	54.00	0.07	0.16
3VX545GL	3VX	1384	54.50	0.07	0.16
3VX550GL	3VX	1397	55.00	0.08	0.17
3VX555GL	3VX	1410	55.50	0.08	0.17
3VX560GL	3VX	1422	56.00	0.08	0.17
3VX565GL	3VX	1435	56.50	0.08	0.17
3VX570GL	3VX	1448	57.00	0.08	0.17
3VX575GL	3VX	1461	57.50	0.08	0.17
3VX580GL	3VX	1473	58.00	0.08	0.17
3VX585GL	3VX	1486	58.50	0.08	0.18
3VX590GL	3VX	1499	59.00	0.08	0.18
3VX595GL	3VX	1511	59.50	0.08	0.18
3VX600GL	3VX	1524	60.00	0.08	0.18
3VX610GL	3VX	1549	61.00	0.08	0.18
3VX615GL	3VX	1562	61.50	0.08	0.18
3VX620GL	3VX	1575	62.00	0.09	0.19
3VX625GL	3VX	1588	62.50	0.09	0.19
3VX630GL	3VX	1600	63.00	0.09	0.19
3VX640GL	3VX	1626	64.00	0.09	0.19
3VX645GL	3VX	1638	64.50	0.09	0.19
3VX650GL	3VX	1651	65.00	0.09	0.20
3VX670GL	3VX	1702	67.00	0.09	0.20
3VX680GL	3VX	1727	68.00	0.09	0.20

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
3VX685GL	3VX	1740	68.50	0.09	0.21
3VX690GL	3VX	1753	69.00	0.09	0.21
3VX695GL	3VX	1765	69.50	0.10	0.21
3VX700GL	3VX	1778	70.00	0.10	0.21
3VX705GL	3VX	1791	70.50	0.10	0.21
3VX710GL	3VX	1803	71.00	0.10	0.21
3VX715GL	3VX	1816	71.50	0.10	0.21
3VX720GL	3VX	1829	72.00	0.10	0.22
3VX725GL	3VX	1842	72.50	0.10	0.22
3VX735GL	3VX	1867	73.50	0.10	0.22
3VX745GL	3VX	1892	74.50	0.10	0.22
3VX750GL	3VX	1905	75.00	0.10	0.23
3VX765GL	3VX	1943	76.50	0.10	0.23
3VX780GL	3VX	1981	78.00	0.11	0.23
3VX800GL	3VX	2032	80.00	0.11	0.24
3VX850GL	3VX	2159	85.00	0.12	0.26
3VX900GL	3VX	2286	90.00	0.12	0.27
3VX950GL	3VX	2413	95.00	0.13	0.29
* 3VX1000GL	3VX	2540	100.00	0.14	0.30
* 3VX1060GL	3VX	2692	106.00	0.15	0.32
* 3VX1120GL	3VX	2845	112.00	0.15	0.34
* 3VX1180GL	3VX	2997	118.00	0.16	0.35
* 3VX1250GL	3VX	3175	125.00	0.17	0.38
* 3VX1320GL	3VX	3353	132.00	0.18	0.40
5VX220GL	5VX	559	22.00	0.07	0.15
5VX225GL	5VX	572	22.50	0.07	0.16
5VX230GL	5VX	584	23.00	0.08	0.16
5VX240GL	5VX	610	24.00	0.08	0.17
5VX245GL	5VX	622	24.50	0.08	0.17
5VX250GL	5VX	635	25.00	0.08	0.18
5VX255GL	5VX	648	25.50	0.08	0.18
5VX260GL	5VX	660	26.00	0.09	0.18
5VX270GL	5VX	686	27.00	0.09	0.19
5VX275GL	5VX	699	27.50	0.09	0.19
5VX285GL	5VX	724	28.50	0.09	0.20
5VX290GL	5VX	737	29.00	0.10	0.20
5VX295GL	5VX	749	29.50	0.10	0.21
5VX305GL	5VX	775	30.50	0.10	0.21
5VX310GL	5VX	787	31.00	0.10	0.22
5VX315GL	5VX	800	31.50	0.10	0.22

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
5VX320GL	5VX	813	32.00	0.10	0.22
5VX330GL	5VX	838	33.00	0.11	0.23
5VX335GL	5VX	851	33.50	0.11	0.23
5VX340GL	5VX	864	34.00	0.11	0.24
5VX345GL	5VX	876	34.50	0.11	0.24
5VX350GL	5VX	889	35.00	0.11	0.25
5VX355GL	5VX	902	35.50	0.12	0.25
5VX365GL	5VX	927	36.50	0.12	0.26
5VX370GL	5VX	940	37.00	0.12	0.26
5VX375GL	5VX	953	37.50	0.12	0.26
5VX380GL	5VX	965	38.00	0.12	0.27
5VX385GL	5VX	978	38.50	0.13	0.27
5VX390GL	5VX	991	39.00	0.13	0.27
5VX395GL	5VX	1003	39.50	0.13	0.28
5VX400GL	5VX	1016	40.00	0.13	0.28
5VX405GL	5VX	1029	40.50	0.13	0.28
5VX410GL	5VX	1041	41.00	0.13	0.29
5VX415GL	5VX	1054	41.50	0.14	0.29
5VX425GL	5VX	1080	42.50	0.14	0.30
5VX430GL	5VX	1092	43.00	0.14	0.30
5VX440GL	5VX	1118	44.00	0.14	0.31
5VX445GL	5VX	1130	44.50	0.15	0.31
5VX450GL	5VX	1143	45.00	0.15	0.32
5VX455GL	5VX	1156	45.50	0.15	0.32
5VX460GL	5VX	1168	46.00	0.15	0.32
5VX465GL	5VX	1181	46.50	0.15	0.33
5VX470GL	5VX	1194	47.00	0.15	0.33
5VX475GL	5VX	1207	47.50	0.16	0.33
5VX480GL	5VX	1219	48.00	0.16	0.34
5VX485GL	5VX	1232	48.50	0.16	0.34
5VX490GL	5VX	1245	49.00	0.16	0.34
5VX495GL	5VX	1257	49.50	0.16	0.35
5VX500GL	5VX	1270	50.00	0.16	0.35
5VX505GL	5VX	1283	50.50	0.17	0.35
5VX510GL	5VX	1295	51.00	0.17	0.36
5VX515GL	5VX	1308	51.50	0.17	0.36
5VX525GL	5VX	1334	52.50	0.17	0.37
5VX530GL	5VX	1346	53.00	0.17	0.37
5VX535GL	5VX	1359	53.50	0.18	0.37
5VX540GL	5VX	1372	54.00	0.18	0.38

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
5VX545GL	5VX	1384	54.50	0.18	0.38
5VX550GL	5VX	1397	55.00	0.18	0.39
5VX555GL	5VX	1410	55.50	0.18	0.39
5VX560GL	5VX	1422	56.00	0.18	0.39
5VX565GL	5VX	1435	56.50	0.19	0.40
5VX570GL	5VX	1448	57.00	0.19	0.40
5VX575GL	5VX	1461	57.50	0.19	0.40
5VX580GL	5VX	1473	58.00	0.19	0.41
5VX585GL	5VX	1486	58.50	0.19	0.41
5VX590GL	5VX	1499	59.00	0.19	0.41
5VX595GL	5VX	1511	59.50	0.19	0.42
5VX600GL	5VX	1524	60.00	0.20	0.42
5VX605GL	5VX	1537	60.50	0.20	0.42
5VX610GL	5VX	1549	61.00	0.20	0.43
5VX615GL	5VX	1562	61.50	0.20	0.43
5VX620GL	5VX	1575	62.00	0.20	0.43
5VX630GL	5VX	1600	63.00	0.21	0.44
5VX640GL	5VX	1626	64.00	0.21	0.45
5VX650GL	5VX	1651	65.00	0.21	0.46
5VX660GL	5VX	1676	66.00	0.22	0.46
5VX665GL	5VX	1689	66.50	0.22	0.47
5VX670GL	5VX	1702	67.00	0.22	0.47
5VX680GL	5VX	1727	68.00	0.22	0.48
5VX685GL	5VX	1740	68.50	0.22	0.48
5VX690GL	5VX	1753	69.00	0.23	0.48
5VX695GL	5VX	1765	69.50	0.23	0.49
5VX700GL	5VX	1778	70.00	0.23	0.49
5VX710GL	5VX	1803	71.00	0.23	0.50
5VX715GL	5VX	1816	71.50	0.23	0.50
5VX720GL	5VX	1829	72.00	0.24	0.50
5VX730GL	5VX	1854	73.00	0.24	0.51
5VX740GL	5VX	1880	74.00	0.24	0.52
5VX750GL	5VX	1905	75.00	0.25	0.53
5VX760GL	5VX	1930	76.00	0.25	0.53
5VX780GL	5VX	1981	78.00	0.26	0.55
5VX800GL	5VX	2032	80.00	0.26	0.56
5VX810GL	5VX	2057	81.00	0.27	0.57
5VX830GL	5VX	2108	83.00	0.27	0.58
5VX840GL	5VX	2134	84.00	0.28	0.59
5VX850GL	5VX	2159	85.00	0.28	0.60

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
5VX860GL	5VX	2184	86.00	0.28	0.60
5VX880GL	5VX	2235	88.00	0.29	0.62
5VX890GL	5VX	2261	89.00	0.29	0.62
5VX900GL	5VX	2286	90.00	0.29	0.63
5VX930GL	5VX	2362	93.00	0.30	0.65
5VX940GL	5VX	2388	94.00	0.31	0.66
5VX950GL	5VX	2413	95.00	0.31	0.67
5VX960GL	5VX	2438	96.00	0.31	0.67
* 5VX970GL	5VX	2464	97.00	0.32	0.68
* 5VX990GL	5VX	2515	99.00	0.32	0.69
* 5VX1000GL	5VX	2540	100.00	0.33	0.70
* 5VX1030GL	5VX	2616	103.00	0.34	0.72
* 5VX1050GL	5VX	2667	105.00	0.34	0.74
* 5VX1060GL	5VX	2692	106.00	0.35	0.74
* 5VX1080GL	5VX	2743	108.00	0.35	0.76
* 5VX1120GL	5VX	2845	112.00	0.37	0.78
* 5VX1150GL	5VX	2921	115.00	0.38	0.81
5VX1160GL	5VX	2946	116.00	0.38	0.81
* 5VX1180GL	5VX	2997	118.00	0.39	0.83
* 5VX1230GL	5VX	3124	123.00	0.40	0.86
* 5VX1250GL	5VX	3175	125.00	0.41	0.88
* 5VX1320GL	5VX	3353	132.00	0.43	0.92
* 5VX1350GL	5VX	3418	135.00	0.44	0.94
* 5VX1400GL	5VX	3545	140.00	0.46	0.98

GOLD LABEL X Wedge - Product Description



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

V-Belt Raw Edge

Part Number Description: **XPA1200GL**

XPA: Profile (13mm X 10mm)

1200: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance.

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching


Designed for OEMs

Markets and Applications:

Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps...), in particular where temperature, power capacity, space and weight are critical.


Pulley Standards: DIN2211 – ISO 4183

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ512GL	XPZ	512	20.15	0.03	0.06
XPZ520GL	XPZ	520	20.45	0.03	0.06
XPZ550GL	XPZ	550	21.65	0.03	0.06
XPZ560GL	XPZ	560	22.05	0.03	0.07
XPZ562GL	XPZ	562	22.15	0.03	0.07
XPZ580GL	XPZ	580	22.85	0.03	0.07
XPZ587GL	XPZ	587	23.10	0.04	0.07
XPZ600GL	XPZ	600	23.60	0.04	0.07
XPZ604GL	XPZ	604	23.80	0.04	0.07
XPZ612GL	XPZ	612	24.10	0.04	0.07
XPZ615GL	XPZ	615	24.20	0.04	0.07
XPZ630GL	XPZ	630	24.80	0.04	0.07
XPZ637GL	XPZ	637	25.10	0.04	0.08
XPZ640GL	XPZ	640	25.20	0.04	0.08
XPZ646GL	XPZ	646	25.45	0.04	0.08
XPZ660GL	XPZ	660	26.00	0.04	0.08
XPZ662GL	XPZ	662	26.05	0.04	0.08
XPZ670GL	XPZ	670	26.40	0.04	0.08
XPZ672GL	XPZ	672	26.45	0.04	0.08
XPZ675GL	XPZ	675	26.60	0.04	0.08
XPZ682GL	XPZ	682	26.85	0.04	0.08
XPZ687GL	XPZ	687	27.05	0.04	0.08
XPZ690GL	XPZ	690	27.15	0.04	0.08
XPZ700GL	XPZ	700	27.55	0.04	0.08
XPZ710GL	XPZ	710	27.95	0.04	0.08
XPZ722GL	XPZ	722	28.40	0.04	0.09
XPZ725GL	XPZ	725	28.55	0.04	0.09
XPZ730GL	XPZ	730	28.75	0.04	0.09
XPZ737GL	XPZ	737	29.00	0.04	0.09
XPZ750GL	XPZ	750	29.55	0.05	0.09
XPZ758GL	XPZ	758	29.85	0.05	0.09
XPZ760GL	XPZ	760	29.90	0.05	0.09
XPZ762GL	XPZ	762	30.00	0.05	0.09
XPZ772GL	XPZ	772	30.40	0.05	0.09
XPZ775GL	XPZ	775	30.50	0.05	0.09
XPZ787GL	XPZ	787	31.00	0.05	0.09
XPZ800GL	XPZ	800	31.50	0.05	0.09

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ812GL	XPZ	812	32.00	0.05	0.10
XPZ821GL	XPZ	821	32.30	0.05	0.10
XPZ825GL	XPZ	825	32.50	0.05	0.10
XPZ837GL	XPZ	837	32.95	0.05	0.10
XPZ845GL	XPZ	845	33.25	0.05	0.10
XPZ850GL	XPZ	850	33.45	0.05	0.10
XPZ862GL	XPZ	862	33.95	0.05	0.10
XPZ875GL	XPZ	875	34.45	0.05	0.10
XPZ887GL	XPZ	887	34.90	0.05	0.10
XPZ900GL	XPZ	900	35.45	0.05	0.11
XPZ912GL	XPZ	912	35.90	0.05	0.11
XPZ925GL	XPZ	925	36.40	0.06	0.11
XPZ937GL	XPZ	937	36.90	0.06	0.11
XPZ940GL	XPZ	940	37.00	0.06	0.11
XPZ950GL	XPZ	950	37.40	0.06	0.11
XPZ957GL	XPZ	957	37.70	0.06	0.11
XPZ962GL	XPZ	962	37.85	0.06	0.11
XPZ975GL	XPZ	975	38.40	0.06	0.12
XPZ980GL	XPZ	980	38.60	0.06	0.12
XPZ985GL	XPZ	985	38.80	0.06	0.12
XPZ987GL	XPZ	987	38.85	0.06	0.12
XPZ1000GL	XPZ	1000	39.35	0.06	0.12
XPZ1010GL	XPZ	1010	39.75	0.06	0.12
XPZ1012GL	XPZ	1012	39.85	0.06	0.12
XPZ1024GL	XPZ	1024	40.30	0.06	0.12
XPZ1030GL	XPZ	1030	40.55	0.06	0.12
XPZ1037GL	XPZ	1037	40.85	0.06	0.12
XPZ1047GL	XPZ	1047	41.20	0.06	0.12
XPZ1060GL	XPZ	1060	41.75	0.06	0.13
XPZ1062GL	XPZ	1062	41.80	0.06	0.13
XPZ1077GL	XPZ	1077	42.40	0.06	0.13
XPZ1080GL	XPZ	1080	42.50	0.06	0.13
XPZ1087GL	XPZ	1087	42.80	0.07	0.13
XPZ1090GL	XPZ	1090	42.90	0.07	0.13
XPZ1100GL	XPZ	1100	43.30	0.07	0.13
XPZ1112GL	XPZ	1112	43.80	0.07	0.13
XPZ1120GL	XPZ	1120	44.10	0.07	0.13

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1137GL	XPZ	1137	44.75	0.07	0.13
XPZ1140GL	XPZ	1140	44.90	0.07	0.13
XPZ1150GL	XPZ	1150	45.30	0.07	0.14
XPZ1162GL	XPZ	1162	45.75	0.07	0.14
XPZ1166GL	XPZ	1166	45.90	0.07	0.14
XPZ1170GL	XPZ	1170	46.05	0.07	0.14
XPZ1180GL	XPZ	1180	46.45	0.07	0.14
XPZ1187GL	XPZ	1187	46.75	0.07	0.14
XPZ1195GL	XPZ	1195	47.05	0.07	0.14
XPZ1200GL	XPZ	1200	47.25	0.07	0.14
XPZ1202GL	XPZ	1202	47.30	0.07	0.14
XPZ1210GL	XPZ	1210	47.65	0.07	0.14
XPZ1212GL	XPZ	1212	47.70	0.07	0.14
XPZ1220GL	XPZ	1220	48.05	0.07	0.14
XPZ1227GL	XPZ	1227	48.30	0.07	0.14
XPZ1237GL	XPZ	1237	48.70	0.07	0.15
XPZ1240GL	XPZ	1240	48.80	0.07	0.15
XPZ1250GL	XPZ	1250	49.20	0.08	0.15
XPZ1262GL	XPZ	1262	49.70	0.08	0.15
XPZ1270GL	XPZ	1270	50.00	0.08	0.15
XPZ1280GL	XPZ	1280	50.40	0.08	0.15
XPZ1282GL	XPZ	1282	50.45	0.08	0.15
XPZ1285GL	XPZ	1285	50.60	0.08	0.15
XPZ1287GL	XPZ	1287	50.65	0.08	0.15
XPZ1312GL	XPZ	1312	51.65	0.08	0.15
XPZ1320GL	XPZ	1320	51.95	0.08	0.16
XPZ1337GL	XPZ	1337	52.65	0.08	0.16
XPZ1340GL	XPZ	1340	52.76	0.08	0.16
XPZ1350GL	XPZ	1350	53.15	0.08	0.16
XPZ1362GL	XPZ	1362	53.60	0.08	0.16
XPZ1370GL	XPZ	1370	53.95	0.08	0.16
XPZ1380GL	XPZ	1380	54.35	0.08	0.16
XPZ1387GL	XPZ	1387	54.60	0.08	0.16
XPZ1400GL	XPZ	1400	55.10	0.08	0.17
XPZ1412GL	XPZ	1412	55.60	0.08	0.17
XPZ1415GL	XPZ	1415	55.70	0.08	0.17
XPZ1420GL	XPZ	1420	55.90	0.09	0.17

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1430GL	XPZ	1430	56.30	0.09	0.17
XPZ1437GL	XPZ	1437	56.60	0.09	0.17
XPZ1450GL	XPZ	1450	57.10	0.09	0.17
XPZ1462GL	XPZ	1462	57.55	0.09	0.17
XPZ1470GL	XPZ	1470	57.85	0.09	0.17
XPZ1475GL	XPZ	1475	58.05	0.09	0.17
XPZ1487GL	XPZ	1487	58.55	0.09	0.18
XPZ1490GL	XPZ	1490	58.65	0.09	0.18
XPZ1500GL	XPZ	1500	59.05	0.09	0.18
XPZ1512GL	XPZ	1512	59.55	0.09	0.18
XPZ1520GL	XPZ	1520	59.85	0.09	0.18
XPZ1527GL	XPZ	1527	60.10	0.09	0.18
XPZ1537GL	XPZ	1537	60.50	0.09	0.18
XPZ1545GL	XPZ	1545	60.85	0.09	0.18
XPZ1550GL	XPZ	1550	61.00	0.09	0.18
XPZ1560GL	XPZ	1560	61.40	0.09	0.18
XPZ1562GL	XPZ	1562	61.50	0.09	0.18
XPZ1587GL	XPZ	1587	62.50	0.10	0.19
XPZ1600GL	XPZ	1600	63.00	0.10	0.19
XPZ1612GL	XPZ	1612	63.45	0.10	0.19
XPZ1630GL	XPZ	1630	64.15	0.10	0.19
XPZ1637GL	XPZ	1637	64.45	0.10	0.19
XPZ1640GL	XPZ	1640	64.55	0.10	0.19
XPZ1650GL	XPZ	1650	64.95	0.10	0.19
XPZ1652GL	XPZ	1652	65.05	0.10	0.20
XPZ1662GL	XPZ	1662	65.45	0.10	0.20
XPZ1687GL	XPZ	1687	66.40	0.10	0.20
XPZ1700GL	XPZ	1700	66.90	0.10	0.20
XPZ1707GL	XPZ	1707	67.20	0.10	0.20
XPZ1710GL	XPZ	1710	67.30	0.10	0.20
XPZ1712GL	XPZ	1712	67.40	0.10	0.20
XPZ1737GL	XPZ	1737	68.40	0.10	0.21
XPZ1750GL	XPZ	1750	68.90	0.11	0.21
XPZ1760GL	XPZ	1760	69.30	0.11	0.21
XPZ1762GL	XPZ	1762	69.35	0.11	0.21
XPZ1782GL	XPZ	1782	70.15	0.11	0.21
XPZ1787GL	XPZ	1787	70.35	0.11	0.21

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1800GL	XPZ	1800	70.85	0.11	0.21
XPZ1812GL	XPZ	1812	71.35	0.11	0.21
XPZ1837GL	XPZ	1837	72.30	0.11	0.22
XPZ1845GL	XPZ	1845	72.65	0.11	0.22
XPZ1850GL	XPZ	1850	72.85	0.11	0.22
XPZ1862GL	XPZ	1862	73.30	0.11	0.22
XPZ1875GL	XPZ	1875	73.80	0.11	0.22
XPZ1887GL	XPZ	1887	74.30	0.11	0.22
XPZ1900GL	XPZ	1900	74.80	0.11	0.22
XPZ1937GL	XPZ	1937	76.25	0.12	0.23
XPZ1950GL	XPZ	1950	76.75	0.12	0.23
XPZ1962GL	XPZ	1962	77.25	0.12	0.23
XPZ1987GL	XPZ	1987	78.20	0.12	0.23
XPZ2000GL	XPZ	2000	78.75	0.12	0.24
XPZ2012GL	XPZ	2012	79.20	0.12	0.24
XPZ2030GL	XPZ	2030	79.90	0.12	0.24
XPZ2037GL	XPZ	2037	80.20	0.12	0.24
XPZ2060GL	XPZ	2060	81.10	0.12	0.24
XPZ2062GL	XPZ	2062	81.20	0.12	0.24
XPZ2087GL	XPZ	2087	82.15	0.13	0.25
XPZ2120GL	XPZ	2120	83.45	0.13	0.25
XPZ2137GL	XPZ	2137	84.15	0.13	0.25
XPZ2160GL	XPZ	2160	85.05	0.13	0.26
XPZ2187GL	XPZ	2187	86.10	0.13	0.26
XPZ2220GL	XPZ	2220	87.40	0.13	0.26
XPZ2240GL	XPZ	2240	88.20	0.13	0.26
XPZ2280GL	XPZ	2280	89.75	0.14	0.27
XPZ2287GL	XPZ	2287	90.05	0.14	0.27
XPZ2300GL	XPZ	2300	90.55	0.14	0.27
XPZ2360GL	XPZ	2360	92.90	0.14	0.28
XPZ2410GL	XPZ	2410	94.90	0.14	0.28
XPZ2430GL	XPZ	2430	95.65	0.15	0.29
* XPZ2437GL	XPZ	2437	95.95	0.15	0.29
* XPZ2487GL	XPZ	2487	97.90	0.15	0.29
* XPZ2500GL	XPZ	2500	98.40	0.15	0.30
* XPZ2530GL	XPZ	2530	99.60	0.15	0.30
* XPZ2540GL	XPZ	2540	100.00	0.15	0.30

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPZ2580GL	XPZ	2580	101.55	0.15	0.30
*	XPZ2650GL	XPZ	2650	104.35	0.16	0.31
*	XPZ2690GL	XPZ	2690	105.90	0.16	0.32
*	XPZ2750GL	XPZ	2750	108.25	0.17	0.32
*	XPZ2800GL	XPZ	2800	110.25	0.17	0.33
*	XPZ2840GL	XPZ	2840	111.80	0.17	0.34
*	XPZ2900GL	XPZ	2900	114.15	0.17	0.34
	XPZ2915GL	XPZ	2915	114.75	0.17	0.34
*	XPZ2987GL	XPZ	2987	117.60	0.18	0.35
*	XPZ2990GL	XPZ	2990	117.70	0.18	0.35
*	XPZ3000GL	XPZ	3000	118.10	0.18	0.35
	XPA550GL	XPA	550	21.65	0.05	0.13
	XPA575GL	XPA	575	22.65	0.06	0.14
	XPA630GL	XPA	630	24.80	0.06	0.15
	XPA667GL	XPA	667	26.25	0.07	0.16
	XPA670GL	XPA	670	26.40	0.07	0.16
	XPA690GL	XPA	690	27.15	0.07	0.16
	XPA710GL	XPA	710	27.95	0.07	0.17
	XPA730GL	XPA	730	28.75	0.07	0.17
	XPA732GL	XPA	732	28.80	0.07	0.17
	XPA742GL	XPA	742	29.20	0.07	0.18
	XPA747GL	XPA	747	29.40	0.07	0.18
	XPA750GL	XPA	750	29.55	0.07	0.18
	XPA757GL	XPA	757	29.80	0.07	0.18
	XPA760GL	XPA	760	29.90	0.07	0.18
	XPA762GL	XPA	762	30.00	0.07	0.18
	XPA766GL	XPA	766	30.15	0.08	0.18
	XPA772GL	XPA	772	30.40	0.08	0.18
	XPA775GL	XPA	775	30.50	0.08	0.18
	XPA782GL	XPA	782	30.80	0.08	0.18
	XPA800GL	XPA	800	31.50	0.08	0.19
	XPA807GL	XPA	807	31.75	0.08	0.19
	XPA825GL	XPA	825	32.50	0.08	0.19
	XPA832GL	XPA	832	32.75	0.08	0.20
	XPA840GL	XPA	840	33.05	0.08	0.20
	XPA850GL	XPA	850	33.45	0.08	0.20
	XPA857GL	XPA	857	33.75	0.08	0.20

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA861GL	XPA	861	33.90	0.08	0.20
XPA875GL	XPA	875	34.45	0.09	0.21
XPA882GL	XPA	882	34.70	0.09	0.21
XPA900GL	XPA	900	35.45	0.09	0.21
XPA907GL	XPA	907	35.70	0.09	0.21
XPA910GL	XPA	910	35.85	0.09	0.21
XPA912GL	XPA	912	35.90	0.09	0.22
XPA918GL	XPA	918	36.15	0.09	0.22
XPA922GL	XPA	922	36.30	0.09	0.22
XPA925GL	XPA	925	36.40	0.09	0.22
XPA930GL	XPA	930	36.60	0.09	0.22
XPA932GL	XPA	932	36.70	0.09	0.22
XPA940GL	XPA	940	37.00	0.09	0.22
XPA950GL	XPA	950	37.40	0.09	0.22
XPA957GL	XPA	957	37.70	0.09	0.23
XPA960GL	XPA	960	37.80	0.09	0.23
XPA963GL	XPA	963	37.90	0.09	0.23
XPA967GL	XPA	967	38.05	0.09	0.23
XPA969GL	XPA	969	38.15	0.09	0.23
XPA975GL	XPA	975	38.40	0.10	0.23
XPA982GL	XPA	982	38.65	0.10	0.23
XPA1000GL	XPA	1000	39.35	0.10	0.24
XPA1007GL	XPA	1007	39.65	0.10	0.24
XPA1017GL	XPA	1017	40.05	0.10	0.24
XPA1030GL	XPA	1030	40.55	0.10	0.24
XPA1032GL	XPA	1032	40.65	0.10	0.24
XPA1055GL	XPA	1055	41.55	0.10	0.25
XPA1060GL	XPA	1060	41.75	0.10	0.25
XPA1070GL	XPA	1070	42.10	0.10	0.25
XPA1082GL	XPA	1082	42.60	0.11	0.26
XPA1090GL	XPA	1090	42.90	0.11	0.26
XPA1107GL	XPA	1107	43.60	0.11	0.26
XPA1120GL	XPA	1120	44.10	0.11	0.26
XPA1132GL	XPA	1132	44.55	0.11	0.27
XPA1140GL	XPA	1140	44.90	0.11	0.27
XPA1150GL	XPA	1150	45.30	0.11	0.27
XPA1155GL	XPA	1155	45.45	0.11	0.27

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1157GL	XPA	1157	45.55	0.11	0.27
XPA1175GL	XPA	1175	46.25	0.12	0.28
XPA1180GL	XPA	1180	46.45	0.12	0.28
XPA1190GL	XPA	1190	46.85	0.12	0.28
XPA1200GL	XPA	1200	47.25	0.12	0.28
XPA1207GL	XPA	1207	47.50	0.12	0.29
XPA1215GL	XPA	1215	47.85	0.12	0.29
XPA1220GL	XPA	1220	48.05	0.12	0.29
XPA1232GL	XPA	1232	48.50	0.12	0.29
XPA1250GL	XPA	1250	49.20	0.12	0.30
XPA1257GL	XPA	1257	49.50	0.12	0.30
XPA1272GL	XPA	1272	50.10	0.12	0.30
XPA1280GL	XPA	1280	50.40	0.13	0.30
XPA1282GL	XPA	1282	50.45	0.13	0.30
XPA1285GL	XPA	1285	50.60	0.13	0.30
XPA1300GL	XPA	1300	51.20	0.13	0.31
XPA1307GL	XPA	1307	51.45	0.13	0.31
XPA1320GL	XPA	1320	51.95	0.13	0.31
XPA1332GL	XPA	1332	52.45	0.13	0.31
XPA1340GL	XPA	1340	52.75	0.13	0.32
XPA1357GL	XPA	1357	53.40	0.13	0.32
XPA1360GL	XPA	1360	53.55	0.13	0.32
XPA1367GL	XPA	1367	53.80	0.13	0.32
XPA1375GL	XPA	1375	54.15	0.13	0.32
XPA1382GL	XPA	1382	54.40	0.14	0.33
XPA1400GL	XPA	1400	55.10	0.14	0.33
XPA1407GL	XPA	1407	55.40	0.14	0.33
XPA1415GL	XPA	1415	55.70	0.14	0.33
XPA1420GL	XPA	1420	55.90	0.14	0.34
XPA1425GL	XPA	1425	56.10	0.14	0.34
XPA1430GL	XPA	1430	56.30	0.14	0.34
XPA1432GL	XPA	1432	56.40	0.14	0.34
XPA1450GL	XPA	1450	57.10	0.14	0.34
XPA1457GL	XPA	1457	57.35	0.14	0.34
XPA1465GL	XPA	1465	57.70	0.14	0.35
XPA1475GL	XPA	1475	58.05	0.14	0.35
XPA1482GL	XPA	1482	58.35	0.15	0.35

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1490GL	XPA	1490	58.65	0.15	0.35
XPA1500GL	XPA	1500	59.05	0.15	0.35
XPA1507GL	XPA	1507	59.35	0.15	0.36
XPA1520GL	XPA	1520	59.85	0.15	0.36
XPA1525GL	XPA	1525	60.05	0.15	0.36
XPA1532GL	XPA	1532	60.30	0.15	0.36
XPA1550GL	XPA	1550	61.00	0.15	0.37
XPA1557GL	XPA	1557	61.30	0.15	0.37
XPA1582GL	XPA	1582	62.30	0.16	0.37
XPA1600GL	XPA	1600	63.00	0.16	0.38
XPA1607GL	XPA	1607	63.25	0.16	0.38
XPA1610GL	XPA	1610	63.40	0.16	0.38
XPA1618GL	XPA	1618	63.70	0.16	0.38
XPA1630GL	XPA	1630	64.15	0.16	0.39
XPA1632GL	XPA	1632	64.25	0.16	0.39
XPA1650GL	XPA	1650	64.95	0.16	0.39
XPA1652GL	XPA	1652	65.05	0.16	0.39
XPA1657GL	XPA	1657	65.25	0.16	0.39
XPA1662GL	XPA	1662	65.45	0.16	0.39
XPA1675GL	XPA	1675	65.95	0.16	0.40
XPA1680GL	XPA	1680	66.15	0.16	0.40
XPA1682GL	XPA	1682	66.20	0.16	0.40
XPA1700GL	XPA	1700	66.95	0.17	0.40
XPA1707GL	XPA	1707	67.20	0.17	0.40
XPA1725GL	XPA	1725	67.90	0.17	0.41
XPA1732GL	XPA	1732	68.20	0.17	0.41
XPA1750GL	XPA	1750	68.90	0.17	0.41
XPA1757GL	XPA	1757	69.15	0.17	0.42
XPA1782GL	XPA	1782	70.15	0.17	0.42
XPA1800GL	XPA	1800	70.85	0.18	0.43
XPA1807GL	XPA	1807	71.15	0.18	0.43
XPA1820GL	XPA	1820	71.65	0.18	0.43
XPA1825GL	XPA	1825	71.85	0.18	0.43
XPA1832GL	XPA	1832	72.15	0.18	0.43
XPA1850GL	XPA	1850	72.85	0.18	0.44
XPA1857GL	XPA	1857	73.10	0.18	0.44
XPA1875GL	XPA	1875	73.80	0.18	0.44

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1882GL	XPA	1882	74.10	0.18	0.44
XPA1885GL	XPA	1885	74.20	0.18	0.45
XPA1900GL	XPA	1900	74.80	0.19	0.45
XPA1907GL	XPA	1907	75.10	0.19	0.45
XPA1925GL	XPA	1925	75.80	0.19	0.45
XPA1932GL	XPA	1932	76.05	0.19	0.46
XPA1950GL	XPA	1950	76.75	0.19	0.46
XPA1957GL	XPA	1957	77.05	0.19	0.46
XPA1982GL	XPA	1982	78.05	0.19	0.47
XPA1987GL	XPA	1987	78.25	0.19	0.47
XPA2000GL	XPA	2000	78.75	0.20	0.47
XPA2032GL	XPA	2032	80.00	0.20	0.48
XPA2050GL	XPA	2050	80.70	0.20	0.48
XPA2057GL	XPA	2057	81.00	0.20	0.49
XPA2060GL	XPA	2060	81.10	0.20	0.49
XPA2082GL	XPA	2082	81.95	0.20	0.49
XPA2100GL	XPA	2100	82.70	0.21	0.50
XPA2120GL	XPA	2120	83.45	0.21	0.50
XPA2130GL	XPA	2130	83.85	0.21	0.50
XPA2132GL	XPA	2132	83.95	0.21	0.50
XPA2150GL	XPA	2150	84.65	0.21	0.51
XPA2160GL	XPA	2160	85.05	0.21	0.51
XPA2180GL	XPA	2180	85.85	0.21	0.51
XPA2182GL	XPA	2182	85.90	0.21	0.52
XPA2200GL	XPA	2200	86.60	0.22	0.52
XPA2207GL	XPA	2207	86.90	0.22	0.52
XPA2227GL	XPA	2227	87.70	0.22	0.53
XPA2232GL	XPA	2232	87.85	0.22	0.53
XPA2240GL	XPA	2240	88.20	0.22	0.53
XPA2282GL	XPA	2282	89.85	0.22	0.54
XPA2300GL	XPA	2300	90.55	0.23	0.54
XPA2307GL	XPA	2307	90.85	0.23	0.54
XPA2330GL	XPA	2330	91.75	0.23	0.55
XPA2332GL	XPA	2332	91.80	0.23	0.55
XPA2360GL	XPA	2360	92.90	0.23	0.56
XPA2380GL	XPA	2380	93.70	0.23	0.56
XPA2382GL	XPA	2382	93.80	0.23	0.56

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPA2430GL	XPA	2430	95.65	0.24	0.57
*	XPA2432GL	XPA	2432	95.75	0.24	0.57
*	XPA2450GL	XPA	2450	96.45	0.24	0.58
*	XPA2482GL	XPA	2482	97.70	0.24	0.59
*	XPA2500GL	XPA	2500	98.40	0.25	0.59
*	XPA2532GL	XPA	2532	99.70	0.25	0.60
*	XPA2582GL	XPA	2582	101.65	0.25	0.61
*	XPA2600GL	XPA	2600	102.35	0.25	0.61
*	XPA2607GL	XPA	2607	102.65	0.26	0.62
*	XPA2632GL	XPA	2632	103.60	0.26	0.62
*	XPA2650GL	XPA	2650	104.35	0.26	0.63
*	XPA2682GL	XPA	2682	105.60	0.26	0.63
*	XPA2732GL	XPA	2732	107.55	0.27	0.65
*	XPA2782GL	XPA	2782	109.55	0.27	0.66
*	XPA2800GL	XPA	2800	110.25	0.27	0.66
*	XPA2832GL	XPA	2832	111.50	0.28	0.67
*	XPA2847GL	XPA	2847	112.10	0.28	0.67
*	XPA2882GL	XPA	2882	113.45	0.28	0.68
*	XPA2900GL	XPA	2900	114.15	0.28	0.69
*	XPA2932GL	XPA	2932	115.45	0.29	0.69
*	XPA2982GL	XPA	2982	117.40	0.29	0.70
*	XPA3000GL	XPA	3000	118.10	0.29	0.71
*	XPA3020GL	XPA	3020	118.90	0.30	0.71
*	XPA3030GL	XPA	3030	119.30	0.30	0.72
*	XPA3150GL	XPA	3150	124.00	0.31	0.74
*	XPA3350GL	XPA	3350	131.90	0.33	0.79
*	XPA3550GL	XPA	3550	139.75	0.35	0.84
	XPB1000GL	XPB	1000	39.40	0.16	0.35
	XPB1060GL	XPB	1060	41.75	0.17	0.38
	XPB1160GL	XPB	1160	45.70	0.18	0.41
	XPB1250GL	XPB	1250	49.25	0.20	0.44
	XPB1260GL	XPB	1260	49.65	0.20	0.45
	XPB1270GL	XPB	1270	50.00	0.20	0.45
	XPB1280GL	XPB	1280	50.40	0.20	0.45
	XPB1300GL	XPB	1300	51.20	0.20	0.46
	XPB1320GL	XPB	1320	52.00	0.21	0.47
	XPB1340GL	XPB	1340	52.80	0.21	0.47

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPB1360GL	XPB	1360	53.55	0.21	0.48
XPB1375GL	XPB	1375	54.15	0.22	0.49
XPB1380GL	XPB	1380	54.35	0.22	0.49
XPB1400GL	XPB	1400	55.15	0.22	0.50
XPB1410GL	XPB	1410	55.55	0.22	0.50
XPB1425GL	XPB	1425	56.10	0.22	0.50
XPB1435GL	XPB	1435	56.50	0.23	0.51
XPB1450GL	XPB	1450	57.10	0.23	0.51
XPB1465GL	XPB	1465	57.70	0.23	0.52
XPB1480GL	XPB	1480	58.30	0.23	0.52
XPB1485GL	XPB	1485	58.50	0.23	0.53
XPB1500GL	XPB	1500	59.10	0.24	0.53
XPB1510GL	XPB	1510	59.45	0.24	0.54
XPB1525GL	XPB	1525	60.05	0.24	0.54
XPB1540GL	XPB	1540	60.65	0.24	0.55
XPB1550GL	XPB	1550	61.05	0.24	0.55
XPB1555GL	XPB	1555	61.25	0.24	0.55
XPB1560GL	XPB	1560	61.45	0.24	0.55
XPB1590GL	XPB	1590	62.60	0.25	0.56
XPB1600GL	XPB	1600	63.00	0.25	0.57
XPB1627GL	XPB	1627	64.10	0.26	0.58
XPB1630GL	XPB	1630	64.20	0.26	0.58
XPB1650GL	XPB	1650	65.00	0.26	0.58
XPB1690GL	XPB	1690	66.55	0.27	0.60
XPB1700GL	XPB	1700	66.95	0.27	0.60
XPB1720GL	XPB	1720	67.75	0.27	0.61
XPB1750GL	XPB	1750	68.90	0.27	0.62
XPB1778GL	XPB	1778	70.00	0.28	0.63
XPB1800GL	XPB	1800	70.90	0.28	0.64
XPB1850GL	XPB	1850	72.85	0.29	0.66
XPB1860GL	XPB	1860	73.25	0.29	0.66
XPB1900GL	XPB	1900	74.80	0.30	0.67
XPB1950GL	XPB	1950	76.80	0.31	0.69
XPB2000GL	XPB	2000	78.75	0.31	0.71
XPB2020GL	XPB	2020	79.55	0.32	0.72
XPB2032GL	XPB	2032	80.00	0.32	0.72
XPB2060GL	XPB	2060	81.10	0.32	0.73

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPB2098GL	XPB	2098	82.60	0.33	0.74
XPB2100GL	XPB	2100	82.70	0.33	0.74
XPB2120GL	XPB	2120	83.50	0.33	0.75
XPB2150GL	XPB	2150	84.65	0.34	0.76
XPB2160GL	XPB	2160	85.05	0.34	0.77
XPB2180GL	XPB	2180	85.85	0.34	0.77
XPB2240GL	XPB	2240	88.20	0.35	0.79
XPB2260GL	XPB	2260	89.00	0.35	0.80
XPB2280GL	XPB	2280	89.80	0.36	0.81
XPB2300GL	XPB	2300	90.55	0.36	0.81
XPB2360GL	XPB	2360	92.95	0.37	0.84
XPB2391GL	XPB	2391	94.15	0.38	0.85
XPB2400GL	XPB	2400	94.50	0.38	0.85
XPB2410GL	XPB	2410	94.90	0.38	0.85
XPB2430GL	XPB	2430	95.70	0.38	0.86
* XPB2450GL	XPB	2450	96.50	0.38	0.87
* XPB2480GL	XPB	2480	97.65	0.39	0.88
* XPB2500GL	XPB	2500	98.45	0.39	0.89
* XPB2510GL	XPB	2510	98.85	0.39	0.89
* XPB2530GL	XPB	2530	99.65	0.40	0.90
* XPB2580GL	XPB	2580	101.60	0.41	0.91
* XPB2600GL	XPB	2600	102.40	0.41	0.92
* XPB2650GL	XPB	2650	104.35	0.42	0.94
* XPB2680GL	XPB	2680	105.55	0.42	0.95
* XPB2700GL	XPB	2700	106.30	0.42	0.96
* XPB2720GL	XPB	2720	107.10	0.43	0.96
* XPB2750GL	XPB	2750	108.30	0.43	0.97
* XPB2800GL	XPB	2800	110.25	0.44	0.99
* XPB2840GL	XPB	2840	111.85	0.45	1.01
* XPB2900GL	XPB	2900	114.20	0.46	1.03
* XPB2990GL	XPB	2990	117.75	0.47	1.06
* XPB3000GL	XPB	3000	118.15	0.47	1.06
* XPB3150GL	XPB	3150	124.05	0.49	1.12
* XPB3170GL	XPB	3170	124.80	0.50	1.12
* XPB3340GL	XPB	3340	131.50	0.52	1.18
* XPB3350GL	XPB	3350	131.90	0.53	1.19
* XPB3450GL	XPB	3450	135.85	0.54	1.22

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPB3550GL	XPB	3550	139.80	0.56	1.26
	XPC1260GL	XPC	1260	49.65	0.35	0.79
	XPC1700GL	XPC	1700	66.95	0.48	1.07
	XPC1800GL	XPC	1800	70.90	0.50	1.13
	XPC1900GL	XPC	1900	74.80	0.53	1.20
	XPC2000GL	XPC	2000	78.75	0.56	1.26
	XPC2120GL	XPC	2120	83.50	0.59	1.34
	XPC2170GL	XPC	2170	85.45	0.61	1.37
	XPC2240GL	XPC	2240	88.20	0.63	1.41
	XPC2360GL	XPC	2360	92.95	0.66	1.49
*	XPC2500GL	XPC	2500	98.45	0.70	1.57
*	XPC2600GL	XPC	2600	102.40	0.73	1.64
*	XPC2650GL	XPC	2650	104.35	0.74	1.67
*	XPC2800GL	XPC	2800	110.25	0.78	1.76
*	XPC2900GL	XPC	2900	114.20	0.81	1.83
*	XPC2995GL	XPC	2995	117.95	0.84	1.89
*	XPC3000GL	XPC	3000	118.15	0.84	1.89
*	XPC3150GL	XPC	3150	124.05	0.88	1.98
*	XPC3350GL	XPC	3350	131.90	0.94	2.11
*	XPC3550GL	XPC	3550	139.80	0.99	2.24



MOVE FORWARD. ALWAYS.™

PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is < 30 °C / 86 °F
- Continues high temperature (50 °C / 122 °F) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly storage belt shelf life is at least 5 years
- Short belt up to 1,5 m / 59 in can be stored on pegs
- Long belts better to be coiled on shelves for distortion – free

