


GOLD LABEL Narrow - Product Description



V-Belt

GOLD LABEL



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/m)
3V	9	8	0.076
5V	15	13	0.223
8V	25	23	0.504

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/inches)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.028

V-Belt

Part Number Description: **3V300GL**

3V: Profile (9.5mm X 8mm)

300: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Fabric Cover: PET/Cotton, CR Impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/NR Rubber blend

- Resistant to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 C. / -31 To 160 F.

MM: Made for Match

Wedge Profile (RMA): Up to 3 times the Power transmission capacity compared to Classical V Profiles (Z, A, B, C, D, E)
Designed for OEMs

Markets and Applications:

Recommended for industrial applications where space, weight and power capacity are critical


Pulley Standards: IP22

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/m)
3V	9	8	0.076
5V	15	13	0.223
8V	25	23	0.504

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/inches)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.028


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3V250GL	3V	635	25.00	0.05	0.11
3V265GL	3V	673	26.50	0.05	0.11
3V280GL	3V	711	28.00	0.05	0.12
3V300GL	3V	762	30.00	0.06	0.13
3V315GL	3V	800	31.50	0.06	0.13
3V325GL	3V	826	32.50	0.06	0.14
3V335GL	3V	851	33.50	0.06	0.14
3V355GL	3V	902	35.50	0.07	0.15
3V375GL	3V	953	37.50	0.07	0.16
3V400GL	3V	1016	40.00	0.08	0.17
3V425GL	3V	1080	42.50	0.08	0.18
3V450GL	3V	1143	45.00	0.09	0.19
3V475GL	3V	1207	47.50	0.09	0.20
3V500GL	3V	1270	50.00	0.10	0.21
3V530GL	3V	1346	53.00	0.10	0.23
3V560GL	3V	1422	56.00	0.11	0.24
3V600GL	3V	1524	60.00	0.12	0.26
3V630GL	3V	1600	63.00	0.12	0.27
3V650GL	3V	1651	65.00	0.13	0.28
3V670GL	3V	1702	67.00	0.13	0.29
3V710GL	3V	1803	71.00	0.14	0.30
3V730GL	3V	1854	73.00	0.14	0.31
3V750GL	3V	1905	75.00	0.15	0.32
3V780GL	3V	1981	78.00	0.15	0.33
3V800GL	3V	2032	80.00	0.15	0.34
3V830GL	3V	2108	83.00	0.16	0.35
3V850GL	3V	2159	85.00	0.16	0.36
3V900GL	3V	2286	90.00	0.17	0.38
3V950GL	3V	2413	95.00	0.18	0.40
3V1000GL	3V	2540	100.00	0.19	0.43
3V1060GL	3V	2692	106.00	0.21	0.45
3V1120GL	3V	2845	112.00	0.22	0.48
3V1180GL	3V	2997	118.00	0.23	0.50
3V1250GL	3V	3175	125.00	0.24	0.53
3V1320GL	3V	3353	132.00	0.26	0.56
3V1400GL	3V	3556	140.00	0.27	0.60
3V1500GL	3V	3810	150.00	0.29	0.64
5V500GL	5V	1270	50.00	0.28	0.62
5V530GL	5V	1346	53.00	0.30	0.66
5V560GL	5V	1422	56.00	0.32	0.70
5V600GL	5V	1524	60.00	0.34	0.75
5V630GL	5V	1600	63.00	0.36	0.79
5V670GL	5V	1702	67.00	0.38	0.84
5V710GL	5V	1803	71.00	0.40	0.88

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL.



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/m)
3V	9	8	0.076
5V	15	13	0.223
8V	25	23	0.504

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/inches)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.028


DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5V750GL	5V	1905	75.00	0.42	0.94
5V800GL	5V	2032	80.00	0.45	1.00
5V850GL	5V	2159	85.00	0.48	1.06
5V900GL	5V	2286	90.00	0.51	1.12
5V950GL	5V	2413	95.00	0.54	1.18
5V1000GL	5V	2540	100.00	0.57	1.25
5V1060GL	5V	2692	106.00	0.60	1.32
5V1080GL	5V	2743	108.00	0.61	1.35
5V1120GL	5V	2845	112.00	0.63	1.40
5V1180GL	5V	2997	118.00	0.67	1.47
5V1250GL	5V	3175	125.00	0.71	1.56
5V1320GL	5V	3353	132.00	0.75	1.65
5V1400GL	5V	3556	140.00	0.79	1.75
5V1500GL	5V	3810	150.00	0.85	1.87
5V1600GL	5V	4064	160.00	0.91	1.99
5V1630GL	5V	4140	163.00	0.92	2.03
5V1700GL	5V	4318	170.00	0.96	2.12
5V1800GL	5V	4572	180.00	1.02	2.24
5V1900GL	5V	4826	190.00	1.08	2.37
5V2000GL	5V	5080	200.00	1.13	2.49
5V2120GL	5V	5385	212.00	1.20	2.64
5V2240GL	5V	5690	224.00	1.27	2.79
5V2360GL	5V	5994	236.00	1.34	2.94
5V2500GL	5V	6350	250.00	1.42	3.12
5V2650GL	5V	6731	265.00	1.50	3.30
5V2800GL	5V	7112	280.00	1.58	3.49
5V3000GL	5V	7620	300.00	1.70	3.74
5V3150GL	5V	8001	315.00	1.78	3.93
5V3350GL	5V	8509	335.00	1.90	4.18
5V3550GL	5V	9017	355.00	2.01	4.43
8V1000GL	8V	2540	100.00	1.28	2.82
8V1060GL	8V	2692	106.00	1.36	2.99
8V1120GL	8V	2845	112.00	1.43	3.16
8V1180GL	8V	2997	118.00	1.51	3.33
8V1250GL	8V	3175	125.00	1.60	3.52
8V1320GL	8V	3353	132.00	1.69	3.72
8V1400GL	8V	3556	140.00	1.79	3.95
8V1500GL	8V	3810	150.00	1.92	4.23
8V1600GL	8V	4064	160.00	2.05	4.51
8V1700GL	8V	4318	170.00	2.18	4.79
8V1800GL	8V	4572	180.00	2.30	5.07
8V1900GL	8V	4826	190.00	2.43	5.36
8V2000GL	8V	5080	200.00	2.56	5.64
8V2120GL	8V	5385	212.00	2.71	5.98

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL



Metric			
Section	W - Width (mm)	H - Height (mm)	Weight (Kg/m)
3V	9	8	0.076
5V	15	13	0.223
8V	25	23	0.504

Imperial			
Section	W - Width (in)	H - Height (in)	Weight (lb/inches)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.028

DAYCO Part Nr	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
8V2240GL	8V	5690	224.00	2.87	6.32
8V2300GL	8V	5842	230.00	2.94	6.48
8V2360GL	8V	5994	236.00	3.02	6.65
8V2500GL	8V	6350	250.00	3.20	7.05
8V2550GL	8V	6477	255.00	3.26	7.19
8V2650GL	8V	6731	265.00	3.39	7.47
8V2800GL	8V	7112	280.00	3.58	7.89
8V3000GL	8V	7620	300.00	3.84	8.46
8V3150GL	8V	8001	315.00	4.03	8.88
8V3300GL	8V	8382	330.00	4.22	9.30
8V3350GL	8V	8509	335.00	4.29	9.44
8V3550GL	8V	9017	355.00	4.54	10.01
8V3600GL	8V	9144	360.00	4.61	10.15
8V3750GL	8V	9525	375.00	4.80	10.57
8V4000GL	8V	10160	400.00	5.12	11.28
8V4250GL	8V	10795	425.00	5.44	11.98
8V4500GL	8V	11430	450.00	5.76	12.69
8V4750GL	8V	12065	475.00	6.08	13.39
8V5000GL	8V	12700	500.00	6.40	14.10
8V5600GL	8V	14224	560.00	7.17	15.79