



GOLD LABEL™

Designed for **OEMs**



MOVE FORWARD. ALWAYS.™

Product Guide

GOLD LABEL™ Industrial Wrapped V-Belts



GOLD LABEL™

Designed for **OEMs**

DAYCO®
MOVE FORWARD. ALWAYS.™



MOVE FORWARD. ALWAYS.™

GOLD LABEL Wrapped - Table of Contents



V-Belt

GOLD LABEL™



A-B-C-D-E

GOLD LABEL Classical

Wrapped classical V-Belt.


Product description3

Size List4



V-Belt

GOLD LABEL™



3V-5V-8V

GOLD LABEL Narrow

Designed for more compact multiple-belt drives. Imperial design.


Product description24

Size List25



V-Belt

GOLD LABEL™



SPZ-SPA-SPB-SPC

GOLD LABEL Wedge

Designed for more compact multiple-belt drives. Metric design.

Product description28


Size List29

GOLD LABEL Classical - Product Description



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

V-Belt

Part Number Description: **A120GL**

A: Profile (13mm X 8mm)

120: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 to +70 °C / -31 to +160 °F

RLT: Restricted length tolerance, matching set according to ISO 4184

Designed for OEMs

Markets and Applications:

Suitable for all Industrial applications

Pulley Standards: DIN2217 – ISO 4183



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
A21GL	A	533	566	21.00	22.30	0.07	0.16
A22GL	A	559	592	22.00	23.30	0.07	0.16
A23GL	A	584	617	23.00	24.30	0.07	0.17
A24GL	A	610	643	24.00	25.30	0.07	0.18
A25GL	A	635	668	25.00	26.30	0.08	0.18
A26GL	A	660	693	26.00	27.30	0.08	0.19
A27GL	A	686	719	27.00	28.30	0.08	0.20
A28GL	A	711	744	28.00	29.30	0.09	0.21
A29GL	A	737	770	29.00	30.30	0.09	0.21
A30GL	A	762	795	30.00	31.30	0.09	0.22
A31GL	A	787	820	31.00	32.30	0.10	0.23
A32GL	A	813	846	32.00	33.30	0.10	0.23
A33GL	A	838	871	33.00	34.30	0.10	0.24
A33.5GL	A	851	884	33.50	34.80	0.10	0.24
A34GL	A	864	897	34.00	35.30	0.11	0.25
A35GL	A	889	922	35.00	36.30	0.11	0.25
A36GL	A	914	947	36.00	37.30	0.11	0.26
A37GL	A	940	973	37.00	38.30	0.11	0.27
A38GL	A	965	998	38.00	39.30	0.12	0.28
A38.5GL	A	978	1011	38.50	39.80	0.12	0.28
A39GL	A	991	1024	39.00	40.30	0.12	0.28
A40GL	A	1016	1049	40.00	41.30	0.12	0.29
A41GL	A	1041	1074	41.00	42.30	0.13	0.30
A42GL	A	1067	1100	42.00	43.30	0.13	0.30
A43GL	A	1092	1125	43.00	44.30	0.13	0.31
A44GL	A	1118	1151	44.00	45.30	0.14	0.32
A45GL	A	1143	1176	45.00	46.30	0.14	0.32
A45.5GL	A	1156	1189	45.50	46.80	0.14	0.33
A46GL	A	1168	1201	46.00	47.30	0.14	0.33
A47GL	A	1194	1227	47.00	48.30	0.15	0.34
A48GL	A	1219	1252	48.00	49.30	0.15	0.35
A49GL	A	1245	1278	49.00	50.30	0.15	0.35




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
A50GL	A	1270	1303	50.00	51.30	0.15	0.36
A51GL	A	1295	1328	51.00	52.30	0.16	0.37
A52GL	A	1321	1354	52.00	53.30	0.16	0.37
A53GL	A	1346	1379	53.00	54.30	0.16	0.38
A54GL	A	1372	1405	54.00	55.30	0.17	0.39
A55GL	A	1397	1430	55.00	56.30	0.17	0.39
A56GL	A	1422	1455	56.00	57.30	0.17	0.40
A57GL	A	1448	1481	57.00	58.30	0.18	0.41
A58GL	A	1473	1506	58.00	59.30	0.18	0.42
A59GL	A	1499	1532	59.00	60.30	0.18	0.42
A60GL	A	1524	1557	60.00	61.30	0.19	0.43
A61GL	A	1549	1582	61.00	62.30	0.19	0.44
A62GL	A	1575	1608	62.00	63.30	0.19	0.44
A63GL	A	1600	1633	63.00	64.30	0.20	0.45
A64GL	A	1626	1659	64.00	65.30	0.20	0.46
A65GL	A	1651	1684	65.00	66.30	0.20	0.46
A66GL	A	1676	1709	66.00	67.30	0.20	0.47
A67GL	A	1702	1735	67.00	68.30	0.21	0.48
A68GL	A	1727	1760	68.00	69.30	0.21	0.49
A69GL	A	1753	1786	69.00	70.30	0.21	0.49
A70GL	A	1778	1811	70.00	71.30	0.22	0.50
A71GL	A	1803	1836	71.00	72.30	0.22	0.51
A72GL	A	1829	1862	72.00	73.30	0.22	0.51
A73GL	A	1854	1887	73.00	74.30	0.23	0.52
A73.5GL	A	1867	1900	73.50	74.80	0.23	0.52
A74GL	A	1880	1913	74.00	75.30	0.23	0.53
A75GL	A	1905	1938	75.00	76.30	0.23	0.53
A76GL	A	1930	1963	76.00	77.30	0.24	0.54
A77GL	A	1956	1989	77.00	78.30	0.24	0.55
A77.5GL	A	1969	2002	77.50	78.80	0.24	0.55
A78GL	A	1981	2014	78.00	79.30	0.24	0.56
A79GL	A	2007	2040	79.00	80.30	0.24	0.56



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
A80GL	A	2032	2065	80.00	81.30	0.25	0.57
A81GL	A	2057	2090	81.00	82.30	0.25	0.58
A82GL	A	2083	2116	82.00	83.30	0.25	0.58
A83GL	A	2108	2141	83.00	84.30	0.26	0.59
A84GL	A	2134	2167	84.00	85.30	0.26	0.60
A85GL	A	2159	2192	85.00	86.30	0.26	0.60
A86GL	A	2184	2217	86.00	87.30	0.27	0.61
A86.5	A	2197	2230	86.50	87.80	0.27	0.61
A87GL	A	2210	2243	87.00	88.30	0.27	0.62
A88GL	A	2235	2268	88.00	89.30	0.27	0.63
A89GL	A	2261	2294	89.00	90.30	0.28	0.63
A90GL	A	2286	2319	90.00	91.30	0.28	0.64
A91GL	A	2311	2344	91.00	92.30	0.28	0.65
A91.5GL	A	2324	2357	91.50	92.80	0.28	0.65
A92GL	A	2337	2370	92.00	93.30	0.29	0.65
A93GL	A	2362	2395	93.00	94.30	0.29	0.66
A94GL	A	2388	2421	94.00	95.30	0.29	0.67
A95GL	A	2413	2446	95.00	96.30	0.29	0.67
A96GL	A	2438	2471	96.00	97.30	0.30	0.68
A96.5GL	A	2451	2484	96.50	97.80	0.30	0.68
A97GL	A	2464	2497	97.00	98.30	0.30	0.69
A98GL	A	2489	2522	98.00	99.30	0.30	0.70
A99GL	A	2515	2548	99.00	100.30	0.31	0.70
A100GL	A	2540	2573	100.00	101.30	0.31	0.71
A101GL	A	2565	2598	101.00	102.30	0.31	0.72
A102GL	A	2591	2624	102.00	103.30	0.32	0.72
A103GL	A	2616	2649	103.00	104.30	0.32	0.73
A104GL	A	2642	2675	104.00	105.30	0.32	0.74
A105GL	A	2667	2700	105.00	106.30	0.33	0.74
A106GL	A	2692	2725	106.00	107.30	0.33	0.75
A107GL	A	2718	2751	107.00	108.30	0.33	0.76
A108GL	A	2743	2776	108.00	109.30	0.33	0.77




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
A109GL	A	2769	2802	109.00	110.30	0.34	0.77
A110GL	A	2794	2827	110.00	111.30	0.34	0.78
A112GL	A	2845	2878	112.00	113.30	0.35	0.79
A113GL	A	2870	2903	113.00	114.30	0.35	0.80
A114GL	A	2896	2929	114.00	115.30	0.35	0.81
A115GL	A	2921	2954	115.00	116.30	0.36	0.81
A116GL	A	2946	2979	116.00	117.30	0.36	0.82
A117GL	A	2972	3005	117.00	118.30	0.36	0.83
A118GL	A	2997	3030	118.00	119.30	0.37	0.84
A120GL	A	3048	3081	120.00	121.30	0.37	0.85
A123GL	A	3124	3157	123.00	124.30	0.38	0.87
A124GL	A	3150	3183	124.00	125.30	0.38	0.88
A125GL	A	3175	3208	125.00	126.30	0.39	0.88
A126GL	A	3200	3233	126.00	127.30	0.39	0.89
A127GL	A	3226	3259	127.00	128.30	0.39	0.90
A128GL	A	3251	3284	128.00	129.30	0.40	0.91
A130GL	A	3302	3335	130.00	131.30	0.40	0.92
A132GL	A	3353	3386	132.00	133.30	0.41	0.93
A133GL	A	3378	3411	133.00	134.30	0.41	0.94
A134GL	A	3404	3437	134.00	135.30	0.42	0.95
A136GL	A	3454	3487	136.00	137.30	0.42	0.96
A137GL	A	3480	3513	137.00	138.30	0.42	0.97
A140GL	A	3556	3589	140.00	141.30	0.43	0.99
A144GL	A	3658	3691	144.00	145.30	0.45	1.02
A148GL	A	3759	3792	148.00	149.30	0.46	1.05
A150GL	A	3810	3843	150.00	151.30	0.46	1.06
A152GL	A	3861	3894	152.00	153.30	0.47	1.07
A155GL	A	3937	3970	155.00	156.30	0.48	1.09
A156GL	A	3962	3995	156.00	157.30	0.48	1.10
A158GL	A	4013	4046	158.00	159.30	0.49	1.12
A160GL	A	4064	4097	160.00	161.30	0.50	1.13
A162GL	A	4115	4148	162.00	163.30	0.50	1.14




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
A165GL	A	4191	4224	165.00	166.30	0.51	1.16
A166GL	A	4216	4249	166.00	167.30	0.51	1.17
A167GL	A	4242	4275	167.00	168.30	0.52	1.18
A173GL	A	4394	4427	173.00	174.30	0.54	1.22
A177GL	A	4496	4529	177.00	178.30	0.55	1.25
A180GL	A	4572	4605	180.00	181.30	0.56	1.27
A187GL	A	4750	4783	187.00	188.30	0.58	1.32
A197GL	A	5004	5037	197.00	198.30	0.61	1.39
A236.5GL	A	6007	6040	236.50	237.80	0.73	1.66
B22.5GL	B	572	611	22.50	24.10	0.11	0.26
B23GL	B	584	624	23.00	24.60	0.11	0.27
B24GL	B	610	650	24.00	25.60	0.12	0.28
B25GL	B	635	675	25.00	26.60	0.12	0.29
B26GL	B	660	700	26.00	27.60	0.12	0.30
B27GL	B	686	726	27.00	28.60	0.13	0.31
B28GL	B	711	751	28.00	29.60	0.13	0.33
B29GL	B	737	777	29.00	30.60	0.14	0.34
B30GL	B	762	802	30.00	31.60	0.14	0.35
B31GL	B	787	827	31.00	32.60	0.15	0.36
B32GL	B	813	853	32.00	33.60	0.15	0.37
B32.5GL	B	826	866	32,50	34,05	0.16	0.38
B33GL	B	838	878	33.00	34.60	0.16	0.38
B33.5GL	B	851	891	33,50	35,05	0.16	0.39
B34GL	B	864	904	34.00	35.60	0.16	0.39
B34.5GL	B	876	916	34,50	36,05	0.17	0.40
B35GL	B	889	929	35.00	36.60	0.17	0.40
B35.5GL	B	902	942	35,50	37,05	0.17	0.41
B36GL	B	914	954	36.00	37.60	0.17	0.41
B36.5GL	B	927	967	36,50	38,05	0.18	0.42
B37GL	B	940	980	37.00	38.60	0.18	0.42
B37.5GL	B	953	993	37,50	39,05	0.18	0.43
B38GL	B	965	1005	38.00	39.60	0.18	0.44




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B38.5GL	B	978	1018	38,50	40,05	0.18	0.44
B39GL	B	991	1031	39.00	40.60	0.19	0.45
B39.5GL	B	1003	1043	39,50	41,05	0.19	0.45
B40GL	B	1016	1056	40.00	41.60	0.19	0.46
B40.5GL	B	1029	1068	40,50	42,05	0.19	0.46
B41GL	B	1041	1081	41.00	42.60	0.20	0.47
B42GL	B	1067	1107	42.00	43.60	0.20	0.48
B42.5GL	B	1080	1120	42,50	44,05	0.20	0.49
B43GL	B	1092	1132	43.00	44.60	0.21	0.49
B43.5GL	B	1105	1145	43,50	45,05	0.21	0.50
B44GL	B	1118	1158	44.00	45.60	0.21	0.50
B45GL	B	1143	1183	45.00	46.60	0.22	0.51
B45.5GL	B	1156	1196	45,50	47,05	0.22	0.52
B46GL	B	1168	1208	46.00	47.60	0.22	0.52
B46.5GL	B	1181	1221	46,50	48,05	0.22	0.53
B47GL	B	1194	1234	47.00	48.60	0.23	0.53
B48GL	B	1219	1259	48.00	49.60	0.23	0.55
B49GL	B	1245	1285	49.00	50.60	0.24	0.56
B50GL	B	1270	1310	50.00	51.60	0.24	0.57
B51GL	B	1295	1335	51.00	52.60	0.24	0.58
B52GL	B	1321	1361	52.00	53.60	0.25	0.59
B53GL	B	1346	1386	53.00	54.60	0.25	0.60
B54GL	B	1372	1412	54.00	55.60	0.26	0.61
B55GL	B	1397	1437	55.00	56.60	0.26	0.62
B56GL	B	1422	1462	56.00	57.60	0.27	0.63
B57GL	B	1448	1488	57.00	58.60	0.27	0.64
B58GL	B	1473	1513	58.00	59.60	0.28	0.66
B59GL	B	1499	1539	59.00	60.60	0.28	0.67
B60GL	B	1524	1564	60.00	61.60	0.29	0.68
B61GL	B	1549	1589	61.00	62.60	0.29	0.69
B62GL	B	1575	1615	62.00	63.60	0.30	0.70
B63GL	B	1600	1640	63.00	64.60	0.30	0.71




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B64GL	B	1626	1666	64.00	65.60	0.31	0.72
B65GL	B	1651	1691	65.00	66.60	0.31	0.73
B66GL	B	1676	1716	66.00	67.60	0.32	0.74
B67GL	B	1702	1742	67.00	68.60	0.32	0.75
B68GL	B	1727	1767	68.00	69.60	0.33	0.77
B69GL	B	1753	1793	69.00	70.60	0.33	0.78
B69.5GL	B	1765	1805	69.50	71.10	0.33	0.78
B70GL	B	1778	1818	70.00	71.60	0.34	0.79
B71GL	B	1803	1843	71.00	72.60	0.34	0.80
B72GL	B	1829	1869	72.00	73.60	0.35	0.81
B73GL	B	1854	1894	73.00	74.60	0.35	0.82
B74GL	B	1880	1920	74.00	75.60	0.36	0.83
B75GL	B	1905	1945	75.00	76.60	0.36	0.84
B76GL	B	1930	1970	76.00	77.60	0.36	0.85
B77GL	B	1956	1996	77.00	78.60	0.37	0.86
B78GL	B	1981	2021	78.00	79.60	0.37	0.88
B79GL	B	2007	2047	79.00	80.60	0.38	0.89
B80GL	B	2032	2072	80.00	81.60	0.38	0.90
B81GL	B	2057	2097	81.00	82.60	0.39	0.91
B82GL	B	2083	2123	82.00	83.60	0.39	0.92
B83GL	B	2108	2148	83.00	84.60	0.40	0.93
B84GL	B	2134	2174	84.00	85.60	0.40	0.94
B85GL	B	2159	2199	85.00	86.60	0.41	0.95
B86GL	B	2184	2224	86.00	87.60	0.41	0.96
B86.5GL	B	2197	2237	86.50	88.05	0.42	0.97
B87GL	B	2210	2250	87.00	88.60	0.42	0.97
B88GL	B	2235	2275	88.00	89.60	0.42	0.99
B88.5GL	B	2248	2288	88.50	90.05	0.42	0.99
B89GL	B	2261	2301	89.00	90.60	0.43	1.00
B90GL	B	2286	2326	90.00	91.60	0.43	1.01
B91GL	B	2311	2351	91.00	92.60	0.44	1.02
B92GL	B	2337	2377	92.00	93.60	0.44	1.03



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B93GL	B	2362	2402	93.00	94.60	0.45	1.04
B94GL	B	2388	2428	94.00	95.60	0.45	1.05
B94.5GL	B	2400	2440	94.50	96.05	0.45	1.06
B95GL	B	2413	2453	95.00	96.60	0.46	1.06
B96GL	B	2438	2478	96.00	97.60	0.46	1.07
B97GL	B	2464	2504	97.00	98.60	0.47	1.08
B98GL	B	2489	2529	98.00	99.60	0.47	1.10
B99GL	B	2515	2555	99.00	100.60	0.48	1.11
B100GL	B	2540	2580	100.00	101.60	0.48	1.12
B101GL	B	2565	2605	101.00	102.60	0.48	1.13
B102GL	B	2591	2631	102.00	103.60	0.49	1.14
B103GL	B	2616	2656	103.00	104.60	0.49	1.15
B104GL	B	2642	2682	104.00	105.60	0.50	1.16
B105GL	B	2667	2707	105.00	106.60	0.50	1.17
B106GL	B	2692	2732	106.00	107.60	0.51	1.18
B107GL	B	2718	2758	107.00	108.60	0.51	1.19
B108GL	B	2743	2783	108.00	109.60	0.52	1.21
B109GL	B	2769	2809	109.00	110.60	0.52	1.22
B110GL	B	2794	2834	110.00	111.60	0.53	1.23
B111GL	B	2819	2859	111.00	112.60	0.53	1.24
B112GL	B	2845	2885	112.00	113.60	0.54	1.25
B113GL	B	2870	2910	113.00	114.60	0.54	1.26
B114GL	B	2896	2936	114.00	115.60	0.55	1.27
B115GL	B	2921	2961	115.00	116.60	0.55	1.28
B116GL	B	2946	2986	116.00	117.60	0.56	1.29
B116.5GL	B	2959	2999	116.50	118.05	0.56	1.30
B117GL	B	2972	3012	117.00	118.60	0.56	1.30
B118GL	B	2997	3037	118.00	119.60	0.57	1.32
B119GL	B	3023	3063	119.00	120.60	0.57	1.33
B120GL	B	3048	3088	120.00	121.60	0.58	1.34
B121GL	B	3073	3113	121.00	122.60	0.58	1.35
B122GL	B	3099	3139	122.00	123.60	0.59	1.36




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B123GL	B	3124	3164	123.00	124.60	0.59	1.37
B124GL	B	3150	3190	124.00	125.60	0.60	1.38
B125GL	B	3175	3215	125.00	126.60	0.60	1.39
B126GL	B	3200	3240	126.00	127.60	0.60	1.40
B127GL	B	3226	3266	127.00	128.60	0.61	1.41
B128GL	B	3251	3291	128.00	129.60	0.61	1.43
B130GL	B	3302	3342	130.00	131.60	0.62	1.45
B131GL	B	3327	3367	131.00	132.60	0.63	1.46
B132GL	B	3353	3393	132.00	133.60	0.63	1.47
B133GL	B	3378	3418	133.00	134.60	0.64	1.48
B134GL	B	3404	3444	134.00	135.60	0.64	1.49
B135GL	B	3429	3469	135.00	136.60	0.65	1.50
B136GL	B	3454	3494	136.00	137.60	0.65	1.51
B137GL	B	3480	3520	137.00	138.60	0.66	1.52
B138GL	B	3505	3545	138.00	139.60	0.66	1.54
B139GL	B	3531	3571	139.00	140.60	0.67	1.55
B140GL	B	3556	3596	140.00	141.60	0.67	1.56
B141GL	B	3581	3621	141.00	142.60	0.68	1.57
B142GL	B	3607	3647	142.00	143.60	0.68	1.58
B143GL	B	3632	3672	143.00	144.60	0.69	1.59
B144GL	B	3658	3698	144.00	145.60	0.69	1.60
B145GL	B	3683	3723	145.00	146.60	0.70	1.61
B146GL	B	3708	3748	146.00	147.60	0.70	1.62
B147GL	B	3734	3774	147.00	148.60	0.71	1.63
B148GL	B	3759	3799	148.00	149.60	0.71	1.65
B149GL	B	3785	3825	149.00	150.60	0.72	1.66
B150GL	B	3810	3850	150.00	151.60	0.72	1.67
B151GL	B	3835	3875	151.00	152.60	0.72	1.68
B152GL	B	3861	3901	152.00	153.60	0.73	1.69
B153GL	B	3886	3926	153.00	154.60	0.73	1.70
B154GL	B	3912	3952	154.00	155.60	0.74	1.71
B155GL	B	3937	3977	155.00	156.60	0.74	1.72



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B156GL	B	3962	4002	156.00	157.60	0.75	1.73
B157GL	B	3988	4028	157.00	158.60	0.75	1.74
B158GL	B	4013	4053	158.00	159.60	0.76	1.76
B159GL	B	4039	4079	159.00	160.60	0.76	1.77
B160GL	B	4064	4104	160.00	161.60	0.77	1.78
B162GL	B	4115	4155	162.00	163.60	0.78	1.80
B163GL	B	4140	4180	163.00	164.60	0.78	1.81
B164GL	B	4166	4206	164.00	165.60	0.79	1.82
B165GL	B	4191	4231	165.00	166.60	0.79	1.83
B166GL	B	4216	4256	166.00	167.60	0.80	1.84
B167GL	B	4242	4282	167.00	168.60	0.80	1.85
B168GL	B	4267	4307	168.00	169.60	0.81	1.87
B170GL	B	4318	4358	170.00	171.60	0.82	1.89
B172GL	B	4369	4409	172.00	173.60	0.83	1.91
B173GL	B	4394	4434	173.00	174.60	0.83	1.92
B174GL	B	4420	4460	174.00	175.60	0.84	1.93
B175GL	B	4445	4485	175.00	176.60	0.84	1.94
B177GL	B	4496	4536	177.00	178.60	0.85	1.96
B178GL	B	4521	4561	178.00	179.60	0.85	1.98
B180GL	B	4572	4612	180.00	181.60	0.86	2.00
B182GL	B	4623	4663	182.00	183.60	0.87	2.02
B184GL	B	4674	4714	184.00	185.60	0.88	2.04
B185GL	B	4699	4739	185.00	186.60	0.89	2.05
B187GL	B	4750	4790	187.00	188.60	0.90	2.07
B188GL	B	4775	4815	188.00	189.60	0.90	2.09
B190GL	B	4826	4866	190.00	191.60	0.91	2.11
B191GL	B	4851	4891	191.00	192.60	0.92	2.12
B192GL	B	4877	4917	192.00	193.60	0.92	2.13
B195GL	B	4953	4993	195.00	196.60	0.94	2.16
B197GL	B	5004	5044	197.00	198.60	0.95	2.18
B198GL	B	5029	5069	198.00	199.55	0.95	2.20
B199GL	B	5055	5095	199.00	200.60	0.96	2.21




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
B200GL	B	5080	5120	200.00	201.60	0.96	2.22
B204GL	B	5182	5222	204.00	205.60	0.98	2.26
B205GL	B	5207	5247	205.00	206.60	0.98	2.27
B208GL	B	5283	5323	208.00	209.55	1.00	2.31
B210GL	B	5334	5374	210.00	211.60	1.01	2.33
B215GL	B	5461	5501	215.00	216.60	1.03	2.38
B220GL	B	5588	5628	220.00	221.60	1.06	2.44
B223GL	B	5664	5704	223.00	224.60	1.07	2.47
B225GL	B	5715	5755	225.00	226.60	1.08	2.49
B228GL	B	5791	5831	228.00	229.60	1.09	2.53
B229GL	B	5817	5857	229.00	230.60	1.10	2.54
B235GL	B	5969	6009	235.00	236.55	1.13	2.60
B236GL	B	5994	6034	236.00	237.60	1.13	2.61
B238GL	B	6045	6085	238.00	239.60	1.14	2.64
B240GL	B	6096	6136	240.00	241.60	1.15	2.66
B248GL	B	6299	6339	248.00	249.60	1.19	2.75
B249GL	B	6325	6365	249.00	250.60	1.20	2.76
B253GL	B	6426	6466	253.00	254.60	1.21	2.80
B255GL	B	6477	6517	255.00	256.60	1.22	2.82
B256GL	B	6502	6542	256.00	257.55	1.23	2.83
B270GL	B	6858	6898	270.00	271.60	1.30	2.99
B275GL	B	6985	7025	275.00	276.60	1.32	3.04
B276GL	B	7010	7050	276.00	277.60	1.32	3.05
B280GL	B	7112	7152	280.00	281.60	1.34	3.10
B285GL	B	7239	7279	285.00	286.60	1.37	3.15
B292GL	B	7417	7457	292.00	293.60	1.40	3.23
B300GL	B	7620	7660	300.00	301.60	1.44	3.32
B315GL	B	8001	8041	315.00	316.60	1.51	3.48
B330GL	B	8382	8422	330.00	331.60	1.58	3.65
B345GL	B	8763	8803	345.00	346.60	1.66	3.81
B355GL	B	9017	9057	355.00	356.60	1.70	3.92
B360GL	B	9144	9184	360.00	361.60	1.73	3.98




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C43GL	C	1092	1151	43.00	45.35	0.36	0.82
C46GL	C	1168	1227	46.00	48.35	0.38	0.87
C47GL	C	1194	1253	47.00	49.35	0.39	0.89
C48GL	C	1219	1278	48.00	50.35	0.40	0.91
C49GL	C	1245	1304	49.00	51.35	0.41	0.92
C50GL	C	1270	1329	50.00	52.35	0.42	0.94
C51GL	C	1295	1354	51.00	53.35	0.42	0.96
C52GL	C	1321	1380	52.00	54.35	0.43	0.98
C53GL	C	1346	1405	53.00	55.35	0.44	1.00
C54GL	C	1372	1431	54.00	56.35	0.45	1.01
C55GL	C	1397	1456	55.00	57.35	0.46	1.03
C56GL	C	1422	1481	56.00	58.35	0.46	1.05
C57GL	C	1448	1507	57.00	59.35	0.47	1.07
C58GL	C	1473	1532	58.00	60.35	0.48	1.09
C59GL	C	1499	1558	59.00	61.35	0.49	1.10
C60GL	C	1524	1583	60.00	62.35	0.50	1.12
C61GL	C	1549	1608	61.00	63.35	0.51	1.14
C62GL	C	1575	1634	62.00	64.35	0.52	1.16
C62.25GL	C	1581	1640	62.25	64.60	0.52	1.16
C63GL	C	1600	1659	63.00	65.35	0.52	1.18
C64GL	C	1626	1685	64.00	66.35	0.53	1.19
C65GL	C	1651	1710	65.00	67.35	0.54	1.21
C66GL	C	1676	1735	66.00	68.35	0.55	1.23
C67GL	C	1702	1761	67.00	69.35	0.56	1.25
C68GL	C	1727	1786	68.00	70.35	0.56	1.27
C69GL	C	1753	1812	69.00	71.35	0.57	1.28
C70GL	C	1778	1837	70.00	72.35	0.58	1.30
C71GL	C	1803	1862	71.00	73.35	0.59	1.32
C72GL	C	1829	1888	72.00	74.35	0.60	1.34
C72.5GL	C	1842	1901	72.50	74.85	0.60	1.35
C73GL	C	1854	1913	73.00	75.35	0.61	1.36
C74GL	C	1880	1939	74.00	76.35	0.61	1.37



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C75GL	C	1905	1964	75.00	77.35	0.62	1.39
C76GL	C	1930	1989	76.00	78.35	0.63	1.41
C77GL	C	1956	2015	77.00	79.35	0.64	1.43
C78GL	C	1981	2040	78.00	80.35	0.65	1.45
C79GL	C	2007	2066	79.00	81.35	0.66	1.46
C80GL	C	2032	2091	80.00	82.35	0.66	1.48
C81GL	C	2057	2116	81.00	83.35	0.67	1.50
C82GL	C	2083	2142	82.00	84.35	0.68	1.52
C83GL	C	2108	2167	83.00	85.35	0.69	1.54
C84GL	C	2134	2193	84.00	86.35	0.70	1.55
C85GL	C	2159	2218	85.00	87.35	0.71	1.57
C86GL	C	2184	2243	86.00	88.35	0.71	1.59
C87GL	C	2210	2269	87.00	89.35	0.72	1.61
C88GL	C	2235	2294	88.00	90.35	0.73	1.63
C89GL	C	2261	2320	89.00	91.35	0.74	1.64
C90GL	C	2286	2345	90.00	92.35	0.75	1.66
C91GL	C	2311	2370	91.00	93.35	0.76	1.68
C92GL	C	2337	2396	92.00	94.35	0.76	1.70
C93GL	C	2362	2421	93.00	95.35	0.77	1.72
C94GL	C	2388	2447	94.00	96.35	0.78	1.73
C95GL	C	2413	2472	95.00	97.35	0.79	1.75
C96GL	C	2438	2497	96.00	98.35	0.80	1.77
C96.5GL	C	2451	2510	96.50	98.85	0.80	1.78
C97GL	C	2464	2523	97.00	99.35	0.81	1.79
C98GL	C	2489	2548	98.00	100.35	0.81	1.81
C99GL	C	2515	2574	99.00	101.35	0.82	1.82
C100GL	C	2540	2599	100.00	102.35	0.83	1.84
C101GL	C	2565	2624	101.00	103.35	0.84	1.86
C102GL	C	2591	2650	102.00	104.35	0.85	1.88
C103GL	C	2616	2675	103.00	105.35	0.86	1.90
C104GL	C	2642	2701	104.00	106.35	0.86	1.91
C105GL	C	2667	2726	105.00	107.35	0.87	1.93

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C106GL	C	2692	2751	106.00	108.35	0.88	1.95
C107GL	C	2718	2777	107.00	109.35	0.89	1.97
C108GL	C	2743	2802	108.00	110.35	0.90	1.99
C109GL	C	2769	2828	109.00	111.35	0.91	2.00
C110GL	C	2794	2853	110.00	112.35	0.91	2.02
C111GL	C	2819	2878	111.00	113.35	0.92	2.04
C112GL	C	2845	2904	112.00	114.35	0.93	2.06
C113GL	C	2870	2929	113.00	115.35	0.94	2.08
C114GL	C	2896	2955	114.00	116.35	0.95	2.09
C115GL	C	2921	2980	115.00	117.35	0.96	2.11
C116GL	C	2946	3005	116.00	118.35	0.96	2.13
C117GL	C	2972	3031	117.00	119.35	0.97	2.15
C118GL	C	2997	3056	118.00	120.35	0.98	2.17
C119GL	C	3023	3082	119.00	121.35	0.99	2.18
C120GL	C	3048	3107	120.00	122.35	1.00	2.20
C121GL	C	3073	3132	121.00	123.35	1.00	2.22
C122GL	C	3099	3158	122.00	124.35	1.01	2.24
C123GL	C	3124	3183	123.00	125.35	1.02	2.26
C124GL	C	3150	3209	124.00	126.35	1.03	2.27
C125GL	C	3175	3234	125.00	127.35	1.04	2.29
C126GL	C	3200	3259	126.00	128.35	1.05	2.31
C127GL	C	3226	3285	127.00	129.35	1.05	2.33
C128GL	C	3251	3310	128.00	130.35	1.06	2.35
C129GL	C	3277	3336	129.00	131.35	1.07	2.36
C130GL	C	3302	3361	130.00	132.35	1.08	2.38
C131GL	C	3327	3386	131.00	133.35	1.09	2.40
C132GL	C	3353	3412	132.00	134.35	1.10	2.42
C133GL	C	3378	3437	133.00	135.35	1.10	2.44
C134GL	C	3404	3463	134.00	136.35	1.11	2.45
C135GL	C	3429	3488	135.00	137.35	1.12	2.47
C136GL	C	3454	3513	136.00	138.35	1.13	2.49
C137GL	C	3480	3539	137.00	139.35	1.14	2.51
C138GL	C	3505	3564	138.00	140.35	1.15	2.53




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C140GL	C	3556	3615	140.00	142.35	1.16	2.56
C141GL	C	3581	3640	141.00	143.35	1.17	2.58
C142GL	C	3607	3666	142.00	144.35	1.18	2.60
C143GL	C	3632	3691	143.00	145.35	1.19	2.62
C144GL	C	3658	3717	144.00	146.35	1.20	2.63
C145GL	C	3683	3742	145.00	147.35	1.20	2.65
C146GL	C	3708	3767	146.00	148.35	1.21	2.67
C147GL	C	3734	3793	147.00	149.35	1.22	2.69
C148GL	C	3759	3818	148.00	150.35	1.23	2.71
C149GL	C	3785	3844	149.00	151.35	1.24	2.72
C150GL	C	3810	3869	150.00	152.35	1.25	2.74
C151GL	C	3835	3894	151.00	153.35	1.25	2.76
C152GL	C	3861	3920	152.00	154.35	1.26	2.78
C153GL	C	3886	3945	153.00	155.35	1.27	2.80
C154GL	C	3912	3971	154.00	156.35	1.28	2.81
C155GL	C	3937	3996	155.00	157.35	1.29	2.83
C156GL	C	3962	4021	156.00	158.35	1.30	2.85
C158GL	C	4013	4072	158.00	160.35	1.31	2.89
C159GL	C	4039	4098	159.00	161.35	1.32	2.90
C160GL	C	4064	4123	160.00	162.35	1.33	2.92
C161GL	C	4089	4148	161.00	163.35	1.34	2.94
C162GL	C	4115	4174	162.00	164.35	1.35	2.96
C163GL	C	4140	4199	163.00	165.35	1.35	2.98
C164GL	C	4166	4225	164.00	166.35	1.36	2.99
C165GL	C	4191	4250	165.00	167.35	1.37	3.01
C166GL	C	4216	4275	166.00	168.35	1.38	3.03
C167GL	C	4242	4301	167.00	169.35	1.39	3.05
C168GL	C	4267	4326	168.00	170.35	1.40	3.07
C169GL	C	4293	4352	169.00	171.35	1.40	3.08
C170GL	C	4318	4377	170.00	172.35	1.41	3.10
C172GL	C	4369	4428	172.00	174.35	1.43	3.14
C173GL	C	4394	4453	173.00	175.35	1.44	3.16



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C175GL	C	4445	4504	175.00	177.35	1.45	3.19
C177GL	C	4496	4555	177.00	179.35	1.47	3.23
C178GL	C	4521	4580	178.00	180.35	1.48	3.25
C180GL	C	4572	4631	180.00	182.35	1.50	3.28
C181GL	C	4597	4656	181.00	183.35	1.50	3.30
C182GL	C	4623	4682	182.00	184.35	1.51	3.32
C183GL	C	4648	4707	183.00	185.35	1.52	3.34
C184GL	C	4674	4733	184.00	186.35	1.53	3.35
C185GL	C	4699	4758	185.00	187.35	1.54	3.37
C187GL	C	4750	4809	187.00	189.35	1.55	3.41
C188GL	C	4775	4834	188.00	190.35	1.56	3.43
C189GL	C	4801	4860	189.00	191.35	1.57	3.44
C190GL	C	4826	4885	190.00	192.35	1.58	3.46
C192GL	C	4877	4936	192.00	194.35	1.59	3.50
C193GL	C	4902	4961	193.00	195.35	1.60	3.52
C194GL	C	4928	4987	194.00	196.35	1.61	3.53
C195GL	C	4953	5012	195.00	197.35	1.62	3.55
C196GL	C	4978	5037	196.00	198.35	1.63	3.57
C197GL	C	5004	5063	197.00	199.35	1.64	3.59
C198GL	C	5029	5088	198.00	200.35	1.64	3.61
C200GL	C	5080	5139	200.00	202.35	1.66	3.64
C202GL	C	5131	5190	202.00	204.35	1.68	3.68
C204GL	C	5182	5241	204.00	206.35	1.69	3.71
C205GL	C	5207	5266	205.00	207.35	1.70	3.73
C206GL	C	5232	5291	206.00	208.35	1.71	3.75
C207GL	C	5258	5317	207.00	209.35	1.72	3.77
C208GL	C	5283	5342	208.00	210.35	1.73	3.79
C210GL	C	5334	5393	210.00	212.35	1.74	3.82
C212GL	C	5385	5444	212.00	214.35	1.76	3.86
C215GL	C	5461	5520	215.00	217.35	1.79	3.91
C216GL	C	5486	5545	216.00	218.35	1.79	3.93
C218GL	C	5537	5596	218.00	220.35	1.81	3.97
C220GL	C	5588	5647	220.00	222.35	1.83	4.00




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C221GL	C	5613	5672	221.00	223.35	1.84	4.02
C222GL	C	5639	5698	222.00	224.35	1.84	4.04
C225GL	C	5715	5774	225.00	227.35	1.87	4.09
C228GL	C	5791	5850	228.00	230.35	1.89	4.15
C230GL	C	5842	5901	230.00	232.35	1.91	4.18
C232GL	C	5893	5952	232.00	234.35	1.93	4.22
C235GL	C	5969	6028	235.00	237.35	1.95	4.27
C236GL	C	5994	6053	236.00	238.35	1.96	4.29
C238GL	C	6045	6104	238.00	240.35	1.98	4.33
C240GL	C	6096	6155	240.00	242.35	1.99	4.36
C242GL	C	6147	6206	242.00	244.35	2.01	4.40
C245GL	C	6223	6282	245.00	247.35	2.03	4.45
C246GL	C	6248	6307	246.00	248.35	2.04	4.47
C248GL	C	6299	6358	248.00	250.35	2.06	4.51
C250GL	C	6350	6409	250.00	252.35	2.08	4.54
C255GL	C	6477	6536	255.00	257.35	2.12	4.63
C262GL	C	6655	6714	262.00	264.35	2.18	4.76
C264GL	C	6706	6765	264.00	266.35	2.19	4.79
C265GL	C	6731	6790	265.00	267.35	2.20	4.81
C270GL	C	6858	6917	270.00	272.35	2.24	4.90
C276GL	C	7010	7069	276.00	278.35	2.29	5.01
C280GL	C	7112	7171	280.00	282.35	2.33	5.08
C285GL	C	7239	7298	285.00	287.35	2.37	5.17
C295GL	C	7493	7552	295.00	297.35	2.45	5.35
C297GL	C	7544	7603	297.00	299.35	2.47	5.39
C300GL	C	7620	7679	300.00	302.35	2.49	5.44
C303GL	C	7696	7755	303.00	305.35	2.52	5.50
C314GL	C	7976	8035	314.00	316.35	2.61	5.69
C315GL	C	8001	8060	315.00	317.35	2.62	5.71
C316GL	C	8026	8085	316.00	318.35	2.62	5.73
C330GL	C	8382	8441	330.00	332.35	2.74	5.98
C336GL	C	8534	8593	336.00	338.35	2.79	6.09
C345GL	C	8763	8822	345.00	347.35	2.87	6.25




MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
C360GL	C	9144	9203	360.00	362.35	2.99	6.52
C390GL	C	9906	9965	390.00	392.35	3.24	7.06
C420GL	C	10668	10727	420.00	422.35	3.49	7.60
D79GL	D	2007	2083	79.00	82.00	1.34	3.03
D90GL	D	2286	2362	90.00	166.00	1.53	3.44
D98GL	D	2489	2565	98.00	174.00	1.67	3.74
D104GL	D	2642	2718	104.00	180.00	1.77	3.96
D105GL	D	2667	2743	105.00	181.00	1.78	4.00
D110GL	D	2794	2870	110.00	186.00	1.87	4.18
D115GL	D	2921	2997	115.00	191.00	1.95	4.37
D118GL	D	2997	3073	118.00	121.00	2.00	4.48
D120GL	D	3048	3124	120.00	196.00	2.04	4.55
D124GL	D	3150	3226	124.00	200.00	2.11	4.70
D126GL	D	3200	3276	126.00	129.00	2.14	4.77
D128GL	D	3251	3327	128.00	204.00	2.17	4.85
D132GL	D	3353	3429	132.00	208.00	2.24	5.00
D135GL	D	3429	3505	135.00	211.00	2.29	5.11
D136GL	D	3454	3530	136.00	212.00	2.31	5.14
D140GL	D	3556	3632	140.00	216.00	2.38	5.29
D144GL	D	3658	3734	144.00	220.00	2.45	5.44
D148GL	D	3759	3835	148.00	224.00	2.51	5.59
D152GL	D	3861	3937	152.00	228.00	2.58	5.74
D154GL	D	3912	3988	154.00	230.00	2.62	5.81
D155GL	D	3937	4013	155.00	158.00	2.63	5.85
D156GL	D	3962	4038	156.00	232.00	2.65	5.88
D158GL	D	4013	4089	158.00	234.00	2.68	5.96
D160GL	D	4064	4140	160.00	236.00	2.72	6.03
D162GL	D	4115	4191	162.00	238.00	2.75	6.11
D164GL	D	4166	4242	164.00	240.00	2.79	6.18
D165GL	D	4191	4267	165.00	241.00	2.80	6.22
D167GL	D	4242	4318	167.00	243.00	2.84	6.29
D170GL	D	4318	4394	170.00	246.00	2.89	6.40
D171GL	D	4343	4419	171.00	247.00	2.91	6.44



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
D173GL	D	4394	4470	173.00	249.00	2.94	6.51
D177GL	D	4496	4572	177.00	180.00	3.01	6.66
D180GL	D	4572	4648	180.00	256.00	3.06	6.77
D187GL	D	4750	4826	187.00	190.00	3.18	7.03
D195GL	D	4953	5029	195.00	271.00	3.31	7.33
D197GL	D	5004	5080	197.00	200.00	3.35	7.40
D208GL	D	5283	5359	208.00	211.00	3.53	7.81
D210GL	D	5334	5410	210.00	286.00	3.57	7.88
D220GL	D	5588	5664	220.00	296.00	3.74	8.25
D224GL	D	5690	5766	224.00	300.00	3.81	8.40
D225GL	D	5715	5791	225.00	301.00	3.82	8.44
D230GL	D	5842	5918	230.00	306.00	3.91	8.62
D233GL	D	5918	5994	233.00	236.00	3.96	8.73
D236GL	D	5994	6070	236.00	239.00	4.01	8.84
D240GL	D	6096	6172	240.00	316.00	4.08	8.99
D248GL	D	6299	6375	248.00	324.00	4.21	9.29
D250GL	D	6350	6426	250.00	326.00	4.25	9.36
D255GL	D	6477	6553	255.00	331.00	4.33	9.55
D260GL	D	6604	6680	260.00	336.00	4.42	9.73
D264GL	D	6706	6782	264.00	267.00	4.49	9.88
D270GL	D	6858	6934	270.00	346.00	4.59	10.10
D275GL	D	6985	7061	275.00	351.00	4.67	10.29
D280GL	D	7112	7188	280.00	356.00	4.76	10.47
D285GL	D	7239	7315	285.00	361.00	4.84	10.66
D295GL	D	7493	7569	295.00	298.00	5.01	11.03
D300GL	D	7620	7696	300.00	376.00	5.10	11.21
D315GL	D	8001	8077	315.00	391.00	5.35	11.77
D330GL	D	8382	8458	330.00	406.00	5.61	12.32
D335GL	D	8509	8585	335.00	411.00	5.69	12.51
D345GL	D	8763	8839	345.00	421.00	5.86	12.88
D354GL	D	8992	9068	354.00	430.00	6.02	13.21
D355GL	D	9017	9093	355.00	431.00	6.03	13.25
D360GL	D	9144	9220	360.00	436.00	6.12	13.43



MOVE FORWARD. ALWAYS.™

GOLD LABEL Classical - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
A	13	8	0.122
B	17	11	0.189
C	22	14	0.327
D	32	19	0.669
E	38	25	0.937

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
A	1/2	5/16	0.007
B	21/32	13/32	0.011
C	7/8	17/32	0.018
D	1-1/4	3/4	0.037
E	1-1/2	1	0.052


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
D374GL	D	9500	9576	374.00	377.00	6.36	13.95
D380GL	D	9652	9728	380.00	456.00	6.46	14.17
D390GL	D	9906	9982	390.00	466.00	6.63	14.54
D394GL	D	10008	10084	394.00	470.00	6.70	14.69
D418GL	D	10617	10693	418.00	421.00	7.10	15.58
D420GL	D	10668	10744	420.00	496.00	7.14	15.65
D436GL	D	11074	11150	436.00	512.00	7.41	16.24
D441GL	D	11201	11277	441.00	517.00	7.49	16.43
D450GL	D	11430	11506	450.00	526.00	7.65	16.76
D480GL	D	12192	12268	480.00	556.00	8.16	17.87
D492GL	D	12497	12573	492.00	495.00	8.36	18.32
D540GL	D	13716	13792	540.00	616.00	9.18	20.09
D600GL	D	15240	15316	600.00	676.00	10.20	22.31
D660GL	D	16764	16840	660.00	663.00	11.22	24.53
E144GL	E	3658	3739	144.00	147.00	3.43	7.65
E158GL	E	4013	4094	158.00	161.00	3.76	8.38
E180GL	E	4572	4653	180.00	183.00	4.28	9.53
E195GL	E	4953	5034	195.00	198.00	4.64	10.31
E202GL	E	5131	5212	202.00	205.00	4.81	10.67
E210GL	E	5334	5415	210.00	213.00	5.00	11.09
E225GL	E	5715	5796	225.00	228.00	5.35	11.87
E240GL	E	6096	6177	240.00	243.00	5.71	12.65
E270GL	E	6858	6939	270.00	273.00	6.43	14.21
E300GL	E	7620	7701	300.00	303.00	7.14	15.77
E310GL	E	7874	7955	310.00	313.00	7.38	16.29
E325GL	E	8255	8336	325.00	328.00	7.73	17.07
E330GL	E	8382	8463	330.00	333.00	7.85	17.33
E360GL	E	9144	9225	360.00	363.00	8.57	18.89
E390GL	E	9906	9987	390.00	393.00	9.28	20.45
E420GL	E	10668	10749	420.00	423.00	10.00	22.01
E441GL	E	11201	11282	441.00	444.00	10.50	23.10
E480GL	E	12192	12273	480.00	483.00	11.42	25.13
E540GL	E	13716	13797	540.00	543.00	12.85	28.25
E600GL	E	15240	15321	600.00	603.20	14.28	31.37
E660GL	E	16764	16845	660.00	663.20	15.71	34.49

GOLD LABEL Narrow - Product Description



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3V	9	8	0.075
5V	15	13	0.217
8V	25	23	0.551

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.031

V-Belt Wrapped

Part Number Description: **3V300GL**

3V: Profile (9mm X 8mm)

300: Outside Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 to +70 °C / -31 to +160 °F

RLT: Restricted length tolerance, matching set according to ISO 4184

Wedge Profile (RMA): Up to 3 times the Power transmission capacity compared to Classical V Profiles (Z, A, B, C, D, E)

Designed for OEMs

Markets and Applications:

Recommended for industrial applications where space, weight and power capacity are critical

Pulley Standards: ARPM/MPTA IP-22




MOVE FORWARD. ALWAYS.™

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3V	9	8	0.075
5V	15	13	0.217
8V	25	23	0.551

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.031

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3V560GL	3V	1422	56.00	0.11	0.22
3V600GL	3V	1524	60.00	0.11	0.24
3V630GL	3V	1600	63.00	0.12	0.25
3V650GL	3V	1651	65.00	0.12	0.26
3V670GL	3V	1702	67.00	0.13	0.27
3V710GL	3V	1803	71.00	0.14	0.28
3V730GL	3V	1854	73.00	0.14	0.29
3V750GL	3V	1905	75.00	0.14	0.30
3V780GL	3V	1981	78.00	0.15	0.31
3V800GL	3V	2032	80.00	0.15	0.32
3V830GL	3V	2108	83.00	0.16	0.33
3V850GL	3V	2159	85.00	0.16	0.34
3V900GL	3V	2286	90.00	0.17	0.36
3V950GL	3V	2413	95.00	0.18	0.38
3V1000GL	3V	2540	100.00	0.19	0.40
3V1060GL	3V	2692	106.00	0.20	0.42
3V1120GL	3V	2845	112.00	0.21	0.45
3V1180GL	3V	2997	118.00	0.22	0.47
3V1250GL	3V	3175	125.00	0.24	0.50
3V1320GL	3V	3353	132.00	0.25	0.53
3V1400GL	3V	3556	140.00	0.27	0.56
3V1450GL	3V	3683	145.00	0.28	0.58
3V1500GL	3V	3810	150.00	0.29	0.60
5V560GL	5V	1422	56.00	0.31	0.67
5V600GL	5V	1524	60.00	0.33	0.72
5V630GL	5V	1600	63.00	0.35	0.76
5V670GL	5V	1702	67.00	0.37	0.80
5V710GL	5V	1803	71.00	0.39	0.85
5V750GL	5V	1905	75.00	0.41	0.90
5V800GL	5V	2032	80.00	0.44	0.96
5V850GL	5V	2159	85.00	0.47	1.02
5V900GL	5V	2286	90.00	0.50	1.08
5V950GL	5V	2413	95.00	0.52	1.14
5V1000GL	5V	2540	100.00	0.55	1.20
5V1020GL	5V	2591	102.00	0.56	1.22
5V1060GL	5V	2692	106.00	0.58	1.27
5V1080GL	5V	2743	108.00	0.60	1.30
5V1120GL	5V	2845	112.00	0.62	1.34
5V1150GL	5V	2921	115.00	0.63	1.38




MOVE FORWARD. ALWAYS.™

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3V	9	8	0.075
5V	15	13	0.217
8V	25	23	0.551

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.031

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5V1180GL	5V	2997	118.00	0.65	1.42
5V1190GL	5V	3023	119.00	0.66	1.43
5V1250GL	5V	3175	125.00	0.69	1.50
5V1320GL	5V	3353	132.00	0.73	1.58
5V1400GL	5V	3556	140.00	0.77	1.68
5V1500GL	5V	3810	150.00	0.83	1.80
5V1600GL	5V	4064	160.00	0.88	1.92
5V1630GL	5V	4140	163.00	0.90	1.96
5V1700GL	5V	4318	170.00	0.94	2.04
5V1800GL	5V	4572	180.00	0.99	2.16
5V1850GL	5V	4699	185.00	1.02	2.22
5V1900GL	5V	4826	190.00	1.05	2.28
5V2000GL	5V	5080	200.00	1.10	2.40
5V2120GL	5V	5385	212.00	1.17	2.54
5V2240GL	5V	5690	224.00	1.23	2.69
5V2360GL	5V	5994	236.00	1.30	2.83
5V2500GL	5V	6350	250.00	1.38	3.00
5V2650GL	5V	6731	265.00	1.46	3.18
5V2800GL	5V	7112	280.00	1.54	3.36
5V3000GL	5V	7620	300.00	1.65	3.60
5V3150GL	5V	8001	315.00	1.74	3.78
5V3350GL	5V	8509	335.00	1.85	4.02
5V3550GL	5V	9017	355.00	1.96	4.26
8V1000GL	8V	2540	100.00	1.40	3.10
8V1060GL	8V	2692	106.00	1.48	3.29
8V1120GL	8V	2845	112.00	1.57	3.47
8V1180GL	8V	2997	118.00	1.65	3.66
8V1250GL	8V	3175	125.00	1.75	3.88
8V1320GL	8V	3353	132.00	1.85	4.09
8V1400GL	8V	3556	140.00	1.96	4.34
8V1500GL	8V	3810	150.00	2.10	4.65
8V1600GL	8V	4064	160.00	2.24	4.96
8V1700GL	8V	4318	170.00	2.38	5.27
8V1800GL	8V	4572	180.00	2.52	5.58
8V1900GL	8V	4826	190.00	2.66	5.89
8V2000GL	8V	5080	200.00	2.80	6.20
8V2120GL	8V	5385	212.00	2.97	6.57
8V2240GL	8V	5690	224.00	3.14	6.94
8V2300GL	8V	5842	230.00	3.22	7.13




MOVE FORWARD. ALWAYS.™

GOLD LABEL Narrow - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3V	9	8	0.075
5V	15	13	0.217
8V	25	23	0.551

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3V	3/8	5/16	0.004
5V	5/8	17/32	0.012
8V	1	7/8	0.031


DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
8V2360GL	8V	5994	236.00	3.30	7.32
8V2500GL	8V	6350	250.00	3.50	7.75
8V2550GL	8V	6477	255.00	3.57	7.91
8V2650GL	8V	6731	265.00	3.71	8.22
8V2800GL	8V	7112	280.00	3.92	8.68
8V3000GL	8V	7620	300.00	4.20	9.30
8V3150GL	8V	8001	315.00	4.41	9.77
8V3300GL	8V	8382	330.00	4.62	10.23
8V3350GL	8V	8509	335.00	4.69	10.39
8V3550GL	8V	9017	355.00	4.97	11.01
8V3600GL	8V	9144	360.00	5.04	11.16
8V3750GL	8V	9525	375.00	5.25	11.63
8V4000GL	8V	10160	400.00	5.60	12.40
8V4250GL	8V	10795	425.00	5.95	13.18
8V4500GL	8V	11430	450.00	6.30	13.95
8V4750GL	8V	12065	475.00	6.65	14.73
8V5000GL	8V	12700	500.00	7.00	15.50
8V5600GL	8V	14224	560.00	7.84	17.36

GOLD LABEL Wedge - Product Description



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

V-Belt Wrapped

Part Number Description: **SPA1200GL**

SPA: Profile (13mm X 10mm)

1200: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Fabric Cover: PET/Cotton, rubber Impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 to +70 °C / -31 to +160 °F

RLT: Restricted length tolerance, matching set according to ISO 4184

Wedge Profile (Metric): Up to 3 times the Power transmission capacity of Classical V Profiles (Z, A, B, C, D, E)

Designed for OEMs

Markets and Applications:

Recommended for industrial applications, designed with Metric cross-sections belts, where space, weight and power capacity are critical

Pulley Standards: DIN2211 – ISO 4183




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPZ637GL	SPZ	637	25.10	0.05	0.10
SPZ662GL	SPZ	662	26.10	0.05	0.10
SPZ687GL	SPZ	687	27.05	0.05	0.11
SPZ710GL	SPZ	710	27.95	0.06	0.11
SPZ737GL	SPZ	737	29.05	0.06	0.12
SPZ750GL	SPZ	750	29.55	0.06	0.12
SPZ762GL	SPZ	762	30.00	0.06	0.12
SPZ772GL	SPZ	772	30.40	0.06	0.12
SPZ787GL	SPZ	787	31.00	0.06	0.12
SPZ800GL	SPZ	800	31.50	0.06	0.13
SPZ812GL	SPZ	812	32.00	0.06	0.13
SPZ825GL	SPZ	825	32.50	0.07	0.13
SPZ837GL	SPZ	837	32.95	0.07	0.13
SPZ850GL	SPZ	850	33.50	0.07	0.13
SPZ862GL	SPZ	862	33.95	0.07	0.14
SPZ875GL	SPZ	875	34.45	0.07	0.14
SPZ887GL	SPZ	887	34.95	0.07	0.14
SPZ900GL	SPZ	900	35.45	0.07	0.14
SPZ912GL	SPZ	912	35.95	0.07	0.14
SPZ925GL	SPZ	925	36.45	0.07	0.15
SPZ937GL	SPZ	937	36.90	0.07	0.15
SPZ950GL	SPZ	950	37.40	0.08	0.15
SPZ962GL	SPZ	962	37.90	0.08	0.15
SPZ987GL	SPZ	987	38.90	0.08	0.16
SPZ1000GL	SPZ	1000	39.40	0.08	0.16
SPZ1012GL	SPZ	1012	39.85	0.08	0.16
SPZ1024GL	SPZ	1024	40.35	0.08	0.16
SPZ1037GL	SPZ	1037	40.85	0.08	0.16
SPZ1087GL	SPZ	1087	42.80	0.09	0.17
SPZ1120GL	SPZ	1120	44.10	0.09	0.18
SPZ1147GL	SPZ	1147	45.15	0.09	0.18
SPZ1270GL	SPZ	1270	50.00	0.10	0.20
SPZ1287GL	SPZ	1287	50.70	0.10	0.20
SPZ1312GL	SPZ	1312	51.65	0.10	0.21
SPZ1337GL	SPZ	1337	52.65	0.11	0.21
SPZ1362GL	SPZ	1362	53.65	0.11	0.21
SPZ1387GL	SPZ	1387	54.65	0.11	0.22




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPZ1412GL	SPZ	1412	55.60	0.11	0.22
SPZ1437GL	SPZ	1437	56.60	0.11	0.23
SPZ1462GL	SPZ	1462	57.60	0.12	0.23
SPZ1470GL	SPZ	1470	57.90	0.12	0.23
SPZ1487GL	SPZ	1487	58.60	0.12	0.23
SPZ1500GL	SPZ	1500	59.10	0.12	0.24
SPZ1512GL	SPZ	1512	59.55	0.12	0.24
SPZ1520GL	SPZ	1520	59.90	0.12	0.24
SPZ1537GL	SPZ	1537	60.55	0.12	0.24
SPZ1562GL	SPZ	1562	61.50	0.12	0.25
SPZ1575GL	SPZ	1575	62.05	0.12	0.25
SPZ1587GL	SPZ	1587	62.50	0.13	0.25
SPZ1600GL	SPZ	1600	63.00	0.13	0.25
SPZ1612GL	SPZ	1612	63.50	0.13	0.25
SPZ1637GL	SPZ	1637	64.45	0.13	0.26
SPZ1650GL	SPZ	1650	65.00	0.13	0.26
SPZ1662GL	SPZ	1662	65.45	0.13	0.26
SPZ1687GL	SPZ	1687	66.45	0.13	0.27
SPZ1700GL	SPZ	1700	66.95	0.13	0.27
SPZ1737GL	SPZ	1737	68.40	0.14	0.27
SPZ1750GL	SPZ	1750	68.90	0.14	0.28
SPZ1762GL	SPZ	1762	69.40	0.14	0.28
SPZ1787GL	SPZ	1787	70.35	0.14	0.28
SPZ1800GL	SPZ	1800	70.90	0.14	0.28
SPZ1812GL	SPZ	1812	71.40	0.14	0.29
SPZ1837GL	SPZ	1837	72.35	0.15	0.29
SPZ1850GL	SPZ	1850	72.85	0.15	0.29
SPZ1862GL	SPZ	1862	73.35	0.15	0.29
SPZ1887GL	SPZ	1887	74.30	0.15	0.30
SPZ1900GL	SPZ	1900	74.80	0.15	0.30
SPZ1937GL	SPZ	1937	76.30	0.15	0.31
SPZ1950GL	SPZ	1950	76.80	0.15	0.31
SPZ1962GL	SPZ	1962	77.30	0.15	0.31
SPZ1987GL	SPZ	1987	78.25	0.16	0.31
SPZ2000GL	SPZ	2000	78.80	0.16	0.31
SPZ2030GL	SPZ	2030	79.95	0.16	0.32
SPZ2037GL	SPZ	2037	80.20	0.16	0.32




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPZ2060GL	SPZ	2060	81.10	0.16	0.32
SPZ2062GL	SPZ	2062	81.20	0.16	0.32
SPZ2087GL	SPZ	2087	82.20	0.16	0.33
SPZ2100GL	SPZ	2100	82.70	0.17	0.33
SPZ2120GL	SPZ	2120	83.50	0.17	0.33
SPZ2130GL	SPZ	2130	83.85	0.17	0.34
SPZ2137GL	SPZ	2137	84.15	0.17	0.34
SPZ2150GL	SPZ	2150	84.65	0.17	0.34
SPZ2160GL	SPZ	2160	85.10	0.17	0.34
SPZ2180GL	SPZ	2180	85.85	0.17	0.34
SPZ2187GL	SPZ	2187	86.10	0.17	0.34
SPZ2240GL	SPZ	2240	88.20	0.18	0.35
SPZ2287GL	SPZ	2287	90.10	0.18	0.36
SPZ2300GL	SPZ	2300	90.55	0.18	0.36
SPZ2360GL	SPZ	2360	92.95	0.19	0.37
SPZ2387GL	SPZ	2387	94.00	0.19	0.38
SPZ2410GL	SPZ	2410	94.90	0.19	0.38
SPZ2437GL	SPZ	2437	96.00	0.19	0.38
SPZ2487GL	SPZ	2487	97.95	0.20	0.39
SPZ2500GL	SPZ	2500	98.45	0.20	0.39
SPZ2540GL	SPZ	2540	100.00	0.20	0.40
SPZ2650GL	SPZ	2650	104.35	0.21	0.42
SPZ2800GL	SPZ	2800	110.30	0.22	0.44
SPZ2840GL	SPZ	2840	111.85	0.22	0.45
SPZ3000GL	SPZ	3000	118.15	0.24	0.47
SPZ3150GL	SPZ	3150	124.05	0.25	0.50
SPZ3350GL	SPZ	3350	131.90	0.26	0.53
SPZ3550GL	SPZ	3550	139.80	0.28	0.56
SPA1482GL	SPA	1482	58.35	0.19	0.41
SPA1500GL	SPA	1500	59.10	0.19	0.41
SPA1507GL	SPA	1507	59.35	0.19	0.42
SPA1525GL	SPA	1525	60.05	0.19	0.42
SPA1532GL	SPA	1532	60.35	0.19	0.42
SPA1550GL	SPA	1550	61.05	0.20	0.43
SPA1557GL	SPA	1557	61.30	0.20	0.43
SPA1582GL	SPA	1582	62.30	0.20	0.44
SPA1600GL	SPA	1600	63.00	0.20	0.44




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPA1607GL	SPA	1607	63.30	0.20	0.44
SPA1632GL	SPA	1632	64.25	0.21	0.45
SPA1637GL	SPA	1637	64.45	0.21	0.45
SPA1650GL	SPA	1650	65.00	0.21	0.45
SPA1657GL	SPA	1657	65.25	0.21	0.46
SPA1675GL	SPA	1675	65.95	0.21	0.46
SPA1682GL	SPA	1682	66.25	0.21	0.46
SPA1700GL	SPA	1700	66.95	0.21	0.47
SPA1707GL	SPA	1707	67.20	0.22	0.47
SPA1732GL	SPA	1732	68.20	0.22	0.48
SPA1750GL	SPA	1750	68.90	0.22	0.48
SPA1757GL	SPA	1757	69.20	0.22	0.48
SPA1782GL	SPA	1782	70.20	0.22	0.49
SPA1800GL	SPA	1800	70.90	0.23	0.50
SPA1807GL	SPA	1807	71.15	0.23	0.50
SPA1832GL	SPA	1832	72.15	0.23	0.50
SPA1850GL	SPA	1850	72.85	0.23	0.51
SPA1857GL	SPA	1857	73.15	0.23	0.51
SPA1882GL	SPA	1882	74.10	0.24	0.52
SPA1900GL	SPA	1900	74.80	0.24	0.52
SPA1907GL	SPA	1907	75.10	0.24	0.53
SPA1925GL	SPA	1925	75.80	0.24	0.53
SPA1932GL	SPA	1932	76.10	0.24	0.53
SPA1950GL	SPA	1950	76.80	0.25	0.54
SPA1957GL	SPA	1957	77.05	0.25	0.54
SPA1982GL	SPA	1982	78.05	0.25	0.55
SPA2000GL	SPA	2000	78.75	0.25	0.55
SPA2032GL	SPA	2032	80.00	0.26	0.56
SPA2057GL	SPA	2057	81.00	0.26	0.57
SPA2082GL	SPA	2082	82.00	0.26	0.57
SPA2100GL	SPA	2100	82.70	0.26	0.58
SPA2120GL	SPA	2120	83.50	0.27	0.58
SPA2132GL	SPA	2132	83.95	0.27	0.59
SPA2150GL	SPA	2150	84.65	0.27	0.59
SPA2180GL	SPA	2180	85.85	0.27	0.60
SPA2182GL	SPA	2182	85.95	0.27	0.60
SPA2207GL	SPA	2207	86.90	0.28	0.61




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPA2232GL	SPA	2232	87.90	0.28	0.62
SPA2240GL	SPA	2240	88.20	0.28	0.62
SPA2282GL	SPA	2282	89.85	0.29	0.63
SPA2300GL	SPA	2300	90.55	0.29	0.63
SPA2307GL	SPA	2307	90.85	0.29	0.64
SPA2332GL	SPA	2332	91.85	0.29	0.64
SPA2360GL	SPA	2360	92.95	0.30	0.65
SPA2382GL	SPA	2382	93.80	0.30	0.66
SPA2400GL	SPA	2400	94.50	0.30	0.66
SPA2425GL	SPA	2425	95.45	0.31	0.67
SPA2432GL	SPA	2432	95.75	0.31	0.67
SPA2450GL	SPA	2450	96.50	0.31	0.68
SPA2482GL	SPA	2482	97.75	0.31	0.68
SPA2500GL	SPA	2500	98.45	0.32	0.69
SPA2532GL	SPA	2532	99.70	0.32	0.70
SPA2550GL	SPA	2550	100.40	0.32	0.70
SPA2582GL	SPA	2582	101.65	0.33	0.71
SPA2600GL	SPA	2600	102.40	0.33	0.72
SPA2607GL	SPA	2607	102.65	0.33	0.72
SPA2632GL	SPA	2632	103.65	0.33	0.73
SPA2650GL	SPA	2650	104.35	0.33	0.73
SPA2682GL	SPA	2682	105.60	0.34	0.74
SPA2700GL	SPA	2700	106.30	0.34	0.74
SPA2720GL	SPA	2720	107.10	0.34	0.75
SPA2732GL	SPA	2732	107.60	0.34	0.75
SPA2750GL	SPA	2750	108.30	0.35	0.76
SPA2782GL	SPA	2782	109.55	0.35	0.77
SPA2800GL	SPA	2800	110.25	0.35	0.77
SPA2832GL	SPA	2832	111.50	0.36	0.78
SPA2847GL	SPA	2847	112.10	0.36	0.78
SPA2882GL	SPA	2882	113.50	0.36	0.79
SPA2900GL	SPA	2900	114.20	0.37	0.80
SPA2932GL	SPA	2932	115.45	0.37	0.81
SPA2950GL	SPA	2950	116.15	0.37	0.81
SPA2982GL	SPA	2982	117.40	0.38	0.82
SPA3000GL	SPA	3000	118.15	0.38	0.83
SPA3032GL	SPA	3032	119.40	0.38	0.84




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPA3082GL	SPA	3082	121.35	0.39	0.85
SPA3150GL	SPA	3150	124.05	0.40	0.87
SPA3182GL	SPA	3182	125.30	0.40	0.88
SPA3200GL	SPA	3200	126.00	0.40	0.88
SPA3250GL	SPA	3250	127.95	0.41	0.90
SPA3282GL	SPA	3282	129.25	0.41	0.90
SPA3350GL	SPA	3350	131.90	0.42	0.92
SPA3382GL	SPA	3382	133.15	0.43	0.93
SPA3450GL	SPA	3450	135.85	0.43	0.95
SPA3500GL	SPA	3500	137.80	0.44	0.96
SPA3550GL	SPA	3550	139.80	0.45	0.98
SPA3650GL	SPA	3650	143.70	0.46	1.01
SPA3750GL	SPA	3750	147.65	0.47	1.03
SPA4000GL	SPA	4000	157.50	0.50	1.10
SPA4250GL	SPA	4250	167.35	0.54	1.17
SPA4500GL	SPA	4500	177.20	0.57	1.24
SPB1500GL	SPB	1500	59.10	0.29	0.65
SPB1520GL	SPB	1520	59.85	0.29	0.66
SPB1525GL	SPB	1525	60.05	0.29	0.66
SPB1550GL	SPB	1550	61.05	0.30	0.67
SPB1600GL	SPB	1600	63.00	0.31	0.69
SPB1650GL	SPB	1650	65.00	0.32	0.71
SPB1675GL	SPB	1675	65.95	0.32	0.73
SPB1700GL	SPB	1700	66.95	0.33	0.74
SPB1725GL	SPB	1725	67.90	0.33	0.75
SPB1750GL	SPB	1750	68.90	0.34	0.76
SPB1800GL	SPB	1800	70.90	0.35	0.78
SPB1850GL	SPB	1850	72.85	0.36	0.80
SPB1860GL	SPB	1860	73.20	0.36	0.81
SPB1900GL	SPB	1900	74.80	0.37	0.82
SPB1930GL	SPB	1930	76.00	0.37	0.84
SPB1950GL	SPB	1950	76.80	0.38	0.84
SPB2000GL	SPB	2000	78.75	0.39	0.87
SPB2020GL	SPB	2020	79.55	0.39	0.87
SPB2030GL	SPB	2030	79.90	0.39	0.88
SPB2050GL	SPB	2050	80.70	0.40	0.89
SPB2060GL	SPB	2060	81.10	0.40	0.89




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPB2080GL	SPB	2080	81.90	0.40	0.90
SPB2100GL	SPB	2100	82.70	0.41	0.91
SPB2120GL	SPB	2120	83.50	0.41	0.92
SPB2150GL	SPB	2150	84.65	0.41	0.93
SPB2180GL	SPB	2180	85.85	0.42	0.94
SPB2210GL	SPB	2210	87.00	0.43	0.96
SPB2240GL	SPB	2240	88.20	0.43	0.97
SPB2280GL	SPB	2280	89.80	0.44	0.99
SPB2300GL	SPB	2300	90.55	0.44	1.00
SPB2320GL	SPB	2320	91.35	0.45	1.00
SPB2360GL	SPB	2360	92.95	0.46	1.02
SPB2391GL	SPB	2391	94.15	0.46	1.04
SPB2400GL	SPB	2400	94.50	0.46	1.04
SPB2410GL	SPB	2410	94.90	0.47	1.04
SPB2430GL	SPB	2430	95.70	0.47	1.05
SPB2450GL	SPB	2450	96.45	0.47	1.06
SPB2475GL	SPB	2475	97.45	0.48	1.07
SPB2500GL	SPB	2500	98.45	0.48	1.08
SPB2530GL	SPB	2530	99.65	0.49	1.10
SPB2550GL	SPB	2550	100.40	0.49	1.10
SPB2580GL	SPB	2580	101.60	0.50	1.12
SPB2600GL	SPB	2600	102.35	0.50	1.13
SPB2650GL	SPB	2650	104.35	0.51	1.15
SPB2680GL	SPB	2680	105.55	0.52	1.16
SPB2700GL	SPB	2700	106.30	0.52	1.17
SPB2720GL	SPB	2720	107.10	0.52	1.18
SPB2732GL	SPB	2732	107.55	0.53	1.18
SPB2750GL	SPB	2750	108.25	0.53	1.19
SPB2800GL	SPB	2800	110.25	0.54	1.21
SPB2840GL	SPB	2840	111.85	0.55	1.23
SPB2850GL	SPB	2850	112.20	0.55	1.23
SPB2900GL	SPB	2900	114.20	0.56	1.26
SPB2920GL	SPB	2920	114.95	0.56	1.26
SPB2950GL	SPB	2950	116.15	0.57	1.28
SPB3000GL	SPB	3000	118.15	0.58	1.30
SPB3050GL	SPB	3050	120.10	0.59	1.32
SPB3070GL	SPB	3070	120.90	0.59	1.33




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPB3100GL	SPB	3100	122.05	0.60	1.34
SPB3150GL	SPB	3150	124.05	0.61	1.36
SPB3170GL	SPB	3170	124.80	0.61	1.37
SPB3200GL	SPB	3200	126.00	0.62	1.39
SPB3250GL	SPB	3250	127.95	0.63	1.41
SPB3300GL	SPB	3300	129.90	0.64	1.43
SPB3340GL	SPB	3340	131.50	0.64	1.45
SPB3350GL	SPB	3350	131.90	0.65	1.45
SPB3450GL	SPB	3450	135.85	0.67	1.49
SPB3500GL	SPB	3500	137.80	0.68	1.52
SPB3550GL	SPB	3550	139.80	0.69	1.54
SPB3650GL	SPB	3650	143.70	0.70	1.58
SPB3750GL	SPB	3750	147.65	0.72	1.62
SPB3800GL	SPB	3800	149.65	0.73	1.65
SPB3870GL	SPB	3870	152.40	0.75	1.68
SPB4000GL	SPB	4000	157.50	0.77	1.73
SPB4060GL	SPB	4060	159.85	0.78	1.76
SPB4120GL	SPB	4120	162.20	0.80	1.78
SPB4250GL	SPB	4250	167.35	0.82	1.84
SPB4310GL	SPB	4310	169.70	0.83	1.87
SPB4370GL	SPB	4370	172.05	0.84	1.89
SPB4500GL	SPB	4500	177.20	0.87	1.95
SPB4560GL	SPB	4560	179.55	0.88	1.97
SPB4750GL	SPB	4750	187.05	0.92	2.06
SPB4820GL	SPB	4820	189.80	0.93	2.09
SPB5000GL	SPB	5000	196.85	0.97	2.17
SPB5300GL	SPB	5300	208.70	1.02	2.30
SPB5600GL	SPB	5600	220.50	1.08	2.43
SPB6000GL	SPB	6000	236.25	1.16	2.60
SPB6300GL	SPB	6300	248.05	1.22	2.73
SPB6700GL	SPB	6700	263.80	1.29	2.90
SPB7100GL	SPB	7100	279.55	1.37	3.07
SPB7500GL	SPB	7500	295.30	1.45	3.25
SPB8000GL	SPB	8000	315.00	1.54	3.46
SPB9500GL	SPB	9500	374.00	1.83	4.11
SPC2000GL	SPC	2000	78.75	0.77	1.73
SPC2120GL	SPC	2120	83.50	0.82	1.84




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPC2240GL	SPC	2240	88.20	0.86	1.94
SPC2340GL	SPC	2340	92.15	0.90	2.03
SPC2360GL	SPC	2360	92.95	0.91	2.04
SPC2400GL	SPC	2400	94.50	0.93	2.08
SPC2500GL	SPC	2500	98.45	0.97	2.17
SPC2600GL	SPC	2600	102.40	1.00	2.25
SPC2650GL	SPC	2650	104.35	1.02	2.30
SPC2700GL	SPC	2700	106.30	1.04	2.34
SPC2750GL	SPC	2750	108.25	1.06	2.38
SPC2800GL	SPC	2800	110.25	1.08	2.43
SPC2850GL	SPC	2850	112.20	1.10	2.47
SPC2890GL	SPC	2890	113.80	1.12	2.50
SPC2900GL	SPC	2900	114.15	1.12	2.51
SPC2950GL	SPC	2950	116.15	1.14	2.56
SPC3000GL	SPC	3000	118.15	1.16	2.60
SPC3150GL	SPC	3150	124.05	1.22	2.73
SPC3200GL	SPC	3200	126.00	1.24	2.77
SPC3250GL	SPC	3250	127.95	1.25	2.81
SPC3300GL	SPC	3300	129.90	1.27	2.86
SPC3350GL	SPC	3350	131.90	1.29	2.90
SPC3400GL	SPC	3400	133.85	1.31	2.94
SPC3450GL	SPC	3450	135.85	1.33	2.99
SPC3500GL	SPC	3500	137.80	1.35	3.03
SPC3550GL	SPC	3550	139.80	1.37	3.07
SPC3750GL	SPC	3750	147.65	1.45	3.25
SPC4000GL	SPC	4000	157.50	1.54	3.46
SPC4250GL	SPC	4250	167.35	1.64	3.68
SPC4400GL	SPC	4400	173.25	1.70	3.81
SPC4500GL	SPC	4500	177.20	1.74	3.90
SPC4710GL	SPC	4710	185.45	1.82	4.08
SPC4750GL	SPC	4750	187.05	1.83	4.11
SPC5000GL	SPC	5000	196.85	1.93	4.33
SPC5300GL	SPC	5300	208.70	2.05	4.59
SPC5600GL	SPC	5600	220.50	2.16	4.85
SPC5800GL	SPC	5800	228.35	2.24	5.02
SPC6000GL	SPC	6000	236.25	2.32	5.20
SPC6250GL	SPC	6250	246.05	2.41	5.41




MOVE FORWARD. ALWAYS.™

GOLD LABEL Wedge - Size List



V-Belt

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
SPZ	10	8	0.079
SPA	13	10	0.126
SPB	17	14	0.193
SPC	22	18	0.386

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
SPZ	25/64	5/16	0.004
SPA	33/64	25/64	0.007
SPB	43/64	35/64	0.011
SPC	7/8	45/64	0.022

DAYCO Part Nr	Section	Ld Datum length (mm)	Lo Datum length (in)	Weight (Kg)	Weight (lbs)
SPC6300GL	SPC	6300	248.05	2.43	5.46
SPC6700GL	SPC	6700	263.80	2.59	5.80
SPC6800GL	SPC	6800	267.70	2.62	5.89
SPC7000GL	SPC	7000	275.60	2.70	6.06
SPC7100GL	SPC	7100	279.55	2.74	6.15
SPC7500GL	SPC	7500	295.30	2.90	6.50
SPC7800GL	SPC	7800	307.10	3.01	6.76
SPC8000GL	SPC	8000	315.00	3.09	6.93
SPC8500GL	SPC	8500	334.65	3.28	7.36
SPC8750GL	SPC	8750	344.50	3.38	7.58
SPC9000GL	SPC	9000	354.35	3.47	7.80
SPC9500GL	SPC	9500	374.05	3.67	8.23
SPC10000GL	SPC	10000	393.70	3.86	8.66
SPC10600GL	SPC	10600	417.35	4.09	9.18
SPC11200GL	SPC	11200	440.95	4.32	9.70



PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is < 30 °C / 86 °F
- Continues high temperature (50 °C / 122 °F) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly storage belt shelf life is at least 5 years
- Short belt up to 1,5 m / 59 in can be stored on pegs
- Long belts better to be coiled on shelves for distortion – free



This image shows a single page of white paper with horizontal blue or grey ruling lines. The lines are evenly spaced and run across the width of the page, leaving small margins at the top and bottom. There is no handwriting or printed text on the page.

Product Guide

GOLD LABEL™ Industrial Raw Edge V-Belts



GOLD LABEL™


Designed for **OEMs**

DAYCO®
MOVE FORWARD. ALWAYS.™




MOVE FORWARD. ALWAYS.™

GOLD LABEL Raw Edge - Table of Contents



V-Belt

GOLD LABEL™




ZX-AX-BX-CX

GOLD LABEL X Classical

Raw Edge classical V-Belt.


Product description 3

Size List 4



V-Belt

GOLD LABEL™




3VX-5VX

GOLD LABEL X Narrow

Designed for more compact multiple-belt drives. Imperial design.

Product description 18

Size List 19



V-Belt

GOLD LABEL™



XPZ-XPA-XPB-XPC


GOLD LABEL X Wedge

Designed for more compact multiple-belt drives. Metric design.


Product description 25

Size List 26

GOLD LABEL X Classical - Product Description



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

V-Belt Raw Edge

Part Number Description: **AX40GL**

AX: Profile (13mm X 8mm)

40: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance.

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching

Designed for OEMs

Markets and Applications:


Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps, woods...), in particular where temperature and power capacity are critical.

Pulley standards: DIN2211-ISO4183




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX18GL	ZX	457	490	18.00	19.25	0.03	0.07
ZX19.5GL	ZX	495	528	19.50	20.75	0.03	0.08
ZX20GL	ZX	508	541	20.00	21.25	0.03	0.08
ZX20.5GL	ZX	521	554	20.50	21.75	0.03	0.08
ZX21GL	ZX	533	566	21.00	22.25	0.03	0.08
ZX21.25GL	ZX	540	573	21.25	22.50	0.03	0.09
ZX21.75GL	ZX	552	585	21.75	23.00	0.03	0.09
ZX22GL	ZX	559	592	22.00	23.25	0.04	0.09
ZX22.25GL	ZX	565	598	22.25	23.50	0.04	0.09
ZX22.5GL	ZX	572	605	22.50	23.75	0.04	0.09
ZX23GL	ZX	584	617	23.00	24.25	0.04	0.09
ZX23.5GL	ZX	597	630	23.50	24.75	0.04	0.09
ZX23.75GL	ZX	603	636	23.75	25.00	0.04	0.09
ZX24GL	ZX	610	643	24.00	25.25	0.04	0.10
ZX24.75GL	ZX	629	662	24.75	26.00	0.04	0.10
ZX25GL	ZX	635	668	25.00	26.25	0.04	0.10
ZX25.5GL	ZX	648	681	25.50	26.75	0.04	0.10
ZX25.75GL	ZX	654	687	25.75	27.00	0.04	0.10
ZX26GL	ZX	660	693	26.00	27.25	0.04	0.10
ZX26.5GL	ZX	673	706	26.50	27.75	0.04	0.11
ZX27GL	ZX	686	719	27.00	28.25	0.04	0.11
ZX27.5GL	ZX	699	732	27.50	28.75	0.04	0.11
ZX28GL	ZX	711	744	28.00	29.25	0.04	0.11
ZX28.5GL	ZX	724	757	28.50	29.75	0.05	0.11
ZX29GL	ZX	737	770	29.00	30.25	0.05	0.12
ZX29.5GL	ZX	749	782	29.50	30.75	0.05	0.12
ZX30GL	ZX	762	795	30.00	31.25	0.05	0.12
ZX30.5GL	ZX	775	808	30.50	31.75	0.05	0.12
ZX30.75GL	ZX	781	814	30.75	32.00	0.05	0.12
ZX31GL	ZX	787	820	31.00	32.25	0.05	0.12
ZX31.5GL	ZX	800	833	31.50	32.75	0.05	0.13




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX32GL	ZX	813	846	32.00	33.25	0.05	0.13
ZX32.5GL	ZX	826	859	32.50	33.75	0.05	0.13
ZX33GL	ZX	838	871	33.00	34.25	0.05	0.13
ZX33.5GL	ZX	851	884	33.50	34.75	0.05	0.13
ZX34GL	ZX	864	897	34.00	35.25	0.05	0.14
ZX34.25GL	ZX	870	903	34.25	35.50	0.05	0.14
ZX34.5GL	ZX	876	909	34.50	35.75	0.06	0.14
ZX35GL	ZX	889	922	35.00	36.25	0.06	0.14
ZX35.5GL	ZX	902	935	35.50	36.75	0.06	0.14
ZX36GL	ZX	914	947	36.00	37.25	0.06	0.14
ZX36.5GL	ZX	927	960	36.50	37.75	0.06	0.15
ZX36.75GL	ZX	933	966	36.75	38.00	0.06	0.15
ZX37GL	ZX	940	973	37.00	38.25	0.06	0.15
ZX37.5GL	ZX	953	986	37.50	38.75	0.06	0.15
ZX38GL	ZX	965	998	38.00	39.25	0.06	0.15
ZX38.25GL	ZX	972	1005	38.25	39.50	0.06	0.15
ZX38.5GL	ZX	978	1011	38.50	39.75	0.06	0.15
ZX39GL	ZX	991	1024	39.00	40.25	0.06	0.16
ZX39.5GL	ZX	1003	1036	39.50	40.75	0.06	0.16
ZX40GL	ZX	1016	1049	40.00	41.25	0.06	0.16
ZX40.5GL	ZX	1029	1062	40.50	41.75	0.06	0.16
ZX41GL	ZX	1041	1074	41.00	42.25	0.07	0.16
ZX41.5GL	ZX	1054	1087	41.50	42.75	0.07	0.17
ZX41.75GL	ZX	1060	1093	41.75	43.00	0.07	0.17
ZX42GL	ZX	1067	1100	42.00	43.25	0.07	0.17
ZX42.5GL	ZX	1080	1113	42.50	43.75	0.07	0.17
ZX43GL	ZX	1092	1125	43.00	44.25	0.07	0.17
ZX43.25GL	ZX	1099	1132	43.25	44.50	0.07	0.17
ZX44GL	ZX	1118	1151	44.00	45.25	0.07	0.18
ZX45GL	ZX	1143	1176	45.00	46.25	0.07	0.18
ZX46GL	ZX	1168	1201	46.00	47.25	0.07	0.18
ZX46.75GL	ZX	1187	1220	46.75	48.00	0.07	0.19




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX47GL	ZX	1194	1227	47.00	48.25	0.08	0.19
ZX47.5GL	ZX	1207	1240	47.50	48.75	0.08	0.19
ZX47.75GL	ZX	1213	1246	47.75	49.00	0.08	0.19
ZX48GL	ZX	1219	1252	48.00	49.25	0.08	0.19
ZX49GL	ZX	1245	1278	49.00	50.25	0.08	0.20
ZX50GL	ZX	1270	1303	50.00	51.25	0.08	0.20
ZX50.5GL	ZX	1283	1316	50.50	51.75	0.08	0.20
ZX51GL	ZX	1295	1328	51.00	52.25	0.08	0.20
ZX52GL	ZX	1321	1354	52.00	53.25	0.08	0.21
ZX53GL	ZX	1346	1379	53.00	54.25	0.08	0.21
ZX54GL	ZX	1372	1405	54.00	55.25	0.09	0.22
ZX55GL	ZX	1397	1430	55.00	56.25	0.09	0.22
ZX56GL	ZX	1422	1455	56.00	57.25	0.09	0.22
ZX57GL	ZX	1448	1481	57.00	58.25	0.09	0.23
ZX58GL	ZX	1473	1506	58.00	59.25	0.09	0.23
ZX59GL	ZX	1499	1532	59.00	60.25	0.09	0.24
ZX59.5GL	ZX	1511	1544	59.50	60.75	0.10	0.24
ZX60GL	ZX	1524	1557	60.00	61.25	0.10	0.24
ZX61GL	ZX	1549	1582	61.00	62.25	0.10	0.24
ZX62GL	ZX	1575	1608	62.00	63.25	0.10	0.25
ZX63GL	ZX	1600	1633	63.00	64.25	0.10	0.25
ZX64GL	ZX	1626	1659	64.00	65.25	0.10	0.26
ZX65GL	ZX	1651	1684	65.00	66.25	0.10	0.26
ZX66GL	ZX	1676	1709	66.00	67.25	0.11	0.26
ZX67GL	ZX	1702	1735	67.00	68.25	0.11	0.27
ZX68GL	ZX	1727	1760	68.00	69.25	0.11	0.27
ZX69GL	ZX	1753	1786	69.00	70.25	0.11	0.28
ZX70GL	ZX	1778	1811	70.00	71.25	0.11	0.28
ZX71GL	ZX	1803	1836	71.00	72.25	0.11	0.28
ZX73GL	ZX	1854	1887	73.00	74.25	0.12	0.29
ZX75GL	ZX	1905	1938	75.00	76.25	0.12	0.30




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
ZX76GL	ZX	1930	1963	76.00	77.25	0.12	0.30
ZX78GL	ZX	1981	2014	78.00	79.25	0.12	0.31
ZX79GL	ZX	2007	2040	79.00	80.25	0.13	0.32
ZX80GL	ZX	2032	2065	80.00	81.25	0.13	0.32
ZX83GL	ZX	2108	2141	83.00	84.25	0.13	0.33
ZX85GL	ZX	2159	2192	85.00	86.25	0.14	0.34
ZX88GL	ZX	2235	2268	88.00	89.25	0.14	0.35
ZX90GL	ZX	2286	2319	90.00	91.25	0.14	0.36
ZX95GL	ZX	2413	2446	95.00	96.25	0.15	0.38
ZX98GL	ZX	2489	2522	98.00	99.25	0.16	0.39
AX18GL	AX	457	508	18.00	20.00	0.04	0.09
AX19GL	AX	483	534	19.00	21.00	0.05	0.10
AX20GL	AX	508	559	20.00	22.00	0.05	0.10
AX21GL	AX	533	584	21.00	23.00	0.05	0.10
AX22GL	AX	559	610	22.00	24.00	0.05	0.11
AX22.75GL	AX	578	629	22.75	24.75	0.05	0.11
AX23GL	AX	584	635	23.00	25.00	0.05	0.11
AX23.5GL	AX	597	648	23.50	25.50	0.06	0.12
AX24GL	AX	610	661	24.00	26.00	0.06	0.12
AX25GL	AX	635	686	25.00	27.00	0.06	0.13
AX25.5GL	AX	648	699	25.50	27.50	0.06	0.13
AX26GL	AX	660	711	26.00	28.00	0.06	0.13
AX26.5GL	AX	673	724	26.50	28.50	0.06	0.13
AX27GL	AX	686	737	27.00	29.00	0.06	0.14
AX27.5GL	AX	699	750	27.50	29.50	0.07	0.14
AX28GL	AX	711	762	28.00	30.00	0.07	0.14
AX28.5GL	AX	724	775	28.50	30.50	0.07	0.14
AX29GL	AX	737	788	29.00	31.00	0.07	0.15
AX29.5GL	AX	749	800	29.50	31.50	0.07	0.15
AX30GL	AX	762	813	30.00	32.00	0.07	0.15
AX30.5GL	AX	775	826	30.50	32.50	0.07	0.15
AX31GL	AX	787	838	31.00	33.00	0.07	0.15




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX31.5GL	AX	800	851	31.50	33.50	0.08	0.16
AX32GL	AX	813	864	32.00	34.00	0.08	0.16
AX32.5GL	AX	826	877	32.50	34.50	0.08	0.16
AX33GL	AX	838	889	33.00	35.00	0.08	0.16
AX33.5GL	AX	851	902	33.50	35.50	0.08	0.17
AX34GL	AX	864	915	34.00	36.00	0.08	0.17
AX35GL	AX	889	940	35.00	37.00	0.08	0.18
AX35.5GL	AX	902	953	35.50	37.50	0.08	0.18
AX36GL	AX	914	965	36.00	38.00	0.09	0.18
AX36.25GL	AX	921	972	36.25	38.25	0.09	0.18
AX36.5GL	AX	927	978	36.50	38.50	0.09	0.18
AX37GL	AX	940	991	37.00	39.00	0.09	0.19
AX37.5GL	AX	953	1004	37.50	39.50	0.09	0.19
AX38GL	AX	965	1016	38.00	40.00	0.09	0.19
AX38.5GL	AX	978	1029	38.50	40.50	0.09	0.19
AX39GL	AX	991	1042	39.00	41.00	0.09	0.20
AX40GL	AX	1016	1067	40.00	42.00	0.10	0.20
AX40.5GL	AX	1029	1080	40.50	42.50	0.10	0.20
AX41GL	AX	1041	1092	41.00	43.00	0.10	0.20
AX41.5GL	AX	1054	1105	41.50	43.50	0.10	0.21
AX42GL	AX	1067	1118	42.00	44.00	0.10	0.21
AX42.5GL	AX	1080	1131	42.50	44.50	0.10	0.21
AX43GL	AX	1092	1143	43.00	45.00	0.10	0.21
AX44GL	AX	1118	1169	44.00	46.00	0.11	0.22
AX45GL	AX	1143	1194	45.00	47.00	0.11	0.23
AX45.25GL	AX	1149	1200	45.25	47.25	0.11	0.23
AX45.5GL	AX	1156	1207	45.50	47.50	0.11	0.23
AX46GL	AX	1168	1219	46.00	48.00	0.11	0.23
AX46.5GL	AX	1181	1232	46.50	48.50	0.11	0.23
AX47GL	AX	1194	1245	47.00	49.00	0.11	0.24
AX48GL	AX	1219	1270	48.00	50.00	0.11	0.24
AX49GL	AX	1245	1296	49.00	51.00	0.12	0.25

GOLD LABEL X Classical - Size list



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX50GL	AX	1270	1321	50.00	52.00	0.12	0.25
AX51GL	AX	1295	1346	51.00	53.00	0.12	0.25
AX52GL	AX	1321	1372	52.00	54.00	0.12	0.26
AX53GL	AX	1346	1397	53.00	55.00	0.13	0.26
AX54GL	AX	1372	1423	54.00	56.00	0.13	0.27
AX55GL	AX	1397	1448	55.00	57.00	0.13	0.28
AX56GL	AX	1422	1473	56.00	58.00	0.13	0.28
AX57GL	AX	1448	1499	57.00	59.00	0.14	0.29
AX58GL	AX	1473	1524	58.00	60.00	0.14	0.29
AX59GL	AX	1499	1550	59.00	61.00	0.14	0.30
AX60GL	AX	1524	1575	60.00	62.00	0.14	0.30
AX61GL	AX	1549	1600	61.00	63.00	0.15	0.30
AX62GL	AX	1575	1626	62.00	64.00	0.15	0.31
AX63GL	AX	1600	1651	63.00	65.00	0.15	0.31
AX63.5GL	AX	1613	1664	63.50	65.50	0.15	0.32
AX64GL	AX	1626	1677	64.00	66.00	0.15	0.32
AX65GL	AX	1651	1702	65.00	67.00	0.16	0.33
AX65.5GL	AX	1664	1715	65.50	67.50	0.16	0.33
AX66GL	AX	1676	1727	66.00	68.00	0.16	0.33
AX67GL	AX	1702	1753	67.00	69.00	0.16	0.34
AX67.5GL	AX	1715	1766	67.50	69.50	0.16	0.34
AX68GL	AX	1727	1778	68.00	70.00	0.16	0.34
AX69GL	AX	1753	1804	69.00	71.00	0.16	0.35
AX70GL	AX	1778	1829	70.00	72.00	0.17	0.35
AX71GL	AX	1803	1854	71.00	73.00	0.17	0.35
AX71.5GL	AX	1816	1867	71.50	73.50	0.17	0.36
AX72GL	AX	1829	1880	72.00	74.00	0.17	0.36
AX73GL	AX	1854	1905	73.00	75.00	0.17	0.36
AX74GL	AX	1880	1931	74.00	76.00	0.18	0.37
AX75GL	AX	1905	1956	75.00	77.00	0.18	0.38
AX75.5GL	AX	1918	1969	75.50	77.50	0.18	0.38
AX76GL	AX	1930	1981	76.00	78.00	0.18	0.38




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX77GL	AX	1956	2007	77.00	79.00	0.18	0.39
AX78GL	AX	1981	2032	78.00	80.00	0.19	0.39
AX79GL	AX	2007	2058	79.00	81.00	0.19	0.40
AX80GL	AX	2032	2083	80.00	82.00	0.19	0.40
AX81GL	AX	2057	2108	81.00	83.00	0.19	0.40
AX82GL	AX	2083	2134	82.00	84.00	0.20	0.41
AX83GL	AX	2108	2159	83.00	85.00	0.20	0.41
AX84GL	AX	2134	2185	84.00	86.00	0.20	0.42
AX85GL	AX	2159	2210	85.00	87.00	0.20	0.43
AX86GL	AX	2184	2235	86.00	88.00	0.21	0.43
AX87GL	AX	2210	2261	87.00	89.00	0.21	0.44
AX88GL	AX	2235	2286	88.00	90.00	0.21	0.44
AX89GL	AX	2261	2312	89.00	91.00	0.21	0.45
AX90GL	AX	2286	2337	90.00	92.00	0.21	0.45
AX91GL	AX	2311	2362	91.00	93.00	0.22	0.45
AX92GL	AX	2337	2388	92.00	94.00	0.22	0.46
AX93GL	AX	2362	2413	93.00	95.00	0.22	0.46
AX94GL	AX	2388	2439	94.00	96.00	0.22	0.47
AX95GL	AX	2413	2464	95.00	97.00	0.23	0.48
AX96GL	AX	2438	2489	96.00	98.00	0.23	0.48
AX97GL	AX	2464	2515	97.00	99.00	0.23	0.49
AX98GL	AX	2489	2540	98.00	100.00	0.23	0.49
AX100GL	AX	2540	2591	100.00	102.00	0.24	0.50
AX101GL	AX	2565	2616	101.00	103.00	0.24	0.50
AX102GL	AX	2591	2642	102.00	104.00	0.24	0.51
AX103GL	AX	2616	2667	103.00	105.00	0.25	0.51
AX105GL	AX	2667	2718	105.00	107.00	0.25	0.53
AX106GL	AX	2692	2743	106.00	108.00	0.25	0.53
AX107GL	AX	2718	2769	107.00	109.00	0.26	0.54
AX108GL	AX	2743	2794	108.00	110.00	0.26	0.54
AX109GL	AX	2769	2820	109.00	111.00	0.26	0.55
AX110GL	AX	2794	2845	110.00	112.00	0.26	0.55




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
AX112GL	AX	2845	2896	112.00	114.00	0.27	0.56
AX114GL	AX	2896	2947	114.00	116.00	0.27	0.57
AX115GL	AX	2921	2972	115.00	117.00	0.27	0.58
* AX118GL	AX	2997	3048	118.00	120.00	0.28	0.59
* AX120GL	AX	3048	3099	120.00	122.00	0.29	0.60
* AX128GL	AX	3251	3302	128.00	130.00	0.31	0.64
* AX130GL	AX	3302	3353	130.00	132.00	0.31	0.65
* AX136GL	AX	3454	3505	136.00	138.00	0.32	0.68
BX22GL	BX	559	623	22.00	24.50	0.07	0.15
BX23GL	BX	584	648	23.00	25.50	0.08	0.16
BX24GL	BX	610	674	24.00	26.50	0.08	0.17
BX25GL	BX	635	699	25.00	27.50	0.09	0.18
BX26GL	BX	660	724	26.00	28.50	0.09	0.18
BX26.5GL	BX	673	737	26.50	29.00	0.09	0.19
BX27GL	BX	686	750	27.00	29.50	0.09	0.19
BX28GL	BX	711	775	28.00	30.50	0.10	0.20
BX28.5GL	BX	724	788	28.50	31.00	0.10	0.20
BX29GL	BX	737	801	29.00	31.50	0.10	0.20
BX29.5GL	BX	749	813	29.50	32.00	0.10	0.21
BX30GL	BX	762	826	30.00	32.50	0.10	0.21
BX31GL	BX	787	851	31.00	33.50	0.11	0.22
BX31.5GL	BX	800	864	31.50	34.00	0.11	0.22
BX32GL	BX	813	877	32.00	34.50	0.11	0.22
BX32.5GL	BX	826	890	32.50	35.00	0.11	0.23
BX33GL	BX	838	902	33.00	35.50	0.11	0.23
BX33.5GL	BX	851	915	33.50	36.00	0.11	0.23
BX34GL	BX	864	928	34.00	36.50	0.12	0.24
BX34.5GL	BX	876	940	34.50	37.00	0.12	0.24
BX35GL	BX	889	953	35.00	37.50	0.12	0.25
BX35.5GL	BX	902	966	35.50	38.00	0.12	0.25
BX35.75GL	BX	908	972	35.75	38.25	0.12	0.25
BX36GL	BX	914	978	36.00	38.50	0.12	0.25




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX36.25GL	BX	921	985	36.25	38.75	0.12	0.25
BX36.5GL	BX	927	991	36.50	39.00	0.12	0.26
BX37GL	BX	940	1004	37.00	39.50	0.13	0.26
BX37.5GL	BX	953	1017	37.50	40.00	0.13	0.26
BX38GL	BX	965	1029	38.00	40.50	0.13	0.27
BX38.5GL	BX	978	1042	38.50	41.00	0.13	0.27
BX39GL	BX	991	1055	39.00	41.50	0.13	0.27
BX39.5GL	BX	1003	1067	39.50	42.00	0.13	0.28
BX40GL	BX	1016	1080	40.00	42.50	0.14	0.28
BX40.5GL	BX	1029	1093	40.50	43.00	0.14	0.28
BX41GL	BX	1041	1105	41.00	43.50	0.14	0.29
BX41.5GL	BX	1054	1118	41.50	44.00	0.14	0.29
BX42GL	BX	1067	1131	42.00	44.50	0.14	0.29
BX42.5GL	BX	1080	1144	42.50	45.00	0.14	0.30
BX43GL	BX	1092	1156	43.00	45.50	0.15	0.30
BX43.25GL	BX	1099	1163	43.25	45.75	0.15	0.30
BX44GL	BX	1118	1182	44.00	46.50	0.15	0.31
BX45GL	BX	1143	1207	45.00	47.50	0.15	0.32
BX45.5GL	BX	1156	1220	45.50	48.00	0.15	0.32
BX46GL	BX	1168	1232	46.00	48.50	0.16	0.32
BX46.5GL	BX	1181	1245	46.50	49.00	0.16	0.33
BX47GL	BX	1194	1258	47.00	49.50	0.16	0.33
BX47.5GL	BX	1207	1271	47.50	50.00	0.16	0.33
BX48GL	BX	1219	1283	48.00	50.50	0.16	0.34
BX49GL	BX	1245	1309	49.00	51.50	0.17	0.34
BX49.5GL	BX	1257	1321	49.50	52.00	0.17	0.35
BX50GL	BX	1270	1334	50.00	52.50	0.17	0.35
BX50.5GL	BX	1283	1347	50.50	53.00	0.17	0.35
BX51GL	BX	1295	1359	51.00	53.50	0.17	0.36
BX52GL	BX	1321	1385	52.00	54.50	0.18	0.36
BX52.5GL	BX	1334	1398	52.50	55.00	0.18	0.37
BX53GL	BX	1346	1410	53.00	55.50	0.18	0.37




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX53.5GL	BX	1359	1423	53.50	56.00	0.18	0.37
BX54GL	BX	1372	1436	54.00	56.50	0.18	0.38
BX55GL	BX	1397	1461	55.00	57.50	0.19	0.39
BX56GL	BX	1422	1486	56.00	58.50	0.19	0.39
BX57GL	BX	1448	1512	57.00	59.50	0.19	0.40
BX57.5GL	BX	1461	1525	57.50	60.00	0.20	0.40
BX58GL	BX	1473	1537	58.00	60.50	0.20	0.41
BX59GL	BX	1499	1563	59.00	61.50	0.20	0.41
BX60GL	BX	1524	1588	60.00	62.50	0.20	0.42
BX61GL	BX	1549	1613	61.00	63.50	0.21	0.43
BX61.5GL	BX	1562	1626	61.50	64.00	0.21	0.43
BX62GL	BX	1575	1639	62.00	64.50	0.21	0.43
BX63GL	BX	1600	1664	63.00	65.50	0.21	0.44
BX63.5GL	BX	1613	1677	63.50	66.00	0.22	0.44
BX64GL	BX	1626	1690	64.00	66.50	0.22	0.45
BX65GL	BX	1651	1715	65.00	67.50	0.22	0.46
BX66GL	BX	1676	1740	66.00	68.50	0.22	0.46
BX67GL	BX	1702	1766	67.00	69.50	0.23	0.47
BX67.5GL	BX	1715	1779	67.50	70.00	0.23	0.47
BX68GL	BX	1727	1791	68.00	70.50	0.23	0.48
BX69GL	BX	1753	1817	69.00	71.50	0.23	0.48
BX69.5GL	BX	1765	1829	69.50	72.00	0.24	0.49
BX70GL	BX	1778	1842	70.00	72.50	0.24	0.49
BX71GL	BX	1803	1867	71.00	73.50	0.24	0.50
BX72GL	BX	1829	1893	72.00	74.50	0.25	0.50
BX73GL	BX	1854	1918	73.00	75.50	0.25	0.51
BX74GL	BX	1880	1944	74.00	76.50	0.25	0.52
BX75GL	BX	1905	1969	75.00	77.50	0.26	0.53
BX76GL	BX	1930	1994	76.00	78.50	0.26	0.53
BX77GL	BX	1956	2020	77.00	79.50	0.26	0.54
BX78GL	BX	1981	2045	78.00	80.50	0.27	0.55
BX79GL	BX	2007	2071	79.00	81.50	0.27	0.55




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
BX80GL	BX	2032	2096	80.00	82.50	0.27	0.56
BX81GL	BX	2057	2121	81.00	83.50	0.28	0.57
BX82GL	BX	2083	2147	82.00	84.50	0.28	0.57
BX83GL	BX	2108	2172	83.00	85.50	0.28	0.58
BX83.5GL	BX	2121	2185	83.50	86.00	0.28	0.58
BX84GL	BX	2134	2198	84.00	86.50	0.29	0.59
BX85GL	BX	2159	2223	85.00	87.50	0.29	0.60
BX86GL	BX	2184	2248	86.00	88.50	0.29	0.60
BX87GL	BX	2210	2274	87.00	89.50	0.30	0.61
BX88GL	BX	2235	2299	88.00	90.50	0.30	0.62
BX89GL	BX	2261	2325	89.00	91.50	0.30	0.62
BX90GL	BX	2286	2350	90.00	92.50	0.31	0.63
BX91GL	BX	2311	2375	91.00	93.50	0.31	0.64
BX91.5GL	BX	2324	2388	91.50	94.00	0.31	0.64
BX92GL	BX	2337	2401	92.00	94.50	0.31	0.64
BX93GL	BX	2362	2426	93.00	95.50	0.32	0.65
BX94GL	BX	2388	2452	94.00	96.50	0.32	0.66
* BX95GL	BX	2413	2477	95.00	97.50	0.32	0.67
* BX96GL	BX	2438	2502	96.00	98.50	0.33	0.67
* BX97GL	BX	2464	2528	97.00	99.50	0.33	0.68
* BX98GL	BX	2489	2553	98.00	100.50	0.33	0.69
* BX99GL	BX	2515	2579	99.00	101.50	0.34	0.69
* BX100GL	BX	2540	2604	100.00	102.50	0.34	0.70
* BX101GL	BX	2565	2629	101.00	103.50	0.34	0.71
* BX102GL	BX	2591	2655	102.00	104.50	0.35	0.71
* BX102.5GL	BX	2604	2668	102.50	105.00	0.35	0.72
* BX103GL	BX	2616	2680	103.00	105.50	0.35	0.72
* BX104GL	BX	2642	2706	104.00	106.50	0.35	0.73
* BX105GL	BX	2667	2731	105.00	107.50	0.36	0.74
* BX106GL	BX	2692	2756	106.00	108.50	0.36	0.74
* BX107GL	BX	2718	2782	107.00	109.50	0.36	0.75
* BX108GL	BX	2743	2807	108.00	110.50	0.37	0.76




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

	DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
*	BX108.5GL	BX	2756	2820	108.50	111.00	0.37	0.76
*	BX110GL	BX	2794	2858	110.00	112.50	0.37	0.77
*	BX111GL	BX	2819	2883	111.00	113.50	0.38	0.78
*	BX112GL	BX	2845	2909	112.00	114.50	0.38	0.78
	BX113GL	BX	2870	2934	113.00	115.50	0.38	0.79
	BX114GL	BX	2896	2960	114.00	116.50	0.39	0.80
*	BX115GL	BX	2921	2985	115.00	117.50	0.39	0.81
*	BX116GL	BX	2946	3010	116.00	118.50	0.39	0.81
*	BX118GL	BX	2997	3061	118.00	120.50	0.40	0.83
*	BX119GL	BX	3023	3087	119.00	121.50	0.41	0.83
*	BX120GL	BX	3048	3112	120.00	122.50	0.41	0.84
*	BX123GL	BX	3124	3188	123.00	125.50	0.42	0.86
*	BX124GL	BX	3150	3214	124.00	126.50	0.42	0.87
*	BX126GL	BX	3200	3264	126.00	128.50	0.43	0.88
*	BX128GL	BX	3251	3315	128.00	130.50	0.44	0.90
*	BX130GL	BX	3302	3366	130.00	132.50	0.44	0.91
*	BX132GL	BX	3353	3417	132.00	134.50	0.45	0.92
*	BX136GL	BX	3454	3518	136.00	138.50	0.46	0.95
	CX42GL	CX	1067	1142	42.00	45.00	0.25	0.55
	CX43GL	CX	1092	1167	43.00	46.00	0.26	0.56
	CX46.5GL	CX	1181	1256	46.50	49.50	0.28	0.60
	CX47GL	CX	1194	1269	47.00	50.00	0.28	0.61
	CX49GL	CX	1245	1320	49.00	52.00	0.29	0.64
	CX50GL	CX	1270	1345	50.00	53.00	0.30	0.65
	CX51GL	CX	1295	1370	51.00	54.00	0.31	0.66
	CX52GL	CX	1321	1396	52.00	55.00	0.31	0.68
	CX53GL	CX	1346	1421	53.00	56.00	0.32	0.69
	CX54GL	CX	1372	1447	54.00	57.00	0.32	0.70
	CX55GL	CX	1397	1472	55.00	58.00	0.33	0.72
	CX56GL	CX	1422	1497	56.00	59.00	0.34	0.73
	CX57GL	CX	1448	1523	57.00	60.00	0.34	0.74
	CX58GL	CX	1473	1548	58.00	61.00	0.35	0.75




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013


*= Under preparation

DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
CX59GL	CX	1499	1574	59.00	62.00	0.35	0.77
CX60GL	CX	1524	1599	60.00	63.00	0.36	0.78
CX61GL	CX	1549	1624	61.00	64.00	0.37	0.79
CX62GL	CX	1575	1650	62.00	65.00	0.37	0.81
CX63GL	CX	1600	1675	63.00	66.00	0.38	0.82
CX64GL	CX	1626	1701	64.00	67.00	0.38	0.83
CX65GL	CX	1651	1726	65.00	68.00	0.39	0.85
CX66GL	CX	1676	1751	66.00	69.00	0.40	0.86
CX67GL	CX	1702	1777	67.00	70.00	0.40	0.87
CX68GL	CX	1727	1802	68.00	71.00	0.41	0.88
CX69GL	CX	1753	1828	69.00	72.00	0.41	0.90
CX70GL	CX	1778	1853	70.00	73.00	0.42	0.91
CX71GL	CX	1803	1878	71.00	74.00	0.43	0.92
CX72GL	CX	1829	1904	72.00	75.00	0.43	0.94
CX73GL	CX	1854	1929	73.00	76.00	0.44	0.95
CX74GL	CX	1880	1955	74.00	77.00	0.44	0.96
CX74.5GL	CX	1892	1967	74.50	77.50	0.45	0.97
CX75GL	CX	1905	1980	75.00	78.00	0.45	0.98
CX76GL	CX	1930	2005	76.00	79.00	0.46	0.99
CX76.25GL	CX	1937	2012	76.25	79.25	0.46	0.99
CX77GL	CX	1956	2031	77.00	80.00	0.46	1.00
CX78GL	CX	1981	2056	78.00	81.00	0.47	1.01
CX79GL	CX	2007	2082	79.00	82.00	0.47	1.03
CX80GL	CX	2032	2107	80.00	83.00	0.48	1.04
CX81GL	CX	2057	2132	81.00	84.00	0.49	1.05
CX82GL	CX	2083	2158	82.00	85.00	0.49	1.07
CX83GL	CX	2108	2183	83.00	86.00	0.50	1.08
CX84GL	CX	2134	2209	84.00	87.00	0.50	1.09
CX85GL	CX	2159	2234	85.00	88.00	0.51	1.11
CX86GL	CX	2184	2259	86.00	89.00	0.52	1.12
CX87GL	CX	2210	2285	87.00	90.00	0.52	1.13
CX88GL	CX	2235	2310	88.00	91.00	0.53	1.14




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Classical - Size list



V-Belt Raw Edge

GOLD LABEL™




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
ZX	10	6	0.063
AX	13	8	0.094
BX	17	11	0.134
CX	22	14	0.236

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
ZX	25/64	15/64	0.004
AX	1/2	5/16	0.005
BX	21/32	13/32	0.007
CX	7/8	17/32	0.013

*= Under preparation


DAYCO Part Nr	Section	Li Inside length (mm)	Ld Datum length (mm)	Li Inside length (in)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
CX89GL	CX	2261	2336	89.00	92.00	0.53	1.16
CX90GL	CX	2286	2361	90.00	93.00	0.54	1.17
CX91GL	CX	2311	2386	91.00	94.00	0.55	1.18
CX92GL	CX	2337	2412	92.00	95.00	0.55	1.20
CX93GL	CX	2362	2437	93.00	96.00	0.56	1.21
CX94GL	CX	2388	2463	94.00	97.00	0.56	1.22
* CX95GL	CX	2413	2488	95.00	98.00	0.57	1.24
* CX96GL	CX	2438	2513	96.00	99.00	0.58	1.25
* CX97GL	CX	2464	2539	97.00	100.00	0.58	1.26
* CX98GL	CX	2489	2564	98.00	101.00	0.59	1.27
* CX98.5GL	CX	2502	2577	98.50	101.50	0.59	1.28
* CX99GL	CX	2515	2590	99.00	102.00	0.59	1.29
* CX100GL	CX	2540	2615	100.00	103.00	0.60	1.30
* CX101GL	CX	2565	2640	101.00	104.00	0.61	1.31
* CX102GL	CX	2591	2666	102.00	105.00	0.61	1.33
* CX103GL	CX	2616	2691	103.00	106.00	0.62	1.34
* CX104GL	CX	2642	2717	104.00	107.00	0.62	1.35
* CX105GL	CX	2667	2742	105.00	108.00	0.63	1.37
* CX107GL	CX	2718	2793	107.00	110.00	0.64	1.39
* CX108GL	CX	2743	2818	108.00	111.00	0.65	1.40
* CX109GL	CX	2769	2844	109.00	112.00	0.65	1.42
* CX110GL	CX	2794	2869	110.00	113.00	0.66	1.43
* CX111GL	CX	2819	2894	111.00	114.00	0.67	1.44
* CX112GL	CX	2845	2920	112.00	115.00	0.67	1.46
CX113GL	CX	2870	2945	113.00	116.00	0.68	1.47
CX114GL	CX	2896	2971	114.00	117.00	0.68	1.48
* CX115GL	CX	2921	2996	115.00	118.00	0.69	1.50
* CX116GL	CX	2946	3021	116.00	119.00	0.70	1.51
* CX117GL	CX	2972	3047	117.00	120.00	0.70	1.52
* CX118GL	CX	2997	3072	118.00	121.00	0.71	1.53
* CX119GL	CX	3023	3098	119.00	122.00	0.71	1.55
* CX120GL	CX	3048	3123	120.00	123.00	0.72	1.56
* CX124GL	CX	3150	3225	124.00	127.00	0.74	1.61

GOLD LABEL X Narrow - Product Description



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

V-Belt Raw Edge

Part Number Description: **3VX300GL**

3VX: Profile (9mm X 8mm)

300: Outside Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching

Designed for OEMs

Markets and Applications:


Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps...), in particular where temperature, power capacity, space and weight are critical.

Pulley Standards: ARPM/MPTA IP-22




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
3VX220GL	3VX	559	22.00	0.03	0.07
3VX230GL	3VX	584	23.00	0.03	0.07
3VX250GL	3VX	635	25.00	0.03	0.08
3VX255GL	3VX	648	25.50	0.03	0.08
3VX260GL	3VX	660	26.00	0.04	0.08
3VX265GL	3VX	673	26.50	0.04	0.08
3VX270GL	3VX	686	27.00	0.04	0.08
3VX275GL	3VX	699	27.50	0.04	0.08
3VX280GL	3VX	711	28.00	0.04	0.08
3VX290GL	3VX	737	29.00	0.04	0.09
3VX295GL	3VX	749	29.50	0.04	0.09
3VX300GL	3VX	762	30.00	0.04	0.09
3VX305GL	3VX	775	30.50	0.04	0.09
3VX310GL	3VX	787	31.00	0.04	0.09
3VX315GL	3VX	800	31.50	0.04	0.09
3VX320GL	3VX	813	32.00	0.04	0.10
3VX325GL	3VX	826	32.50	0.04	0.10
3VX330GL	3VX	838	33.00	0.05	0.10
3VX335GL	3VX	851	33.50	0.05	0.10
3VX340GL	3VX	864	34.00	0.05	0.10
3VX345GL	3VX	876	34.50	0.05	0.10
3VX350GL	3VX	889	35.00	0.05	0.11
3VX355GL	3VX	902	35.50	0.05	0.11
3VX360GL	3VX	914	36.00	0.05	0.11
3VX365GL	3VX	927	36.50	0.05	0.11
3VX370GL	3VX	940	37.00	0.05	0.11
3VX375GL	3VX	953	37.50	0.05	0.11
3VX380GL	3VX	965	38.00	0.05	0.11
3VX385GL	3VX	978	38.50	0.05	0.12
3VX390GL	3VX	991	39.00	0.05	0.12
3VX395GL	3VX	1003	39.50	0.05	0.12
3VX400GL	3VX	1016	40.00	0.05	0.12
3VX405GL	3VX	1029	40.50	0.06	0.12
3VX410GL	3VX	1041	41.00	0.06	0.12
3VX415GL	3VX	1054	41.50	0.06	0.12
3VX420GL	3VX	1067	42.00	0.06	0.13
3VX425GL	3VX	1080	42.50	0.06	0.13
3VX430GL	3VX	1092	43.00	0.06	0.13
3VX440GL	3VX	1118	44.00	0.06	0.13
3VX445GL	3VX	1130	44.50	0.06	0.13




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
3VX450GL	3VX	1143	45.00	0.06	0.14
3VX455GL	3VX	1156	45.50	0.06	0.14
3VX460GL	3VX	1168	46.00	0.06	0.14
3VX465GL	3VX	1181	46.50	0.06	0.14
3VX470GL	3VX	1194	47.00	0.06	0.14
3VX475GL	3VX	1207	47.50	0.07	0.14
3VX480GL	3VX	1219	48.00	0.07	0.14
3VX490GL	3VX	1245	49.00	0.07	0.15
3VX495GL	3VX	1257	49.50	0.07	0.15
3VX500GL	3VX	1270	50.00	0.07	0.15
3VX505GL	3VX	1283	50.50	0.07	0.15
3VX510GL	3VX	1295	51.00	0.07	0.15
3VX515GL	3VX	1308	51.50	0.07	0.15
3VX520GL	3VX	1321	52.00	0.07	0.16
3VX525GL	3VX	1334	52.50	0.07	0.16
3VX530GL	3VX	1346	53.00	0.07	0.16
3VX535GL	3VX	1359	53.50	0.07	0.16
3VX540GL	3VX	1372	54.00	0.07	0.16
3VX545GL	3VX	1384	54.50	0.07	0.16
3VX550GL	3VX	1397	55.00	0.08	0.17
3VX555GL	3VX	1410	55.50	0.08	0.17
3VX560GL	3VX	1422	56.00	0.08	0.17
3VX565GL	3VX	1435	56.50	0.08	0.17
3VX570GL	3VX	1448	57.00	0.08	0.17
3VX575GL	3VX	1461	57.50	0.08	0.17
3VX580GL	3VX	1473	58.00	0.08	0.17
3VX585GL	3VX	1486	58.50	0.08	0.18
3VX590GL	3VX	1499	59.00	0.08	0.18
3VX595GL	3VX	1511	59.50	0.08	0.18
3VX600GL	3VX	1524	60.00	0.08	0.18
3VX610GL	3VX	1549	61.00	0.08	0.18
3VX615GL	3VX	1562	61.50	0.08	0.18
3VX620GL	3VX	1575	62.00	0.09	0.19
3VX625GL	3VX	1588	62.50	0.09	0.19
3VX630GL	3VX	1600	63.00	0.09	0.19
3VX640GL	3VX	1626	64.00	0.09	0.19
3VX645GL	3VX	1638	64.50	0.09	0.19
3VX650GL	3VX	1651	65.00	0.09	0.20
3VX670GL	3VX	1702	67.00	0.09	0.20
3VX680GL	3VX	1727	68.00	0.09	0.20




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
	3VX685GL	3VX	1740	68.50	0.09	0.21
	3VX690GL	3VX	1753	69.00	0.09	0.21
	3VX695GL	3VX	1765	69.50	0.10	0.21
	3VX700GL	3VX	1778	70.00	0.10	0.21
	3VX705GL	3VX	1791	70.50	0.10	0.21
	3VX710GL	3VX	1803	71.00	0.10	0.21
	3VX715GL	3VX	1816	71.50	0.10	0.21
	3VX720GL	3VX	1829	72.00	0.10	0.22
	3VX725GL	3VX	1842	72.50	0.10	0.22
	3VX735GL	3VX	1867	73.50	0.10	0.22
	3VX745GL	3VX	1892	74.50	0.10	0.22
	3VX750GL	3VX	1905	75.00	0.10	0.23
	3VX765GL	3VX	1943	76.50	0.10	0.23
	3VX780GL	3VX	1981	78.00	0.11	0.23
	3VX800GL	3VX	2032	80.00	0.11	0.24
	3VX850GL	3VX	2159	85.00	0.12	0.26
	3VX900GL	3VX	2286	90.00	0.12	0.27
	3VX950GL	3VX	2413	95.00	0.13	0.29
*	3VX1000GL	3VX	2540	100.00	0.14	0.30
*	3VX1060GL	3VX	2692	106.00	0.15	0.32
*	3VX1120GL	3VX	2845	112.00	0.15	0.34
*	3VX1180GL	3VX	2997	118.00	0.16	0.35
*	3VX1250GL	3VX	3175	125.00	0.17	0.38
*	3VX1320GL	3VX	3353	132.00	0.18	0.40
	5VX220GL	5VX	559	22.00	0.07	0.15
	5VX225GL	5VX	572	22.50	0.07	0.16
	5VX230GL	5VX	584	23.00	0.08	0.16
	5VX240GL	5VX	610	24.00	0.08	0.17
	5VX245GL	5VX	622	24.50	0.08	0.17
	5VX250GL	5VX	635	25.00	0.08	0.18
	5VX255GL	5VX	648	25.50	0.08	0.18
	5VX260GL	5VX	660	26.00	0.09	0.18
	5VX270GL	5VX	686	27.00	0.09	0.19
	5VX275GL	5VX	699	27.50	0.09	0.19
	5VX285GL	5VX	724	28.50	0.09	0.20
	5VX290GL	5VX	737	29.00	0.10	0.20
	5VX295GL	5VX	749	29.50	0.10	0.21
	5VX305GL	5VX	775	30.50	0.10	0.21
	5VX310GL	5VX	787	31.00	0.10	0.22
	5VX315GL	5VX	800	31.50	0.10	0.22




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
5VX320GL	5VX	813	32.00	0.10	0.22
5VX330GL	5VX	838	33.00	0.11	0.23
5VX335GL	5VX	851	33.50	0.11	0.23
5VX340GL	5VX	864	34.00	0.11	0.24
5VX345GL	5VX	876	34.50	0.11	0.24
5VX350GL	5VX	889	35.00	0.11	0.25
5VX355GL	5VX	902	35.50	0.12	0.25
5VX365GL	5VX	927	36.50	0.12	0.26
5VX370GL	5VX	940	37.00	0.12	0.26
5VX375GL	5VX	953	37.50	0.12	0.26
5VX380GL	5VX	965	38.00	0.12	0.27
5VX385GL	5VX	978	38.50	0.13	0.27
5VX390GL	5VX	991	39.00	0.13	0.27
5VX395GL	5VX	1003	39.50	0.13	0.28
5VX400GL	5VX	1016	40.00	0.13	0.28
5VX405GL	5VX	1029	40.50	0.13	0.28
5VX410GL	5VX	1041	41.00	0.13	0.29
5VX415GL	5VX	1054	41.50	0.14	0.29
5VX425GL	5VX	1080	42.50	0.14	0.30
5VX430GL	5VX	1092	43.00	0.14	0.30
5VX440GL	5VX	1118	44.00	0.14	0.31
5VX445GL	5VX	1130	44.50	0.15	0.31
5VX450GL	5VX	1143	45.00	0.15	0.32
5VX455GL	5VX	1156	45.50	0.15	0.32
5VX460GL	5VX	1168	46.00	0.15	0.32
5VX465GL	5VX	1181	46.50	0.15	0.33
5VX470GL	5VX	1194	47.00	0.15	0.33
5VX475GL	5VX	1207	47.50	0.16	0.33
5VX480GL	5VX	1219	48.00	0.16	0.34
5VX485GL	5VX	1232	48.50	0.16	0.34
5VX490GL	5VX	1245	49.00	0.16	0.34
5VX495GL	5VX	1257	49.50	0.16	0.35
5VX500GL	5VX	1270	50.00	0.16	0.35
5VX505GL	5VX	1283	50.50	0.17	0.35
5VX510GL	5VX	1295	51.00	0.17	0.36
5VX515GL	5VX	1308	51.50	0.17	0.36
5VX525GL	5VX	1334	52.50	0.17	0.37
5VX530GL	5VX	1346	53.00	0.17	0.37
5VX535GL	5VX	1359	53.50	0.18	0.37
5VX540GL	5VX	1372	54.00	0.18	0.38




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
5VX545GL	5VX	1384	54.50	0.18	0.38
5VX550GL	5VX	1397	55.00	0.18	0.39
5VX555GL	5VX	1410	55.50	0.18	0.39
5VX560GL	5VX	1422	56.00	0.18	0.39
5VX565GL	5VX	1435	56.50	0.19	0.40
5VX570GL	5VX	1448	57.00	0.19	0.40
5VX575GL	5VX	1461	57.50	0.19	0.40
5VX580GL	5VX	1473	58.00	0.19	0.41
5VX585GL	5VX	1486	58.50	0.19	0.41
5VX590GL	5VX	1499	59.00	0.19	0.41
5VX595GL	5VX	1511	59.50	0.19	0.42
5VX600GL	5VX	1524	60.00	0.20	0.42
5VX605GL	5VX	1537	60.50	0.20	0.42
5VX610GL	5VX	1549	61.00	0.20	0.43
5VX615GL	5VX	1562	61.50	0.20	0.43
5VX620GL	5VX	1575	62.00	0.20	0.43
5VX630GL	5VX	1600	63.00	0.21	0.44
5VX640GL	5VX	1626	64.00	0.21	0.45
5VX650GL	5VX	1651	65.00	0.21	0.46
5VX660GL	5VX	1676	66.00	0.22	0.46
5VX665GL	5VX	1689	66.50	0.22	0.47
5VX670GL	5VX	1702	67.00	0.22	0.47
5VX680GL	5VX	1727	68.00	0.22	0.48
5VX685GL	5VX	1740	68.50	0.22	0.48
5VX690GL	5VX	1753	69.00	0.23	0.48
5VX695GL	5VX	1765	69.50	0.23	0.49
5VX700GL	5VX	1778	70.00	0.23	0.49
5VX710GL	5VX	1803	71.00	0.23	0.50
5VX715GL	5VX	1816	71.50	0.23	0.50
5VX720GL	5VX	1829	72.00	0.24	0.50
5VX730GL	5VX	1854	73.00	0.24	0.51
5VX740GL	5VX	1880	74.00	0.24	0.52
5VX750GL	5VX	1905	75.00	0.25	0.53
5VX760GL	5VX	1930	76.00	0.25	0.53
5VX780GL	5VX	1981	78.00	0.26	0.55
5VX800GL	5VX	2032	80.00	0.26	0.56
5VX810GL	5VX	2057	81.00	0.27	0.57
5VX830GL	5VX	2108	83.00	0.27	0.58
5VX840GL	5VX	2134	84.00	0.28	0.59
5VX850GL	5VX	2159	85.00	0.28	0.60




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™





Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
3VX	9	8	0.054
5VX	15	13	0.129

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
3VX	3/8	5/16	0.003
5VX	5/8	17/32	0.007

*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
	5VX860GL	5VX	2184	86.00	0.28	0.60
	5VX880GL	5VX	2235	88.00	0.29	0.62
	5VX890GL	5VX	2261	89.00	0.29	0.62
	5VX900GL	5VX	2286	90.00	0.29	0.63
	5VX930GL	5VX	2362	93.00	0.30	0.65
	5VX940GL	5VX	2388	94.00	0.31	0.66
	5VX950GL	5VX	2413	95.00	0.31	0.67
	5VX960GL	5VX	2438	96.00	0.31	0.67
*	5VX970GL	5VX	2464	97.00	0.32	0.68
*	5VX990GL	5VX	2515	99.00	0.32	0.69
*	5VX1000GL	5VX	2540	100.00	0.33	0.70
*	5VX1030GL	5VX	2616	103.00	0.34	0.72
*	5VX1050GL	5VX	2667	105.00	0.34	0.74
*	5VX1060GL	5VX	2692	106.00	0.35	0.74
*	5VX1080GL	5VX	2743	108.00	0.35	0.76
*	5VX1120GL	5VX	2845	112.00	0.37	0.78
*	5VX1150GL	5VX	2921	115.00	0.38	0.81
	5VX1160GL	5VX	2946	116.00	0.38	0.81
*	5VX1180GL	5VX	2997	118.00	0.39	0.83
*	5VX1230GL	5VX	3124	123.00	0.40	0.86
*	5VX1250GL	5VX	3175	125.00	0.41	0.88
*	5VX1320GL	5VX	3353	132.00	0.43	0.92
*	5VX1350GL	5VX	3418	135.00	0.44	0.94
*	5VX1400GL	5VX	3545	140.00	0.46	0.98

GOLD LABEL X Wedge - Product Description



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

V-Belt Raw Edge

Part Number Description: **XPA1200GL**

XPA: Profile (13mm X 10mm)

1200: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Back fabric: PET/Cotton to enhance flexibility

Polyester cord designed for improved performance: high stability, very low tension decay, enable resistance to overloads and shock loads, improved durability, reduced maintenance.

Cogs profile engineered to improve bending fatigue, provide extra flexibility for smaller pulley and cooling effects.

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

RLT: Restricted length tolerance, manufactured with restricted tolerance for set matching

Designed for OEMs

Markets and Applications:


Recommended for all Industrial applications (textile mills, fan, lathes, grinding machine, compressors, pumps...), in particular where temperature, power capacity, space and weight are critical.

Pulley Standards: DIN2211 – ISO 4183




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ512GL	XPZ	512	20.15	0.03	0.06
XPZ520GL	XPZ	520	20.45	0.03	0.06
XPZ550GL	XPZ	550	21.65	0.03	0.06
XPZ560GL	XPZ	560	22.05	0.03	0.07
XPZ562GL	XPZ	562	22.15	0.03	0.07
XPZ580GL	XPZ	580	22.85	0.03	0.07
XPZ587GL	XPZ	587	23.10	0.04	0.07
XPZ600GL	XPZ	600	23.60	0.04	0.07
XPZ604GL	XPZ	604	23.80	0.04	0.07
XPZ612GL	XPZ	612	24.10	0.04	0.07
XPZ615GL	XPZ	615	24.20	0.04	0.07
XPZ630GL	XPZ	630	24.80	0.04	0.07
XPZ637GL	XPZ	637	25.10	0.04	0.08
XPZ640GL	XPZ	640	25.20	0.04	0.08
XPZ646GL	XPZ	646	25.45	0.04	0.08
XPZ660GL	XPZ	660	26.00	0.04	0.08
XPZ662GL	XPZ	662	26.05	0.04	0.08
XPZ670GL	XPZ	670	26.40	0.04	0.08
XPZ672GL	XPZ	672	26.45	0.04	0.08
XPZ675GL	XPZ	675	26.60	0.04	0.08
XPZ682GL	XPZ	682	26.85	0.04	0.08
XPZ687GL	XPZ	687	27.05	0.04	0.08
XPZ690GL	XPZ	690	27.15	0.04	0.08
XPZ700GL	XPZ	700	27.55	0.04	0.08
XPZ710GL	XPZ	710	27.95	0.04	0.08
XPZ722GL	XPZ	722	28.40	0.04	0.09
XPZ725GL	XPZ	725	28.55	0.04	0.09
XPZ730GL	XPZ	730	28.75	0.04	0.09
XPZ737GL	XPZ	737	29.00	0.04	0.09
XPZ750GL	XPZ	750	29.55	0.05	0.09
XPZ758GL	XPZ	758	29.85	0.05	0.09
XPZ760GL	XPZ	760	29.90	0.05	0.09
XPZ762GL	XPZ	762	30.00	0.05	0.09
XPZ772GL	XPZ	772	30.40	0.05	0.09
XPZ775GL	XPZ	775	30.50	0.05	0.09
XPZ787GL	XPZ	787	31.00	0.05	0.09
XPZ800GL	XPZ	800	31.50	0.05	0.09




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ812GL	XPZ	812	32.00	0.05	0.10
XPZ821GL	XPZ	821	32.30	0.05	0.10
XPZ825GL	XPZ	825	32.50	0.05	0.10
XPZ837GL	XPZ	837	32.95	0.05	0.10
XPZ845GL	XPZ	845	33.25	0.05	0.10
XPZ850GL	XPZ	850	33.45	0.05	0.10
XPZ862GL	XPZ	862	33.95	0.05	0.10
XPZ875GL	XPZ	875	34.45	0.05	0.10
XPZ887GL	XPZ	887	34.90	0.05	0.10
XPZ900GL	XPZ	900	35.45	0.05	0.11
XPZ912GL	XPZ	912	35.90	0.05	0.11
XPZ925GL	XPZ	925	36.40	0.06	0.11
XPZ937GL	XPZ	937	36.90	0.06	0.11
XPZ940GL	XPZ	940	37.00	0.06	0.11
XPZ950GL	XPZ	950	37.40	0.06	0.11
XPZ957GL	XPZ	957	37.70	0.06	0.11
XPZ962GL	XPZ	962	37.85	0.06	0.11
XPZ975GL	XPZ	975	38.40	0.06	0.12
XPZ980GL	XPZ	980	38.60	0.06	0.12
XPZ985GL	XPZ	985	38.80	0.06	0.12
XPZ987GL	XPZ	987	38.85	0.06	0.12
XPZ1000GL	XPZ	1000	39.35	0.06	0.12
XPZ1010GL	XPZ	1010	39.75	0.06	0.12
XPZ1012GL	XPZ	1012	39.85	0.06	0.12
XPZ1024GL	XPZ	1024	40.30	0.06	0.12
XPZ1030GL	XPZ	1030	40.55	0.06	0.12
XPZ1037GL	XPZ	1037	40.85	0.06	0.12
XPZ1047GL	XPZ	1047	41.20	0.06	0.12
XPZ1060GL	XPZ	1060	41.75	0.06	0.13
XPZ1062GL	XPZ	1062	41.80	0.06	0.13
XPZ1077GL	XPZ	1077	42.40	0.06	0.13
XPZ1080GL	XPZ	1080	42.50	0.06	0.13
XPZ1087GL	XPZ	1087	42.80	0.07	0.13
XPZ1090GL	XPZ	1090	42.90	0.07	0.13
XPZ1100GL	XPZ	1100	43.30	0.07	0.13
XPZ1112GL	XPZ	1112	43.80	0.07	0.13
XPZ1120GL	XPZ	1120	44.10	0.07	0.13




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1137GL	XPZ	1137	44.75	0.07	0.13
XPZ1140GL	XPZ	1140	44.90	0.07	0.13
XPZ1150GL	XPZ	1150	45.30	0.07	0.14
XPZ1162GL	XPZ	1162	45.75	0.07	0.14
XPZ1166GL	XPZ	1166	45.90	0.07	0.14
XPZ1170GL	XPZ	1170	46.05	0.07	0.14
XPZ1180GL	XPZ	1180	46.45	0.07	0.14
XPZ1187GL	XPZ	1187	46.75	0.07	0.14
XPZ1195GL	XPZ	1195	47.05	0.07	0.14
XPZ1200GL	XPZ	1200	47.25	0.07	0.14
XPZ1202GL	XPZ	1202	47.30	0.07	0.14
XPZ1210GL	XPZ	1210	47.65	0.07	0.14
XPZ1212GL	XPZ	1212	47.70	0.07	0.14
XPZ1220GL	XPZ	1220	48.05	0.07	0.14
XPZ1227GL	XPZ	1227	48.30	0.07	0.14
XPZ1237GL	XPZ	1237	48.70	0.07	0.15
XPZ1240GL	XPZ	1240	48.80	0.07	0.15
XPZ1250GL	XPZ	1250	49.20	0.08	0.15
XPZ1262GL	XPZ	1262	49.70	0.08	0.15
XPZ1270GL	XPZ	1270	50.00	0.08	0.15
XPZ1280GL	XPZ	1280	50.40	0.08	0.15
XPZ1282GL	XPZ	1282	50.45	0.08	0.15
XPZ1285GL	XPZ	1285	50.60	0.08	0.15
XPZ1287GL	XPZ	1287	50.65	0.08	0.15
XPZ1312GL	XPZ	1312	51.65	0.08	0.15
XPZ1320GL	XPZ	1320	51.95	0.08	0.16
XPZ1337GL	XPZ	1337	52.65	0.08	0.16
XPZ1340GL	XPZ	1340	52.76	0.08	0.16
XPZ1350GL	XPZ	1350	53.15	0.08	0.16
XPZ1362GL	XPZ	1362	53.60	0.08	0.16
XPZ1370GL	XPZ	1370	53.95	0.08	0.16
XPZ1380GL	XPZ	1380	54.35	0.08	0.16
XPZ1387GL	XPZ	1387	54.60	0.08	0.16
XPZ1400GL	XPZ	1400	55.10	0.08	0.17
XPZ1412GL	XPZ	1412	55.60	0.08	0.17
XPZ1415GL	XPZ	1415	55.70	0.08	0.17
XPZ1420GL	XPZ	1420	55.90	0.09	0.17




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1430GL	XPZ	1430	56.30	0.09	0.17
XPZ1437GL	XPZ	1437	56.60	0.09	0.17
XPZ1450GL	XPZ	1450	57.10	0.09	0.17
XPZ1462GL	XPZ	1462	57.55	0.09	0.17
XPZ1470GL	XPZ	1470	57.85	0.09	0.17
XPZ1475GL	XPZ	1475	58.05	0.09	0.17
XPZ1487GL	XPZ	1487	58.55	0.09	0.18
XPZ1490GL	XPZ	1490	58.65	0.09	0.18
XPZ1500GL	XPZ	1500	59.05	0.09	0.18
XPZ1512GL	XPZ	1512	59.55	0.09	0.18
XPZ1520GL	XPZ	1520	59.85	0.09	0.18
XPZ1527GL	XPZ	1527	60.10	0.09	0.18
XPZ1537GL	XPZ	1537	60.50	0.09	0.18
XPZ1545GL	XPZ	1545	60.85	0.09	0.18
XPZ1550GL	XPZ	1550	61.00	0.09	0.18
XPZ1560GL	XPZ	1560	61.40	0.09	0.18
XPZ1562GL	XPZ	1562	61.50	0.09	0.18
XPZ1587GL	XPZ	1587	62.50	0.10	0.19
XPZ1600GL	XPZ	1600	63.00	0.10	0.19
XPZ1612GL	XPZ	1612	63.45	0.10	0.19
XPZ1630GL	XPZ	1630	64.15	0.10	0.19
XPZ1637GL	XPZ	1637	64.45	0.10	0.19
XPZ1640GL	XPZ	1640	64.55	0.10	0.19
XPZ1650GL	XPZ	1650	64.95	0.10	0.19
XPZ1652GL	XPZ	1652	65.05	0.10	0.20
XPZ1662GL	XPZ	1662	65.45	0.10	0.20
XPZ1687GL	XPZ	1687	66.40	0.10	0.20
XPZ1700GL	XPZ	1700	66.90	0.10	0.20
XPZ1707GL	XPZ	1707	67.20	0.10	0.20
XPZ1710GL	XPZ	1710	67.30	0.10	0.20
XPZ1712GL	XPZ	1712	67.40	0.10	0.20
XPZ1737GL	XPZ	1737	68.40	0.10	0.21
XPZ1750GL	XPZ	1750	68.90	0.11	0.21
XPZ1760GL	XPZ	1760	69.30	0.11	0.21
XPZ1762GL	XPZ	1762	69.35	0.11	0.21
XPZ1782GL	XPZ	1782	70.15	0.11	0.21
XPZ1787GL	XPZ	1787	70.35	0.11	0.21




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPZ1800GL	XPZ	1800	70.85	0.11	0.21
XPZ1812GL	XPZ	1812	71.35	0.11	0.21
XPZ1837GL	XPZ	1837	72.30	0.11	0.22
XPZ1845GL	XPZ	1845	72.65	0.11	0.22
XPZ1850GL	XPZ	1850	72.85	0.11	0.22
XPZ1862GL	XPZ	1862	73.30	0.11	0.22
XPZ1875GL	XPZ	1875	73.80	0.11	0.22
XPZ1887GL	XPZ	1887	74.30	0.11	0.22
XPZ1900GL	XPZ	1900	74.80	0.11	0.22
XPZ1937GL	XPZ	1937	76.25	0.12	0.23
XPZ1950GL	XPZ	1950	76.75	0.12	0.23
XPZ1962GL	XPZ	1962	77.25	0.12	0.23
XPZ1987GL	XPZ	1987	78.20	0.12	0.23
XPZ2000GL	XPZ	2000	78.75	0.12	0.24
XPZ2012GL	XPZ	2012	79.20	0.12	0.24
XPZ2030GL	XPZ	2030	79.90	0.12	0.24
XPZ2037GL	XPZ	2037	80.20	0.12	0.24
XPZ2060GL	XPZ	2060	81.10	0.12	0.24
XPZ2062GL	XPZ	2062	81.20	0.12	0.24
XPZ2087GL	XPZ	2087	82.15	0.13	0.25
XPZ2120GL	XPZ	2120	83.45	0.13	0.25
XPZ2137GL	XPZ	2137	84.15	0.13	0.25
XPZ2160GL	XPZ	2160	85.05	0.13	0.26
XPZ2187GL	XPZ	2187	86.10	0.13	0.26
XPZ2220GL	XPZ	2220	87.40	0.13	0.26
XPZ2240GL	XPZ	2240	88.20	0.13	0.26
XPZ2280GL	XPZ	2280	89.75	0.14	0.27
XPZ2287GL	XPZ	2287	90.05	0.14	0.27
XPZ2300GL	XPZ	2300	90.55	0.14	0.27
XPZ2360GL	XPZ	2360	92.90	0.14	0.28
XPZ2410GL	XPZ	2410	94.90	0.14	0.28
XPZ2430GL	XPZ	2430	95.65	0.15	0.29
* XPZ2437GL	XPZ	2437	95.95	0.15	0.29
* XPZ2487GL	XPZ	2487	97.90	0.15	0.29
* XPZ2500GL	XPZ	2500	98.40	0.15	0.30
* XPZ2530GL	XPZ	2530	99.60	0.15	0.30
* XPZ2540GL	XPZ	2540	100.00	0.15	0.30




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPZ2580GL	XPZ	2580	101.55	0.15	0.30
*	XPZ2650GL	XPZ	2650	104.35	0.16	0.31
*	XPZ2690GL	XPZ	2690	105.90	0.16	0.32
*	XPZ2750GL	XPZ	2750	108.25	0.17	0.32
*	XPZ2800GL	XPZ	2800	110.25	0.17	0.33
*	XPZ2840GL	XPZ	2840	111.80	0.17	0.34
*	XPZ2900GL	XPZ	2900	114.15	0.17	0.34
*	XPZ2915GL	XPZ	2915	114.75	0.17	0.34
*	XPZ2987GL	XPZ	2987	117.60	0.18	0.35
*	XPZ2990GL	XPZ	2990	117.70	0.18	0.35
*	XPZ3000GL	XPZ	3000	118.10	0.18	0.35
	XPA550GL	XPA	550	21.65	0.05	0.13
	XPA575GL	XPA	575	22.65	0.06	0.14
	XPA630GL	XPA	630	24.80	0.06	0.15
	XPA667GL	XPA	667	26.25	0.07	0.16
	XPA670GL	XPA	670	26.40	0.07	0.16
	XPA690GL	XPA	690	27.15	0.07	0.16
	XPA710GL	XPA	710	27.95	0.07	0.17
	XPA730GL	XPA	730	28.75	0.07	0.17
	XPA732GL	XPA	732	28.80	0.07	0.17
	XPA742GL	XPA	742	29.20	0.07	0.18
	XPA747GL	XPA	747	29.40	0.07	0.18
	XPA750GL	XPA	750	29.55	0.07	0.18
	XPA757GL	XPA	757	29.80	0.07	0.18
	XPA760GL	XPA	760	29.90	0.07	0.18
	XPA762GL	XPA	762	30.00	0.07	0.18
	XPA766GL	XPA	766	30.15	0.08	0.18
	XPA772GL	XPA	772	30.40	0.08	0.18
	XPA775GL	XPA	775	30.50	0.08	0.18
	XPA782GL	XPA	782	30.80	0.08	0.18
	XPA800GL	XPA	800	31.50	0.08	0.19
	XPA807GL	XPA	807	31.75	0.08	0.19
	XPA825GL	XPA	825	32.50	0.08	0.19
	XPA832GL	XPA	832	32.75	0.08	0.20
	XPA840GL	XPA	840	33.05	0.08	0.20
	XPA850GL	XPA	850	33.45	0.08	0.20
	XPA857GL	XPA	857	33.75	0.08	0.20




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA861GL	XPA	861	33.90	0.08	0.20
XPA875GL	XPA	875	34.45	0.09	0.21
XPA882GL	XPA	882	34.70	0.09	0.21
XPA900GL	XPA	900	35.45	0.09	0.21
XPA907GL	XPA	907	35.70	0.09	0.21
XPA910GL	XPA	910	35.85	0.09	0.21
XPA912GL	XPA	912	35.90	0.09	0.22
XPA918GL	XPA	918	36.15	0.09	0.22
XPA922GL	XPA	922	36.30	0.09	0.22
XPA925GL	XPA	925	36.40	0.09	0.22
XPA930GL	XPA	930	36.60	0.09	0.22
XPA932GL	XPA	932	36.70	0.09	0.22
XPA940GL	XPA	940	37.00	0.09	0.22
XPA950GL	XPA	950	37.40	0.09	0.22
XPA957GL	XPA	957	37.70	0.09	0.23
XPA960GL	XPA	960	37.80	0.09	0.23
XPA963GL	XPA	963	37.90	0.09	0.23
XPA967GL	XPA	967	38.05	0.09	0.23
XPA969GL	XPA	969	38.15	0.09	0.23
XPA975GL	XPA	975	38.40	0.10	0.23
XPA982GL	XPA	982	38.65	0.10	0.23
XPA1000GL	XPA	1000	39.35	0.10	0.24
XPA1007GL	XPA	1007	39.65	0.10	0.24
XPA1017GL	XPA	1017	40.05	0.10	0.24
XPA1030GL	XPA	1030	40.55	0.10	0.24
XPA1032GL	XPA	1032	40.65	0.10	0.24
XPA1055GL	XPA	1055	41.55	0.10	0.25
XPA1060GL	XPA	1060	41.75	0.10	0.25
XPA1070GL	XPA	1070	42.10	0.10	0.25
XPA1082GL	XPA	1082	42.60	0.11	0.26
XPA1090GL	XPA	1090	42.90	0.11	0.26
XPA1107GL	XPA	1107	43.60	0.11	0.26
XPA1120GL	XPA	1120	44.10	0.11	0.26
XPA1132GL	XPA	1132	44.55	0.11	0.27
XPA1140GL	XPA	1140	44.90	0.11	0.27
XPA1150GL	XPA	1150	45.30	0.11	0.27
XPA1155GL	XPA	1155	45.45	0.11	0.27




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1157GL	XPA	1157	45.55	0.11	0.27
XPA1175GL	XPA	1175	46.25	0.12	0.28
XPA1180GL	XPA	1180	46.45	0.12	0.28
XPA1190GL	XPA	1190	46.85	0.12	0.28
XPA1200GL	XPA	1200	47.25	0.12	0.28
XPA1207GL	XPA	1207	47.50	0.12	0.29
XPA1215GL	XPA	1215	47.85	0.12	0.29
XPA1220GL	XPA	1220	48.05	0.12	0.29
XPA1232GL	XPA	1232	48.50	0.12	0.29
XPA1250GL	XPA	1250	49.20	0.12	0.30
XPA1257GL	XPA	1257	49.50	0.12	0.30
XPA1272GL	XPA	1272	50.10	0.12	0.30
XPA1280GL	XPA	1280	50.40	0.13	0.30
XPA1282GL	XPA	1282	50.45	0.13	0.30
XPA1285GL	XPA	1285	50.60	0.13	0.30
XPA1300GL	XPA	1300	51.20	0.13	0.31
XPA1307GL	XPA	1307	51.45	0.13	0.31
XPA1320GL	XPA	1320	51.95	0.13	0.31
XPA1332GL	XPA	1332	52.45	0.13	0.31
XPA1340GL	XPA	1340	52.75	0.13	0.32
XPA1357GL	XPA	1357	53.40	0.13	0.32
XPA1360GL	XPA	1360	53.55	0.13	0.32
XPA1367GL	XPA	1367	53.80	0.13	0.32
XPA1375GL	XPA	1375	54.15	0.13	0.32
XPA1382GL	XPA	1382	54.40	0.14	0.33
XPA1400GL	XPA	1400	55.10	0.14	0.33
XPA1407GL	XPA	1407	55.40	0.14	0.33
XPA1415GL	XPA	1415	55.70	0.14	0.33
XPA1420GL	XPA	1420	55.90	0.14	0.34
XPA1425GL	XPA	1425	56.10	0.14	0.34
XPA1430GL	XPA	1430	56.30	0.14	0.34
XPA1432GL	XPA	1432	56.40	0.14	0.34
XPA1450GL	XPA	1450	57.10	0.14	0.34
XPA1457GL	XPA	1457	57.35	0.14	0.34
XPA1465GL	XPA	1465	57.70	0.14	0.35
XPA1475GL	XPA	1475	58.05	0.14	0.35
XPA1482GL	XPA	1482	58.35	0.15	0.35




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1490GL	XPA	1490	58.65	0.15	0.35
XPA1500GL	XPA	1500	59.05	0.15	0.35
XPA1507GL	XPA	1507	59.35	0.15	0.36
XPA1520GL	XPA	1520	59.85	0.15	0.36
XPA1525GL	XPA	1525	60.05	0.15	0.36
XPA1532GL	XPA	1532	60.30	0.15	0.36
XPA1550GL	XPA	1550	61.00	0.15	0.37
XPA1557GL	XPA	1557	61.30	0.15	0.37
XPA1582GL	XPA	1582	62.30	0.16	0.37
XPA1600GL	XPA	1600	63.00	0.16	0.38
XPA1607GL	XPA	1607	63.25	0.16	0.38
XPA1610GL	XPA	1610	63.40	0.16	0.38
XPA1618GL	XPA	1618	63.70	0.16	0.38
XPA1630GL	XPA	1630	64.15	0.16	0.39
XPA1632GL	XPA	1632	64.25	0.16	0.39
XPA1650GL	XPA	1650	64.95	0.16	0.39
XPA1652GL	XPA	1652	65.05	0.16	0.39
XPA1657GL	XPA	1657	65.25	0.16	0.39
XPA1662GL	XPA	1662	65.45	0.16	0.39
XPA1675GL	XPA	1675	65.95	0.16	0.40
XPA1680GL	XPA	1680	66.15	0.16	0.40
XPA1682GL	XPA	1682	66.20	0.16	0.40
XPA1700GL	XPA	1700	66.95	0.17	0.40
XPA1707GL	XPA	1707	67.20	0.17	0.40
XPA1725GL	XPA	1725	67.90	0.17	0.41
XPA1732GL	XPA	1732	68.20	0.17	0.41
XPA1750GL	XPA	1750	68.90	0.17	0.41
XPA1757GL	XPA	1757	69.15	0.17	0.42
XPA1782GL	XPA	1782	70.15	0.17	0.42
XPA1800GL	XPA	1800	70.85	0.18	0.43
XPA1807GL	XPA	1807	71.15	0.18	0.43
XPA1820GL	XPA	1820	71.65	0.18	0.43
XPA1825GL	XPA	1825	71.85	0.18	0.43
XPA1832GL	XPA	1832	72.15	0.18	0.43
XPA1850GL	XPA	1850	72.85	0.18	0.44
XPA1857GL	XPA	1857	73.10	0.18	0.44
XPA1875GL	XPA	1875	73.80	0.18	0.44




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPA1882GL	XPA	1882	74.10	0.18	0.44
XPA1885GL	XPA	1885	74.20	0.18	0.45
XPA1900GL	XPA	1900	74.80	0.19	0.45
XPA1907GL	XPA	1907	75.10	0.19	0.45
XPA1925GL	XPA	1925	75.80	0.19	0.45
XPA1932GL	XPA	1932	76.05	0.19	0.46
XPA1950GL	XPA	1950	76.75	0.19	0.46
XPA1957GL	XPA	1957	77.05	0.19	0.46
XPA1982GL	XPA	1982	78.05	0.19	0.47
XPA1987GL	XPA	1987	78.25	0.19	0.47
XPA2000GL	XPA	2000	78.75	0.20	0.47
XPA2032GL	XPA	2032	80.00	0.20	0.48
XPA2050GL	XPA	2050	80.70	0.20	0.48
XPA2057GL	XPA	2057	81.00	0.20	0.49
XPA2060GL	XPA	2060	81.10	0.20	0.49
XPA2082GL	XPA	2082	81.95	0.20	0.49
XPA2100GL	XPA	2100	82.70	0.21	0.50
XPA2120GL	XPA	2120	83.45	0.21	0.50
XPA2130GL	XPA	2130	83.85	0.21	0.50
XPA2132GL	XPA	2132	83.95	0.21	0.50
XPA2150GL	XPA	2150	84.65	0.21	0.51
XPA2160GL	XPA	2160	85.05	0.21	0.51
XPA2180GL	XPA	2180	85.85	0.21	0.51
XPA2182GL	XPA	2182	85.90	0.21	0.52
XPA2200GL	XPA	2200	86.60	0.22	0.52
XPA2207GL	XPA	2207	86.90	0.22	0.52
XPA2227GL	XPA	2227	87.70	0.22	0.53
XPA2232GL	XPA	2232	87.85	0.22	0.53
XPA2240GL	XPA	2240	88.20	0.22	0.53
XPA2282GL	XPA	2282	89.85	0.22	0.54
XPA2300GL	XPA	2300	90.55	0.23	0.54
XPA2307GL	XPA	2307	90.85	0.23	0.54
XPA2330GL	XPA	2330	91.75	0.23	0.55
XPA2332GL	XPA	2332	91.80	0.23	0.55
XPA2360GL	XPA	2360	92.90	0.23	0.56
XPA2380GL	XPA	2380	93.70	0.23	0.56
XPA2382GL	XPA	2382	93.80	0.23	0.56




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPA2430GL	XPA	2430	95.65	0.24	0.57
*	XPA2432GL	XPA	2432	95.75	0.24	0.57
*	XPA2450GL	XPA	2450	96.45	0.24	0.58
*	XPA2482GL	XPA	2482	97.70	0.24	0.59
*	XPA2500GL	XPA	2500	98.40	0.25	0.59
*	XPA2532GL	XPA	2532	99.70	0.25	0.60
*	XPA2582GL	XPA	2582	101.65	0.25	0.61
*	XPA2600GL	XPA	2600	102.35	0.25	0.61
*	XPA2607GL	XPA	2607	102.65	0.26	0.62
*	XPA2632GL	XPA	2632	103.60	0.26	0.62
*	XPA2650GL	XPA	2650	104.35	0.26	0.63
*	XPA2682GL	XPA	2682	105.60	0.26	0.63
*	XPA2732GL	XPA	2732	107.55	0.27	0.65
*	XPA2782GL	XPA	2782	109.55	0.27	0.66
*	XPA2800GL	XPA	2800	110.25	0.27	0.66
*	XPA2832GL	XPA	2832	111.50	0.28	0.67
*	XPA2847GL	XPA	2847	112.10	0.28	0.67
*	XPA2882GL	XPA	2882	113.45	0.28	0.68
*	XPA2900GL	XPA	2900	114.15	0.28	0.69
*	XPA2932GL	XPA	2932	115.45	0.29	0.69
*	XPA2982GL	XPA	2982	117.40	0.29	0.70
*	XPA3000GL	XPA	3000	118.10	0.29	0.71
*	XPA3020GL	XPA	3020	118.90	0.30	0.71
*	XPA3030GL	XPA	3030	119.30	0.30	0.72
*	XPA3150GL	XPA	3150	124.00	0.31	0.74
*	XPA3350GL	XPA	3350	131.90	0.33	0.79
*	XPA3550GL	XPA	3550	139.75	0.35	0.84
	XPB1000GL	XPB	1000	39.40	0.16	0.35
	XPB1060GL	XPB	1060	41.75	0.17	0.38
	XPB1160GL	XPB	1160	45.70	0.18	0.41
	XPB1250GL	XPB	1250	49.25	0.20	0.44
	XPB1260GL	XPB	1260	49.65	0.20	0.45
	XPB1270GL	XPB	1270	50.00	0.20	0.45
	XPB1280GL	XPB	1280	50.40	0.20	0.45
	XPB1300GL	XPB	1300	51.20	0.20	0.46
	XPB1320GL	XPB	1320	52.00	0.21	0.47
	XPB1340GL	XPB	1340	52.80	0.21	0.47




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016


*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPB1360GL	XPB	1360	53.55	0.21	0.48
XPB1375GL	XPB	1375	54.15	0.22	0.49
XPB1380GL	XPB	1380	54.35	0.22	0.49
XPB1400GL	XPB	1400	55.15	0.22	0.50
XPB1410GL	XPB	1410	55.55	0.22	0.50
XPB1425GL	XPB	1425	56.10	0.22	0.50
XPB1435GL	XPB	1435	56.50	0.23	0.51
XPB1450GL	XPB	1450	57.10	0.23	0.51
XPB1465GL	XPB	1465	57.70	0.23	0.52
XPB1480GL	XPB	1480	58.30	0.23	0.52
XPB1485GL	XPB	1485	58.50	0.23	0.53
XPB1500GL	XPB	1500	59.10	0.24	0.53
XPB1510GL	XPB	1510	59.45	0.24	0.54
XPB1525GL	XPB	1525	60.05	0.24	0.54
XPB1540GL	XPB	1540	60.65	0.24	0.55
XPB1550GL	XPB	1550	61.05	0.24	0.55
XPB1555GL	XPB	1555	61.25	0.24	0.55
XPB1560GL	XPB	1560	61.45	0.24	0.55
XPB1590GL	XPB	1590	62.60	0.25	0.56
XPB1600GL	XPB	1600	63.00	0.25	0.57
XPB1627GL	XPB	1627	64.10	0.26	0.58
XPB1630GL	XPB	1630	64.20	0.26	0.58
XPB1650GL	XPB	1650	65.00	0.26	0.58
XPB1690GL	XPB	1690	66.55	0.27	0.60
XPB1700GL	XPB	1700	66.95	0.27	0.60
XPB1720GL	XPB	1720	67.75	0.27	0.61
XPB1750GL	XPB	1750	68.90	0.27	0.62
XPB1778GL	XPB	1778	70.00	0.28	0.63
XPB1800GL	XPB	1800	70.90	0.28	0.64
XPB1850GL	XPB	1850	72.85	0.29	0.66
XPB1860GL	XPB	1860	73.25	0.29	0.66
XPB1900GL	XPB	1900	74.80	0.30	0.67
XPB1950GL	XPB	1950	76.80	0.31	0.69
XPB2000GL	XPB	2000	78.75	0.31	0.71
XPB2020GL	XPB	2020	79.55	0.32	0.72
XPB2032GL	XPB	2032	80.00	0.32	0.72
XPB2060GL	XPB	2060	81.10	0.32	0.73




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
XPB2098GL	XPB	2098	82.60	0.33	0.74
XPB2100GL	XPB	2100	82.70	0.33	0.74
XPB2120GL	XPB	2120	83.50	0.33	0.75
XPB2150GL	XPB	2150	84.65	0.34	0.76
XPB2160GL	XPB	2160	85.05	0.34	0.77
XPB2180GL	XPB	2180	85.85	0.34	0.77
XPB2240GL	XPB	2240	88.20	0.35	0.79
XPB2260GL	XPB	2260	89.00	0.35	0.80
XPB2280GL	XPB	2280	89.80	0.36	0.81
XPB2300GL	XPB	2300	90.55	0.36	0.81
XPB2360GL	XPB	2360	92.95	0.37	0.84
XPB2391GL	XPB	2391	94.15	0.38	0.85
XPB2400GL	XPB	2400	94.50	0.38	0.85
XPB2410GL	XPB	2410	94.90	0.38	0.85
XPB2430GL	XPB	2430	95.70	0.38	0.86
* XPB2450GL	XPB	2450	96.50	0.38	0.87
* XPB2480GL	XPB	2480	97.65	0.39	0.88
* XPB2500GL	XPB	2500	98.45	0.39	0.89
* XPB2510GL	XPB	2510	98.85	0.39	0.89
* XPB2530GL	XPB	2530	99.65	0.40	0.90
* XPB2580GL	XPB	2580	101.60	0.41	0.91
* XPB2600GL	XPB	2600	102.40	0.41	0.92
* XPB2650GL	XPB	2650	104.35	0.42	0.94
* XPB2680GL	XPB	2680	105.55	0.42	0.95
* XPB2700GL	XPB	2700	106.30	0.42	0.96
* XPB2720GL	XPB	2720	107.10	0.43	0.96
* XPB2750GL	XPB	2750	108.30	0.43	0.97
* XPB2800GL	XPB	2800	110.25	0.44	0.99
* XPB2840GL	XPB	2840	111.85	0.45	1.01
* XPB2900GL	XPB	2900	114.20	0.46	1.03
* XPB2990GL	XPB	2990	117.75	0.47	1.06
* XPB3000GL	XPB	3000	118.15	0.47	1.06
* XPB3150GL	XPB	3150	124.05	0.49	1.12
* XPB3170GL	XPB	3170	124.80	0.50	1.12
* XPB3340GL	XPB	3340	131.50	0.52	1.18
* XPB3350GL	XPB	3350	131.90	0.53	1.19
* XPB3450GL	XPB	3450	135.85	0.54	1.22




MOVE FORWARD. ALWAYS.™

GOLD LABEL X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
XPZ	10	8	0.060
XPA	13	10	0.098
XPB	17	14	0.157
XPC	22	18	0.280

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
XPZ	25/64	5/16	0.003
XPA	33/64	25/64	0.006
XPB	43/64	35/64	0.009
XPC	7/8	45/64	0.016

*= Under preparation

	DAYCO Part Nr	Section	Li Outside length (mm)	Lo Outside length (mm)	Weight (Kg)	Weight (lbs)
*	XPB3550GL	XPB	3550	139.80	0.56	1.26
	XPC1260GL	XPC	1260	49.65	0.35	0.79
	XPC1700GL	XPC	1700	66.95	0.48	1.07
	XPC1800GL	XPC	1800	70.90	0.50	1.13
	XPC1900GL	XPC	1900	74.80	0.53	1.20
	XPC2000GL	XPC	2000	78.75	0.56	1.26
	XPC2120GL	XPC	2120	83.50	0.59	1.34
	XPC2170GL	XPC	2170	85.45	0.61	1.37
	XPC2240GL	XPC	2240	88.20	0.63	1.41
	XPC2360GL	XPC	2360	92.95	0.66	1.49
*	XPC2500GL	XPC	2500	98.45	0.70	1.57
*	XPC2600GL	XPC	2600	102.40	0.73	1.64
*	XPC2650GL	XPC	2650	104.35	0.74	1.67
*	XPC2800GL	XPC	2800	110.25	0.78	1.76
*	XPC2900GL	XPC	2900	114.20	0.81	1.83
*	XPC2995GL	XPC	2995	117.95	0.84	1.89
*	XPC3000GL	XPC	3000	118.15	0.84	1.89
*	XPC3150GL	XPC	3150	124.05	0.88	1.98
*	XPC3350GL	XPC	3350	131.90	0.94	2.11
*	XPC3550GL	XPC	3550	139.80	0.99	2.24



PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is < 30 °C / 86 °F
- Continues high temperature (50 °C / 122 °F) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly storage belt shelf life is at least 5 years
- Short belt up to 1,5 m / 59 in can be stored on pegs
- Long belts better to be coiled on shelves for distortion – free



MOVE FORWARD. ALWAYS.™

GOLD LABEL - Notes

[illegible]

Product Guide

GOLD LABEL™ Industrial Double Angle V-Belts




GOLD LABEL™


Designed for **OEMs**

DAYCO®
MOVE FORWARD. ALWAYS.™

GOLD LABEL Double Angle - Table of Contents



V-Belt Double Angle **GOLD LABEL™**




AA-BB-CC-AAG-BBG

GOLD LABEL Double Angle


Product description3

Size List4

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

V-Belt

Part Number Description: **AAG70GL**

AA: Profile (13mm X 10mm)

G: Grooved profile

70: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 °C / -31 To 160 °F

Designed for Back-Side Pulleys Application

Markets and Applications:


Perfect solution for serpentine drives

These belts are used on drives with one or more reverse bend where power is transmitted from the belt on both side and in reverse conditions as well


Fits on application such as Lawn & Garden, Agriculture Harvesters, Chicken Pluckers, Mixers, Agitators, Conveyors, Crushers

Pulley Standards: DIN2217 – ISO 4183

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
AA60GL	AA	1524	1577	60.00	62.00	0.23	0.51
AA62GL	AA	1575	1628	62.00	64.00	0.24	0.53
AA64GL	AA	1626	1679	64.00	66.00	0.25	0.54
AA66GL	AA	1676	1729	66.00	68.00	0.25	0.56
AA68GL	AA	1727	1780	68.00	70.00	0.26	0.57
AA70GL	AA	1778	1831	70.00	72.00	0.27	0.59
AA73GL	AA	1854	1907	73.00	75.00	0.28	0.62
AA75GL	AA	1905	1958	75.00	77.00	0.29	0.63
AA78GL	AA	1981	2034	78.00	80.00	0.30	0.66
AA80GL	AA	2032	2085	80.00	82.00	0.31	0.67
AA85GL	AA	2159	2212	85.00	87.00	0.32	0.71
AA88GL	AA	2235	2288	88.00	90.00	0.34	0.74
AA90GL	AA	2286	2339	90.00	92.00	0.34	0.76
AA92GL	AA	2337	2390	92.00	94.00	0.35	0.77
BB85GL	BB	2159	2233	85.00	88.00	0.51	1.12
BB90GL	BB	2286	2360	90.00	93.00	0.54	1.18
BB92GL	BB	2337	2411	92.00	95.00	0.55	1.21
BB93GL	BB	2362	2436	93.00	96.00	0.55	1.22
BB94GL	BB	2388	2462	94.00	97.00	0.56	1.23
BB96GL	BB	2438	2512	96.00	99.00	0.57	1.26
BB97GL	BB	2464	2538	97.00	100.00	0.58	1.27
BB100GL	BB	2540	2614	100.00	103.00	0.59	1.31
BB103GL	BB	2616	2690	103.00	106.00	0.61	1.34
BB105GL	BB	2667	2741	105.00	108.00	0.62	1.37
BB107GL	BB	2718	2792	107.00	110.00	0.63	1.40
BB108GL	BB	2743	2817	108.00	111.00	0.64	1.41
BB111GL	BB	2819	2893	111.00	114.00	0.66	1.45
BB112GL	BB	2845	2919	112.00	115.00	0.66	1.46
BB114GL	BB	2896	2970	114.00	117.00	0.67	1.48
BB116GL	BB	2946	3020	116.00	119.00	0.68	1.51
BB117GL	BB	2972	3046	117.00	120.00	0.69	1.52
BB118GL	BB	2997	3071	118.00	121.00	0.70	1.54

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
BB120GL	BB	3048	3122	120.00	123.00	0.71	1.56
BB122GL	BB	3099	3173	122.00	125.00	0.72	1.59
BB123GL	BB	3124	3198	123.00	126.00	0.73	1.60
BB124GL	BB	3150	3224	124.00	127.00	0.73	1.61
BB127GL	BB	3226	3300	127.00	130.00	0.75	1.65
BB128GL	BB	3251	3325	128.00	131.00	0.75	1.66
BB130GL	BB	3302	3376	130.00	133.00	0.77	1.69
BB133GL	BB	3378	3452	133.00	136.00	0.78	1.73
BB135GL	BB	3429	3503	135.00	138.00	0.79	1.75
BB136GL	BB	3454	3528	136.00	139.00	0.80	1.76
BB140GL	BB	3556	3630	140.00	143.00	0.82	1.81
BB144GL	BB	3658	3732	144.00	147.00	0.85	1.87
BB155GL	BB	3937	4011	155.00	158.00	0.91	2.01
BB158GL	BB	4013	4087	158.00	161.00	0.93	2.04
BB162GL	BB	4115	4189	162.00	165.00	0.95	2.09
BB168GL	BB	4267	4341	168.00	171.00	0.98	2.17
BB170GL	BB	4318	4392	170.00	173.00	1.00	2.20
BB173GL	BB	4394	4468	173.00	176.00	1.01	2.23
BB180GL	BB	4572	4646	180.00	183.00	1.05	2.32
BB182GL	BB	4623	4697	182.00	185.00	1.07	2.35
BB187GL	BB	4750	4824	187.00	190.00	1.09	2.41
BB190GL	BB	4826	4900	190.00	193.00	1.11	2.45
BB195GL	BB	4953	5027	195.00	198.00	1.14	2.51
BB210GL	BB	5334	5408	210.00	213.00	1.23	2.70
BB225GL	BB	5715	5751	225.00	226.00	1.30	2.88
BB228GL	BB	5791	5827	228.00	229.00	1.32	2.91
BB240GL	BB	6096	6132	240.00	241.00	1.39	3.07
BB255GL	BB	6477	6513	255.00	256.00	1.48	3.26
BB270GL	BB	6858	6894	270.00	271.00	1.56	3.45
BB285GL	BB	7239	7275	285.00	286.00	1.65	3.64
BB300GL	BB	7620	7656	300.00	301.00	1.74	3.83
CC75GL	CC	1905	2012	75.00	79.00	0.79	1.74

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
CC81GL	CC	2057	2164	81.00	85.00	0.85	1.87
CC85GL	CC	2159	2266	85.00	89.00	0.89	1.96
CC90GL	CC	2286	2393	90.00	94.00	0.94	2.07
CC96GL	CC	2438	2545	96.00	100.00	1.00	2.20
CC105GL	CC	2667	2774	105.00	109.00	1.09	2.40
CC112GL	CC	2845	2952	112.00	116.00	1.16	2.55
CC120GL	CC	3048	3155	120.00	124.00	1.24	2.73
CC128GL	CC	3251	3358	128.00	132.00	1.32	2.90
CC136GL	CC	3454	3561	136.00	140.00	1.40	3.08
CC140GL	CC	3556	3663	140.00	144.00	1.44	3.17
CC144GL	CC	3658	3765	144.00	148.00	1.48	3.25
CC158GL	CC	4013	4120	158.00	162.00	1.62	3.56
CC162GL	CC	4115	4222	162.00	166.00	1.66	3.65
CC173GL	CC	4394	4501	173.00	177.00	1.77	3.89
CC180GL	CC	4572	4679	180.00	184.00	1.83	4.04
CC195GL	CC	4953	5060	195.00	199.00	1.98	4.37
CC210GL	CC	5334	5441	210.00	214.00	2.13	4.70
CC240GL	CC	6096	6152	240.00	242.00	2.41	5.32
CC255GL	CC	6477	6533	255.00	257.00	2.56	5.65
CC270GL	CC	6858	6914	270.00	272.00	2.71	5.98
CC300GL	CC	7620	7676	300.00	302.00	3.01	6.64
CC330GL	CC	8382	8438	330.00	332.00	3.31	7.29
CC360GL	CC	9144	9200	360.00	362.00	3.61	7.95
CC390GL	CC	9906	9962	390.00	392.00	3.91	8.61
CC420GL	CC	10668	10724	420.00	422.00	4.21	9.27
AAG60GL	AAG	1524	1577	60.00	62.00	0.23	0.51
AAG62GL	AAG	1575	1628	62.00	64.00	0.24	0.53
AAG64GL	AAG	1626	1679	64.00	66.00	0.25	0.54
AAG66GL	AAG	1676	1729	66.00	68.00	0.25	0.56
AAG68GL	AAG	1727	1780	68.00	70.00	0.26	0.57
AAG70GL	AAG	1778	1831	70.00	72.00	0.27	0.59
AAG73GL	AAG	1854	1907	73.00	75.00	0.28	0.62

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
AAG75GL	AAG	1905	1958	75.00	77.00	0.29	0.63
AAG78GL	AAG	1981	2034	78.00	80.00	0.30	0.66
AAG80GL	AAG	2032	2085	80.00	82.00	0.31	0.67
AAG85GL	AAG	2159	2212	85.00	87.00	0.32	0.71
AAG88GL	AAG	2235	2288	88.00	90.00	0.34	0.74
AAG90GL	AAG	2286	2339	90.00	92.00	0.34	0.76
AAG92GL	AAG	2337	2390	92.00	94.00	0.35	0.77
AAG96GL	AAG	2438	2491	96.00	98.00	0.36	0.80
AAG105GL	AAG	2667	2720	105.00	107.00	0.40	0.88
AAG112GL	AAG	2845	2898	112.00	114.00	0.42	0.94
AAG120GL	AAG	3048	3101	120.00	122.00	0.45	1.00
AAG128GL	AAG	3251	3304	128.00	130.00	0.48	1.07
AAG148GL	AAG	3759	3812	148.00	150.00	0.56	1.23
BBG60GL	BBG	1524	1598	60.00	63.00	0.36	0.80
BBG64GL	BBG	1626	1700	64.00	67.00	0.39	0.85
BBG66GL	BBG	1676	1750	66.00	69.00	0.40	0.88
BBG68GL	BBG	1727	1801	68.00	71.00	0.41	0.90
BBG71GL	BBG	1803	1877	71.00	74.00	0.43	0.94
BBG72GL	BBG	1829	1903	72.00	75.00	0.43	0.95
BBG73GL	BBG	1854	1928	73.00	76.00	0.44	0.96
BBG74GL	BBG	1880	1954	74.00	77.00	0.44	0.98
BBG75GL	BBG	1905	1979	75.00	78.00	0.45	0.99
BBG81GL	BBG	2057	2131	81.00	84.00	0.48	1.07
BBG83GL	BBG	2108	2182	83.00	86.00	0.49	1.09
BBG85GL	BBG	2159	2233	85.00	88.00	0.51	1.12
BBG90GL	BBG	2286	2360	90.00	93.00	0.54	1.18
BBG92GL	BBG	2337	2411	92.00	95.00	0.55	1.21
BBG93GL	BBG	2362	2436	93.00	96.00	0.55	1.22
BBG94GL	BBG	2388	2462	94.00	97.00	0.56	1.23
BBG96GL	BBG	2438	2512	96.00	99.00	0.57	1.26
BBG97GL	BBG	2464	2538	97.00	100.00	0.58	1.27
BBG100GL	BBG	2540	2614	100.00	103.00	0.59	1.31

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**




Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227


Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
BBG103GL	BBG	2616	2690	103.00	106.00	0.61	1.34
BBG105GL	BBG	2667	2741	105.00	108.00	0.62	1.37
BBG107GL	BBG	2718	2792	107.00	110.00	0.63	1.40
BBG108GL	BBG	2743	2817	108.00	111.00	0.64	1.41
BBG111GL	BBG	2819	2893	111.00	114.00	0.66	1.45
BBG112GL	BBG	2845	2919	112.00	115.00	0.66	1.46
BBG114GL	BBG	2896	2970	114.00	117.00	0.67	1.48
BBG116GL	BBG	2946	3020	116.00	119.00	0.68	1.51
BBG117GL	BBG	2972	3046	117.00	120.00	0.69	1.52
BBG118GL	BBG	2997	3071	118.00	121.00	0.70	1.54
BBG120GL	BBG	3048	3122	120.00	123.00	0.71	1.56
BBG122GL	BBG	3099	3173	122.00	125.00	0.72	1.59
BBG123GL	BBG	3124	3198	123.00	126.00	0.73	1.60
BBG124GL	BBG	3150	3224	124.00	127.00	0.73	1.61
BBG127GL	BBG	3226	3300	127.00	130.00	0.75	1.65
BBG128GL	BBG	3251	3325	128.00	131.00	0.75	1.66
BBG130GL	BBG	3302	3376	130.00	133.00	0.77	1.69
BBG133GL	BBG	3378	3452	133.00	136.00	0.78	1.73
BBG135GL	BBG	3429	3503	135.00	138.00	0.79	1.75
BBG136GL	BBG	3454	3528	136.00	139.00	0.80	1.76
BBG140GL	BBG	3556	3630	140.00	143.00	0.82	1.81
BBG144GL	BBG	3658	3732	144.00	147.00	0.85	1.87
BBG155GL	BBG	3937	4011	155.00	158.00	0.91	2.01
BBG158GL	BBG	4013	4087	158.00	161.00	0.93	2.04
BBG162GL	BBG	4115	4189	162.00	165.00	0.95	2.09
BBG168GL	BBG	4267	4341	168.00	171.00	0.98	2.17
BBG170GL	BBG	4318	4392	170.00	173.00	1.00	2.20
BBG173GL	BBG	4394	4468	173.00	176.00	1.01	2.23
BBG180GL	BBG	4572	4646	180.00	183.00	1.05	2.32
BBG182GL	BBG	4623	4697	182.00	185.00	1.07	2.35
BBG187GL	BBG	4750	4824	187.00	190.00	1.09	2.41
BBG190GL	BBG	4826	4900	190.00	193.00	1.11	2.45

GOLD LABEL Double Angle - Size List



V-Belt Double Angle **GOLD LABEL**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/m)
AA	13	10	0.146
BB	17	13	0.227
CC	22	17	0.392
AAG	13	10	0.146
BBG	17	13	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/in)
AA	1/2	5/16	0.008
BB	21/32	13/32	0.013
CC	7/8	17/32	0.022
AAG	1-1/4	3/4	0.008
BBG	1-1/2	1	0.013

DAYCO Part Nr	Section	Li Inside length (mm)	Le Effective length (mm)	Li Inside length (in)	Le Effective length (in)	Weight (Kg)	Weight (lbs)
BBG195GL	BBG	4953	5027	195.00	198.00	1.14	2.51
BBG210GL	BBG	5334	5408	210.00	213.00	1.23	2.70
BBG225GL	BBG	5715	5751	225.00	226.00	1.30	2.88
BBG228GL	BBG	5791	5827	228.00	229.00	1.32	2.91
BBG240GL	BBG	6096	6132	240.00	241.00	1.39	3.07
BBG255GL	BBG	6477	6513	255.00	256.00	1.48	3.26
BBG270GL	BBG	6858	6894	270.00	271.00	1.56	3.45
BBG285GL	BBG	7239	7275	285.00	286.00	1.65	3.64
BBG300GL	BBG	7620	7656	300.00	301.00	1.74	3.83



PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is < 30 °C / 86 °F
- Continues high temperature (50 °C / 122 °F) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly stored belt shelf life is at least 5 years
- Short belt up to 1,5m can be stored on pegs
- Long belts better to be coiled on shelves for distortion - free



GOLD LABEL Double Angle - Notes



www.dayco.com



Product Guide

GOLD LABEL™ Industrial Banded Wrapped V-Belts




GOLD LABEL™

Designed for **OEMs**

DAYCO®
MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Wrapped - Table of Contents



V-Belt Banded **GOLD LABEL**

A-B-C-D

GOLD LABEL Banded Classical

Product description3
Size List4



V-Belt Banded **GOLD LABEL**

3V-5V-8V

GOLD LABEL Banded Narrow

Product description38
Size List39



V-Belt Banded **GOLD LABEL**

SPZ-SPA-SPB-SPC

GOLD LABEL Banded Wedge

Product description51
Size List52

GOLD LABEL Banded Wrapped Classical - Product Description



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

V-Belt

Part Number Description: **2/B120GL**

2/: Number of ribs

B: Profile

120: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Prevents Vibrations and belt Turn-over

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 °C / -31 To 160 °F

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty drives

Recommended solution for multiple belts drives where single belts vibrate or turn over

Pulley Standards: ISO 5291

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/A58GL	2	A	1473	58.00	0.54	1.19
2/A59GL	2	A	1499	59.00	0.55	1.21
2/A60GL	2	A	1524	60.00	0.56	1.23
2/A62GL	2	A	1575	62.00	0.57	1.27
2/A64GL	2	A	1626	64.00	0.59	1.31
2/A65GL	2	A	1651	65.00	0.60	1.33
2/A66GL	2	A	1676	66.00	0.61	1.35
2/A67GL	2	A	1702	67.00	0.62	1.37
2/A68GL	2	A	1727	68.00	0.63	1.39
2/A70GL	2	A	1778	70.00	0.65	1.43
2/A71GL	2	A	1803	71.00	0.66	1.45
2/A74GL	2	A	1880	74.00	0.69	1.51
2/A75GL	2	A	1905	75.00	0.70	1.53
2/A77GL	2	A	1956	77.00	0.71	1.57
2/A78GL	2	A	1981	78.00	0.72	1.59
2/A79GL	2	A	2007	79.00	0.73	1.61
2/A80GL	2	A	2032	80.00	0.74	1.64
2/A81GL	2	A	2057	81.00	0.75	1.66
2/A83GL	2	A	2108	83.00	0.77	1.70
2/A85GL	2	A	2159	85.00	0.79	1.74
2/A88GL	2	A	2235	88.00	0.82	1.80
2/A90GL	2	A	2286	90.00	0.83	1.84
2/A92GL	2	A	2337	92.00	0.85	1.88
2/A96GL	2	A	2438	96.00	0.89	1.96
2/A98GL	2	A	2489	98.00	0.91	2.00
2/A100GL	2	A	2540	100.00	0.93	2.04
2/A104GL	2	A	2642	104.00	0.96	2.13
2/A105GL	2	A	2667	105.00	0.97	2.15
2/A110GL	2	A	2794	110.00	1.02	2.25
2/A112GL	2	A	2845	112.00	1.04	2.29
2/A120GL	2	A	3048	120.00	1.11	2.45
2/A128GL	2	A	3251	128.00	1.19	2.62

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/A136GL	2	A	3454	136.00	1.26	2.78
2/A144GL	2	A	3658	144.00	1.34	2.94
2/A158GL	2	A	4013	158.00	1.46	3.23
2/A167GL	2	A	4242	167.00	1.55	3.41
2/A173GL	2	A	4394	173.00	1.60	3.54
2/A180GL	2	A	4572	180.00	1.67	3.68
2/A187GL	2	A	4750	187.00	1.73	3.82
3/A58GL	3	A	1473	58.00	0.81	1.78
3/A59GL	3	A	1499	59.00	0.82	1.81
3/A60GL	3	A	1524	60.00	0.83	1.84
3/A62GL	3	A	1575	62.00	0.86	1.90
3/A64GL	3	A	1626	64.00	0.89	1.96
3/A65GL	3	A	1651	65.00	0.90	1.99
3/A66GL	3	A	1676	66.00	0.92	2.02
3/A67GL	3	A	1702	67.00	0.93	2.05
3/A68GL	3	A	1727	68.00	0.95	2.08
3/A70GL	3	A	1778	70.00	0.97	2.15
3/A71GL	3	A	1803	71.00	0.99	2.18
3/A74GL	3	A	1880	74.00	1.03	2.27
3/A75GL	3	A	1905	75.00	1.04	2.30
3/A77GL	3	A	1956	77.00	1.07	2.36
3/A78GL	3	A	1981	78.00	1.08	2.39
3/A79GL	3	A	2007	79.00	1.10	2.42
3/A80GL	3	A	2032	80.00	1.11	2.45
3/A81GL	3	A	2057	81.00	1.13	2.48
3/A83GL	3	A	2108	83.00	1.15	2.54
3/A85GL	3	A	2159	85.00	1.18	2.61
3/A88GL	3	A	2235	88.00	1.22	2.70
3/A90GL	3	A	2286	90.00	1.25	2.76
3/A92GL	3	A	2337	92.00	1.28	2.82
3/A96GL	3	A	2438	96.00	1.34	2.94
3/A98GL	3	A	2489	98.00	1.36	3.00

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/A100GL	3	A	2540	100.00	1.39	3.07
3/A104GL	3	A	2642	104.00	1.45	3.19
3/A105GL	3	A	2667	105.00	1.46	3.22
3/A110GL	3	A	2794	110.00	1.53	3.37
3/A112GL	3	A	2845	112.00	1.56	3.43
3/A120GL	3	A	3048	120.00	1.67	3.68
3/A128GL	3	A	3251	128.00	1.78	3.92
3/A136GL	3	A	3454	136.00	1.89	4.17
3/A144GL	3	A	3658	144.00	2.00	4.42
3/A158GL	3	A	4013	158.00	2.20	4.84
3/A167GL	3	A	4242	167.00	2.32	5.12
3/A173GL	3	A	4394	173.00	2.41	5.30
3/A180GL	3	A	4572	180.00	2.50	5.52
3/A187GL	3	A	4750	187.00	2.60	5.73
4/A58GL	4	A	1473	58.00	1.08	2.37
4/A59GL	4	A	1499	59.00	1.09	2.41
4/A60GL	4	A	1524	60.00	1.11	2.45
4/A62GL	4	A	1575	62.00	1.15	2.53
4/A64GL	4	A	1626	64.00	1.19	2.62
4/A65GL	4	A	1651	65.00	1.21	2.66
4/A66GL	4	A	1676	66.00	1.22	2.70
4/A67GL	4	A	1702	67.00	1.24	2.74
4/A68GL	4	A	1727	68.00	1.26	2.78
4/A70GL	4	A	1778	70.00	1.30	2.86
4/A71GL	4	A	1803	71.00	1.32	2.90
4/A74GL	4	A	1880	74.00	1.37	3.03
4/A75GL	4	A	1905	75.00	1.39	3.07
4/A77GL	4	A	1956	77.00	1.43	3.15
4/A78GL	4	A	1981	78.00	1.45	3.19
4/A79GL	4	A	2007	79.00	1.46	3.23
4/A80GL	4	A	2032	80.00	1.48	3.27
4/A81GL	4	A	2057	81.00	1.50	3.31

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/A83GL	4	A	2108	83.00	1.54	3.39
4/A85GL	4	A	2159	85.00	1.58	3.47
4/A88GL	4	A	2235	88.00	1.63	3.60
4/A90GL	4	A	2286	90.00	1.67	3.68
4/A92GL	4	A	2337	92.00	1.71	3.76
4/A96GL	4	A	2438	96.00	1.78	3.92
4/A98GL	4	A	2489	98.00	1.82	4.01
4/A100GL	4	A	2540	100.00	1.85	4.09
4/A104GL	4	A	2642	104.00	1.93	4.25
4/A105GL	4	A	2667	105.00	1.95	4.29
4/A110GL	4	A	2794	110.00	2.04	4.50
4/A112GL	4	A	2845	112.00	2.08	4.58
4/A120GL	4	A	3048	120.00	2.23	4.91
4/A128GL	4	A	3251	128.00	2.37	5.23
4/A136GL	4	A	3454	136.00	2.52	5.56
4/A144GL	4	A	3658	144.00	2.67	5.89
4/A158GL	4	A	4013	158.00	2.93	6.46
4/A167GL	4	A	4242	167.00	3.10	6.83
4/A173GL	4	A	4394	173.00	3.21	7.07
4/A180GL	4	A	4572	180.00	3.34	7.36
4/A187GL	4	A	4750	187.00	3.47	7.64
5/A58GL	5	A	1473	58.00	1.34	2.96
5/A59GL	5	A	1499	59.00	1.37	3.01
5/A60GL	5	A	1524	60.00	1.39	3.07
5/A62GL	5	A	1575	62.00	1.44	3.17
5/A64GL	5	A	1626	64.00	1.48	3.27
5/A65GL	5	A	1651	65.00	1.51	3.32
5/A66GL	5	A	1676	66.00	1.53	3.37
5/A67GL	5	A	1702	67.00	1.55	3.42
5/A68GL	5	A	1727	68.00	1.58	3.47
5/A70GL	5	A	1778	70.00	1.62	3.58
5/A71GL	5	A	1803	71.00	1.65	3.63

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/A74GL	5	A	1880	74.00	1.72	3.78
5/A75GL	5	A	1905	75.00	1.74	3.83
5/A77GL	5	A	1956	77.00	1.78	3.93
5/A78GL	5	A	1981	78.00	1.81	3.99
5/A79GL	5	A	2007	79.00	1.83	4.04
5/A80GL	5	A	2032	80.00	1.85	4.09
5/A81GL	5	A	2057	81.00	1.88	4.14
5/A83GL	5	A	2108	83.00	1.92	4.24
5/A85GL	5	A	2159	85.00	1.97	4.34
5/A88GL	5	A	2235	88.00	2.04	4.50
5/A90GL	5	A	2286	90.00	2.09	4.60
5/A92GL	5	A	2337	92.00	2.13	4.70
5/A96GL	5	A	2438	96.00	2.23	4.91
5/A98GL	5	A	2489	98.00	2.27	5.01
5/A100GL	5	A	2540	100.00	2.32	5.11
5/A104GL	5	A	2642	104.00	2.41	5.31
5/A105GL	5	A	2667	105.00	2.43	5.37
5/A110GL	5	A	2794	110.00	2.55	5.62
5/A112GL	5	A	2845	112.00	2.60	5.72
5/A120GL	5	A	3048	120.00	2.78	6.13
5/A128GL	5	A	3251	128.00	2.97	6.54
5/A136GL	5	A	3454	136.00	3.15	6.95
5/A144GL	5	A	3658	144.00	3.34	7.36
5/A158GL	5	A	4013	158.00	3.66	8.07
5/A167GL	5	A	4242	167.00	3.87	8.53
5/A173GL	5	A	4394	173.00	4.01	8.84
5/A180GL	5	A	4572	180.00	4.17	9.20
5/A187GL	5	A	4750	187.00	4.33	9.56
19/A58GL	19	A	1473	58.00	5.11	11.26
19/A59GL	19	A	1499	59.00	5.20	11.46
19/A60GL	19	A	1524	60.00	5.28	11.65
19/A62GL	19	A	1575	62.00	5.46	12.04

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
19/A64GL	19	A	1626	64.00	5.64	12.43
19/A65GL	19	A	1651	65.00	5.73	12.62
19/A66GL	19	A	1676	66.00	5.81	12.82
19/A67GL	19	A	1702	67.00	5.90	13.01
19/A68GL	19	A	1727	68.00	5.99	13.20
19/A70GL	19	A	1778	70.00	6.17	13.59
19/A71GL	19	A	1803	71.00	6.25	13.79
19/A74GL	19	A	1880	74.00	6.52	14.37
19/A75GL	19	A	1905	75.00	6.61	14.56
19/A77GL	19	A	1956	77.00	6.78	14.95
19/A78GL	19	A	1981	78.00	6.87	15.15
19/A79GL	19	A	2007	79.00	6.96	15.34
19/A80GL	19	A	2032	80.00	7.05	15.53
19/A81GL	19	A	2057	81.00	7.13	15.73
19/A83GL	19	A	2108	83.00	7.31	16.12
19/A85GL	19	A	2159	85.00	7.49	16.51
19/A88GL	19	A	2235	88.00	7.75	17.09
19/A90GL	19	A	2286	90.00	7.93	17.48
19/A92GL	19	A	2337	92.00	8.10	17.86
19/A96GL	19	A	2438	96.00	8.46	18.64
19/A98GL	19	A	2489	98.00	8.63	19.03
19/A100GL	19	A	2540	100.00	8.81	19.42
19/A104GL	19	A	2642	104.00	9.16	20.20
19/A105GL	19	A	2667	105.00	9.25	20.39
19/A110GL	19	A	2794	110.00	9.69	21.36
19/A112GL	19	A	2845	112.00	9.86	21.75
19/A120GL	19	A	3048	120.00	10.57	23.30
19/A128GL	19	A	3251	128.00	11.27	24.86
19/A136GL	19	A	3454	136.00	11.98	26.41
19/A144GL	19	A	3658	144.00	12.68	27.96
19/A158GL	19	A	4013	158.00	13.92	30.68
19/A167GL	19	A	4242	167.00	14.71	32.43

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
19/A173GL	19	A	4394	173.00	15.24	33.59
19/A180GL	19	A	4572	180.00	15.85	34.95
19/A187GL	19	A	4750	187.00	16.47	36.31
2/B56GL	2	B	1422	56.00	0.73	1.61
2/B57GL	2	B	1448	57.00	0.74	1.64
2/B58GL	2	B	1473	58.00	0.76	1.67
2/B59GL	2	B	1499	59.00	0.77	1.69
2/B60GL	2	B	1524	60.00	0.78	1.72
2/B61GL	2	B	1549	61.00	0.79	1.75
2/B62GL	2	B	1575	62.00	0.81	1.78
2/B63GL	2	B	1600	63.00	0.82	1.81
2/B64GL	2	B	1626	64.00	0.83	1.84
2/B65GL	2	B	1651	65.00	0.85	1.87
2/B66GL	2	B	1676	66.00	0.86	1.90
2/B67GL	2	B	1702	67.00	0.87	1.92
2/B68GL	2	B	1727	68.00	0.89	1.95
2/B70GL	2	B	1778	70.00	0.91	2.01
2/B71GL	2	B	1803	71.00	0.93	2.04
2/B72GL	2	B	1829	72.00	0.94	2.07
2/B73GL	2	B	1854	73.00	0.95	2.10
2/B74GL	2	B	1880	74.00	0.96	2.13
2/B75GL	2	B	1905	75.00	0.98	2.15
2/B77GL	2	B	1956	77.00	1.00	2.21
2/B78GL	2	B	1981	78.00	1.02	2.24
2/B79GL	2	B	2007	79.00	1.03	2.27
2/B80GL	2	B	2032	80.00	1.04	2.30
2/B81GL	2	B	2057	81.00	1.06	2.33
2/B82GL	2	B	2083	82.00	1.07	2.36
2/B83GL	2	B	2108	83.00	1.08	2.38
2/B84GL	2	B	2134	84.00	1.09	2.41
2/B85GL	2	B	2159	85.00	1.11	2.44
2/B86GL	2	B	2184	86.00	1.12	2.47

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B87GL	2	B	2210	87.00	1.13	2.50
2/B88GL	2	B	2235	88.00	1.15	2.53
2/B90GL	2	B	2286	90.00	1.17	2.59
2/B91GL	2	B	2311	91.00	1.19	2.61
2/B92GL	2	B	2337	92.00	1.20	2.64
2/B93GL	2	B	2362	93.00	1.21	2.67
2/B94.5GL	2	B	2400	94.50	1.23	2.71
2/B95GL	2	B	2413	95.00	1.24	2.73
2/B96GL	2	B	2438	96.00	1.25	2.76
2/B97GL	2	B	2464	97.00	1.26	2.79
2/B98GL	2	B	2489	98.00	1.28	2.81
2/B99GL	2	B	2515	99.00	1.29	2.84
2/B100GL	2	B	2540	100.00	1.30	2.87
2/B102GL	2	B	2591	102.00	1.33	2.93
2/B103GL	2	B	2616	103.00	1.34	2.96
2/B104GL	2	B	2642	104.00	1.35	2.99
2/B105GL	2	B	2667	105.00	1.37	3.02
2/B106GL	2	B	2692	106.00	1.38	3.04
2/B108GL	2	B	2743	108.00	1.41	3.10
2/B109GL	2	B	2769	109.00	1.42	3.13
2/B110GL	2	B	2794	110.00	1.43	3.16
2/B112GL	2	B	2845	112.00	1.46	3.22
2/B113GL	2	B	2870	113.00	1.47	3.25
2/B114GL	2	B	2896	114.00	1.49	3.27
2/B115GL	2	B	2921	115.00	1.50	3.30
2/B116GL	2	B	2946	116.00	1.51	3.33
2/B118GL	2	B	2997	118.00	1.54	3.39
2/B120GL	2	B	3048	120.00	1.56	3.45
2/B124GL	2	B	3150	124.00	1.62	3.56
2/B128GL	2	B	3251	128.00	1.67	3.68
2/B130GL	2	B	3302	130.00	1.69	3.73
2/B132GL	2	B	3353	132.00	1.72	3.79

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B133GL	2	B	3378	133.00	1.73	3.82
2/B136GL	2	B	3454	136.00	1.77	3.91
2/B138GL	2	B	3505	138.00	1.80	3.96
2/B139GL	2	B	3531	139.00	1.81	3.99
2/B140GL	2	B	3556	140.00	1.82	4.02
2/B141GL	2	B	3581	141.00	1.84	4.05
2/B144GL	2	B	3658	144.00	1.88	4.14
2/B146GL	2	B	3708	146.00	1.90	4.19
2/B148GL	2	B	3759	148.00	1.93	4.25
2/B150GL	2	B	3810	150.00	1.95	4.31
2/B154GL	2	B	3912	154.00	2.01	4.42
2/B158GL	2	B	4013	158.00	2.06	4.54
2/B160GL	2	B	4064	160.00	2.08	4.60
2/B162GL	2	B	4115	162.00	2.11	4.65
2/B167GL	2	B	4242	167.00	2.18	4.80
2/B168GL	2	B	4267	168.00	2.19	4.83
2/B173GL	2	B	4394	173.00	2.25	4.97
2/B177GL	2	B	4496	177.00	2.31	5.08
2/B180GL	2	B	4572	180.00	2.35	5.17
2/B185GL	2	B	4699	185.00	2.41	5.31
2/B187GL	2	B	4750	187.00	2.44	5.37
2/B190GL	2	B	4826	190.00	2.48	5.46
2/B195GL	2	B	4953	195.00	2.54	5.60
2/B197GL	2	B	5004	197.00	2.57	5.66
2/B208GL	2	B	5283	208.00	2.71	5.97
2/B210GL	2	B	5334	210.00	2.74	6.03
2/B218GL	2	B	5537	218.00	2.84	6.26
2/B220GL	2	B	5588	220.00	2.87	6.32
2/B225GL	2	B	5715	225.00	2.93	6.46
2/B240GL	2	B	6096	240.00	3.13	6.89
2/B255GL	2	B	6477	255.00	3.32	7.32
2/B270GL	2	B	6858	270.00	3.52	7.76

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/B300GL	2	B	7620	300.00	3.91	8.62
2/B315GL	2	B	8001	315.00	4.10	9.05
3/B56GL	3	B	1422	56.00	1.09	2.41
3/B57GL	3	B	1448	57.00	1.11	2.46
3/B58GL	3	B	1473	58.00	1.13	2.50
3/B59GL	3	B	1499	59.00	1.15	2.54
3/B60GL	3	B	1524	60.00	1.17	2.59
3/B61GL	3	B	1549	61.00	1.19	2.63
3/B62GL	3	B	1575	62.00	1.21	2.67
3/B63GL	3	B	1600	63.00	1.23	2.71
3/B64GL	3	B	1626	64.00	1.25	2.76
3/B65GL	3	B	1651	65.00	1.27	2.80
3/B66GL	3	B	1676	66.00	1.29	2.84
3/B67GL	3	B	1702	67.00	1.31	2.89
3/B68GL	3	B	1727	68.00	1.33	2.93
3/B70GL	3	B	1778	70.00	1.37	3.02
3/B71GL	3	B	1803	71.00	1.39	3.06
3/B72GL	3	B	1829	72.00	1.41	3.10
3/B73GL	3	B	1854	73.00	1.43	3.15
3/B74GL	3	B	1880	74.00	1.45	3.19
3/B75GL	3	B	1905	75.00	1.47	3.23
3/B77GL	3	B	1956	77.00	1.50	3.32
3/B78GL	3	B	1981	78.00	1.52	3.36
3/B79GL	3	B	2007	79.00	1.54	3.40
3/B80GL	3	B	2032	80.00	1.56	3.45
3/B81GL	3	B	2057	81.00	1.58	3.49
3/B82GL	3	B	2083	82.00	1.60	3.53
3/B83GL	3	B	2108	83.00	1.62	3.58
3/B84GL	3	B	2134	84.00	1.64	3.62
3/B85GL	3	B	2159	85.00	1.66	3.66
3/B86GL	3	B	2184	86.00	1.68	3.71
3/B87GL	3	B	2210	87.00	1.70	3.75

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B88GL	3	B	2235	88.00	1.72	3.79
3/B90GL	3	B	2286	90.00	1.76	3.88
3/B91GL	3	B	2311	91.00	1.78	3.92
3/B92GL	3	B	2337	92.00	1.80	3.96
3/B93GL	3	B	2362	93.00	1.82	4.01
3/B94.5GL	3	B	2400	94.50	1.85	4.07
3/B95GL	3	B	2413	95.00	1.86	4.09
3/B96GL	3	B	2438	96.00	1.88	4.14
3/B97GL	3	B	2464	97.00	1.90	4.18
3/B98GL	3	B	2489	98.00	1.92	4.22
3/B99GL	3	B	2515	99.00	1.93	4.27
3/B100GL	3	B	2540	100.00	1.95	4.31
3/B102GL	3	B	2591	102.00	1.99	4.39
3/B103GL	3	B	2616	103.00	2.01	4.44
3/B104GL	3	B	2642	104.00	2.03	4.48
3/B105GL	3	B	2667	105.00	2.05	4.52
3/B106GL	3	B	2692	106.00	2.07	4.57
3/B108GL	3	B	2743	108.00	2.11	4.65
3/B109GL	3	B	2769	109.00	2.13	4.70
3/B110GL	3	B	2794	110.00	2.15	4.74
3/B112GL	3	B	2845	112.00	2.19	4.83
3/B113GL	3	B	2870	113.00	2.21	4.87
3/B114GL	3	B	2896	114.00	2.23	4.91
3/B115GL	3	B	2921	115.00	2.25	4.95
3/B116GL	3	B	2946	116.00	2.27	5.00
3/B118GL	3	B	2997	118.00	2.31	5.08
3/B120GL	3	B	3048	120.00	2.35	5.17
3/B124GL	3	B	3150	124.00	2.42	5.34
3/B128GL	3	B	3251	128.00	2.50	5.51
3/B130GL	3	B	3302	130.00	2.54	5.60
3/B132GL	3	B	3353	132.00	2.58	5.69
3/B133GL	3	B	3378	133.00	2.60	5.73

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B136GL	3	B	3454	136.00	2.66	5.86
3/B138GL	3	B	3505	138.00	2.70	5.95
3/B139GL	3	B	3531	139.00	2.72	5.99
3/B140GL	3	B	3556	140.00	2.74	6.03
3/B141GL	3	B	3581	141.00	2.76	6.07
3/B144GL	3	B	3658	144.00	2.81	6.20
3/B146GL	3	B	3708	146.00	2.85	6.29
3/B148GL	3	B	3759	148.00	2.89	6.38
3/B150GL	3	B	3810	150.00	2.93	6.46
3/B154GL	3	B	3912	154.00	3.01	6.64
3/B158GL	3	B	4013	158.00	3.09	6.81
3/B160GL	3	B	4064	160.00	3.13	6.89
3/B162GL	3	B	4115	162.00	3.17	6.98
3/B167GL	3	B	4242	167.00	3.26	7.20
3/B168GL	3	B	4267	168.00	3.28	7.24
3/B173GL	3	B	4394	173.00	3.38	7.45
3/B177GL	3	B	4496	177.00	3.46	7.63
3/B180GL	3	B	4572	180.00	3.52	7.76
3/B185GL	3	B	4699	185.00	3.62	7.97
3/B187GL	3	B	4750	187.00	3.65	8.06
3/B190GL	3	B	4826	190.00	3.71	8.19
3/B195GL	3	B	4953	195.00	3.81	8.40
3/B197GL	3	B	5004	197.00	3.85	8.49
3/B208GL	3	B	5283	208.00	4.06	8.96
3/B210GL	3	B	5334	210.00	4.10	9.05
3/B218GL	3	B	5537	218.00	4.26	9.39
3/B220GL	3	B	5588	220.00	4.30	9.48
3/B225GL	3	B	5715	225.00	4.40	9.69
3/B240GL	3	B	6096	240.00	4.69	10.34
3/B255GL	3	B	6477	255.00	4.98	10.99
3/B270GL	3	B	6858	270.00	5.28	11.63
3/B300GL	3	B	7620	300.00	5.86	12.93

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/B315GL	3	B	8001	315.00	6.16	13.57
4/B56GL	4	B	1422	56.00	1.46	3.22
4/B57GL	4	B	1448	57.00	1.49	3.27
4/B58GL	4	B	1473	58.00	1.51	3.33
4/B59GL	4	B	1499	59.00	1.54	3.39
4/B60GL	4	B	1524	60.00	1.56	3.45
4/B61GL	4	B	1549	61.00	1.59	3.50
4/B62GL	4	B	1575	62.00	1.62	3.56
4/B63GL	4	B	1600	63.00	1.64	3.62
4/B64GL	4	B	1626	64.00	1.67	3.68
4/B65GL	4	B	1651	65.00	1.69	3.73
4/B66GL	4	B	1676	66.00	1.72	3.79
4/B67GL	4	B	1702	67.00	1.75	3.85
4/B68GL	4	B	1727	68.00	1.77	3.91
4/B70GL	4	B	1778	70.00	1.82	4.02
4/B71GL	4	B	1803	71.00	1.85	4.08
4/B72GL	4	B	1829	72.00	1.88	4.14
4/B73GL	4	B	1854	73.00	1.90	4.19
4/B74GL	4	B	1880	74.00	1.93	4.25
4/B75GL	4	B	1905	75.00	1.95	4.31
4/B77GL	4	B	1956	77.00	2.01	4.42
4/B78GL	4	B	1981	78.00	2.03	4.48
4/B79GL	4	B	2007	79.00	2.06	4.54
4/B80GL	4	B	2032	80.00	2.08	4.60
4/B81GL	4	B	2057	81.00	2.11	4.65
4/B82GL	4	B	2083	82.00	2.14	4.71
4/B83GL	4	B	2108	83.00	2.16	4.77
4/B84GL	4	B	2134	84.00	2.19	4.83
4/B85GL	4	B	2159	85.00	2.21	4.88
4/B86GL	4	B	2184	86.00	2.24	4.94
4/B87GL	4	B	2210	87.00	2.27	5.00
4/B88GL	4	B	2235	88.00	2.29	5.06

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/B90GL	4	B	2286	90.00	2.35	5.17
4/B91GL	4	B	2311	91.00	2.37	5.23
4/B92GL	4	B	2337	92.00	2.40	5.29
4/B93GL	4	B	2362	93.00	2.42	5.34
4/B94.5GL	4	B	2400	94.50	2.46	5.43
4/B95GL	4	B	2413	95.00	2.48	5.46
4/B96GL	4	B	2438	96.00	2.50	5.51
4/B97GL	4	B	2464	97.00	2.53	5.57
4/B98GL	4	B	2489	98.00	2.55	5.63
4/B99GL	4	B	2515	99.00	2.58	5.69
4/B100GL	4	B	2540	100.00	2.61	5.74
4/B102GL	4	B	2591	102.00	2.66	5.86
4/B103GL	4	B	2616	103.00	2.68	5.92
4/B104GL	4	B	2642	104.00	2.71	5.97
4/B105GL	4	B	2667	105.00	2.74	6.03
4/B106GL	4	B	2692	106.00	2.76	6.09
4/B108GL	4	B	2743	108.00	2.81	6.20
4/B109GL	4	B	2769	109.00	2.84	6.26
4/B110GL	4	B	2794	110.00	2.87	6.32
4/B112GL	4	B	2845	112.00	2.92	6.43
4/B113GL	4	B	2870	113.00	2.94	6.49
4/B114GL	4	B	2896	114.00	2.97	6.55
4/B115GL	4	B	2921	115.00	3.00	6.61
4/B116GL	4	B	2946	116.00	3.02	6.66
4/B118GL	4	B	2997	118.00	3.07	6.78
4/B120GL	4	B	3048	120.00	3.13	6.89
4/B124GL	4	B	3150	124.00	3.23	7.12
4/B128GL	4	B	3251	128.00	3.34	7.35
4/B130GL	4	B	3302	130.00	3.39	7.47
4/B132GL	4	B	3353	132.00	3.44	7.58
4/B133GL	4	B	3378	133.00	3.47	7.64
4/B136GL	4	B	3454	136.00	3.54	7.81

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/B138GL	4	B	3505	138.00	3.60	7.93
4/B139GL	4	B	3531	139.00	3.62	7.99
4/B140GL	4	B	3556	140.00	3.65	8.04
4/B141GL	4	B	3581	141.00	3.67	8.10
4/B144GL	4	B	3658	144.00	3.75	8.27
4/B146GL	4	B	3708	146.00	3.80	8.39
4/B148GL	4	B	3759	148.00	3.86	8.50
4/B150GL	4	B	3810	150.00	3.91	8.62
4/B154GL	4	B	3912	154.00	4.01	8.85
4/B158GL	4	B	4013	158.00	4.12	9.08
4/B160GL	4	B	4064	160.00	4.17	9.19
4/B162GL	4	B	4115	162.00	4.22	9.31
4/B167GL	4	B	4242	167.00	4.35	9.59
4/B168GL	4	B	4267	168.00	4.38	9.65
4/B173GL	4	B	4394	173.00	4.51	9.94
4/B177GL	4	B	4496	177.00	4.61	10.17
4/B180GL	4	B	4572	180.00	4.69	10.34
4/B185GL	4	B	4699	185.00	4.82	10.63
4/B187GL	4	B	4750	187.00	4.87	10.74
4/B190GL	4	B	4826	190.00	4.95	10.91
4/B195GL	4	B	4953	195.00	5.08	11.20
4/B197GL	4	B	5004	197.00	5.13	11.32
4/B208GL	4	B	5283	208.00	5.42	11.95
4/B210GL	4	B	5334	210.00	5.47	12.06
4/B218GL	4	B	5537	218.00	5.68	12.52
4/B220GL	4	B	5588	220.00	5.73	12.64
4/B225GL	4	B	5715	225.00	5.86	12.93
4/B240GL	4	B	6096	240.00	6.25	13.79
4/B255GL	4	B	6477	255.00	6.64	14.65
4/B270GL	4	B	6858	270.00	7.04	15.51
4/B300GL	4	B	7620	300.00	7.82	17.23
4/B315GL	4	B	8001	315.00	8.21	18.10

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B56GL	5	B	1422	56.00	1.82	4.02
5/B57GL	5	B	1448	57.00	1.86	4.09
5/B58GL	5	B	1473	58.00	1.89	4.16
5/B59GL	5	B	1499	59.00	1.92	4.24
5/B60GL	5	B	1524	60.00	1.95	4.31
5/B61GL	5	B	1549	61.00	1.99	4.38
5/B62GL	5	B	1575	62.00	2.02	4.45
5/B63GL	5	B	1600	63.00	2.05	4.52
5/B64GL	5	B	1626	64.00	2.08	4.60
5/B65GL	5	B	1651	65.00	2.12	4.67
5/B66GL	5	B	1676	66.00	2.15	4.74
5/B67GL	5	B	1702	67.00	2.18	4.81
5/B68GL	5	B	1727	68.00	2.21	4.88
5/B70GL	5	B	1778	70.00	2.28	5.03
5/B71GL	5	B	1803	71.00	2.31	5.10
5/B72GL	5	B	1829	72.00	2.35	5.17
5/B73GL	5	B	1854	73.00	2.38	5.24
5/B74GL	5	B	1880	74.00	2.41	5.31
5/B75GL	5	B	1905	75.00	2.44	5.39
5/B77GL	5	B	1956	77.00	2.51	5.53
5/B78GL	5	B	1981	78.00	2.54	5.60
5/B79GL	5	B	2007	79.00	2.57	5.67
5/B80GL	5	B	2032	80.00	2.61	5.74
5/B81GL	5	B	2057	81.00	2.64	5.82
5/B82GL	5	B	2083	82.00	2.67	5.89
5/B83GL	5	B	2108	83.00	2.70	5.96
5/B84GL	5	B	2134	84.00	2.74	6.03
5/B85GL	5	B	2159	85.00	2.77	6.10
5/B86GL	5	B	2184	86.00	2.80	6.18
5/B87GL	5	B	2210	87.00	2.83	6.25
5/B88GL	5	B	2235	88.00	2.87	6.32
5/B90GL	5	B	2286	90.00	2.93	6.46

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B91GL	5	B	2311	91.00	2.96	6.53
5/B92GL	5	B	2337	92.00	3.00	6.61
5/B93GL	5	B	2362	93.00	3.03	6.68
5/B94.5GL	5	B	2400	94.50	3.08	6.79
5/B95GL	5	B	2413	95.00	3.09	6.82
5/B96GL	5	B	2438	96.00	3.13	6.89
5/B97GL	5	B	2464	97.00	3.16	6.97
5/B98GL	5	B	2489	98.00	3.19	7.04
5/B99GL	5	B	2515	99.00	3.22	7.11
5/B100GL	5	B	2540	100.00	3.26	7.18
5/B102GL	5	B	2591	102.00	3.32	7.32
5/B103GL	5	B	2616	103.00	3.35	7.40
5/B104GL	5	B	2642	104.00	3.39	7.47
5/B105GL	5	B	2667	105.00	3.42	7.54
5/B106GL	5	B	2692	106.00	3.45	7.61
5/B108GL	5	B	2743	108.00	3.52	7.76
5/B109GL	5	B	2769	109.00	3.55	7.83
5/B110GL	5	B	2794	110.00	3.58	7.90
5/B112GL	5	B	2845	112.00	3.65	8.04
5/B113GL	5	B	2870	113.00	3.68	8.11
5/B114GL	5	B	2896	114.00	3.71	8.19
5/B115GL	5	B	2921	115.00	3.75	8.26
5/B116GL	5	B	2946	116.00	3.78	8.33
5/B118GL	5	B	2997	118.00	3.84	8.47
5/B120GL	5	B	3048	120.00	3.91	8.62
5/B124GL	5	B	3150	124.00	4.04	8.90
5/B128GL	5	B	3251	128.00	4.17	9.19
5/B130GL	5	B	3302	130.00	4.23	9.34
5/B132GL	5	B	3353	132.00	4.30	9.48
5/B133GL	5	B	3378	133.00	4.33	9.55
5/B136GL	5	B	3454	136.00	4.43	9.77
5/B138GL	5	B	3505	138.00	4.49	9.91

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/B139GL	5	B	3531	139.00	4.53	9.98
5/B140GL	5	B	3556	140.00	4.56	10.05
5/B141GL	5	B	3581	141.00	4.59	10.12
5/B144GL	5	B	3658	144.00	4.69	10.34
5/B146GL	5	B	3708	146.00	4.76	10.48
5/B148GL	5	B	3759	148.00	4.82	10.63
5/B150GL	5	B	3810	150.00	4.89	10.77
5/B154GL	5	B	3912	154.00	5.02	11.06
5/B158GL	5	B	4013	158.00	5.15	11.35
5/B160GL	5	B	4064	160.00	5.21	11.49
5/B162GL	5	B	4115	162.00	5.28	11.63
5/B167GL	5	B	4242	167.00	5.44	11.99
5/B168GL	5	B	4267	168.00	5.47	12.06
5/B173GL	5	B	4394	173.00	5.63	12.42
5/B177GL	5	B	4496	177.00	5.77	12.71
5/B180GL	5	B	4572	180.00	5.86	12.93
5/B185GL	5	B	4699	185.00	6.03	13.28
5/B187GL	5	B	4750	187.00	6.09	13.43
5/B190GL	5	B	4826	190.00	6.19	13.64
5/B195GL	5	B	4953	195.00	6.35	14.00
5/B197GL	5	B	5004	197.00	6.42	14.15
5/B208GL	5	B	5283	208.00	6.77	14.94
5/B210GL	5	B	5334	210.00	6.84	15.08
5/B218GL	5	B	5537	218.00	7.10	15.65
5/B220GL	5	B	5588	220.00	7.17	15.80
5/B225GL	5	B	5715	225.00	7.33	16.16
5/B240GL	5	B	6096	240.00	7.82	17.23
5/B255GL	5	B	6477	255.00	8.31	18.31
5/B270GL	5	B	6858	270.00	8.79	19.39
5/B300GL	5	B	7620	300.00	9.77	21.54
5/B315GL	5	B	8001	315.00	10.26	22.62
16/B56GL	16	B	1422	56.00	5.84	12.87

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
16/B57GL	16	B	1448	57.00	5.94	13.10
16/B58GL	16	B	1473	58.00	6.05	13.33
16/B59GL	16	B	1499	59.00	6.15	13.56
16/B60GL	16	B	1524	60.00	6.25	13.79
16/B61GL	16	B	1549	61.00	6.36	14.02
16/B62GL	16	B	1575	62.00	6.46	14.25
16/B63GL	16	B	1600	63.00	6.57	14.48
16/B64GL	16	B	1626	64.00	6.67	14.71
16/B65GL	16	B	1651	65.00	6.77	14.94
16/B66GL	16	B	1676	66.00	6.88	15.17
16/B67GL	16	B	1702	67.00	6.98	15.40
16/B68GL	16	B	1727	68.00	7.09	15.63
16/B70GL	16	B	1778	70.00	7.30	16.08
16/B71GL	16	B	1803	71.00	7.40	16.31
16/B72GL	16	B	1829	72.00	7.50	16.54
16/B73GL	16	B	1854	73.00	7.61	16.77
16/B74GL	16	B	1880	74.00	7.71	17.00
16/B75GL	16	B	1905	75.00	7.82	17.23
16/B77GL	16	B	1956	77.00	8.03	17.69
16/B78GL	16	B	1981	78.00	8.13	17.92
16/B79GL	16	B	2007	79.00	8.23	18.15
16/B80GL	16	B	2032	80.00	8.34	18.38
16/B81GL	16	B	2057	81.00	8.44	18.61
16/B82GL	16	B	2083	82.00	8.55	18.84
16/B83GL	16	B	2108	83.00	8.65	19.07
16/B84GL	16	B	2134	84.00	8.76	19.30
16/B85GL	16	B	2159	85.00	8.86	19.53
24/B86GL	24	B	2184	86.00	13.45	29.64
24/B87GL	24	B	2210	87.00	13.60	29.99
24/B88GL	24	B	2235	88.00	13.76	30.33
24/B90GL	24	B	2286	90.00	14.07	31.02
24/B91GL	24	B	2311	91.00	14.23	31.37

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
24/B92GL	24	B	2337	92.00	14.38	31.71
24/B93GL	24	B	2362	93.00	14.54	32.05
24/B94.5GL	24	B	2400	94.50	14.77	32.57
24/B95GL	24	B	2413	95.00	14.85	32.74
24/B96GL	24	B	2438	96.00	15.01	33.09
24/B97GL	24	B	2464	97.00	15.17	33.43
24/B98GL	24	B	2489	98.00	15.32	33.78
24/B99GL	24	B	2515	99.00	15.48	34.12
24/B100GL	24	B	2540	100.00	15.63	34.47
24/B102GL	24	B	2591	102.00	15.95	35.16
24/B103GL	24	B	2616	103.00	16.10	35.50
24/B104GL	24	B	2642	104.00	16.26	35.85
24/B105GL	24	B	2667	105.00	16.42	36.19
24/B106GL	24	B	2692	106.00	16.57	36.54
24/B108GL	24	B	2743	108.00	16.89	37.23
24/B109GL	24	B	2769	109.00	17.04	37.57
24/B110GL	24	B	2794	110.00	17.20	37.91
24/B112GL	24	B	2845	112.00	17.51	38.60
24/B113GL	24	B	2870	113.00	17.67	38.95
24/B114GL	24	B	2896	114.00	17.82	39.29
24/B115GL	24	B	2921	115.00	17.98	39.64
24/B116GL	24	B	2946	116.00	18.14	39.98
24/B118GL	24	B	2997	118.00	18.45	40.67
24/B120GL	24	B	3048	120.00	18.76	41.36
24/B124GL	24	B	3150	124.00	19.39	42.74
24/B128GL	24	B	3251	128.00	20.01	44.12
24/B130GL	24	B	3302	130.00	20.32	44.81
24/B132GL	24	B	3353	132.00	20.64	45.50
24/B133GL	24	B	3378	133.00	20.79	45.84
24/B136GL	24	B	3454	136.00	21.26	46.88
24/B138GL	24	B	3505	138.00	21.58	47.57
24/B139GL	24	B	3531	139.00	21.73	47.91

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
24/B140GL	24	B	3556	140.00	21.89	48.25
24/B141GL	24	B	3581	141.00	22.04	48.60
24/B144GL	24	B	3658	144.00	22.51	49.63
24/B146GL	24	B	3708	146.00	22.83	50.32
24/B148GL	24	B	3759	148.00	23.14	51.01
24/B150GL	24	B	3810	150.00	23.45	51.70
24/B154GL	24	B	3912	154.00	24.08	53.08
24/B158GL	24	B	4013	158.00	24.70	54.46
24/B160GL	24	B	4064	160.00	25.01	55.15
24/B162GL	24	B	4115	162.00	25.33	55.84
24/B167GL	24	B	4242	167.00	26.11	57.56
24/B168GL	24	B	4267	168.00	26.27	57.91
24/B173GL	24	B	4394	173.00	27.05	59.63
24/B177GL	24	B	4496	177.00	27.67	61.01
24/B180GL	24	B	4572	180.00	28.14	62.04
24/B185GL	24	B	4699	185.00	28.92	63.77
24/B187GL	24	B	4750	187.00	29.24	64.45
24/B190GL	24	B	4826	190.00	29.71	65.49
24/B195GL	24	B	4953	195.00	30.49	67.21
24/B197GL	24	B	5004	197.00	30.80	67.90
24/B208GL	24	B	5283	208.00	32.52	71.69
24/B210GL	24	B	5334	210.00	32.83	72.38
24/B218GL	24	B	5537	218.00	34.08	75.14
24/B220GL	24	B	5588	220.00	34.40	75.83
24/B225GL	24	B	5715	225.00	35.18	77.55
24/B240GL	24	B	6096	240.00	37.52	82.72
24/B255GL	24	B	6477	255.00	39.87	87.89
24/B270GL	24	B	6858	270.00	42.21	93.06
24/B300GL	24	B	7620	300.00	46.90	103.40
24/B315GL	24	B	8001	315.00	49.25	108.57
2/C60GL	2	C	1524	60.00	1.37	3.03
2/C68GL	2	C	1727	68.00	1.56	3.43

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/C72GL	2	C	1829	72.00	1.65	3.64
2/C75GL	2	C	1905	75.00	1.72	3.79
2/C78GL	2	C	1981	78.00	1.79	3.94
2/C80GL	2	C	2032	80.00	1.83	4.04
2/C81GL	2	C	2057	81.00	1.86	4.09
2/C85GL	2	C	2159	85.00	1.95	4.29
2/C87GL	2	C	2210	87.00	1.99	4.39
2/C90GL	2	C	2286	90.00	2.06	4.54
2/C96GL	2	C	2438	96.00	2.20	4.85
2/C98GL	2	C	2489	98.00	2.24	4.95
2/C99GL	2	C	2515	99.00	2.27	5.00
2/C100GL	2	C	2540	100.00	2.29	5.05
2/C105GL	2	C	2667	105.00	2.40	5.30
2/C108GL	2	C	2743	108.00	2.47	5.45
2/C109GL	2	C	2769	109.00	2.50	5.50
2/C112GL	2	C	2845	112.00	2.57	5.65
2/C120GL	2	C	3048	120.00	2.75	6.06
2/C124GL	2	C	3150	124.00	2.84	6.26
2/C126GL	2	C	3200	126.00	2.89	6.36
2/C128GL	2	C	3251	128.00	2.93	6.46
2/C136GL	2	C	3454	136.00	3.11	6.87
2/C140GL	2	C	3556	140.00	3.21	7.07
2/C144GL	2	C	3658	144.00	3.30	7.27
2/C146GL	2	C	3708	146.00	3.34	7.37
2/C151GL	2	C	3835	151.00	3.46	7.62
2/C158GL	2	C	4013	158.00	3.62	7.98
2/C162GL	2	C	4115	162.00	3.71	8.18
2/C167GL	2	C	4242	167.00	3.82	8.43
2/C173GL	2	C	4394	173.00	3.96	8.73
2/C177GL	2	C	4496	177.00	4.05	8.94
2/C180GL	2	C	4572	180.00	4.12	9.09
2/C185GL	2	C	4699	185.00	4.24	9.34

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/C187GL	2	C	4750	187.00	4.28	9.44
2/C190GL	2	C	4826	190.00	4.35	9.59
2/C195GL	2	C	4953	195.00	4.47	9.85
2/C197GL	2	C	5004	197.00	4.51	9.95
2/C204GL	2	C	5182	204.00	4.67	10.30
2/C208GL	2	C	5283	208.00	4.76	10.50
2/C210GL	2	C	5334	210.00	4.81	10.60
2/C220GL	2	C	5588	220.00	5.04	11.11
2/C225GL	2	C	5715	225.00	5.15	11.36
2/C236GL	2	C	5994	236.00	5.40	11.92
2/C240GL	2	C	6096	240.00	5.50	12.12
2/C248GL	2	C	6299	248.00	5.68	12.52
2/C255GL	2	C	6477	255.00	5.84	12.87
2/C270GL	2	C	6858	270.00	6.18	13.63
2/C285GL	2	C	7239	285.00	6.53	14.39
2/C300GL	2	C	7620	300.00	6.87	15.15
2/C315GL	2	C	8001	315.00	7.21	15.90
2/C330GL	2	C	8382	330.00	7.56	16.66
2/C345GL	2	C	8763	345.00	7.90	17.42
2/C360GL	2	C	9144	360.00	8.24	18.18
2/C390GL	2	C	9906	390.00	8.93	19.69
2/C420GL	2	C	10668	420.00	9.62	21.21
3/C60GL	3	C	1524	60.00	2.06	4.54
3/C68GL	3	C	1727	68.00	2.34	5.15
3/C72GL	3	C	1829	72.00	2.47	5.45
3/C75GL	3	C	1905	75.00	2.58	5.68
3/C78GL	3	C	1981	78.00	2.68	5.91
3/C80GL	3	C	2032	80.00	2.75	6.06
3/C81GL	3	C	2057	81.00	2.78	6.13
3/C85GL	3	C	2159	85.00	2.92	6.44
3/C87GL	3	C	2210	87.00	2.99	6.59
3/C90GL	3	C	2286	90.00	3.09	6.82

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/C96GL	3	C	2438	96.00	3.30	7.27
3/C98GL	3	C	2489	98.00	3.37	7.42
3/C99GL	3	C	2515	99.00	3.40	7.50
3/C100GL	3	C	2540	100.00	3.44	7.57
3/C105GL	3	C	2667	105.00	3.61	7.95
3/C108GL	3	C	2743	108.00	3.71	8.18
3/C109GL	3	C	2769	109.00	3.74	8.26
3/C112GL	3	C	2845	112.00	3.85	8.48
3/C120GL	3	C	3048	120.00	4.12	9.09
3/C124GL	3	C	3150	124.00	4.26	9.39
3/C126GL	3	C	3200	126.00	4.33	9.54
3/C128GL	3	C	3251	128.00	4.40	9.69
3/C136GL	3	C	3454	136.00	4.67	10.30
3/C140GL	3	C	3556	140.00	4.81	10.60
3/C144GL	3	C	3658	144.00	4.95	10.91
3/C146GL	3	C	3708	146.00	5.02	11.06
3/C151GL	3	C	3835	151.00	5.19	11.44
3/C158GL	3	C	4013	158.00	5.43	11.97
3/C162GL	3	C	4115	162.00	5.57	12.27
3/C167GL	3	C	4242	167.00	5.74	12.65
3/C173GL	3	C	4394	173.00	5.94	13.10
3/C177GL	3	C	4496	177.00	6.08	13.41
3/C180GL	3	C	4572	180.00	6.18	13.63
3/C185GL	3	C	4699	185.00	6.36	14.01
3/C187GL	3	C	4750	187.00	6.42	14.16
3/C190GL	3	C	4826	190.00	6.53	14.39
3/C195GL	3	C	4953	195.00	6.70	14.77
3/C197GL	3	C	5004	197.00	6.77	14.92
3/C204GL	3	C	5182	204.00	7.01	15.45
3/C208GL	3	C	5283	208.00	7.15	15.75
3/C210GL	3	C	5334	210.00	7.21	15.90
3/C220GL	3	C	5588	220.00	7.56	16.66

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/C225GL	3	C	5715	225.00	7.73	17.04
3/C236GL	3	C	5994	236.00	8.11	17.87
3/C240GL	3	C	6096	240.00	8.24	18.18
3/C248GL	3	C	6299	248.00	8.52	18.78
3/C255GL	3	C	6477	255.00	8.76	19.31
3/C270GL	3	C	6858	270.00	9.28	20.45
3/C285GL	3	C	7239	285.00	9.79	21.58
3/C300GL	3	C	7620	300.00	10.31	22.72
3/C315GL	3	C	8001	315.00	10.82	23.86
3/C330GL	3	C	8382	330.00	11.34	24.99
3/C345GL	3	C	8763	345.00	11.85	26.13
3/C360GL	3	C	9144	360.00	12.37	27.26
3/C390GL	3	C	9906	390.00	13.40	29.54
3/C420GL	3	C	10668	420.00	14.43	31.81
4/C60GL	4	C	1524	60.00	2.75	6.06
4/C68GL	4	C	1727	68.00	3.11	6.87
4/C72GL	4	C	1829	72.00	3.30	7.27
4/C75GL	4	C	1905	75.00	3.44	7.57
4/C78GL	4	C	1981	78.00	3.57	7.88
4/C80GL	4	C	2032	80.00	3.66	8.08
4/C81GL	4	C	2057	81.00	3.71	8.18
4/C85GL	4	C	2159	85.00	3.89	8.58
4/C87GL	4	C	2210	87.00	3.98	8.79
4/C90GL	4	C	2286	90.00	4.12	9.09
4/C96GL	4	C	2438	96.00	4.40	9.69
4/C98GL	4	C	2489	98.00	4.49	9.90
4/C99GL	4	C	2515	99.00	4.53	10.00
4/C100GL	4	C	2540	100.00	4.58	10.10
4/C105GL	4	C	2667	105.00	4.81	10.60
4/C108GL	4	C	2743	108.00	4.95	10.91
4/C109GL	4	C	2769	109.00	4.99	11.01
4/C112GL	4	C	2845	112.00	5.13	11.31

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/C120GL	4	C	3048	120.00	5.50	12.12
4/C124GL	4	C	3150	124.00	5.68	12.52
4/C126GL	4	C	3200	126.00	5.77	12.72
4/C128GL	4	C	3251	128.00	5.86	12.93
4/C136GL	4	C	3454	136.00	6.23	13.73
4/C140GL	4	C	3556	140.00	6.41	14.14
4/C144GL	4	C	3658	144.00	6.60	14.54
4/C146GL	4	C	3708	146.00	6.69	14.74
4/C151GL	4	C	3835	151.00	6.92	15.25
4/C158GL	4	C	4013	158.00	7.24	15.95
4/C162GL	4	C	4115	162.00	7.42	16.36
4/C167GL	4	C	4242	167.00	7.65	16.86
4/C173GL	4	C	4394	173.00	7.92	17.47
4/C177GL	4	C	4496	177.00	8.11	17.87
4/C180GL	4	C	4572	180.00	8.24	18.18
4/C185GL	4	C	4699	185.00	8.47	18.68
4/C187GL	4	C	4750	187.00	8.57	18.88
4/C190GL	4	C	4826	190.00	8.70	19.19
4/C195GL	4	C	4953	195.00	8.93	19.69
4/C197GL	4	C	5004	197.00	9.02	19.89
4/C204GL	4	C	5182	204.00	9.34	20.60
4/C208GL	4	C	5283	208.00	9.53	21.00
4/C210GL	4	C	5334	210.00	9.62	21.21
4/C220GL	4	C	5588	220.00	10.08	22.22
4/C225GL	4	C	5715	225.00	10.31	22.72
4/C236GL	4	C	5994	236.00	10.81	23.83
4/C240GL	4	C	6096	240.00	10.99	24.24
4/C248GL	4	C	6299	248.00	11.36	25.04
4/C255GL	4	C	6477	255.00	11.68	25.75
4/C270GL	4	C	6858	270.00	12.37	27.26
4/C285GL	4	C	7239	285.00	13.05	28.78
4/C300GL	4	C	7620	300.00	13.74	30.29

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/C315GL	4	C	8001	315.00	14.43	31.81
4/C330GL	4	C	8382	330.00	15.12	33.32
4/C345GL	4	C	8763	345.00	15.80	34.84
4/C360GL	4	C	9144	360.00	16.49	36.35
4/C390GL	4	C	9906	390.00	17.86	39.38
4/C420GL	4	C	10668	420.00	19.24	42.41
5/C60GL	5	C	1524	60.00	3.44	7.57
5/C68GL	5	C	1727	68.00	3.89	8.58
5/C72GL	5	C	1829	72.00	4.12	9.09
5/C75GL	5	C	1905	75.00	4.29	9.47
5/C78GL	5	C	1981	78.00	4.47	9.85
5/C80GL	5	C	2032	80.00	4.58	10.10
5/C81GL	5	C	2057	81.00	4.64	10.22
5/C85GL	5	C	2159	85.00	4.87	10.73
5/C87GL	5	C	2210	87.00	4.98	10.98
5/C90GL	5	C	2286	90.00	5.15	11.36
5/C96GL	5	C	2438	96.00	5.50	12.12
5/C98GL	5	C	2489	98.00	5.61	12.37
5/C99GL	5	C	2515	99.00	5.67	12.50
5/C100GL	5	C	2540	100.00	5.73	12.62
5/C105GL	5	C	2667	105.00	6.01	13.25
5/C108GL	5	C	2743	108.00	6.18	13.63
5/C109GL	5	C	2769	109.00	6.24	13.76
5/C112GL	5	C	2845	112.00	6.41	14.14
5/C120GL	5	C	3048	120.00	6.87	15.15
5/C124GL	5	C	3150	124.00	7.10	15.65
5/C126GL	5	C	3200	126.00	7.21	15.90
5/C128GL	5	C	3251	128.00	7.33	16.16
5/C136GL	5	C	3454	136.00	7.79	17.17
5/C140GL	5	C	3556	140.00	8.02	17.67
5/C144GL	5	C	3658	144.00	8.24	18.18
5/C146GL	5	C	3708	146.00	8.36	18.43

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/C151GL	5	C	3835	151.00	8.65	19.06
5/C158GL	5	C	4013	158.00	9.05	19.94
5/C162GL	5	C	4115	162.00	9.28	20.45
5/C167GL	5	C	4242	167.00	9.56	21.08
5/C173GL	5	C	4394	173.00	9.91	21.84
5/C177GL	5	C	4496	177.00	10.13	22.34
5/C180GL	5	C	4572	180.00	10.31	22.72
5/C185GL	5	C	4699	185.00	10.59	23.35
5/C187GL	5	C	4750	187.00	10.71	23.60
5/C190GL	5	C	4826	190.00	10.88	23.98
5/C195GL	5	C	4953	195.00	11.16	24.61
5/C197GL	5	C	5004	197.00	11.28	24.87
5/C204GL	5	C	5182	204.00	11.68	25.75
5/C208GL	5	C	5283	208.00	11.91	26.25
5/C210GL	5	C	5334	210.00	12.02	26.51
5/C220GL	5	C	5588	220.00	12.60	27.77
5/C225GL	5	C	5715	225.00	12.88	28.40
5/C236GL	5	C	5994	236.00	13.51	29.79
5/C240GL	5	C	6096	240.00	13.74	30.29
5/C248GL	5	C	6299	248.00	14.20	31.30
5/C255GL	5	C	6477	255.00	14.60	32.19
5/C270GL	5	C	6858	270.00	15.46	34.08
5/C285GL	5	C	7239	285.00	16.32	35.97
5/C300GL	5	C	7620	300.00	17.18	37.87
5/C315GL	5	C	8001	315.00	18.04	39.76
5/C330GL	5	C	8382	330.00	18.89	41.65
5/C345GL	5	C	8763	345.00	19.75	43.55
5/C360GL	5	C	9144	360.00	20.61	45.44
5/C390GL	5	C	9906	390.00	22.33	49.23
5/C420GL	5	C	10668	420.00	24.05	53.01
12/C60GL	12	C	1524	60.00	8.24	18.18
12/C68GL	12	C	1727	68.00	9.34	20.60

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
12/C72GL	12	C	1829	72.00	9.89	21.81
12/C75GL	12	C	1905	75.00	10.31	22.72
12/C78GL	12	C	1981	78.00	10.72	23.63
12/C80GL	12	C	2032	80.00	10.99	24.24
12/C81GL	12	C	2057	81.00	11.13	24.54
12/C85GL	12	C	2159	85.00	11.68	25.75
18/C87GL	18	C	2210	87.00	17.93	39.53
18/C90GL	18	C	2286	90.00	18.55	40.90
18/C96GL	18	C	2438	96.00	19.79	43.62
18/C98GL	18	C	2489	98.00	20.20	44.53
18/C99GL	18	C	2515	99.00	20.41	44.99
18/C100GL	18	C	2540	100.00	20.61	45.44
18/C105GL	18	C	2667	105.00	21.64	47.71
18/C108GL	18	C	2743	108.00	22.26	49.08
18/C109GL	18	C	2769	109.00	22.47	49.53
18/C112GL	18	C	2845	112.00	23.09	50.89
18/C120GL	18	C	3048	120.00	24.73	54.53
18/C124GL	18	C	3150	124.00	25.56	56.35
18/C126GL	18	C	3200	126.00	25.97	57.26
18/C128GL	18	C	3251	128.00	26.38	58.16
18/C136GL	18	C	3454	136.00	28.03	61.80
18/C140GL	18	C	3556	140.00	28.86	63.62
18/C144GL	18	C	3658	144.00	29.68	65.43
18/C146GL	18	C	3708	146.00	30.09	66.34
18/C151GL	18	C	3835	151.00	31.12	68.62
18/C158GL	18	C	4013	158.00	32.57	71.80
18/C162GL	18	C	4115	162.00	33.39	73.61
18/C167GL	18	C	4242	167.00	34.42	75.89
18/C173GL	18	C	4394	173.00	35.66	78.61
18/C177GL	18	C	4496	177.00	36.48	80.43
18/C180GL	18	C	4572	180.00	37.10	81.79
18/C185GL	18	C	4699	185.00	38.13	84.07

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
18/C187GL	18	C	4750	187.00	38.54	84.97
18/C190GL	18	C	4826	190.00	39.16	86.34
18/C195GL	18	C	4953	195.00	40.19	88.61
18/C197GL	18	C	5004	197.00	40.60	89.52
18/C204GL	18	C	5182	204.00	42.05	92.70
18/C208GL	18	C	5283	208.00	42.87	94.52
18/C210GL	18	C	5334	210.00	43.28	95.43
18/C220GL	18	C	5588	220.00	45.35	99.97
18/C225GL	18	C	5715	225.00	46.38	102.24
18/C236GL	18	C	5994	236.00	48.64	107.24
18/C240GL	18	C	6096	240.00	49.47	109.06
18/C248GL	18	C	6299	248.00	51.12	112.69
18/C255GL	18	C	6477	255.00	52.56	115.87
18/C270GL	18	C	6858	270.00	55.65	122.69
18/C285GL	18	C	7239	285.00	58.74	129.51
18/C300GL	18	C	7620	300.00	61.84	136.32
18/C315GL	18	C	8001	315.00	64.93	143.14
18/C330GL	18	C	8382	330.00	68.02	149.96
18/C345GL	18	C	8763	345.00	71.11	156.77
18/C360GL	18	C	9144	360.00	74.20	163.59
18/C390GL	18	C	9906	390.00	80.39	177.22
18/C420GL	18	C	10668	420.00	86.57	190.85
2/D110GL	2	D	2794	110.00	4.47	9.85
2/D120GL	2	D	3048	120.00	4.87	10.75
2/D128GL	2	D	3251	128.00	5.20	11.46
2/D144GL	2	D	3658	144.00	5.85	12.89
2/D158GL	2	D	4013	158.00	6.42	14.15
2/D162GL	2	D	4115	162.00	6.58	14.51
2/D173GL	2	D	4394	173.00	7.03	15.49
2/D180GL	2	D	4572	180.00	7.31	16.12
2/D195GL	2	D	4953	195.00	7.92	17.46
2/D210GL	2	D	5334	210.00	8.53	18.80

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/D225GL	2	D	5715	225.00	9.14	20.15
2/D240GL	2	D	6096	240.00	9.75	21.49
2/D255GL	2	D	6477	255.00	10.36	22.83
2/D270GL	2	D	6858	270.00	10.97	24.18
2/D285GL	2	D	7239	285.00	11.58	25.52
2/D300GL	2	D	7620	300.00	12.19	26.86
2/D315GL	2	D	8001	315.00	12.79	28.21
2/D330GL	2	D	8382	330.00	13.40	29.55
2/D345GL	2	D	8763	345.00	14.01	30.89
2/D360GL	2	D	9144	360.00	14.62	32.24
2/D390GL	2	D	9906	390.00	15.84	34.92
2/D420GL	2	D	10668	420.00	17.06	37.61
2/D450GL	2	D	11430	450.00	18.28	40.30
2/D480GL	2	D	12192	480.00	19.50	42.98
2/D540GL	2	D	13716	540.00	21.93	48.35
2/D600GL	2	D	15240	600.00	24.37	53.73
2/D660GL	2	D	16764	660.00	26.81	59.10
2/D700GL	2	D	17780	700.00	28.43	62.68
3/D110GL	3	D	2794	110.00	6.70	14.77
3/D120GL	3	D	3048	120.00	7.31	16.12
3/D128GL	3	D	3251	128.00	7.80	17.19
3/D144GL	3	D	3658	144.00	8.77	19.34
3/D158GL	3	D	4013	158.00	9.63	21.22
3/D162GL	3	D	4115	162.00	9.87	21.76
3/D173GL	3	D	4394	173.00	10.54	23.24
3/D180GL	3	D	4572	180.00	10.97	24.18
3/D195GL	3	D	4953	195.00	11.88	26.19
3/D210GL	3	D	5334	210.00	12.79	28.21
3/D225GL	3	D	5715	225.00	13.71	30.22
3/D240GL	3	D	6096	240.00	14.62	32.24
3/D255GL	3	D	6477	255.00	15.54	34.25
3/D270GL	3	D	6858	270.00	16.45	36.27

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/D285GL	3	D	7239	285.00	17.36	38.28
3/D300GL	3	D	7620	300.00	18.28	40.30
3/D315GL	3	D	8001	315.00	19.19	42.31
3/D330GL	3	D	8382	330.00	20.11	44.32
3/D345GL	3	D	8763	345.00	21.02	46.34
3/D360GL	3	D	9144	360.00	21.93	48.35
3/D390GL	3	D	9906	390.00	23.76	52.38
3/D420GL	3	D	10668	420.00	25.59	56.41
3/D450GL	3	D	11430	450.00	27.42	60.44
3/D480GL	3	D	12192	480.00	29.24	64.47
3/D540GL	3	D	13716	540.00	32.90	72.53
3/D600GL	3	D	15240	600.00	36.56	80.59
3/D660GL	3	D	16764	660.00	40.21	88.65
3/D700GL	3	D	17780	700.00	42.65	94.02
4/D110GL	4	D	2794	110.00	8.94	19.70
4/D120GL	4	D	3048	120.00	9.75	21.49
4/D128GL	4	D	3251	128.00	10.40	22.92
4/D144GL	4	D	3658	144.00	11.70	25.79
4/D158GL	4	D	4013	158.00	12.83	28.30
4/D162GL	4	D	4115	162.00	13.16	29.01
4/D173GL	4	D	4394	173.00	14.05	30.98
4/D180GL	4	D	4572	180.00	14.62	32.24
4/D195GL	4	D	4953	195.00	15.84	34.92
4/D210GL	4	D	5334	210.00	17.06	37.61
4/D225GL	4	D	5715	225.00	18.28	40.30
4/D240GL	4	D	6096	240.00	19.50	42.98
4/D255GL	4	D	6477	255.00	20.71	45.67
4/D270GL	4	D	6858	270.00	21.93	48.35
4/D285GL	4	D	7239	285.00	23.15	51.04
4/D300GL	4	D	7620	300.00	24.37	53.73
4/D315GL	4	D	8001	315.00	25.59	56.41
4/D330GL	4	D	8382	330.00	26.81	59.10

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
4/D345GL	4	D	8763	345.00	28.03	61.79
4/D360GL	4	D	9144	360.00	29.24	64.47
4/D390GL	4	D	9906	390.00	31.68	69.84
4/D420GL	4	D	10668	420.00	34.12	75.22
4/D450GL	4	D	11430	450.00	36.56	80.59
4/D480GL	4	D	12192	480.00	38.99	85.96
4/D540GL	4	D	13716	540.00	43.87	96.71
4/D600GL	4	D	15240	600.00	48.74	107.45
4/D660GL	4	D	16764	660.00	53.61	118.20
4/D700GL	4	D	17780	700.00	56.86	125.36
5/D110GL	5	D	2794	110.00	11.17	24.62
5/D120GL	5	D	3048	120.00	12.19	26.86
5/D128GL	5	D	3251	128.00	13.00	28.65
5/D144GL	5	D	3658	144.00	14.62	32.24
5/D158GL	5	D	4013	158.00	16.04	35.37
5/D162GL	5	D	4115	162.00	16.45	36.27
5/D173GL	5	D	4394	173.00	17.57	38.73
5/D180GL	5	D	4572	180.00	18.28	40.30
5/D195GL	5	D	4953	195.00	19.80	43.65
5/D210GL	5	D	5334	210.00	21.32	47.01
5/D225GL	5	D	5715	225.00	22.85	50.37
5/D240GL	5	D	6096	240.00	24.37	53.73
5/D255GL	5	D	6477	255.00	25.89	57.08
5/D270GL	5	D	6858	270.00	27.42	60.44
5/D285GL	5	D	7239	285.00	28.94	63.80
5/D300GL	5	D	7620	300.00	30.46	67.16
5/D315GL	5	D	8001	315.00	31.99	70.52
5/D330GL	5	D	8382	330.00	33.51	73.87
5/D345GL	5	D	8763	345.00	35.03	77.23
5/D360GL	5	D	9144	360.00	36.56	80.59
5/D390GL	5	D	9906	390.00	39.60	87.31
5/D420GL	5	D	10668	420.00	42.65	94.02

GOLD LABEL Banded Wrapped Classical - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
A	13	10	0.183
B	17	13	0.256
C	22	16	0.451
D	32	22	0.800

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
A	1/2	25/64	0.010
B	21/32	1/2	0.014
C	7/8	5/8	0.025
D	1-1/4	55/64	0.045

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
5/D450GL	5	D	11430	450.00	45.69	100.74
5/D480GL	5	D	12192	480.00	48.74	107.45
5/D540GL	5	D	13716	540.00	54.83	120.89
5/D600GL	5	D	15240	600.00	60.93	134.32
5/D660GL	5	D	16764	660.00	67.02	147.75
5/D700GL	5	D	17780	700.00	71.08	156.70
12/D110GL	12	D	2794	110.00	26.81	59.10
12/D120GL	12	D	3048	120.00	29.24	64.47
12/D128GL	12	D	3251	128.00	31.19	68.77
12/D144GL	12	D	3658	144.00	35.09	77.37
12/D660GL	12	D	16764	660.00	160.84	354.60
12/D700GL	12	D	17780	700.00	170.59	376.09
20/D158GL	20	D	4013	158.00	64.17	141.48
20/D162GL	20	D	4115	162.00	65.80	145.06
20/D173GL	20	D	4394	173.00	70.27	154.91
20/D180GL	20	D	4572	180.00	73.11	161.18
20/D195GL	20	D	4953	195.00	79.20	174.61
20/D210GL	20	D	5334	210.00	85.30	188.04
20/D225GL	20	D	5715	225.00	91.39	201.48
20/D240GL	20	D	6096	240.00	97.48	214.91
20/D255GL	20	D	6477	255.00	103.57	228.34
20/D270GL	20	D	6858	270.00	109.67	241.77
20/D285GL	20	D	7239	285.00	115.76	255.20
20/D300GL	20	D	7620	300.00	121.85	268.63
20/D315GL	20	D	8001	315.00	127.94	282.07
20/D330GL	20	D	8382	330.00	134.04	295.50
20/D345GL	20	D	8763	345.00	140.13	308.93
20/D360GL	20	D	9144	360.00	146.22	322.36
20/D390GL	20	D	9906	390.00	158.41	349.22
20/D420GL	20	D	10668	420.00	170.59	376.09
20/D450GL	20	D	11430	450.00	182.78	402.95
20/D480GL	20	D	12192	480.00	194.96	429.81
20/D540GL	20	D	13716	540.00	219.33	483.54
20/D600GL	20	D	15240	600.00	243.70	537.27

GOLD LABEL Banded Wrapped Narrow - Product Description



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

V-Belt

Part Number Description: **2/3V800GL**

2/: Number of ribs

3V: Profile

800: External Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Prevents Vibrations and belt Turn-over

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 °C / -31 To 160 °F

Wedge Profile (RMA): Up to 3 times the Power transmission capacity compared to Classical V Profiles (A, B, C, D)

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty drives

Recommended solution for multiple belts drives where single belts vibrate or turn over

Pulley Standards: ARPM/MPTA IP-22 / ISO5290

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3V600GL	2	3V	1524	60.00	0.31	0.69
2/3V630GL	2	3V	1600	63.00	0.33	0.73
2/3V670GL	2	3V	1702	67.00	0.35	0.77
2/3V710GL	2	3V	1803	71.00	0.37	0.82
2/3V750GL	2	3V	1905	75.00	0.39	0.87
2/3V800GL	2	3V	2032	80.00	0.42	0.92
2/3V850GL	2	3V	2159	85.00	0.45	0.98
2/3V900GL	2	3V	2286	90.00	0.47	1.04
2/3V950GL	2	3V	2413	95.00	0.50	1.10
2/3V1000GL	2	3V	2540	100.00	0.52	1.15
2/3V1060GL	2	3V	2692	106.00	0.56	1.22
2/3V1120GL	2	3V	2845	112.00	0.59	1.29
2/3V1180GL	2	3V	2997	118.00	0.62	1.36
2/3V1250GL	2	3V	3175	125.00	0.65	1.44
2/3V1320GL	2	3V	3353	132.00	0.69	1.52
2/3V1400GL	2	3V	3556	140.00	0.73	1.62
3/3V600GL	3	3V	1524	60.00	0.47	1.04
3/3V630GL	3	3V	1600	63.00	0.49	1.09
3/3V670GL	3	3V	1702	67.00	0.53	1.16
3/3V710GL	3	3V	1803	71.00	0.56	1.23
3/3V750GL	3	3V	1905	75.00	0.59	1.30
3/3V800GL	3	3V	2032	80.00	0.63	1.39
3/3V850GL	3	3V	2159	85.00	0.67	1.47
3/3V900GL	3	3V	2286	90.00	0.71	1.56
3/3V950GL	3	3V	2413	95.00	0.75	1.65
3/3V1000GL	3	3V	2540	100.00	0.79	1.73
3/3V1060GL	3	3V	2692	106.00	0.83	1.84
3/3V1120GL	3	3V	2845	112.00	0.88	1.94
3/3V1180GL	3	3V	2997	118.00	0.93	2.04
3/3V1250GL	3	3V	3175	125.00	0.98	2.17
3/3V1320GL	3	3V	3353	132.00	1.04	2.29
3/3V1400GL	3	3V	3556	140.00	1.10	2.42
4/3V600GL	4	3V	1524	60.00	0.63	1.39
4/3V630GL	4	3V	1600	63.00	0.66	1.45

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/3V670GL	4	3V	1702	67.00	0.70	1.55
4/3V710GL	4	3V	1803	71.00	0.74	1.64
4/3V750GL	4	3V	1905	75.00	0.79	1.73
4/3V800GL	4	3V	2032	80.00	0.84	1.85
4/3V850GL	4	3V	2159	85.00	0.89	1.96
4/3V900GL	4	3V	2286	90.00	0.94	2.08
4/3V950GL	4	3V	2413	95.00	1.00	2.19
4/3V1000GL	4	3V	2540	100.00	1.05	2.31
4/3V1060GL	4	3V	2692	106.00	1.11	2.45
4/3V1120GL	4	3V	2845	112.00	1.17	2.59
4/3V1180GL	4	3V	2997	118.00	1.24	2.73
4/3V1250GL	4	3V	3175	125.00	1.31	2.89
4/3V1320GL	4	3V	3353	132.00	1.38	3.05
4/3V1400GL	4	3V	3556	140.00	1.47	3.23
5/3V600GL	5	3V	1524	60.00	0.79	1.73
5/3V630GL	5	3V	1600	63.00	0.82	1.82
5/3V670GL	5	3V	1702	67.00	0.88	1.93
5/3V710GL	5	3V	1803	71.00	0.93	2.05
5/3V750GL	5	3V	1905	75.00	0.98	2.17
5/3V800GL	5	3V	2032	80.00	1.05	2.31
5/3V850GL	5	3V	2159	85.00	1.11	2.45
5/3V900GL	5	3V	2286	90.00	1.18	2.60
5/3V950GL	5	3V	2413	95.00	1.24	2.74
5/3V1000GL	5	3V	2540	100.00	1.31	2.89
5/3V1060GL	5	3V	2692	106.00	1.39	3.06
5/3V1120GL	5	3V	2845	112.00	1.47	3.23
5/3V1180GL	5	3V	2997	118.00	1.55	3.41
5/3V1250GL	5	3V	3175	125.00	1.64	3.61
5/3V1320GL	5	3V	3353	132.00	1.73	3.81
5/3V1400GL	5	3V	3556	140.00	1.83	4.04
29/3V600GL	29	3V	1524	60.00	4.56	10.05
29/3V630GL	29	3V	1600	63.00	4.78	10.55
29/3V670GL	29	3V	1702	67.00	5.09	11.22
29/3V710GL	29	3V	1803	71.00	5.39	11.89

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
29/3V750GL	29	3V	1905	75.00	5.70	12.56
29/3V800GL	29	3V	2032	80.00	6.08	13.40
29/3V850GL	29	3V	2159	85.00	6.46	14.23
29/3V900GL	29	3V	2286	90.00	6.84	15.07
29/3V950GL	29	3V	2413	95.00	7.22	15.91
29/3V1000GL	29	3V	2540	100.00	7.59	16.74
29/3V1060GL	29	3V	2692	106.00	8.05	17.75
29/3V1120GL	29	3V	2845	112.00	8.51	18.75
29/3V1180GL	29	3V	2997	118.00	8.96	19.76
29/3V1250GL	29	3V	3175	125.00	9.49	20.93
29/3V1320GL	29	3V	3353	132.00	10.03	22.10
29/3V1400GL	29	3V	3556	140.00	10.63	23.44
2/5V600GL	2	5V	1524	60.00	0.85	1.88
2/5V630GL	2	5V	1600	63.00	0.90	1.97
2/5V670GL	2	5V	1702	67.00	0.95	2.10
2/5V710GL	2	5V	1803	71.00	1.01	2.23
2/5V750GL	2	5V	1905	75.00	1.07	2.35
2/5V800GL	2	5V	2032	80.00	1.14	2.51
2/5V850GL	2	5V	2159	85.00	1.21	2.66
2/5V900GL	2	5V	2286	90.00	1.28	2.82
2/5V950GL	2	5V	2413	95.00	1.35	2.98
2/5V1000GL	2	5V	2540	100.00	1.42	3.13
2/5V1060GL	2	5V	2692	106.00	1.51	3.32
2/5V1120GL	2	5V	2845	112.00	1.59	3.51
2/5V1180GL	2	5V	2997	118.00	1.68	3.70
2/5V1200GL	2	5V	3048	120.00	1.71	3.76
2/5V1210GL	2	5V	3073	121.00	1.72	3.79
2/5V1250GL	2	5V	3175	125.00	1.78	3.92
2/5V1320GL	2	5V	3353	132.00	1.88	4.14
2/5V1400GL	2	5V	3556	140.00	1.99	4.39
2/5V1500GL	2	5V	3810	150.00	2.13	4.70
2/5V1600GL	2	5V	4064	160.00	2.27	5.01
2/5V1700GL	2	5V	4318	170.00	2.42	5.33
2/5V1800GL	2	5V	4572	180.00	2.56	5.64

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/5V1900GL	2	5V	4826	190.00	2.70	5.95
2/5V2000GL	2	5V	5080	200.00	2.84	6.27
2/5V2120GL	2	5V	5385	212.00	3.01	6.64
2/5V2240GL	2	5V	5690	224.00	3.18	7.02
2/5V2360GL	2	5V	5994	236.00	3.35	7.40
2/5V2500GL	2	5V	6350	250.00	3.55	7.83
2/5V2650GL	2	5V	6731	265.00	3.77	8.30
2/5V2800GL	2	5V	7112	280.00	3.98	8.78
2/5V3000GL	2	5V	7620	300.00	4.26	9.40
2/5V3150GL	2	5V	8001	315.00	4.48	9.87
2/5V3350GL	2	5V	8509	335.00	4.76	10.50
2/5V3550GL	2	5V	9017	355.00	5.05	11.13
3/5V600GL	3	5V	1524	60.00	1.28	2.82
3/5V630GL	3	5V	1600	63.00	1.34	2.96
3/5V670GL	3	5V	1702	67.00	1.43	3.15
3/5V710GL	3	5V	1803	71.00	1.51	3.34
3/5V750GL	3	5V	1905	75.00	1.60	3.53
3/5V800GL	3	5V	2032	80.00	1.71	3.76
3/5V850GL	3	5V	2159	85.00	1.81	4.00
3/5V900GL	3	5V	2286	90.00	1.92	4.23
3/5V950GL	3	5V	2413	95.00	2.03	4.47
3/5V1000GL	3	5V	2540	100.00	2.13	4.70
3/5V1060GL	3	5V	2692	106.00	2.26	4.98
3/5V1120GL	3	5V	2845	112.00	2.39	5.27
3/5V1180GL	3	5V	2997	118.00	2.52	5.55
3/5V1200GL	3	5V	3048	120.00	2.56	5.64
3/5V1210GL	3	5V	3073	121.00	2.58	5.69
3/5V1250GL	3	5V	3175	125.00	2.67	5.88
3/5V1320GL	3	5V	3353	132.00	2.81	6.21
3/5V1400GL	3	5V	3556	140.00	2.99	6.58
3/5V1500GL	3	5V	3810	150.00	3.20	7.05
3/5V1600GL	3	5V	4064	160.00	3.41	7.52
3/5V1700GL	3	5V	4318	170.00	3.62	7.99
3/5V1800GL	3	5V	4572	180.00	3.84	8.46

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/5V1900GL	3	5V	4826	190.00	4.05	8.93
3/5V2000GL	3	5V	5080	200.00	4.26	9.40
3/5V2120GL	3	5V	5385	212.00	4.52	9.97
3/5V2240GL	3	5V	5690	224.00	4.78	10.53
3/5V2360GL	3	5V	5994	236.00	5.03	11.09
3/5V2500GL	3	5V	6350	250.00	5.33	11.75
3/5V2650GL	3	5V	6731	265.00	5.65	12.46
3/5V2800GL	3	5V	7112	280.00	5.97	13.16
3/5V3000GL	3	5V	7620	300.00	6.40	14.10
3/5V3150GL	3	5V	8001	315.00	6.72	14.81
3/5V3350GL	3	5V	8509	335.00	7.14	15.75
3/5V3550GL	3	5V	9017	355.00	7.57	16.69
4/5V600GL	4	5V	1524	60.00	1.71	3.76
4/5V630GL	4	5V	1600	63.00	1.79	3.95
4/5V670GL	4	5V	1702	67.00	1.90	4.20
4/5V710GL	4	5V	1803	71.00	2.02	4.45
4/5V750GL	4	5V	1905	75.00	2.13	4.70
4/5V800GL	4	5V	2032	80.00	2.27	5.01
4/5V850GL	4	5V	2159	85.00	2.42	5.33
4/5V900GL	4	5V	2286	90.00	2.56	5.64
4/5V950GL	4	5V	2413	95.00	2.70	5.95
4/5V1000GL	4	5V	2540	100.00	2.84	6.27
4/5V1060GL	4	5V	2692	106.00	3.01	6.64
4/5V1120GL	4	5V	2845	112.00	3.18	7.02
4/5V1180GL	4	5V	2997	118.00	3.35	7.40
4/5V1200GL	4	5V	3048	120.00	3.41	7.52
4/5V1210GL	4	5V	3073	121.00	3.44	7.58
4/5V1250GL	4	5V	3175	125.00	3.55	7.83
4/5V1320GL	4	5V	3353	132.00	3.75	8.27
4/5V1400GL	4	5V	3556	140.00	3.98	8.78
4/5V1500GL	4	5V	3810	150.00	4.26	9.40
4/5V1600GL	4	5V	4064	160.00	4.55	10.03
4/5V1700GL	4	5V	4318	170.00	4.83	10.66
4/5V1800GL	4	5V	4572	180.00	5.12	11.28

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/5V1900GL	4	5V	4826	190.00	5.40	11.91
4/5V2000GL	4	5V	5080	200.00	5.69	12.54
4/5V2120GL	4	5V	5385	212.00	6.03	13.29
4/5V2240GL	4	5V	5690	224.00	6.37	14.04
4/5V2360GL	4	5V	5994	236.00	6.71	14.79
4/5V2500GL	4	5V	6350	250.00	7.11	15.67
4/5V2650GL	4	5V	6731	265.00	7.53	16.61
4/5V2800GL	4	5V	7112	280.00	7.96	17.55
4/5V3000GL	4	5V	7620	300.00	8.53	18.80
4/5V3150GL	4	5V	8001	315.00	8.96	19.74
4/5V3350GL	4	5V	8509	335.00	9.52	21.00
4/5V3550GL	4	5V	9017	355.00	10.09	22.25
5/5V600GL	5	5V	1524	60.00	2.13	4.70
5/5V630GL	5	5V	1600	63.00	2.24	4.94
5/5V670GL	5	5V	1702	67.00	2.38	5.25
5/5V710GL	5	5V	1803	71.00	2.52	5.56
5/5V750GL	5	5V	1905	75.00	2.67	5.88
5/5V800GL	5	5V	2032	80.00	2.84	6.27
5/5V850GL	5	5V	2159	85.00	3.02	6.66
5/5V900GL	5	5V	2286	90.00	3.20	7.05
5/5V950GL	5	5V	2413	95.00	3.38	7.44
5/5V1000GL	5	5V	2540	100.00	3.55	7.83
5/5V1060GL	5	5V	2692	106.00	3.77	8.30
5/5V1120GL	5	5V	2845	112.00	3.98	8.78
5/5V1180GL	5	5V	2997	118.00	4.19	9.25
5/5V1200GL	5	5V	3048	120.00	4.26	9.40
5/5V1210GL	5	5V	3073	121.00	4.30	9.48
5/5V1250GL	5	5V	3175	125.00	4.44	9.79
5/5V1320GL	5	5V	3353	132.00	4.69	10.34
5/5V1400GL	5	5V	3556	140.00	4.98	10.97
5/5V1500GL	5	5V	3810	150.00	5.33	11.75
5/5V1600GL	5	5V	4064	160.00	5.69	12.54
5/5V1700GL	5	5V	4318	170.00	6.04	13.32
5/5V1800GL	5	5V	4572	180.00	6.40	14.10

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/5V1900GL	5	5V	4826	190.00	6.75	14.89
5/5V2000GL	5	5V	5080	200.00	7.11	15.67
5/5V2120GL	5	5V	5385	212.00	7.53	16.61
5/5V2240GL	5	5V	5690	224.00	7.96	17.55
5/5V2360GL	5	5V	5994	236.00	8.39	18.49
5/5V2500GL	5	5V	6350	250.00	8.88	19.59
5/5V2650GL	5	5V	6731	265.00	9.42	20.76
5/5V2800GL	5	5V	7112	280.00	9.95	21.94
5/5V3000GL	5	5V	7620	300.00	10.66	23.50
5/5V3150GL	5	5V	8001	315.00	11.19	24.68
5/5V3350GL	5	5V	8509	335.00	11.91	26.25
5/5V3550GL	5	5V	9017	355.00	12.62	27.81
16/5V600GL	16	5V	1524	60.00	6.82	15.04
26/5V3150GL	26	5V	8001	315.00	58.21	128.34
26/5V3350GL	26	5V	8509	335.00	61.91	136.48
26/5V3550GL	26	5V	9017	355.00	65.60	144.63
32/5V630GL	32	5V	1600	63.00	14.33	31.59
32/5V670GL	32	5V	1702	67.00	15.24	33.60
32/5V710GL	32	5V	1803	71.00	16.15	35.60
32/5V750GL	32	5V	1905	75.00	17.06	37.61
32/5V800GL	32	5V	2032	80.00	18.20	40.11
32/5V850GL	32	5V	2159	85.00	19.33	42.62
32/5V900GL	32	5V	2286	90.00	20.47	45.13
32/5V950GL	32	5V	2413	95.00	21.61	47.64
32/5V1000GL	32	5V	2540	100.00	22.74	50.14
32/5V1060GL	32	5V	2692	106.00	24.11	53.15
32/5V1120GL	32	5V	2845	112.00	25.47	56.16
32/5V1180GL	32	5V	2997	118.00	26.84	59.17
32/5V1200GL	32	5V	3048	120.00	27.29	60.17
32/5V1210GL	32	5V	3073	121.00	27.52	60.67
32/5V1250GL	32	5V	3175	125.00	28.43	62.68
32/5V1320GL	32	5V	3353	132.00	30.02	66.19
32/5V1400GL	32	5V	3556	140.00	31.84	70.20
32/5V1500GL	32	5V	3810	150.00	34.12	75.21

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
32/5V1600GL	32	5V	4064	160.00	36.39	80.23
32/5V1700GL	32	5V	4318	170.00	38.67	85.24
32/5V1800GL	32	5V	4572	180.00	40.94	90.26
32/5V1900GL	32	5V	4826	190.00	43.21	95.27
32/5V2000GL	32	5V	5080	200.00	45.49	100.29
32/5V2120GL	32	5V	5385	212.00	48.22	106.30
32/5V2240GL	32	5V	5690	224.00	50.95	112.32
32/5V2360GL	32	5V	5994	236.00	53.68	118.34
32/5V2500GL	32	5V	6350	250.00	56.86	125.36
32/5V2650GL	32	5V	6731	265.00	60.27	132.88
32/5V2800GL	32	5V	7112	280.00	63.68	140.40
32/5V3000GL	32	5V	7620	300.00	68.23	150.43
2/8V1120GL	2	8V	2845	112.00	3.78	8.33
2/8V1180GL	2	8V	2997	118.00	3.98	8.78
2/8V1250GL	2	8V	3175	125.00	4.22	9.30
2/8V1320GL	2	8V	3353	132.00	4.45	9.82
2/8V1400GL	2	8V	3556	140.00	4.72	10.42
2/8V1500GL	2	8V	3810	150.00	5.06	11.16
2/8V1600GL	2	8V	4064	160.00	5.40	11.90
2/8V1700GL	2	8V	4318	170.00	5.74	12.65
2/8V1800GL	2	8V	4572	180.00	6.07	13.39
2/8V1900GL	2	8V	4826	190.00	6.41	14.14
2/8V2000GL	2	8V	5080	200.00	6.75	14.88
2/8V2120GL	2	8V	5385	212.00	7.15	15.77
2/8V2240GL	2	8V	5690	224.00	7.56	16.67
2/8V2360GL	2	8V	5994	236.00	7.96	17.56
2/8V2500GL	2	8V	6350	250.00	8.44	18.60
2/8V2650GL	2	8V	6731	265.00	8.94	19.72
2/8V2800GL	2	8V	7112	280.00	9.45	20.83
2/8V3000GL	2	8V	7620	300.00	10.12	22.32
2/8V3150GL	2	8V	8001	315.00	10.63	23.44
2/8V3350GL	2	8V	8509	335.00	11.30	24.92
2/8V3550GL	2	8V	9017	355.00	11.98	26.41
2/8V3750GL	2	8V	9525	375.00	12.65	27.90

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/8V4000GL	2	8V	10160	400.00	13.50	29.76
2/8V4250GL	2	8V	10795	425.00	14.34	31.62
2/8V4500GL	2	8V	11430	450.00	15.19	33.48
2/8V4750GL	2	8V	12065	475.00	16.03	35.34
2/8V5000GL	2	8V	12700	500.00	16.87	37.20
2/8V5600GL	2	8V	14224	560.00	18.90	41.66
2/8V6000GL	2	8V	15240	600.00	20.25	44.64
3/8V1120GL	3	8V	2845	112.00	5.67	12.50
3/8V1180GL	3	8V	2997	118.00	5.97	13.17
3/8V1250GL	3	8V	3175	125.00	6.33	13.95
3/8V1320GL	3	8V	3353	132.00	6.68	14.73
3/8V1400GL	3	8V	3556	140.00	7.09	15.62
3/8V1500GL	3	8V	3810	150.00	7.59	16.74
3/8V1600GL	3	8V	4064	160.00	8.10	17.86
3/8V1700GL	3	8V	4318	170.00	8.61	18.97
3/8V1800GL	3	8V	4572	180.00	9.11	20.09
3/8V1900GL	3	8V	4826	190.00	9.62	21.20
3/8V2000GL	3	8V	5080	200.00	10.12	22.32
3/8V2120GL	3	8V	5385	212.00	10.73	23.66
3/8V2240GL	3	8V	5690	224.00	11.34	25.00
3/8V2360GL	3	8V	5994	236.00	11.95	26.34
3/8V2500GL	3	8V	6350	250.00	12.65	27.90
3/8V2650GL	3	8V	6731	265.00	13.41	29.57
3/8V2800GL	3	8V	7112	280.00	14.17	31.25
3/8V3000GL	3	8V	7620	300.00	15.19	33.48
3/8V3150GL	3	8V	8001	315.00	15.95	35.15
3/8V3350GL	3	8V	8509	335.00	16.96	37.38
3/8V3550GL	3	8V	9017	355.00	17.97	39.62
3/8V3750GL	3	8V	9525	375.00	18.98	41.85
3/8V4000GL	3	8V	10160	400.00	20.25	44.64
3/8V4250GL	3	8V	10795	425.00	21.51	47.43
3/8V4500GL	3	8V	11430	450.00	22.78	50.22
3/8V4750GL	3	8V	12065	475.00	24.04	53.01
3/8V5000GL	3	8V	12700	500.00	25.31	55.80

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/8V5600GL	3	8V	14224	560.00	28.35	62.49
3/8V6000GL	3	8V	15240	600.00	30.37	66.96
4/8V1120GL	4	8V	2845	112.00	7.56	16.67
4/8V1180GL	4	8V	2997	118.00	7.96	17.56
4/8V1250GL	4	8V	3175	125.00	8.44	18.60
4/8V1320GL	4	8V	3353	132.00	8.91	19.64
4/8V1400GL	4	8V	3556	140.00	9.45	20.83
4/8V1500GL	4	8V	3810	150.00	10.12	22.32
4/8V1600GL	4	8V	4064	160.00	10.80	23.81
4/8V1700GL	4	8V	4318	170.00	11.47	25.30
4/8V1800GL	4	8V	4572	180.00	12.15	26.78
4/8V1900GL	4	8V	4826	190.00	12.82	28.27
4/8V2000GL	4	8V	5080	200.00	13.50	29.76
4/8V2120GL	4	8V	5385	212.00	14.31	31.54
4/8V2240GL	4	8V	5690	224.00	15.12	33.33
4/8V2360GL	4	8V	5994	236.00	15.93	35.12
4/8V2500GL	4	8V	6350	250.00	16.87	37.20
4/8V2650GL	4	8V	6731	265.00	17.89	39.43
4/8V2800GL	4	8V	7112	280.00	18.90	41.66
4/8V3000GL	4	8V	7620	300.00	20.25	44.64
4/8V3150GL	4	8V	8001	315.00	21.26	46.87
4/8V3350GL	4	8V	8509	335.00	22.61	49.85
4/8V3550GL	4	8V	9017	355.00	23.96	52.82
4/8V3750GL	4	8V	9525	375.00	25.31	55.80
4/8V4000GL	4	8V	10160	400.00	27.00	59.52
4/8V4250GL	4	8V	10795	425.00	28.68	63.24
4/8V4500GL	4	8V	11430	450.00	30.37	66.96
4/8V4750GL	4	8V	12065	475.00	32.06	70.68
4/8V5000GL	4	8V	12700	500.00	33.75	74.40
4/8V5600GL	4	8V	14224	560.00	37.80	83.33
4/8V6000GL	4	8V	15240	600.00	40.50	89.28
5/8V1120GL	5	8V	2845	112.00	9.45	20.83
5/8V1180GL	5	8V	2997	118.00	9.96	21.95
5/8V1250GL	5	8V	3175	125.00	10.55	23.25

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/8V1320GL	5	8V	3353	132.00	11.14	24.55
5/8V1400GL	5	8V	3556	140.00	11.81	26.04
5/8V1500GL	5	8V	3810	150.00	12.65	27.90
5/8V1600GL	5	8V	4064	160.00	13.50	29.76
5/8V1700GL	5	8V	4318	170.00	14.34	31.62
5/8V1800GL	5	8V	4572	180.00	15.19	33.48
5/8V1900GL	5	8V	4826	190.00	16.03	35.34
5/8V2000GL	5	8V	5080	200.00	16.87	37.20
5/8V2120GL	5	8V	5385	212.00	17.89	39.43
5/8V2240GL	5	8V	5690	224.00	18.90	41.66
5/8V2360GL	5	8V	5994	236.00	19.91	43.89
5/8V2500GL	5	8V	6350	250.00	21.09	46.50
5/8V2650GL	5	8V	6731	265.00	22.36	49.29
5/8V2800GL	5	8V	7112	280.00	23.62	52.08
5/8V3000GL	5	8V	7620	300.00	25.31	55.80
5/8V3150GL	5	8V	8001	315.00	26.58	58.59
5/8V3350GL	5	8V	8509	335.00	28.26	62.31
5/8V3550GL	5	8V	9017	355.00	29.95	66.03
5/8V3750GL	5	8V	9525	375.00	31.64	69.75
5/8V4000GL	5	8V	10160	400.00	33.75	74.40
5/8V4250GL	5	8V	10795	425.00	35.86	79.05
5/8V4500GL	5	8V	11430	450.00	37.96	83.70
5/8V4750GL	5	8V	12065	475.00	40.07	88.35
5/8V5000GL	5	8V	12700	500.00	42.18	93.00
5/8V5600GL	5	8V	14224	560.00	47.24	104.16
5/8V6000GL	5	8V	15240	600.00	50.62	111.60
16/8V1120GL	16	8V	2845	112.00	30.24	66.66
16/8V1180GL	16	8V	2997	118.00	31.86	70.23
16/8V1250GL	16	8V	3175	125.00	33.75	74.40
16/8V1320GL	16	8V	3353	132.00	35.64	78.56
16/8V1400GL	16	8V	3556	140.00	37.80	83.33
16/8V1500GL	16	8V	3810	150.00	40.50	89.28
16/8V1600GL	16	8V	4064	160.00	43.19	95.23
16/8V1700GL	16	8V	4318	170.00	45.89	101.18

GOLD LABEL Banded Wrapped Narrow - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3V	9	10	0.103
5V	15	15	0.280
8V	25	25	0.664

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3V	3/8	25/64	0.006
5V	5/8	38/64	0.016
8V	1	1	0.037

All number of ribs between 2 and the max number in the table below are available


DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
16/8V1800GL	16	8V	4572	180.00	48.59	107.13
16/8V1900GL	16	8V	4826	190.00	51.29	113.08
16/8V2000GL	16	8V	5080	200.00	53.99	119.04
16/8V2120GL	16	8V	5385	212.00	57.23	126.18
16/8V2240GL	16	8V	5690	224.00	60.47	133.32
16/8V2360GL	16	8V	5994	236.00	63.71	140.46
16/8V2500GL	16	8V	6350	250.00	67.49	148.79
16/8V2650GL	16	8V	6731	265.00	71.54	157.72
16/8V2800GL	16	8V	7112	280.00	75.59	166.65
16/8V3000GL	16	8V	7620	300.00	80.99	178.55
16/8V3150GL	16	8V	8001	315.00	85.04	187.48
16/8V3350GL	16	8V	8509	335.00	90.44	199.38
16/8V3550GL	16	8V	9017	355.00	95.84	211.29
16/8V3750GL	16	8V	9525	375.00	101.24	223.19
16/8V4000GL	16	8V	10160	400.00	107.99	238.07
16/8V4250GL	16	8V	10795	425.00	114.74	252.95
16/8V4500GL	16	8V	11430	450.00	121.49	267.83
16/8V4750GL	16	8V	12065	475.00	128.24	282.71
16/8V5000GL	16	8V	12700	500.00	134.98	297.59
16/8V5600GL	16	8V	14224	560.00	151.18	333.30
16/8V6000GL	16	8V	15240	600.00	161.98	357.11

GOLD LABEL Banded Wrapped Wedge - Product Description



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

V-Belt

Part Number Description: **2/SPA1500GL**

2/: Number of ribs

SPA: Profile

1500: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Prevents Vibrations and belt Turn-over

Fabric Cover: PET/Cotton, rubber impregnated

- Abrasion, wear and Oil Resistance
- Static Conductivity: ISO 1813

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads

Compression Rubber: SBR/BR Rubber blend

- High resistance to bending stress
- Superior Oil and Heat resistance
- Temperature Range: -35 To +70 °C / -31 To 160 °F

RLT: Restricted length tolerance, matching set according to ISO 4184

Wedge Profile (Metric): Up to 3 times the Power transmission capacity of Classical V Profiles (Z, A, B, C, D, E)

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty Metrics drives where space is critical especially where small or sub-minimal sheave diameters are required

Recommended solution for multiple belts drives where single belts vibrate or turn over

Pulley Standards: DIN2211 – ISO 4183

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPZ1500GL	2	SPZ	1500	59.06	0.38	0.84
2/SPZ1600GL	2	SPZ	1600	62.99	0.41	0.90
2/SPZ1700GL	2	SPZ	1700	66.93	0.43	0.96
2/SPZ1800GL	2	SPZ	1800	70.87	0.46	1.01
2/SPZ1900GL	2	SPZ	1900	74.80	0.49	1.07
2/SPZ2000GL	2	SPZ	2000	78.74	0.51	1.13
2/SPZ2120GL	2	SPZ	2120	83.46	0.54	1.19
2/SPZ2240GL	2	SPZ	2240	88.19	0.57	1.26
2/SPZ2360GL	2	SPZ	2360	92.91	0.60	1.33
2/SPZ2500GL	2	SPZ	2500	98.43	0.64	1.41
2/SPZ2650GL	2	SPZ	2650	104.33	0.68	1.49
2/SPZ2800GL	2	SPZ	2800	110.24	0.72	1.58
2/SPZ3000GL	2	SPZ	3000	118.11	0.77	1.69
2/SPZ3150GL	2	SPZ	3150	124.02	0.80	1.77
2/SPZ3350GL	2	SPZ	3350	131.89	0.86	1.89
2/SPZ3550GL	2	SPZ	3550	139.76	0.91	2.00
3/SPZ1500GL	3	SPZ	1500	59.06	0.57	1.27
3/SPZ1600GL	3	SPZ	1600	62.99	0.61	1.35
3/SPZ1700GL	3	SPZ	1700	66.93	0.65	1.44
3/SPZ1800GL	3	SPZ	1800	70.87	0.69	1.52
3/SPZ1900GL	3	SPZ	1900	74.80	0.73	1.60
3/SPZ2000GL	3	SPZ	2000	78.74	0.77	1.69
3/SPZ2120GL	3	SPZ	2120	83.46	0.81	1.79
3/SPZ2240GL	3	SPZ	2240	88.19	0.86	1.89
3/SPZ2360GL	3	SPZ	2360	92.91	0.90	1.99
3/SPZ2500GL	3	SPZ	2500	98.43	0.96	2.11
3/SPZ2650GL	3	SPZ	2650	104.33	1.02	2.24
3/SPZ2800GL	3	SPZ	2800	110.24	1.07	2.36
3/SPZ3000GL	3	SPZ	3000	118.11	1.15	2.53
3/SPZ3150GL	3	SPZ	3150	124.02	1.21	2.66
3/SPZ3350GL	3	SPZ	3350	131.89	1.28	2.83
3/SPZ3550GL	3	SPZ	3550	139.76	1.36	3.00
4/SPZ1500GL	4	SPZ	1500	59.06	0.77	1.69
4/SPZ1600GL	4	SPZ	1600	62.99	0.82	1.80

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPZ1700GL	4	SPZ	1700	66.93	0.87	1.91
4/SPZ1800GL	4	SPZ	1800	70.87	0.92	2.03
4/SPZ1900GL	4	SPZ	1900	74.80	0.97	2.14
4/SPZ2000GL	4	SPZ	2000	78.74	1.02	2.25
4/SPZ2120GL	4	SPZ	2120	83.46	1.08	2.39
4/SPZ2240GL	4	SPZ	2240	88.19	1.14	2.52
4/SPZ2360GL	4	SPZ	2360	92.91	1.21	2.66
4/SPZ2500GL	4	SPZ	2500	98.43	1.28	2.82
4/SPZ2650GL	4	SPZ	2650	104.33	1.35	2.98
4/SPZ2800GL	4	SPZ	2800	110.24	1.43	3.15
4/SPZ3000GL	4	SPZ	3000	118.11	1.53	3.38
4/SPZ3150GL	4	SPZ	3150	124.02	1.61	3.55
4/SPZ3350GL	4	SPZ	3350	131.89	1.71	3.77
4/SPZ3550GL	4	SPZ	3550	139.76	1.81	4.00
5/SPZ1500GL	5	SPZ	1500	59.06	0.96	2.11
5/SPZ1600GL	5	SPZ	1600	62.99	1.02	2.25
5/SPZ1700GL	5	SPZ	1700	66.93	1.09	2.39
5/SPZ1800GL	5	SPZ	1800	70.87	1.15	2.53
5/SPZ1900GL	5	SPZ	1900	74.80	1.21	2.67
5/SPZ2000GL	5	SPZ	2000	78.74	1.28	2.82
5/SPZ2120GL	5	SPZ	2120	83.46	1.35	2.98
5/SPZ2240GL	5	SPZ	2240	88.19	1.43	3.15
5/SPZ2360GL	5	SPZ	2360	92.91	1.51	3.32
5/SPZ2500GL	5	SPZ	2500	98.43	1.60	3.52
5/SPZ2650GL	5	SPZ	2650	104.33	1.69	3.73
5/SPZ2800GL	5	SPZ	2800	110.24	1.79	3.94
5/SPZ3000GL	5	SPZ	3000	118.11	1.92	4.22
5/SPZ3150GL	5	SPZ	3150	124.02	2.01	4.43
5/SPZ3350GL	5	SPZ	3350	131.89	2.14	4.72
5/SPZ3550GL	5	SPZ	3550	139.76	2.27	5.00
25/SPZ1500GL	25	SPZ	1500	59.06	4.79	10.56
25/SPZ1600GL	25	SPZ	1600	62.99	5.11	11.26
25/SPZ1700GL	25	SPZ	1700	66.93	5.43	11.96
25/SPZ1800GL	25	SPZ	1800	70.87	5.75	12.67

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
25/SPZ1900GL	25	SPZ	1900	74.80	6.07	13.37
25/SPZ2000GL	25	SPZ	2000	78.74	6.38	14.08
25/SPZ2120GL	25	SPZ	2120	83.46	6.77	14.92
25/SPZ2240GL	25	SPZ	2240	88.19	7.15	15.76
25/SPZ2360GL	25	SPZ	2360	92.91	7.53	16.61
25/SPZ2500GL	25	SPZ	2500	98.43	7.98	17.59
25/SPZ2650GL	25	SPZ	2650	104.33	8.46	18.65
25/SPZ2800GL	25	SPZ	2800	110.24	8.94	19.71
25/SPZ3000GL	25	SPZ	3000	118.11	9.58	21.11
25/SPZ3150GL	25	SPZ	3150	124.02	10.06	22.17
25/SPZ3350GL	25	SPZ	3350	131.89	10.69	23.58
25/SPZ3550GL	25	SPZ	3550	139.76	11.33	24.98
2/SPA1500GL	2	SPA	1500	59.06	0.51	1.12
2/SPA1600GL	2	SPA	1600	62.99	0.54	1.20
2/SPA1700GL	2	SPA	1700	66.93	0.58	1.27
2/SPA1800GL	2	SPA	1800	70.87	0.61	1.35
2/SPA1900GL	2	SPA	1900	74.80	0.65	1.42
2/SPA2000GL	2	SPA	2000	78.74	0.68	1.50
2/SPA2120GL	2	SPA	2120	83.46	0.72	1.59
2/SPA2240GL	2	SPA	2240	88.19	0.76	1.68
2/SPA2360GL	2	SPA	2360	92.91	0.80	1.77
2/SPA2500GL	2	SPA	2500	98.43	0.85	1.87
2/SPA2650GL	2	SPA	2650	104.33	0.90	1.99
2/SPA2800GL	2	SPA	2800	110.24	0.95	2.10
2/SPA3000GL	2	SPA	3000	118.11	1.02	2.25
2/SPA3150GL	2	SPA	3150	124.02	1.07	2.36
2/SPA3350GL	2	SPA	3350	131.89	1.14	2.51
2/SPA3550GL	2	SPA	3550	139.76	1.21	2.66
2/SPA3750GL	2	SPA	3750	147.64	1.28	2.81
2/SPA4000GL	2	SPA	4000	157.48	1.36	3.00
2/SPA4250GL	2	SPA	4250	167.32	1.45	3.19
2/SPA4500GL	2	SPA	4500	177.17	1.53	3.37
3/SPA1500GL	3	SPA	1500	59.06	0.77	1.69
3/SPA1600GL	3	SPA	1600	62.99	0.82	1.80

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/SPA1700GL	3	SPA	1700	66.93	0.87	1.91
3/SPA1800GL	3	SPA	1800	70.87	0.92	2.02
3/SPA1900GL	3	SPA	1900	74.80	0.97	2.14
3/SPA2000GL	3	SPA	2000	78.74	1.02	2.25
3/SPA2120GL	3	SPA	2120	83.46	1.08	2.38
3/SPA2240GL	3	SPA	2240	88.19	1.14	2.52
3/SPA2360GL	3	SPA	2360	92.91	1.20	2.65
3/SPA2500GL	3	SPA	2500	98.43	1.28	2.81
3/SPA2650GL	3	SPA	2650	104.33	1.35	2.98
3/SPA2800GL	3	SPA	2800	110.24	1.43	3.15
3/SPA3000GL	3	SPA	3000	118.11	1.53	3.37
3/SPA3150GL	3	SPA	3150	124.02	1.61	3.54
3/SPA3350GL	3	SPA	3350	131.89	1.71	3.77
3/SPA3550GL	3	SPA	3550	139.76	1.81	3.99
3/SPA3750GL	3	SPA	3750	147.64	1.91	4.22
3/SPA4000GL	3	SPA	4000	157.48	2.04	4.50
3/SPA4250GL	3	SPA	4250	167.32	2.17	4.78
3/SPA4500GL	3	SPA	4500	177.17	2.30	5.06
4/SPA1500GL	4	SPA	1500	59.06	1.02	2.25
4/SPA1600GL	4	SPA	1600	62.99	1.09	2.40
4/SPA1700GL	4	SPA	1700	66.93	1.16	2.55
4/SPA1800GL	4	SPA	1800	70.87	1.22	2.70
4/SPA1900GL	4	SPA	1900	74.80	1.29	2.85
4/SPA2000GL	4	SPA	2000	78.74	1.36	3.00
4/SPA2120GL	4	SPA	2120	83.46	1.44	3.18
4/SPA2240GL	4	SPA	2240	88.19	1.52	3.36
4/SPA2360GL	4	SPA	2360	92.91	1.61	3.54
4/SPA2500GL	4	SPA	2500	98.43	1.70	3.75
4/SPA2650GL	4	SPA	2650	104.33	1.80	3.97
4/SPA2800GL	4	SPA	2800	110.24	1.90	4.20
4/SPA3000GL	4	SPA	3000	118.11	2.04	4.50
4/SPA3150GL	4	SPA	3150	124.02	2.14	4.72
4/SPA3350GL	4	SPA	3350	131.89	2.28	5.02
4/SPA3550GL	4	SPA	3550	139.76	2.41	5.32

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPA3750GL	4	SPA	3750	147.64	2.55	5.62
4/SPA4000GL	4	SPA	4000	157.48	2.72	6.00
4/SPA4250GL	4	SPA	4250	167.32	2.89	6.37
4/SPA4500GL	4	SPA	4500	177.17	3.06	6.75
5/SPA1500GL	5	SPA	1500	59.06	1.28	2.81
5/SPA1600GL	5	SPA	1600	62.99	1.36	3.00
5/SPA1700GL	5	SPA	1700	66.93	1.45	3.19
5/SPA1800GL	5	SPA	1800	70.87	1.53	3.37
5/SPA1900GL	5	SPA	1900	74.80	1.62	3.56
5/SPA2000GL	5	SPA	2000	78.74	1.70	3.75
5/SPA2120GL	5	SPA	2120	83.46	1.80	3.97
5/SPA2240GL	5	SPA	2240	88.19	1.90	4.20
5/SPA2360GL	5	SPA	2360	92.91	2.01	4.42
5/SPA2500GL	5	SPA	2500	98.43	2.13	4.69
5/SPA2650GL	5	SPA	2650	104.33	2.25	4.97
5/SPA2800GL	5	SPA	2800	110.24	2.38	5.25
5/SPA3000GL	5	SPA	3000	118.11	2.55	5.62
5/SPA3150GL	5	SPA	3150	124.02	2.68	5.90
5/SPA3350GL	5	SPA	3350	131.89	2.85	6.28
5/SPA3550GL	5	SPA	3550	139.76	3.02	6.65
5/SPA3750GL	5	SPA	3750	147.64	3.19	7.03
5/SPA4000GL	5	SPA	4000	157.48	3.40	7.50
5/SPA4250GL	5	SPA	4250	167.32	3.61	7.97
5/SPA4500GL	5	SPA	4500	177.17	3.83	8.43
20/SPA1500GL	20	SPA	1500	59.06	5.10	11.25
20/SPA1600GL	20	SPA	1600	62.99	5.44	12.00
20/SPA1700GL	20	SPA	1700	66.93	5.78	12.74
20/SPA1800GL	20	SPA	1800	70.87	6.12	13.49
20/SPA1900GL	20	SPA	1900	74.80	6.46	14.24
20/SPA2000GL	20	SPA	2000	78.74	6.80	14.99
20/SPA2120GL	20	SPA	2120	83.46	7.21	15.89
30/SPA2240GL	30	SPA	2240	88.19	11.43	25.19
30/SPA2360GL	30	SPA	2360	92.91	12.04	26.54
30/SPA2500GL	30	SPA	2500	98.43	12.75	28.11

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
30/SPA2650GL	30	SPA	2650	104.33	13.52	29.80
30/SPA2800GL	30	SPA	2800	110.24	14.28	31.49
30/SPA3000GL	30	SPA	3000	118.11	15.30	33.74
30/SPA3150GL	30	SPA	3150	124.02	16.07	35.42
30/SPA3350GL	30	SPA	3350	131.89	17.09	37.67
30/SPA3550GL	30	SPA	3550	139.76	18.11	39.92
30/SPA3750GL	30	SPA	3750	147.64	19.13	42.17
30/SPA4000GL	30	SPA	4000	157.48	20.40	44.98
30/SPA4250GL	30	SPA	4250	167.32	21.68	47.79
30/SPA4500GL	30	SPA	4500	177.17	22.95	50.60
2/SPB2000GL	2	SPB	2000	78.74	1.03	2.28
2/SPB2120GL	2	SPB	2120	83.46	1.09	2.41
2/SPB2240GL	2	SPB	2240	88.19	1.16	2.55
2/SPB2360GL	2	SPB	2360	92.91	1.22	2.69
2/SPB2500GL	2	SPB	2500	98.43	1.29	2.85
2/SPB2650GL	2	SPB	2650	104.33	1.37	3.02
2/SPB2800GL	2	SPB	2800	110.24	1.45	3.19
2/SPB3000GL	2	SPB	3000	118.11	1.55	3.42
2/SPB3150GL	2	SPB	3150	124.02	1.63	3.59
2/SPB3350GL	2	SPB	3350	131.89	1.73	3.81
2/SPB3550GL	2	SPB	3550	139.76	1.83	4.04
2/SPB3750GL	2	SPB	3750	147.64	1.94	4.27
2/SPB4000GL	2	SPB	4000	157.48	2.07	4.55
2/SPB4250GL	2	SPB	4250	167.32	2.19	4.84
2/SPB4500GL	2	SPB	4500	177.17	2.32	5.12
2/SPB4750GL	2	SPB	4750	187.01	2.45	5.41
2/SPB5000GL	2	SPB	5000	196.85	2.58	5.69
2/SPB5300GL	2	SPB	5300	208.66	2.74	6.03
2/SPB5600GL	2	SPB	5600	220.47	2.89	6.38
2/SPB6000GL	2	SPB	6000	236.22	3.10	6.83
2/SPB6300GL	2	SPB	6300	248.03	3.25	7.17
2/SPB6700GL	2	SPB	6700	263.78	3.46	7.63
2/SPB7100GL	2	SPB	7100	279.53	3.67	8.08
2/SPB7500GL	2	SPB	7500	295.28	3.87	8.54

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPB8000GL	2	SPB	8000	314.96	4.13	9.11
3/SPB2000GL	3	SPB	2000	78.74	1.55	3.42
3/SPB2120GL	3	SPB	2120	83.46	1.64	3.62
3/SPB2240GL	3	SPB	2240	88.19	1.74	3.83
3/SPB2360GL	3	SPB	2360	92.91	1.83	4.03
3/SPB2500GL	3	SPB	2500	98.43	1.94	4.27
3/SPB2650GL	3	SPB	2650	104.33	2.05	4.53
3/SPB2800GL	3	SPB	2800	110.24	2.17	4.78
3/SPB3000GL	3	SPB	3000	118.11	2.32	5.12
3/SPB3150GL	3	SPB	3150	124.02	2.44	5.38
3/SPB3350GL	3	SPB	3350	131.89	2.59	5.72
3/SPB3550GL	3	SPB	3550	139.76	2.75	6.06
3/SPB3750GL	3	SPB	3750	147.64	2.90	6.40
3/SPB4000GL	3	SPB	4000	157.48	3.10	6.83
3/SPB4250GL	3	SPB	4250	167.32	3.29	7.26
3/SPB4500GL	3	SPB	4500	177.17	3.49	7.68
3/SPB4750GL	3	SPB	4750	187.01	3.68	8.11
3/SPB5000GL	3	SPB	5000	196.85	3.87	8.54
3/SPB5300GL	3	SPB	5300	208.66	4.11	9.05
3/SPB5600GL	3	SPB	5600	220.47	4.34	9.56
3/SPB6000GL	3	SPB	6000	236.22	4.65	10.25
3/SPB6300GL	3	SPB	6300	248.03	4.88	10.76
3/SPB6700GL	3	SPB	6700	263.78	5.19	11.44
3/SPB7100GL	3	SPB	7100	279.53	5.50	12.13
3/SPB7500GL	3	SPB	7500	295.28	5.81	12.81
3/SPB8000GL	3	SPB	8000	314.96	6.20	13.66
4/SPB2000GL	4	SPB	2000	78.74	2.07	4.55
4/SPB2120GL	4	SPB	2120	83.46	2.19	4.83
4/SPB2240GL	4	SPB	2240	88.19	2.31	5.10
4/SPB2360GL	4	SPB	2360	92.91	2.44	5.37
4/SPB2500GL	4	SPB	2500	98.43	2.58	5.69
4/SPB2650GL	4	SPB	2650	104.33	2.74	6.03
4/SPB2800GL	4	SPB	2800	110.24	2.89	6.38
4/SPB3000GL	4	SPB	3000	118.11	3.10	6.83

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPB3150GL	4	SPB	3150	124.02	3.25	7.17
4/SPB3350GL	4	SPB	3350	131.89	3.46	7.63
4/SPB3550GL	4	SPB	3550	139.76	3.67	8.08
4/SPB3750GL	4	SPB	3750	147.64	3.87	8.54
4/SPB4000GL	4	SPB	4000	157.48	4.13	9.11
4/SPB4250GL	4	SPB	4250	167.32	4.39	9.68
4/SPB4500GL	4	SPB	4500	177.17	4.65	10.25
4/SPB4750GL	4	SPB	4750	187.01	4.91	10.82
4/SPB5000GL	4	SPB	5000	196.85	5.16	11.38
4/SPB5300GL	4	SPB	5300	208.66	5.47	12.07
4/SPB5600GL	4	SPB	5600	220.47	5.78	12.75
4/SPB6000GL	4	SPB	6000	236.22	6.20	13.66
4/SPB6300GL	4	SPB	6300	248.03	6.51	14.35
4/SPB6700GL	4	SPB	6700	263.78	6.92	15.26
4/SPB7100GL	4	SPB	7100	279.53	7.33	16.17
4/SPB7500GL	4	SPB	7500	295.28	7.75	17.08
4/SPB8000GL	4	SPB	8000	314.96	8.26	18.22
5/SPB2000GL	5	SPB	2000	78.74	2.58	5.69
5/SPB2120GL	5	SPB	2120	83.46	2.74	6.03
5/SPB2240GL	5	SPB	2240	88.19	2.89	6.38
5/SPB2360GL	5	SPB	2360	92.91	3.05	6.72
5/SPB2500GL	5	SPB	2500	98.43	3.23	7.12
5/SPB2650GL	5	SPB	2650	104.33	3.42	7.54
5/SPB2800GL	5	SPB	2800	110.24	3.61	7.97
5/SPB3000GL	5	SPB	3000	118.11	3.87	8.54
5/SPB3150GL	5	SPB	3150	124.02	4.07	8.97
5/SPB3350GL	5	SPB	3350	131.89	4.32	9.53
5/SPB3550GL	5	SPB	3550	139.76	4.58	10.10
5/SPB3750GL	5	SPB	3750	147.64	4.84	10.67
5/SPB4000GL	5	SPB	4000	157.48	5.16	11.38
5/SPB4250GL	5	SPB	4250	167.32	5.49	12.10
5/SPB4500GL	5	SPB	4500	177.17	5.81	12.81
5/SPB4750GL	5	SPB	4750	187.01	6.13	13.52
5/SPB5000GL	5	SPB	5000	196.85	6.46	14.23

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/SPB5300GL	5	SPB	5300	208.66	6.84	15.09
5/SPB5600GL	5	SPB	5600	220.47	7.23	15.94
5/SPB6000GL	5	SPB	6000	236.22	7.75	17.08
5/SPB6300GL	5	SPB	6300	248.03	8.13	17.93
5/SPB6700GL	5	SPB	6700	263.78	8.65	19.07
5/SPB7100GL	5	SPB	7100	279.53	9.17	20.21
5/SPB7500GL	5	SPB	7500	295.28	9.68	21.35
5/SPB8000GL	5	SPB	8000	314.96	10.33	22.77
16/SPB2000GL	16	SPB	2000	78.74	8.26	18.22
16/SPB2120GL	16	SPB	2120	83.46	8.76	19.31
16/SPB2240GL	16	SPB	2240	88.19	9.25	20.40
16/SPB2360GL	16	SPB	2360	92.91	9.75	21.49
16/SPB2500GL	16	SPB	2500	98.43	10.33	22.77
16/SPB2650GL	16	SPB	2650	104.33	10.95	24.14
24/SPB2800GL	24	SPB	2800	110.24	17.35	38.25
24/SPB3000GL	24	SPB	3000	118.11	18.59	40.99
24/SPB3150GL	24	SPB	3150	124.02	19.52	43.04
24/SPB3350GL	24	SPB	3350	131.89	20.76	45.77
24/SPB3550GL	24	SPB	3550	139.76	22.00	48.50
24/SPB3750GL	24	SPB	3750	147.64	23.24	51.23
24/SPB4000GL	24	SPB	4000	157.48	24.79	54.65
24/SPB4250GL	24	SPB	4250	167.32	26.34	58.06
24/SPB4500GL	24	SPB	4500	177.17	27.89	61.48
24/SPB4750GL	24	SPB	4750	187.01	29.44	64.89
24/SPB5000GL	24	SPB	5000	196.85	30.98	68.31
24/SPB5300GL	24	SPB	5300	208.66	32.84	72.41
24/SPB5600GL	24	SPB	5600	220.47	34.70	76.51
24/SPB6000GL	24	SPB	6000	236.22	37.18	81.97
24/SPB6300GL	24	SPB	6300	248.03	39.04	86.07
24/SPB6700GL	24	SPB	6700	263.78	41.52	91.54
24/SPB7100GL	24	SPB	7100	279.53	44.00	97.00
24/SPB7500GL	24	SPB	7500	295.28	46.48	102.46
24/SPB8000GL	24	SPB	8000	314.96	49.58	109.30
2/SPC3000GL	2	SPC	3000	118.11	3.41	7.51

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/SPC3150GL	2	SPC	3150	124.02	3.58	7.89
2/SPC3350GL	2	SPC	3350	131.89	3.81	8.39
2/SPC3550GL	2	SPC	3550	139.76	4.03	8.89
2/SPC3750GL	2	SPC	3750	147.64	4.26	9.39
2/SPC4000GL	2	SPC	4000	157.48	4.54	10.02
2/SPC4250GL	2	SPC	4250	167.32	4.83	10.64
2/SPC4500GL	2	SPC	4500	177.17	5.11	11.27
2/SPC4750GL	2	SPC	4750	187.01	5.40	11.90
2/SPC5000GL	2	SPC	5000	196.85	5.68	12.52
2/SPC5300GL	2	SPC	5300	208.66	6.02	13.27
2/SPC5600GL	2	SPC	5600	220.47	6.36	14.02
2/SPC6000GL	2	SPC	6000	236.22	6.82	15.03
2/SPC6300GL	2	SPC	6300	248.03	7.16	15.78
2/SPC6700GL	2	SPC	6700	263.78	7.61	16.78
2/SPC7100GL	2	SPC	7100	279.53	8.07	17.78
2/SPC7500GL	2	SPC	7500	295.28	8.52	18.78
2/SPC8000GL	2	SPC	8000	314.96	9.09	20.04
2/SPC8500GL	2	SPC	8500	334.65	9.66	21.29
2/SPC9000GL	2	SPC	9000	354.33	10.22	22.54
2/SPC9500GL	2	SPC	9500	374.02	10.79	23.79
2/SPC10000GL	2	SPC	10000	393.70	11.36	25.04
2/SPC10600GL	2	SPC	10600	417.32	12.04	26.55
2/SPC11200GL	2	SPC	11200	440.94	12.72	28.05
2/SPC11800GL	2	SPC	11800	464.57	13.40	29.55
2/SPC12500GL	2	SPC	12500	492.13	14.20	31.31
3/SPC3000GL	3	SPC	3000	118.11	5.11	11.27
3/SPC3150GL	3	SPC	3150	124.02	5.37	11.83
3/SPC3350GL	3	SPC	3350	131.89	5.71	12.58
3/SPC3550GL	3	SPC	3550	139.76	6.05	13.34
3/SPC3750GL	3	SPC	3750	147.64	6.39	14.09
3/SPC4000GL	3	SPC	4000	157.48	6.82	15.03
3/SPC4250GL	3	SPC	4250	167.32	7.24	15.97
3/SPC4500GL	3	SPC	4500	177.17	7.67	16.90
3/SPC4750GL	3	SPC	4750	187.01	8.09	17.84

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/SPC5000GL	3	SPC	5000	196.85	8.52	18.78
3/SPC5300GL	3	SPC	5300	208.66	9.03	19.91
3/SPC5600GL	3	SPC	5600	220.47	9.54	21.04
3/SPC6000GL	3	SPC	6000	236.22	10.22	22.54
3/SPC6300GL	3	SPC	6300	248.03	10.74	23.67
3/SPC6700GL	3	SPC	6700	263.78	11.42	25.17
3/SPC7100GL	3	SPC	7100	279.53	12.10	26.67
3/SPC7500GL	3	SPC	7500	295.28	12.78	28.17
3/SPC8000GL	3	SPC	8000	314.96	13.63	30.05
3/SPC8500GL	3	SPC	8500	334.65	14.48	31.93
3/SPC9000GL	3	SPC	9000	354.33	15.34	33.81
3/SPC9500GL	3	SPC	9500	374.02	16.19	35.69
3/SPC10000GL	3	SPC	10000	393.70	17.04	37.57
3/SPC10600GL	3	SPC	10600	417.32	18.06	39.82
3/SPC11200GL	3	SPC	11200	440.94	19.08	42.07
3/SPC11800GL	3	SPC	11800	464.57	20.11	44.33
3/SPC12500GL	3	SPC	12500	492.13	21.30	46.96
4/SPC3000GL	4	SPC	3000	118.11	6.82	15.03
4/SPC3150GL	4	SPC	3150	124.02	7.16	15.78
4/SPC3350GL	4	SPC	3350	131.89	7.61	16.78
4/SPC3550GL	4	SPC	3550	139.76	8.07	17.78
4/SPC3750GL	4	SPC	3750	147.64	8.52	18.78
4/SPC4000GL	4	SPC	4000	157.48	9.09	20.04
4/SPC4250GL	4	SPC	4250	167.32	9.66	21.29
4/SPC4500GL	4	SPC	4500	177.17	10.22	22.54
4/SPC4750GL	4	SPC	4750	187.01	10.79	23.79
4/SPC5000GL	4	SPC	5000	196.85	11.36	25.04
4/SPC5300GL	4	SPC	5300	208.66	12.04	26.55
4/SPC5600GL	4	SPC	5600	220.47	12.72	28.05
4/SPC6000GL	4	SPC	6000	236.22	13.63	30.05
4/SPC6300GL	4	SPC	6300	248.03	14.31	31.56
4/SPC6700GL	4	SPC	6700	263.78	15.22	33.56
4/SPC7100GL	4	SPC	7100	279.53	16.13	35.56
4/SPC7500GL	4	SPC	7500	295.28	17.04	37.57

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/SPC8000GL	4	SPC	8000	314.96	18.18	40.07
4/SPC8500GL	4	SPC	8500	334.65	19.31	42.58
4/SPC9000GL	4	SPC	9000	354.33	20.45	45.08
4/SPC9500GL	4	SPC	9500	374.02	21.58	47.58
4/SPC10000GL	4	SPC	10000	393.70	22.72	50.09
4/SPC10600GL	4	SPC	10600	417.32	24.08	53.09
4/SPC11200GL	4	SPC	11200	440.94	25.45	56.10
4/SPC11800GL	4	SPC	11800	464.57	26.81	59.10
4/SPC12500GL	4	SPC	12500	492.13	28.40	62.61
5/SPC3000GL	5	SPC	3000	118.11	8.52	18.78
5/SPC3150GL	5	SPC	3150	124.02	8.95	19.72
5/SPC3350GL	5	SPC	3350	131.89	9.51	20.97
5/SPC3550GL	5	SPC	3550	139.76	10.08	22.23
5/SPC3750GL	5	SPC	3750	147.64	10.65	23.48
5/SPC4000GL	5	SPC	4000	157.48	11.36	25.04
5/SPC4250GL	5	SPC	4250	167.32	12.07	26.61
5/SPC4500GL	5	SPC	4500	177.17	12.78	28.17
5/SPC4750GL	5	SPC	4750	187.01	13.49	29.74
5/SPC5000GL	5	SPC	5000	196.85	14.20	31.31
5/SPC5300GL	5	SPC	5300	208.66	15.05	33.18
5/SPC5600GL	5	SPC	5600	220.47	15.90	35.06
5/SPC6000GL	5	SPC	6000	236.22	17.04	37.57
5/SPC6300GL	5	SPC	6300	248.03	17.89	39.44
5/SPC6700GL	5	SPC	6700	263.78	19.03	41.95
5/SPC7100GL	5	SPC	7100	279.53	20.16	44.45
5/SPC7500GL	5	SPC	7500	295.28	21.30	46.96
5/SPC8000GL	5	SPC	8000	314.96	22.72	50.09
5/SPC8500GL	5	SPC	8500	334.65	24.14	53.22
5/SPC9000GL	5	SPC	9000	354.33	25.56	56.35
5/SPC9500GL	5	SPC	9500	374.02	26.98	59.48
5/SPC10000GL	5	SPC	10000	393.70	28.40	62.61
5/SPC10600GL	5	SPC	10600	417.32	30.10	66.37
5/SPC11200GL	5	SPC	11200	440.94	31.81	70.12
5/SPC11800GL	5	SPC	11800	464.57	33.51	73.88

GOLD LABEL Banded Wrapped Wedge - Size List



V-Belt Banded

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
SPZ	10	10	0.128
SPA	13	12	0.170
SPB	17	16	0.258
SPC	22	23	0.568

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
SPZ	25/64	25/64	0.007
SPA	33/64	30/64	0.010
SPB	43/64	5/8	0.014
SPC	7/8	58/64	0.032

All number of ribs between 2 and the max number in the table below are available

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/SPC12500GL	5	SPC	12500	492.13	35.50	78.26
18/SPC8000GL	18	SPC	8000	314.96	81.79	180.32
18/SPC8500GL	18	SPC	8500	334.65	86.90	191.59
18/SPC9000GL	18	SPC	9000	354.33	92.02	202.86
18/SPC9500GL	18	SPC	9500	374.02	97.13	214.13
18/SPC10000GL	18	SPC	10000	393.70	102.24	225.40
18/SPC10600GL	18	SPC	10600	417.32	108.37	238.92
18/SPC11200GL	18	SPC	11200	440.94	114.51	252.45
18/SPC11800GL	18	SPC	11800	464.57	120.64	265.97
18/SPC12500GL	18	SPC	12500	492.13	127.80	281.75
22/SPC3000GL	22	SPC	3000	118.11	37.49	82.65
22/SPC3150GL	22	SPC	3150	124.02	39.36	86.78
22/SPC3350GL	22	SPC	3350	131.89	41.86	92.29
22/SPC3550GL	22	SPC	3550	139.76	44.36	97.80
22/SPC3750GL	22	SPC	3750	147.64	46.86	103.31
22/SPC4000GL	22	SPC	4000	157.48	49.98	110.19
22/SPC4250GL	22	SPC	4250	167.32	53.11	117.08
22/SPC4500GL	22	SPC	4500	177.17	56.23	123.97
22/SPC4750GL	22	SPC	4750	187.01	59.36	130.86
22/SPC5000GL	22	SPC	5000	196.85	62.48	137.74
22/SPC5300GL	22	SPC	5300	208.66	66.23	146.01
22/SPC5600GL	22	SPC	5600	220.47	69.98	154.27
22/SPC6000GL	22	SPC	6000	236.22	74.98	165.29
22/SPC6300GL	22	SPC	6300	248.03	78.72	173.56
22/SPC6700GL	22	SPC	6700	263.78	83.72	184.58
22/SPC7100GL	22	SPC	7100	279.53	88.72	195.60
22/SPC7500GL	22	SPC	7500	295.28	93.72	206.62



PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is $< 30\text{ }^{\circ}\text{C}$ / $86\text{ }^{\circ}\text{F}$
- Continues high temperature ($50\text{ }^{\circ}\text{C}$ / $122\text{ }^{\circ}\text{F}$) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly stored belt shelf life is at least 5 years



GOLD LABEL Banded Wrapped - Notes





GOLD LABEL Banded Wrapped - Notes



Product Guide

GOLD LABEL™ Industrial Banded Raw Edge V-Belts




GOLD LABEL™

Designed for **OEMs**

DAYCO®

MOVE FORWARD. ALWAYS.™

GOLD LABEL Banded Raw Edge - Table of Contents



V-Belt Banded


GOLD LABEL™

BX-CX

GOLD LABEL Banded X Classical

Product description3

Size List4



V-Belt Banded

GOLD LABEL™

3VX-5VX

GOLD LABEL Banded X Narrow

Product description7

Size List8



V-Belt Banded

GOLD LABEL™

XPZ-XPA-XPB

GOLD LABEL Banded X Wedge

Product description13

Size List14

GOLD LABEL Banded X Classical - Product Description



V-Belt Raw Edge **GOLD LABEL**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

V-Belt Raw Edge

Part Number Description: **2/BX100GL**

2/: Number of ribs

BX: Profile

100: Internal Length (inches)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion Resistance
- Prevents Vibrations and belt Turn-over

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs profile

- improved bending fatigue
- extra flexibility for smaller pulley
- cooling effects

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty drives

Recommended solution for multiple belts drives where single belts vibrate or turn over, in particular where temperature is critical

Pulley Standards: ISO 5291

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/BX42GL	2	BX	1067	42.00	0.39	0.86
2/BX46GL	2	BX	1168	46.00	0.43	0.94
2/BX51GL	2	BX	1295	51.00	0.47	1.04
2/BX53GL	2	BX	1346	53.00	0.49	1.08
2/BX55GL	2	BX	1397	55.00	0.51	1.12
2/BX56GL	2	BX	1422	56.00	0.52	1.14
2/BX58GL	2	BX	1473	58.00	0.54	1.18
2/BX60GL	2	BX	1524	60.00	0.55	1.22
2/BX62GL	2	BX	1575	62.00	0.57	1.26
2/BX63GL	2	BX	1600	63.00	0.58	1.28
2/BX64GL	2	BX	1626	64.00	0.59	1.31
2/BX65GL	2	BX	1651	65.00	0.60	1.33
2/BX66GL	2	BX	1676	66.00	0.61	1.35
2/BX67GL	2	BX	1702	67.00	0.62	1.37
2/BX68GL	2	BX	1727	68.00	0.63	1.39
2/BX70GL	2	BX	1778	70.00	0.65	1.43
2/BX71GL	2	BX	1803	71.00	0.66	1.45
2/BX74GL	2	BX	1880	74.00	0.68	1.51
2/BX75GL	2	BX	1905	75.00	0.69	1.53
2/BX77GL	2	BX	1956	77.00	0.71	1.57
2/BX79GL	2	BX	2007	79.00	0.73	1.61
2/BX81GL	2	BX	2057	81.00	0.75	1.65
2/BX83GL	2	BX	2108	83.00	0.77	1.69
2/BX84GL	2	BX	2134	84.00	0.78	1.71
2/BX85GL	2	BX	2159	85.00	0.79	1.73
2/BX87GL	2	BX	2210	87.00	0.80	1.77
2/BX90GL	2	BX	2286	90.00	0.83	1.84
2/BX93GL	2	BX	2362	93.00	0.86	1.90
2/BX96GL	2	BX	2438	96.00	0.89	1.96
2/BX97GL	2	BX	2464	97.00	0.90	1.98
2/BX100GL	2	BX	2540	100.00	0.92	2.04
2/BX103GL	2	BX	2616	103.00	0.95	2.10

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
2/BX105GL	2	BX	2667	105.00	0.97	2.14
2/BX112GL	2	BX	2845	112.00	1.04	2.28
3/BX42GL	3	BX	1067	42.00	0.58	1.28
3/BX46GL	3	BX	1168	46.00	0.64	1.41
3/BX51GL	3	BX	1295	51.00	0.71	1.56
3/BX53GL	3	BX	1346	53.00	0.74	1.62
3/BX55GL	3	BX	1397	55.00	0.76	1.68
3/BX56GL	3	BX	1422	56.00	0.78	1.71
3/BX58GL	3	BX	1473	58.00	0.80	1.77
3/BX60GL	3	BX	1524	60.00	0.83	1.84
3/BX62GL	3	BX	1575	62.00	0.86	1.90
3/BX63GL	3	BX	1600	63.00	0.87	1.93
3/BX64GL	3	BX	1626	64.00	0.89	1.96
3/BX65GL	3	BX	1651	65.00	0.90	1.99
3/BX66GL	3	BX	1676	66.00	0.92	2.02
3/BX67GL	3	BX	1702	67.00	0.93	2.05
3/BX68GL	3	BX	1727	68.00	0.94	2.08
3/BX70GL	3	BX	1778	70.00	0.97	2.14
3/BX71GL	3	BX	1803	71.00	0.99	2.17
3/BX74GL	3	BX	1880	74.00	1.03	2.26
3/BX75GL	3	BX	1905	75.00	1.04	2.29
3/BX77GL	3	BX	1956	77.00	1.07	2.36
3/BX79GL	3	BX	2007	79.00	1.10	2.42
3/BX81GL	3	BX	2057	81.00	1.12	2.48
3/BX83GL	3	BX	2108	83.00	1.15	2.54
3/BX84GL	3	BX	2134	84.00	1.17	2.57
3/BX85GL	3	BX	2159	85.00	1.18	2.60
3/BX87GL	3	BX	2210	87.00	1.21	2.66
3/BX90GL	3	BX	2286	90.00	1.25	2.75
3/BX93GL	3	BX	2362	93.00	1.29	2.84
3/BX96GL	3	BX	2438	96.00	1.33	2.94
3/BX97GL	3	BX	2464	97.00	1.35	2.97

GOLD LABEL Banded X Classical - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
BX	17	13	0.182
CX	22	16	0.317

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
BX	21/32	1/2	0.010
CX	7/8	5/8	0.018

DAYCO Part Nr	Ribs number	Section	Li Inside length (mm)	Li Inside length (in)	Weight (Kg)	Weight (lbs)
3/BX100GL	3	BX	2540	100.00	1.39	3.06
3/BX103GL	3	BX	2616	103.00	1.43	3.15
3/BX105GL	3	BX	2667	105.00	1.46	3.21
3/BX112GL	3	BX	2845	112.00	1.55	3.43
2/CX75GL	2	CX	1905	75.00	1.21	2.67
2/CX81GL	2	CX	2057	81.00	1.31	2.88
2/CX85GL	2	CX	2159	85.00	1.37	3.02
2/CX90GL	2	CX	2286	90.00	1.45	3.20
2/CX96GL	2	CX	2438	96.00	1.55	3.41
2/CX100GL	2	CX	2540	100.00	1.61	3.56
2/CX105GL	2	CX	2667	105.00	1.69	3.73
2/CX112GL	2	CX	2845	112.00	1.81	3.98

GOLD LABEL Banded X Narrow - Product Description



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

V-Belt Raw Edge

Part Number Description: **2/3VX800GL**

2/: Number of ribs

3VX: Profile

800: External Length (tenths of an inch)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion Resistance
- Prevents Vibrations and belt Turn-over

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs profile

- improved bending fatigue
- extra flexibility for smaller pulley
- cooling effects

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty drives where space is critical especially where small or sub-minimal sheave diameters are required

Recommended solution for multiple belts drives where single belts vibrate or turn over, in particular where temperature and power capacity is critical

Pulley Standards: ARPM/MPTA IP-22 / ISO5290

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
2/3VX250GL	2	3VX	635	25.00	0.10	0.22
2/3VX265GL	2	3VX	660	26.00	0.11	0.23
2/3VX280GL	2	3VX	711	28.00	0.11	0.25
2/3VX300GL	2	3VX	762	30.00	0.12	0.27
2/3VX315GL	2	3VX	787	31.00	0.13	0.28
2/3VX335GL	2	3VX	838	33.00	0.13	0.30
2/3VX355GL	2	3VX	889	35.00	0.14	0.31
2/3VX375GL	2	3VX	940	37.00	0.15	0.33
2/3VX400GL	2	3VX	1016	40.00	0.16	0.36
2/3VX425GL	2	3VX	1067	42.00	0.17	0.38
2/3VX450GL	2	3VX	1143	45.00	0.18	0.40
2/3VX475GL	2	3VX	1194	47.00	0.19	0.42
2/3VX500GL	2	3VX	1270	50.00	0.20	0.45
2/3VX530GL	2	3VX	1346	53.00	0.22	0.48
2/3VX560GL	2	3VX	1422	56.00	0.23	0.50
2/3VX600GL	2	3VX	1524	60.00	0.24	0.54
2/3VX630GL	2	3VX	1600	63.00	0.26	0.56
2/3VX670GL	2	3VX	1702	67.00	0.27	0.60
2/3VX710GL	2	3VX	1803	71.00	0.29	0.64
2/3VX750GL	2	3VX	1905	75.00	0.30	0.67
2/3VX800GL	2	3VX	2032	80.00	0.33	0.72
2/3VX820GL	2	3VX	2083	82.00	0.33	0.74
2/3VX850GL	2	3VX	2159	85.00	0.35	0.76
2/3VX900GL	2	3VX	2286	90.00	0.37	0.81
2/3VX950GL	2	3VX	2413	95.00	0.39	0.85
2/3VX1000GL	2	3VX	2540	100.00	0.41	0.90
2/3VX1060GL	2	3VX	2692	106.00	0.43	0.95
2/3VX1120GL	2	3VX	2845	112.00	0.46	1.00
3/3VX250GL	3	3VX	635	25.00	0.15	0.34
3/3VX265GL	3	3VX	660	26.00	0.16	0.35
3/3VX280GL	3	3VX	711	28.00	0.17	0.38
3/3VX300GL	3	3VX	762	30.00	0.18	0.40
3/3VX315GL	3	3VX	787	31.00	0.19	0.42
3/3VX335GL	3	3VX	838	33.00	0.20	0.44

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
3/3VX355GL	3	3VX	889	35.00	0.21	0.47
3/3VX375GL	3	3VX	940	37.00	0.23	0.50
3/3VX400GL	3	3VX	1016	40.00	0.24	0.54
3/3VX425GL	3	3VX	1067	42.00	0.26	0.56
3/3VX450GL	3	3VX	1143	45.00	0.27	0.61
3/3VX475GL	3	3VX	1194	47.00	0.29	0.63
3/3VX500GL	3	3VX	1270	50.00	0.30	0.67
3/3VX530GL	3	3VX	1346	53.00	0.32	0.71
3/3VX560GL	3	3VX	1422	56.00	0.34	0.75
3/3VX600GL	3	3VX	1524	60.00	0.37	0.81
3/3VX630GL	3	3VX	1600	63.00	0.38	0.85
3/3VX670GL	3	3VX	1702	67.00	0.41	0.90
3/3VX710GL	3	3VX	1803	71.00	0.43	0.95
3/3VX750GL	3	3VX	1905	75.00	0.46	1.01
3/3VX800GL	3	3VX	2032	80.00	0.49	1.08
3/3VX820GL	3	3VX	2083	82.00	0.50	1.10
3/3VX850GL	3	3VX	2159	85.00	0.52	1.14
3/3VX900GL	3	3VX	2286	90.00	0.55	1.21
3/3VX950GL	3	3VX	2413	95.00	0.58	1.28
3/3VX1000GL	3	3VX	2540	100.00	0.61	1.34
3/3VX1060GL	3	3VX	2692	106.00	0.65	1.43
3/3VX1120GL	3	3VX	2845	112.00	0.68	1.51
4/3VX250GL	4	3VX	635	25.00	0.20	0.45
4/3VX265GL	4	3VX	660	26.00	0.21	0.47
4/3VX280GL	4	3VX	711	28.00	0.23	0.50
4/3VX300GL	4	3VX	762	30.00	0.24	0.54
4/3VX315GL	4	3VX	787	31.00	0.25	0.56
4/3VX335GL	4	3VX	838	33.00	0.27	0.59
4/3VX355GL	4	3VX	889	35.00	0.28	0.63
4/3VX375GL	4	3VX	940	37.00	0.30	0.66
4/3VX400GL	4	3VX	1016	40.00	0.33	0.72
4/3VX425GL	4	3VX	1067	42.00	0.34	0.75
4/3VX450GL	4	3VX	1143	45.00	0.37	0.81
4/3VX475GL	4	3VX	1194	47.00	0.38	0.84

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
4/3VX500GL	4	3VX	1270	50.00	0.41	0.90
4/3VX530GL	4	3VX	1346	53.00	0.43	0.95
4/3VX560GL	4	3VX	1422	56.00	0.46	1.00
4/3VX600GL	4	3VX	1524	60.00	0.49	1.08
4/3VX630GL	4	3VX	1600	63.00	0.51	1.13
4/3VX670GL	4	3VX	1702	67.00	0.54	1.20
4/3VX710GL	4	3VX	1803	71.00	0.58	1.27
4/3VX750GL	4	3VX	1905	75.00	0.61	1.34
4/3VX800GL	4	3VX	2032	80.00	0.65	1.43
4/3VX820GL	4	3VX	2083	82.00	0.67	1.47
4/3VX850GL	4	3VX	2159	85.00	0.69	1.52
4/3VX900GL	4	3VX	2286	90.00	0.73	1.61
4/3VX950GL	4	3VX	2413	95.00	0.77	1.70
4/3VX1000GL	4	3VX	2540	100.00	0.81	1.79
4/3VX1060GL	4	3VX	2692	106.00	0.86	1.90
4/3VX1120GL	4	3VX	2845	112.00	0.91	2.01
5/3VX250GL	5	3VX	635	25.00	0.25	0.56
5/3VX265GL	5	3VX	660	26.00	0.26	0.58
5/3VX280GL	5	3VX	711	28.00	0.28	0.63
5/3VX300GL	5	3VX	762	30.00	0.30	0.67
5/3VX315GL	5	3VX	787	31.00	0.32	0.69
5/3VX335GL	5	3VX	838	33.00	0.34	0.74
5/3VX355GL	5	3VX	889	35.00	0.36	0.78
5/3VX375GL	5	3VX	940	37.00	0.38	0.83
5/3VX400GL	5	3VX	1016	40.00	0.41	0.90
5/3VX425GL	5	3VX	1067	42.00	0.43	0.94
5/3VX450GL	5	3VX	1143	45.00	0.46	1.01
5/3VX475GL	5	3VX	1194	47.00	0.48	1.05
5/3VX500GL	5	3VX	1270	50.00	0.51	1.12
5/3VX530GL	5	3VX	1346	53.00	0.54	1.19
5/3VX560GL	5	3VX	1422	56.00	0.57	1.25
5/3VX600GL	5	3VX	1524	60.00	0.61	1.34
5/3VX630GL	5	3VX	1600	63.00	0.64	1.41
5/3VX670GL	5	3VX	1702	67.00	0.68	1.50

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
5/3VX710GL	5	3VX	1803	71.00	0.72	1.59
5/3VX750GL	5	3VX	1905	75.00	0.76	1.68
5/3VX800GL	5	3VX	2032	80.00	0.81	1.79
5/3VX820GL	5	3VX	2083	82.00	0.83	1.84
5/3VX850GL	5	3VX	2159	85.00	0.86	1.90
5/3VX900GL	5	3VX	2286	90.00	0.91	2.02
5/3VX950GL	5	3VX	2413	95.00	0.97	2.13
5/3VX1000GL	5	3VX	2540	100.00	1.02	2.24
5/3VX1060GL	5	3VX	2692	106.00	1.08	2.38
5/3VX1120GL	5	3VX	2845	112.00	1.14	2.51
6/3VX250GL	6	3VX	635	25.00	0.30	0.67
6/3VX265GL	6	3VX	660	26.00	0.32	0.70
6/3VX280GL	6	3VX	711	28.00	0.34	0.75
6/3VX300GL	6	3VX	762	30.00	0.37	0.81
6/3VX315GL	6	3VX	787	31.00	0.38	0.83
6/3VX335GL	6	3VX	838	33.00	0.40	0.89
6/3VX355GL	6	3VX	889	35.00	0.43	0.94
6/3VX375GL	6	3VX	940	37.00	0.45	0.99
6/3VX400GL	6	3VX	1016	40.00	0.49	1.08
6/3VX425GL	6	3VX	1067	42.00	0.51	1.13
6/3VX450GL	6	3VX	1143	45.00	0.55	1.21
6/3VX475GL	6	3VX	1194	47.00	0.57	1.26
6/3VX500GL	6	3VX	1270	50.00	0.61	1.34
6/3VX530GL	6	3VX	1346	53.00	0.65	1.43
6/3VX560GL	6	3VX	1422	56.00	0.68	1.51
6/3VX600GL	6	3VX	1524	60.00	0.73	1.61
6/3VX630GL	6	3VX	1600	63.00	0.77	1.69
6/3VX670GL	6	3VX	1702	67.00	0.82	1.80
6/3VX710GL	6	3VX	1803	71.00	0.87	1.91
6/3VX750GL	6	3VX	1905	75.00	0.91	2.02
6/3VX800GL	6	3VX	2032	80.00	0.98	2.15
6/3VX820GL	6	3VX	2083	82.00	1.00	2.21
6/3VX850GL	6	3VX	2159	85.00	1.04	2.29
6/3VX900GL	6	3VX	2286	90.00	1.10	2.42

GOLD LABEL Banded X Narrow - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
3VX	9	10	0.080
5VX	15	15	0.227

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
3VX	3/8	25/64	0.004
5VX	5/8	38/64	0.013

DAYCO Part Nr	Ribs number	Section	Lo Outside length (mm)	Lo Outside length (in)	Weight (Kg)	Weight (lbs)
6/3VX950GL	6	3VX	2413	95.00	1.16	2.55
6/3VX1000GL	6	3VX	2540	100.00	1.22	2.69
6/3VX1060GL	6	3VX	2692	106.00	1.29	2.85
6/3VX1120GL	6	3VX	2845	112.00	1.37	3.01
2/5VX500GL	2	5VX	1270	50.00	0.58	1.27
2/5VX530GL	2	5VX	1346	53.00	0.61	1.35
2/5VX560GL	2	5VX	1422	56.00	0.65	1.42
2/5VX600GL	2	5VX	1524	60.00	0.69	1.52
2/5VX630GL	2	5VX	1600	63.00	0.73	1.60
2/5VX670GL	2	5VX	1702	67.00	0.77	1.70
2/5VX710GL	2	5VX	1803	71.00	0.82	1.80
2/5VX750GL	2	5VX	1905	75.00	0.86	1.90
2/5VX800GL	2	5VX	2032	80.00	0.92	2.03
2/5VX850GL	2	5VX	2159	85.00	0.98	2.16
2/5VX900GL	2	5VX	2286	90.00	1.04	2.29
2/5VX950GL	2	5VX	2413	95.00	1.09	2.41
2/5VX1000GL	2	5VX	2540	100.00	1.15	2.54
2/5VX1060GL	2	5VX	2692	106.00	1.22	2.69
2/5VX1120GL	2	5VX	2845	112.00	1.29	2.84
3/5VX500GL	3	5VX	1270	50.00	0.86	1.90
3/5VX530GL	3	5VX	1346	53.00	0.92	2.02
3/5VX560GL	3	5VX	1422	56.00	0.97	2.13
3/5VX600GL	3	5VX	1524	60.00	1.04	2.29
3/5VX630GL	3	5VX	1600	63.00	1.09	2.40
3/5VX670GL	3	5VX	1702	67.00	1.16	2.55
3/5VX710GL	3	5VX	1803	71.00	1.23	2.70
3/5VX750GL	3	5VX	1905	75.00	1.30	2.86
3/5VX800GL	3	5VX	2032	80.00	1.38	3.05
3/5VX850GL	3	5VX	2159	85.00	1.47	3.24
3/5VX900GL	3	5VX	2286	90.00	1.56	3.43
3/5VX950GL	3	5VX	2413	95.00	1.64	3.62
3/5VX1000GL	3	5VX	2540	100.00	1.73	3.81
3/5VX1060GL	3	5VX	2692	106.00	1.83	4.04
3/5VX1120GL	3	5VX	2845	112.00	1.94	4.27

GOLD LABEL Banded X Wedge - Product Description



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

V-Belt Raw Edge

Part Number Description: **2/XPA1250GL**

2/: Number of ribs

XPA: Profile

1250: Datum Length (mm)

GL: Gold Label

Features and Benefits:

Tie Band Fabric: PET/Cotton, rubber impregnated

- Abrasion Resistance
- Prevents Vibrations and belt Turn-over

Tension Cords: High Modulus Polyester

- Superior Dimensional stability (low stretch and tension decay)
- High resistance to overloads and shock loads
- Improved durability
- Reduced maintenance

Cogs profile

- improved bending fatigue
- extra flexibility for smaller pulley
- cooling effects

Body compound fibers loaded made of **EPDM** rubber blend

- Good abrasion resistance
- High Coefficient of friction (increased Power capacity vs. wrapped belt)
- Good Ozone resistance
- Very good Heat resistance
- Temperature Range: -40 To +150 °C / -40 To +302 °F
- Static conductive ISO1813

Designed for OEMs

Markets and Applications:

Ideal solution for shock or pulsating loads

Designed for heavy duty metric drives where space is critical especially where small or sub-minimal sheave diameters are required

Recommended solution for multiple belts drives where single belts vibrate or turn over, in particular where temperature, power capacity, space and weightn are critical

Pulley Standards: DIN2211 - ISO 4183

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPZ800GL	2	XPZ	800	31.50	0.29	0.13
2/XPZ850GL	2	XPZ	850	33.46	0.31	0.14
2/XPZ900GL	2	XPZ	900	35.43	0.33	0.15
2/XPZ950GL	2	XPZ	950	37.40	0.34	0.16
2/XPZ1000GL	2	XPZ	1000	39.37	0.36	0.16
2/XPZ1030GL	2	XPZ	1030	40.55	0.37	0.17
2/XPZ1060GL	2	XPZ	1060	41.73	0.38	0.17
2/XPZ1090GL	2	XPZ	1090	42.91	0.39	0.18
2/XPZ1120GL	2	XPZ	1120	44.09	0.41	0.18
2/XPZ1150GL	2	XPZ	1150	45.28	0.42	0.19
2/XPZ1180GL	2	XPZ	1180	46.46	0.43	0.19
2/XPZ1212GL	2	XPZ	1212	47.72	0.44	0.20
2/XPZ1250GL	2	XPZ	1250	49.21	0.45	0.21
2/XPZ1270GL	2	XPZ	1270	50.00	0.46	0.21
2/XPZ1320GL	2	XPZ	1320	51.97	0.48	0.22
2/XPZ1340GL	2	XPZ	1340	52.76	0.49	0.22
2/XPZ1362GL	2	XPZ	1362	53.62	0.49	0.22
2/XPZ1400GL	2	XPZ	1400	55.12	0.51	0.23
2/XPZ1420GL	2	XPZ	1420	55.91	0.51	0.23
2/XPZ1450GL	2	XPZ	1450	57.09	0.53	0.24
2/XPZ1487GL	2	XPZ	1487	58.54	0.54	0.24
2/XPZ1500GL	2	XPZ	1500	59.06	0.54	0.25
2/XPZ1550GL	2	XPZ	1550	61.02	0.56	0.25
2/XPZ1600GL	2	XPZ	1600	62.99	0.58	0.26
2/XPZ1650GL	2	XPZ	1650	64.96	0.60	0.27
2/XPZ1700GL	2	XPZ	1700	66.93	0.62	0.28
2/XPZ1750GL	2	XPZ	1750	68.90	0.63	0.29
2/XPZ1800GL	2	XPZ	1800	70.87	0.65	0.30
2/XPZ1850GL	2	XPZ	1850	72.83	0.67	0.30
2/XPZ1900GL	2	XPZ	1900	74.80	0.69	0.31
2/XPZ1950GL	2	XPZ	1950	76.77	0.71	0.32
2/XPZ2000GL	2	XPZ	2000	78.74	0.72	0.33
2/XPZ2030GL	2	XPZ	2030	79.92	0.74	0.33
2/XPZ2120GL	2	XPZ	2120	83.46	0.77	0.35

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPZ2160GL	2	XPZ	2160	85.04	0.78	0.35
2/XPZ2240GL	2	XPZ	2240	88.19	0.81	0.37
2/XPZ2360GL	2	XPZ	2360	92.91	0.85	0.39
2/XPZ2500GL	2	XPZ	2500	98.43	0.91	0.41
2/XPZ2650GL	2	XPZ	2650	104.33	0.96	0.44
2/XPZ2800GL	2	XPZ	2800	110.24	1.01	0.46
3/XPZ800GL	3	XPZ	800	31.50	0.43	0.20
3/XPZ850GL	3	XPZ	850	33.46	0.46	0.21
3/XPZ900GL	3	XPZ	900	35.43	0.49	0.22
3/XPZ950GL	3	XPZ	950	37.40	0.52	0.23
3/XPZ1000GL	3	XPZ	1000	39.37	0.54	0.25
3/XPZ1030GL	3	XPZ	1030	40.55	0.56	0.25
3/XPZ1060GL	3	XPZ	1060	41.73	0.58	0.26
3/XPZ1090GL	3	XPZ	1090	42.91	0.59	0.27
3/XPZ1120GL	3	XPZ	1120	44.09	0.61	0.28
3/XPZ1150GL	3	XPZ	1150	45.28	0.62	0.28
3/XPZ1180GL	3	XPZ	1180	46.46	0.64	0.29
3/XPZ1212GL	3	XPZ	1212	47.72	0.66	0.30
3/XPZ1250GL	3	XPZ	1250	49.21	0.68	0.31
3/XPZ1270GL	3	XPZ	1270	50.00	0.69	0.31
3/XPZ1320GL	3	XPZ	1320	51.97	0.72	0.33
3/XPZ1340GL	3	XPZ	1340	52.76	0.73	0.33
3/XPZ1362GL	3	XPZ	1362	53.62	0.74	0.34
3/XPZ1400GL	3	XPZ	1400	55.12	0.76	0.35
3/XPZ1420GL	3	XPZ	1420	55.91	0.77	0.35
3/XPZ1450GL	3	XPZ	1450	57.09	0.79	0.36
3/XPZ1487GL	3	XPZ	1487	58.54	0.81	0.37
3/XPZ1500GL	3	XPZ	1500	59.06	0.81	0.37
3/XPZ1550GL	3	XPZ	1550	61.02	0.84	0.38
3/XPZ1600GL	3	XPZ	1600	62.99	0.87	0.39
3/XPZ1650GL	3	XPZ	1650	64.96	0.90	0.41
3/XPZ1700GL	3	XPZ	1700	66.93	0.92	0.42
3/XPZ1750GL	3	XPZ	1750	68.90	0.95	0.43
3/XPZ1800GL	3	XPZ	1800	70.87	0.98	0.44

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPZ1850GL	3	XPZ	1850	72.83	1.01	0.46
3/XPZ1900GL	3	XPZ	1900	74.80	1.03	0.47
3/XPZ1950GL	3	XPZ	1950	76.77	1.06	0.48
3/XPZ2000GL	3	XPZ	2000	78.74	1.09	0.49
3/XPZ2030GL	3	XPZ	2030	79.92	1.10	0.50
3/XPZ2120GL	3	XPZ	2120	83.46	1.15	0.52
3/XPZ2160GL	3	XPZ	2160	85.04	1.17	0.53
3/XPZ2240GL	3	XPZ	2240	88.19	1.22	0.55
3/XPZ2360GL	3	XPZ	2360	92.91	1.28	0.58
3/XPZ2500GL	3	XPZ	2500	98.43	1.36	0.62
3/XPZ2650GL	3	XPZ	2650	104.33	1.44	0.65
3/XPZ2800GL	3	XPZ	2800	110.24	1.52	0.69
4/XPZ800GL	4	XPZ	800	31.50	0.58	0.26
4/XPZ850GL	4	XPZ	850	33.46	0.62	0.28
4/XPZ900GL	4	XPZ	900	35.43	0.65	0.30
4/XPZ950GL	4	XPZ	950	37.40	0.69	0.31
4/XPZ1000GL	4	XPZ	1000	39.37	0.72	0.33
4/XPZ1030GL	4	XPZ	1030	40.55	0.75	0.34
4/XPZ1060GL	4	XPZ	1060	41.73	0.77	0.35
4/XPZ1090GL	4	XPZ	1090	42.91	0.79	0.36
4/XPZ1120GL	4	XPZ	1120	44.09	0.81	0.37
4/XPZ1150GL	4	XPZ	1150	45.28	0.83	0.38
4/XPZ1180GL	4	XPZ	1180	46.46	0.85	0.39
4/XPZ1212GL	4	XPZ	1212	47.72	0.88	0.40
4/XPZ1250GL	4	XPZ	1250	49.21	0.91	0.41
4/XPZ1270GL	4	XPZ	1270	50.00	0.92	0.42
4/XPZ1320GL	4	XPZ	1320	51.97	0.96	0.43
4/XPZ1340GL	4	XPZ	1340	52.76	0.97	0.44
4/XPZ1362GL	4	XPZ	1362	53.62	0.99	0.45
4/XPZ1400GL	4	XPZ	1400	55.12	1.01	0.46
4/XPZ1420GL	4	XPZ	1420	55.91	1.03	0.47
4/XPZ1450GL	4	XPZ	1450	57.09	1.05	0.48
4/XPZ1487GL	4	XPZ	1487	58.54	1.08	0.49
4/XPZ1500GL	4	XPZ	1500	59.06	1.09	0.49

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/XPZ1550GL	4	XPZ	1550	61.02	1.12	0.51
4/XPZ1600GL	4	XPZ	1600	62.99	1.16	0.53
4/XPZ1650GL	4	XPZ	1650	64.96	1.20	0.54
4/XPZ1700GL	4	XPZ	1700	66.93	1.23	0.56
4/XPZ1750GL	4	XPZ	1750	68.90	1.27	0.58
4/XPZ1800GL	4	XPZ	1800	70.87	1.30	0.59
4/XPZ1850GL	4	XPZ	1850	72.83	1.34	0.61
4/XPZ1900GL	4	XPZ	1900	74.80	1.38	0.62
4/XPZ1950GL	4	XPZ	1950	76.77	1.41	0.64
4/XPZ2000GL	4	XPZ	2000	78.74	1.45	0.66
4/XPZ2030GL	4	XPZ	2030	79.92	1.47	0.67
4/XPZ2120GL	4	XPZ	2120	83.46	1.54	0.70
4/XPZ2160GL	4	XPZ	2160	85.04	1.56	0.71
4/XPZ2240GL	4	XPZ	2240	88.19	1.62	0.74
4/XPZ2360GL	4	XPZ	2360	92.91	1.71	0.78
4/XPZ2500GL	4	XPZ	2500	98.43	1.81	0.82
4/XPZ2650GL	4	XPZ	2650	104.33	1.92	0.87
4/XPZ2800GL	4	XPZ	2800	110.24	2.03	0.92
5/XPZ800GL	5	XPZ	800	31.50	0.72	0.33
5/XPZ850GL	5	XPZ	850	33.46	0.77	0.35
5/XPZ900GL	5	XPZ	900	35.43	0.81	0.37
5/XPZ950GL	5	XPZ	950	37.40	0.86	0.39
5/XPZ1000GL	5	XPZ	1000	39.37	0.91	0.41
5/XPZ1030GL	5	XPZ	1030	40.55	0.93	0.42
5/XPZ1060GL	5	XPZ	1060	41.73	0.96	0.44
5/XPZ1090GL	5	XPZ	1090	42.91	0.99	0.45
5/XPZ1120GL	5	XPZ	1120	44.09	1.01	0.46
5/XPZ1150GL	5	XPZ	1150	45.28	1.04	0.47
5/XPZ1180GL	5	XPZ	1180	46.46	1.07	0.48
5/XPZ1212GL	5	XPZ	1212	47.72	1.10	0.50
5/XPZ1250GL	5	XPZ	1250	49.21	1.13	0.51
5/XPZ1270GL	5	XPZ	1270	50.00	1.15	0.52
5/XPZ1320GL	5	XPZ	1320	51.97	1.20	0.54
5/XPZ1340GL	5	XPZ	1340	52.76	1.21	0.55

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
5/XPZ1362GL	5	XPZ	1362	53.62	1.23	0.56
5/XPZ1400GL	5	XPZ	1400	55.12	1.27	0.58
5/XPZ1420GL	5	XPZ	1420	55.91	1.29	0.58
5/XPZ1450GL	5	XPZ	1450	57.09	1.31	0.60
5/XPZ1487GL	5	XPZ	1487	58.54	1.35	0.61
5/XPZ1500GL	5	XPZ	1500	59.06	1.36	0.62
5/XPZ1550GL	5	XPZ	1550	61.02	1.40	0.64
5/XPZ1600GL	5	XPZ	1600	62.99	1.45	0.66
5/XPZ1650GL	5	XPZ	1650	64.96	1.49	0.68
5/XPZ1700GL	5	XPZ	1700	66.93	1.54	0.70
5/XPZ1750GL	5	XPZ	1750	68.90	1.58	0.72
5/XPZ1800GL	5	XPZ	1800	70.87	1.63	0.74
5/XPZ1850GL	5	XPZ	1850	72.83	1.68	0.76
5/XPZ1900GL	5	XPZ	1900	74.80	1.72	0.78
5/XPZ1950GL	5	XPZ	1950	76.77	1.77	0.80
5/XPZ2000GL	5	XPZ	2000	78.74	1.81	0.82
5/XPZ2030GL	5	XPZ	2030	79.92	1.84	0.83
5/XPZ2120GL	5	XPZ	2120	83.46	1.92	0.87
5/XPZ2160GL	5	XPZ	2160	85.04	1.96	0.89
5/XPZ2240GL	5	XPZ	2240	88.19	2.03	0.92
5/XPZ2360GL	5	XPZ	2360	92.91	2.14	0.97
5/XPZ2500GL	5	XPZ	2500	98.43	2.26	1.03
5/XPZ2650GL	5	XPZ	2650	104.33	2.40	1.09
5/XPZ2800GL	5	XPZ	2800	110.24	2.54	1.15
6/XPZ800GL	6	XPZ	800	31.50	0.87	0.39
6/XPZ850GL	6	XPZ	850	33.46	0.92	0.42
6/XPZ900GL	6	XPZ	900	35.43	0.98	0.44
6/XPZ950GL	6	XPZ	950	37.40	1.03	0.47
6/XPZ1000GL	6	XPZ	1000	39.37	1.09	0.49
6/XPZ1030GL	6	XPZ	1030	40.55	1.12	0.51
6/XPZ1060GL	6	XPZ	1060	41.73	1.15	0.52
6/XPZ1090GL	6	XPZ	1090	42.91	1.18	0.54
6/XPZ1120GL	6	XPZ	1120	44.09	1.22	0.55
6/XPZ1150GL	6	XPZ	1150	45.28	1.25	0.57

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
6/XPZ1180GL	6	XPZ	1180	46.46	1.28	0.58
6/XPZ1212GL	6	XPZ	1212	47.72	1.32	0.60
6/XPZ1250GL	6	XPZ	1250	49.21	1.36	0.62
6/XPZ1270GL	6	XPZ	1270	50.00	1.38	0.63
6/XPZ1320GL	6	XPZ	1320	51.97	1.43	0.65
6/XPZ1340GL	6	XPZ	1340	52.76	1.46	0.66
6/XPZ1362GL	6	XPZ	1362	53.62	1.48	0.67
6/XPZ1400GL	6	XPZ	1400	55.12	1.52	0.69
6/XPZ1420GL	6	XPZ	1420	55.91	1.54	0.70
6/XPZ1450GL	6	XPZ	1450	57.09	1.58	0.71
6/XPZ1487GL	6	XPZ	1487	58.54	1.62	0.73
6/XPZ1500GL	6	XPZ	1500	59.06	1.63	0.74
6/XPZ1550GL	6	XPZ	1550	61.02	1.68	0.76
6/XPZ1600GL	6	XPZ	1600	62.99	1.74	0.79
6/XPZ1650GL	6	XPZ	1650	64.96	1.79	0.81
6/XPZ1700GL	6	XPZ	1700	66.93	1.85	0.84
6/XPZ1750GL	6	XPZ	1750	68.90	1.90	0.86
6/XPZ1800GL	6	XPZ	1800	70.87	1.96	0.89
6/XPZ1850GL	6	XPZ	1850	72.83	2.01	0.91
6/XPZ1900GL	6	XPZ	1900	74.80	2.06	0.94
6/XPZ1950GL	6	XPZ	1950	76.77	2.12	0.96
6/XPZ2000GL	6	XPZ	2000	78.74	2.17	0.99
6/XPZ2030GL	6	XPZ	2030	79.92	2.21	1.00
6/XPZ2120GL	6	XPZ	2120	83.46	2.30	1.04
6/XPZ2160GL	6	XPZ	2160	85.04	2.35	1.06
6/XPZ2240GL	6	XPZ	2240	88.19	2.43	1.10
6/XPZ2360GL	6	XPZ	2360	92.91	2.56	1.16
6/XPZ2500GL	6	XPZ	2500	98.43	2.72	1.23
6/XPZ2650GL	6	XPZ	2650	104.33	2.88	1.31
6/XPZ2800GL	6	XPZ	2800	110.24	3.04	1.38
2/XPA800GL	2	XPA	800	31.50	0.47	0.22
2/XPA850GL	2	XPA	850	33.46	0.50	0.23
2/XPA900GL	2	XPA	900	35.43	0.53	0.24
2/XPA950GL	2	XPA	950	37.40	0.56	0.26

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPA1000GL	2	XPA	1000	39.37	0.59	0.27
2/XPA1030GL	2	XPA	1030	40.55	0.61	0.28
2/XPA1060GL	2	XPA	1060	41.73	0.63	0.29
2/XPA1090GL	2	XPA	1090	42.91	0.65	0.29
2/XPA1120GL	2	XPA	1120	44.09	0.66	0.30
2/XPA1150GL	2	XPA	1150	45.28	0.68	0.31
2/XPA1180GL	2	XPA	1180	46.46	0.70	0.32
2/XPA1250GL	2	XPA	1250	49.21	0.74	0.34
2/XPA1320GL	2	XPA	1320	51.97	0.78	0.35
2/XPA1360GL	2	XPA	1360	53.54	0.81	0.37
2/XPA1400GL	2	XPA	1400	55.12	0.83	0.38
2/XPA1450GL	2	XPA	1450	57.09	0.86	0.39
2/XPA1500GL	2	XPA	1500	59.06	0.89	0.40
2/XPA1550GL	2	XPA	1550	61.02	0.92	0.42
2/XPA1600GL	2	XPA	1600	62.99	0.95	0.43
2/XPA1650GL	2	XPA	1650	64.96	0.98	0.44
2/XPA1700GL	2	XPA	1700	66.93	1.01	0.46
2/XPA1750GL	2	XPA	1750	68.90	1.04	0.47
2/XPA1800GL	2	XPA	1800	70.87	1.07	0.48
2/XPA1850GL	2	XPA	1850	72.83	1.10	0.50
2/XPA1900GL	2	XPA	1900	74.80	1.13	0.51
2/XPA1950GL	2	XPA	1950	76.77	1.16	0.52
2/XPA2000GL	2	XPA	2000	78.74	1.19	0.54
2/XPA2060GL	2	XPA	2060	81.10	1.22	0.55
2/XPA2120GL	2	XPA	2120	83.46	1.26	0.57
2/XPA2240GL	2	XPA	2240	88.19	1.33	0.60
2/XPA2360GL	2	XPA	2360	92.91	1.40	0.63
2/XPA2430GL	2	XPA	2430	95.67	1.44	0.65
2/XPA2500GL	2	XPA	2500	98.43	1.48	0.67
2/XPA2650GL	2	XPA	2650	104.33	1.57	0.71
2/XPA2800GL	2	XPA	2800	110.24	1.66	0.75
3/XPA800GL	3	XPA	800	31.50	0.71	0.32
3/XPA850GL	3	XPA	850	33.46	0.76	0.34
3/XPA900GL	3	XPA	900	35.43	0.80	0.36

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge

GOLD LABEL™



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPA950GL	3	XPA	950	37.40	0.84	0.38
3/XPA1000GL	3	XPA	1000	39.37	0.89	0.40
3/XPA1030GL	3	XPA	1030	40.55	0.92	0.42
3/XPA1060GL	3	XPA	1060	41.73	0.94	0.43
3/XPA1090GL	3	XPA	1090	42.91	0.97	0.44
3/XPA1120GL	3	XPA	1120	44.09	1.00	0.45
3/XPA1150GL	3	XPA	1150	45.28	1.02	0.46
3/XPA1180GL	3	XPA	1180	46.46	1.05	0.48
3/XPA1250GL	3	XPA	1250	49.21	1.11	0.50
3/XPA1320GL	3	XPA	1320	51.97	1.17	0.53
3/XPA1360GL	3	XPA	1360	53.54	1.21	0.55
3/XPA1400GL	3	XPA	1400	55.12	1.24	0.56
3/XPA1450GL	3	XPA	1450	57.09	1.29	0.58
3/XPA1500GL	3	XPA	1500	59.06	1.33	0.61
3/XPA1550GL	3	XPA	1550	61.02	1.38	0.63
3/XPA1600GL	3	XPA	1600	62.99	1.42	0.65
3/XPA1650GL	3	XPA	1650	64.96	1.47	0.67
3/XPA1700GL	3	XPA	1700	66.93	1.51	0.69
3/XPA1750GL	3	XPA	1750	68.90	1.56	0.71
3/XPA1800GL	3	XPA	1800	70.87	1.60	0.73
3/XPA1850GL	3	XPA	1850	72.83	1.65	0.75
3/XPA1900GL	3	XPA	1900	74.80	1.69	0.77
3/XPA1950GL	3	XPA	1950	76.77	1.73	0.79
3/XPA2000GL	3	XPA	2000	78.74	1.78	0.81
3/XPA2060GL	3	XPA	2060	81.10	1.83	0.83
3/XPA2120GL	3	XPA	2120	83.46	1.89	0.86
3/XPA2240GL	3	XPA	2240	88.19	1.99	0.90
3/XPA2360GL	3	XPA	2360	92.91	2.10	0.95
3/XPA2430GL	3	XPA	2430	95.67	2.16	0.98
3/XPA2500GL	3	XPA	2500	98.43	2.22	1.01
3/XPA2650GL	3	XPA	2650	104.33	2.36	1.07
3/XPA2800GL	3	XPA	2800	110.24	2.49	1.13
4/XPA800GL	4	XPA	800	31.50	0.95	0.43
4/XPA850GL	4	XPA	850	33.46	1.01	0.46

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
4/XPA900GL	4	XPA	900	35.43	1.07	0.48
4/XPA950GL	4	XPA	950	37.40	1.13	0.51
4/XPA1000GL	4	XPA	1000	39.37	1.19	0.54
4/XPA1030GL	4	XPA	1030	40.55	1.22	0.55
4/XPA1060GL	4	XPA	1060	41.73	1.26	0.57
4/XPA1090GL	4	XPA	1090	42.91	1.29	0.59
4/XPA1120GL	4	XPA	1120	44.09	1.33	0.60
4/XPA1150GL	4	XPA	1150	45.28	1.36	0.62
4/XPA1180GL	4	XPA	1180	46.46	1.40	0.63
4/XPA1250GL	4	XPA	1250	49.21	1.48	0.67
4/XPA1320GL	4	XPA	1320	51.97	1.56	0.71
4/XPA1360GL	4	XPA	1360	53.54	1.61	0.73
4/XPA1400GL	4	XPA	1400	55.12	1.66	0.75
4/XPA1450GL	4	XPA	1450	57.09	1.72	0.78
4/XPA1500GL	4	XPA	1500	59.06	1.78	0.81
4/XPA1550GL	4	XPA	1550	61.02	1.84	0.83
4/XPA1600GL	4	XPA	1600	62.99	1.90	0.86
4/XPA1650GL	4	XPA	1650	64.96	1.96	0.89
4/XPA1700GL	4	XPA	1700	66.93	2.02	0.91
4/XPA1750GL	4	XPA	1750	68.90	2.07	0.94
4/XPA1800GL	4	XPA	1800	70.87	2.13	0.97
4/XPA1850GL	4	XPA	1850	72.83	2.19	0.99
4/XPA1900GL	4	XPA	1900	74.80	2.25	1.02
4/XPA1950GL	4	XPA	1950	76.77	2.31	1.05
4/XPA2000GL	4	XPA	2000	78.74	2.37	1.08
4/XPA2060GL	4	XPA	2060	81.10	2.44	1.11
4/XPA2120GL	4	XPA	2120	83.46	2.51	1.14
4/XPA2240GL	4	XPA	2240	88.19	2.66	1.20
4/XPA2360GL	4	XPA	2360	92.91	2.80	1.27
4/XPA2430GL	4	XPA	2430	95.67	2.88	1.31
4/XPA2500GL	4	XPA	2500	98.43	2.96	1.34
4/XPA2650GL	4	XPA	2650	104.33	3.14	1.43
4/XPA2800GL	4	XPA	2800	110.24	3.32	1.51
2/XPB1250GL	2	XPB	1250	49.21	1.24	0.56

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
2/XPB1320GL	2	XPB	1320	51.97	1.31	0.59
2/XPB1400GL	2	XPB	1400	55.12	1.38	0.63
2/XPB1450GL	2	XPB	1450	57.09	1.43	0.65
2/XPB1500GL	2	XPB	1500	59.06	1.48	0.67
2/XPB1550GL	2	XPB	1550	61.02	1.53	0.70
2/XPB1600GL	2	XPB	1600	62.99	1.58	0.72
2/XPB1650GL	2	XPB	1650	64.96	1.63	0.74
2/XPB1700GL	2	XPB	1700	66.93	1.68	0.76
2/XPB1750GL	2	XPB	1750	68.90	1.73	0.79
2/XPB1800GL	2	XPB	1800	70.87	1.78	0.81
2/XPB1850GL	2	XPB	1850	72.83	1.83	0.83
2/XPB1900GL	2	XPB	1900	74.80	1.88	0.85
2/XPB1950GL	2	XPB	1950	76.77	1.93	0.87
2/XPB2000GL	2	XPB	2000	78.74	1.98	0.90
2/XPB2120GL	2	XPB	2120	83.46	2.10	0.95
2/XPB2150GL	2	XPB	2150	84.65	2.13	0.96
2/XPB2240GL	2	XPB	2240	88.19	2.22	1.00
2/XPB2280GL	2	XPB	2280	89.76	2.26	1.02
2/XPB2360GL	2	XPB	2360	92.91	2.33	1.06
2/XPB2410GL	2	XPB	2410	94.88	2.38	1.08
2/XPB2500GL	2	XPB	2500	98.43	2.47	1.12
2/XPB2530GL	2	XPB	2530	99.61	2.50	1.14
2/XPB2650GL	2	XPB	2650	104.33	2.62	1.19
2/XPB2680GL	2	XPB	2680	105.51	2.65	1.20
2/XPB2800GL	2	XPB	2800	110.24	2.77	1.26
2/XPB2840GL	2	XPB	2840	111.81	2.81	1.27
3/XPB1250GL	3	XPB	1250	49.21	1.85	0.84
3/XPB1320GL	3	XPB	1320	51.97	1.96	0.89
3/XPB1400GL	3	XPB	1400	55.12	2.08	0.94
3/XPB1450GL	3	XPB	1450	57.09	2.15	0.98
3/XPB1500GL	3	XPB	1500	59.06	2.23	1.01
3/XPB1550GL	3	XPB	1550	61.02	2.30	1.04
3/XPB1600GL	3	XPB	1600	62.99	2.37	1.08
3/XPB1650GL	3	XPB	1650	64.96	2.45	1.11

GOLD LABEL Banded X Wedge - Size List



V-Belt Raw Edge **GOLD LABEL™**



Metric			
Section	W-Width (mm)	H-Height (mm)	Weight (Kg/rib*m)
XPZ	10	10	0.082
XPA	13	12	0.134
XPB	17	16	0.224

Imperial			
Section	W-Width (in)	H-Height (in)	Weight (lb/rib*in)
XPZ	25/64	25/64	0.005
XPA	33/64	30/64	0.008
XPB	43/64	5/8	0.013

DAYCO Part Nr	Ribs number	Section	Ld Datum length (mm)	Ld Datum length (in)	Weight (Kg)	Weight (lbs)
3/XPB1700GL	3	XPB	1700	66.93	2.52	1.14
3/XPB1750GL	3	XPB	1750	68.90	2.60	1.18
3/XPB1800GL	3	XPB	1800	70.87	2.67	1.21
3/XPB1850GL	3	XPB	1850	72.83	2.74	1.24
3/XPB1900GL	3	XPB	1900	74.80	2.82	1.28
3/XPB1950GL	3	XPB	1950	76.77	2.89	1.31
3/XPB2000GL	3	XPB	2000	78.74	2.97	1.35
3/XPB2120GL	3	XPB	2120	83.46	3.15	1.43
3/XPB2150GL	3	XPB	2150	84.65	3.19	1.45
3/XPB2240GL	3	XPB	2240	88.19	3.32	1.51
3/XPB2280GL	3	XPB	2280	89.76	3.38	1.53
3/XPB2360GL	3	XPB	2360	92.91	3.50	1.59
3/XPB2410GL	3	XPB	2410	94.88	3.58	1.62
3/XPB2500GL	3	XPB	2500	98.43	3.71	1.68
3/XPB2530GL	3	XPB	2530	99.61	3.75	1.70
3/XPB2650GL	3	XPB	2650	104.33	3.93	1.78
3/XPB2680GL	3	XPB	2680	105.51	3.98	1.80
3/XPB2800GL	3	XPB	2800	110.24	4.15	1.88
3/XPB2840GL	3	XPB	2840	111.81	4.21	1.91



PRODUCTS STORAGE-HANDLING CONDITIONS

- Possibly dry and cool environment
- Better no direct sunlight
- Prevent moisture contamination
- Avoid contamination with solvents or chemicals
- Ideal temperature for storage conditions is $< 30\text{ }^{\circ}\text{C}$ / $86\text{ }^{\circ}\text{F}$
- Continues high temperature ($50\text{ }^{\circ}\text{C}$ / $122\text{ }^{\circ}\text{F}$) might significantly reduce belt life
- Humidity is not significantly causing issues
- If properly stored belt shelf life is at least 5 years





GOLD LABEL Banded Raw Edge - Notes



